Exhibit 29

DOCKET A L A R M Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

Advanced Threat Prevention Appliance



Product Overview

DOCKET

Juniper Networks Advanced Threat Prevention Appliance is a distributed software platform that combines advanced threat detection, consolidated security analytics, and one-touch threat mitigation to protect organizations from cyber attacks and improve the productivity of security teams. The ATP Appliance detects threats across web. e-mail. and lateral traffic. Additionally, it can ingest logs from security devices to present a consolidated view of all threats in the environment.

Product Description

Organizations worldwide face security and productivity challenges every day. Zero-day malware often goes undetected because traditional security devices, which rely on signature-based detection, can't see it. Adding to the problem, security teams—overwhelmed by large volumes of alerts—often fail to recognize and act on critical incidents.

The Juniper Networks® Advanced Threat Prevention Appliance (formerly the Cyphort Allin-One system) provides continuous, multistage detection and analysis of Web, e-mail, and lateral spread traffic moving through the network. It collects information from multiple attack vectors, using advanced machine learning and behavioral analysis technologies to identify advanced threats in as little as 15 seconds. Those threats are then combined with data collected from other security tools in the network, analyzed, and correlated, creating a consolidated timeline view of all malware events related to an infected host. Once threats are identified, "one-touch" policy updates are pushed to inline tools to protect against a recurrence of advanced attacks.

The detection component of the ATP Appliance monitors network traffic to identify threats as they progress through the kill chain, detecting phishing, exploits, malware downloads, command and control communications, and internal threats. A multistage threat analysis process, which includes static, payload, machine learning, and behavior, as well as malware reputation analysis, continuously adapts to the changing threat landscape leveraging Juniper's Global Security Service, a cloud-based service that offers the latest threat detection and mitigation information produced by a team of security researchers, data scientists, and ethical hackers.

The threat analytics component of the ATP Appliance offers a holistic view of identity and threat activity gathered from a diverse set of sources such as Active Directory, endpoint antivirus, firewalls, secure Web gateways, intrusion detection systems, and endpoint detection and response tools. The analytics component looks at data from these sources, identifies advanced malicious traits, and correlates the events to provide complete visibility into a threat's kill chain. Security analysts receive a comprehensive host and user timeline that depicts how the events that occurred on a host or user unfolded. The timeline enhances the productivity of Tier 1 and Tier 2 security analysts who work on triaging and investigating malware incidents.

The ATP Appliance can integrate with other security devices to mitigate threats, giving users the ability to automatically quarantine e-mails on Google and Office 365 using REST APIs. Communications between the infected endpoint and the command and control servers are blocked by pushing malicious IP addresses to firewall devices. Integration with network access control devices can isolate infected hosts. The ATP Appliance's open API architecture also allows it to integrate with a number of third-party security vendors such as Cisco, Palo Alto Networks, Fortinet, Bluecoat, Check Point, Carbon Black, and Bradford, among others.





Figure 1: Juniper Networks ATP Appliance architecture

Architecture and Key Components

The architecture of the ATP Appliance consists of collectors deployed at critical points in the network, including remote locations. These collectors act like sensors, capturing information about Web, e-mail, and lateral traffic. Data and related executables collected across the fabric are delivered to the SmartCore analytics engine. Along with traffic from the native collectors, the ATP Appliance also ingests logs from other identity and security products such as Active Directory, endpoint antivirus, firewalls, secure Web gateways, intrusion detection systems, and endpoint detection and response tools. The logs can be ingested directly from third-party devices, or they can be forwarded from existing SIEM/syslog servers.

Armed with data collected from various sources, the SmartCore analytics engine performs the following multistage threat analysis processes:

- Static analysis: Applies continuously updated rules and signatures to find known threats that may have eluded inline devices.
- Payload analysis: Leverages an intelligent sandbox array to gain a deeper understanding of malware behavior by detonating suspicious Web and file content that would otherwise target Windows, OSX, or Android endpoint devices.

DOCKE.

- Machine learning and behavioral analysis: Employs patent-pending technologies to recognize the latest threat behaviors (such as multicomponent attacks over time) and quickly detect previously unknown threats.
- Malware reputation analysis: Compares analysis results with similar known threats to determine whether a newly detected threat is a variant of an existing issue or something completely new.
- Prioritization, risk analysis, correlation: Prioritizes threats based on threat severity, asset targets in the network, endpoint environment, and the threat's progression along the kill chain. For example, a high severity Windows malware landing on a Mac receives a lower risk score than a medium severity malware landing on a protected server. All malware events from the ATP Appliance and other security devices are correlated based on endpoint hostname and time and then plotted on a host timeline, allowing security teams to assess the risk of a threat and whether it requires immediate attention. For example, a threat detected by the ATP Appliance but missed by the antivirus solution receives a higher risk score. This allows security teams to go back in time and review all malicious events that have occurred on an infected host.



Figure 2: ATD Appliance events timeline

Find authenticated court documents without watermarks at docketalarm.com.

Features and Benefits

The ATP Appliance includes the following features and benefits:

- Inspects traffic across multiple vectors such as Web, e-mail, and lateral spread
- \cdot $\,$ Uploads suspicious files through the Web UI for processing
- Supports Windows 7 and OSX 10.10 operating systems
- Analyzes multiple file types, including executables, DLL, Mach-o, Dmg, PDF, Office, Flash, ISO, ELF, RTF, APK, Silverlight, Archive, and JAR
- Includes detection techniques such as exploit detection, payload analysis, command and control (C&C) detection, YARA, and SNORT rules
- Provides comprehensive and well-documented APIs that allow easy integration with third-party security devices
- Integrates with Juniper Networks, Palo Alto Networks, Checkpoint, Cisco, Fortinet, and Bluecoat solutions to automatically block malicious IP addresses and URLs
- Automatically quarantines Office 365 and Gmail e-mails
- Integrates with Carbon Black Protect and Response (endpoint solution) to allow upload of binaries executed on endpoints
- Integrates with Cloud Access Security Broker vendor SkyHigh to protect assets in the cloud
- Manages multiple SmartCore analytics engines via Manager of Central Managers functionality
- Supports access and authentication using SAML and RADIUS
- Correlates events across kill chain stages to monitor threat progress and risk
- Visualizes malware activity and groups malware traits to help incident response teams better understand malware behavior
- Prioritizes threats based on risk calculated from threat severity, threat progress, asset value, and other contextual data
- Provides timeline host view to obtain complete context about malware events that have occurred on the host

DOCKE

Product Options

The ATP Appliance is available as both a physical and virtual appliance. Physical appliances can be deployed in all-in-one mode (SmartCore and Fabric Collector are installed on the same physical appliance) or in distributed mode (SmartCore and Fabric Collector are installed on separate appliances). Virtual appliances can be deployed in distributed mode only.

Physical

All in One

Model	Performance (Objects Detonated)	Performance
AIO-R430	Up to 30,000 objects/day	1 Gbps
AIO-R730	Up to 80,000 objects/day	2 Gbps

SmartCore

Model	Performance (Objects Detonated)
SC-R730	Up to 175,000 objects/day
AIO-R730	Up to 80,000 objects/day

Fabric Collector

Model	Performance
FC-R330	1 Gbps
FC-R730	4 Gbps

Virtual

Virtual SmartCore Engine

Model	Performance (Objects Detonated)	Virtual CPU	Virtual Memory	Virtual Disk
vSC-8	Up to 40,000 objects/day	8	32 GB	1.5 TB
vSC-24	Up to 140,000 objects/day	24	96 GB	1.5 TB

Virtual Fabric Collector

Model	Performance	Virtual CPU	Virtual Memory	Virtual Disk
FC-v50M	50 Mbps	1	1.5 GB	16 GB
FC-v100M	100 Mbps	2	4 GB	16 GB
FC-v500M	500 Mbps	4	16 GB	512 GB
FC-v1G	1 Gbps	8	32 GB	512 GB
FC-v2.5G	2.5 Gbps	24	64 GB	512 GB



Advanced Threat Prevention Appliance

Memory 32 GB 96 GB Weight 43.87 lb (19.94 kg) 68 lb (30.4 kg) Dimensions (WHxD) 19" rack 19" rack Enclosure 19" rack 19" rack Management Interface (eth) (1) 10/100/1000BASE-T copper Gigabit Ethernet port 10/10/1000BASE-T copper Gigabit Ethernet port 10/100/1000BASE-T copper Gigabit Ethernet port Atternate Analysis Engine Exhaust Interface (eth2) (1) reserved) 1000BASE-T copper Gigabit Ethernet port 10/100/1000BASE-T copper Gigabit Ethernet port CPU 1000BASE-T copper Gigabit Ethernet port 10/100/1000BASE-T copper Gigabit Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) 10/100/1000BASE-T copper Gigabit Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) CPU Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) 1000BASE-T copper Gigabit Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) CPU Intel Xeon ES-2650 v3 20057 QPL Turb. HT, 642011-3120W 100108-000BASE-T copper Gigabit Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) AC Input Voltage Auto-switching 100-240V Auto-switching 100-240V AC Input Voltage Dual Hot Swap 50W Dual Hot Swap 50W AC Input Voltage So0 Watts (maximum 50 OWAtts (maximum temperature gradaction of 20° Prefuperature gr		AIO-R430	AIO-R730
Weight4387 lo (199 kg)68 lo (30.8 kg)Dimensions (WXHXD)1899 x 168 x 23.9 in (48.24 x 4.28 x 60.7 cm.).10Tr/9 x 3.44 x 26.92 in (44.42 x 8.73 x 68.37 cm.).20Enclosure19 "rack19 "rackManagement Interface (eth0)(1) 10/100/1000BASE-T copper Gigabit chemet port1) 10/100/1000BASE-T copper Gigabit chemet portMonitoring Interface (eth1) (Not relevant for core devices)(1 reserved) 1000BASE-T copper Gigabit chemet port1) 10/100/1000BASE-T copper Gigabit chemet portsAlternate Analysis Engine Exhaust Interface (eth2)1) 1000BASE-T copper Gigabit Ethernet x520 DP 10Gb DA/SFP+ Server Adapter (optional)1) 1000ASE-T copper Gigabit Ethernet x520 DP 10Gb DA/SFP+ server Adapter (optional)CPU Alternate Analysis Engine Exhaust Interface (eth2)1) 1012 Comed Gigabit Ethernet x520 DP 10Gb DA/SFP+ server Adapter (optional)1) 1000ASE-T copper Gigabit Ethernet x520 DP 10Gb DA/SFP+ server Adapter (optional)CPU Alternate Analysis Engine Exhaust Interface (eth2)1) 1012 Comed Gigabit Ethernet x520 DP 10Gb DA/SFP+ server Adapter (optional)1) 1000ASE-T copper Gigabit chemet portsCPU Alternate Analysis Engine Exhaust Interface (eth2)1) 1112 Ethernet x520 DP 10Gb DA/SFP+ server Adapter (optional)1000BASE-T copper Gigabit chemet portsCPU Alternate Chemet X520 DP 10Gb DA/SFP+ server Adapter (optional)10018 Comet X520 DP 10Gb DA/SFP+ server Adapter (optional)1000EASE-T copper Gigabit chemet portsCPU Alternate Chemet X520 DP 10Gb DA/SFP+ server Adapter (optional)10018 Comet X520 DP 10Gb DA/SFP+ Server Adapter (optional)1000EASE-T copper Gigabit c	Memory	32 GB	96 GB
Dimensions (WxHxD)18.99 x1.68 x 23.9 in (48.24 x 4.28 x 60.7 cm), 1U17.49 x 3.44 x 26.92 in (44.42 x 8.73 x 68.37 cm), 2UEnclosure19 rack19 rackManagement Interface (eth0)(1) 10/100/1000BASE-T copper Gigabit Ethernet port(1) 10/100/1000BASE-T copper Gigabit Ethernet portMonitoring Interface (eth1)(1) reserved) 1000BASE-T copper Gigabit Ethernet port• 10/100/1000BASE-T copper Gigabit Ethernet portAuternate Analysis Engine Exhaust Interface (eth2)• 1000BASE-T copper Gigabit Ethernet port (optional)• 1000BASE-T copper Gigabit Ethernet port (optional)Alternate Analysis Engine Exhaust Interface (eth2)• 1000BASE-T copper Gigabit Ethernet port (optional)• 1000BASE-T copper Gigabit Ethernet port (optional)CPU CPU CPUIntel Xeon E5-2650 v3 2.3GHz 25M Cache, 9.60GT/S QPI, Turbo, HT, 10C/20T (105W) Max Mem 2.133MHzDual Xeon E5-2695V314- Core 2.3GHZ 25MB L3 Cache 9.60T/S QPI Socket- L320W1213AC Input Voltage A CoreverAuto-switching 100-240VAuto-switching 100-240VAC Input Voltage A CowerDual Hot Swap 550WDual Hot Swap 750WAC Power Sopoly UnitsDual Hot Swap 550WDual Hot Swap 750WPower Supply Units FrequencySo-60 Hz-400°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourDD (behind front panel FRUS) Su 250GB 72X RPM SAT 36Dps 35 in Hot-plug Hard Drive, 136 SAT 36Dps 35 in Hot-plug Hard Drive, 136 SAT 36Dps 35 in Hot-plug Hard Drive, 136PERCH730 Ra6 Son 140 Ethernet Core 230HZ 25° HDD FRUSAdditional NIC1Dual Port 16B1Dual P	Weight	43.87 lb (19.9 kg)	68 lb (30.8 kg)
Enclosure19° rack9° rackManagement Interface (eth0)(1) 10/100/1000BASE-T copper Gigabit Ethemet port(1) 10/100/1000BASE-T copper Gigabit Ethemet portMonitoring Interface (eth1) (Not relevant for core devices)(1) reserved) 1000BASE-T copper Gigabit Ethemet port-10/100/1000BASE-T copper Gigabit Ethemet portAlternate Analysis Engine Exhaust Interface (eth2)-1000BASE-T copper Gigabit Ethernet port server Adapter (optional)-1000BASE-T copper Gigabit Ethernet port server Adapter (optional)CPU CPU-1000BASE-T coper Gigabit Ethernet port Server Adapter (optional; not relevant for Collector or AWS devices)-1000BASE-T coper Gigabit Ethernet port collector or AWS devices)CPU Adapter (optional; not relevant for Collector or AWS devices)Dual Xeon E5-269SV314- Core 2.36H2 35MB L3 2.36Hz, 25M Cache, GooT/S QPL Turbo, HT, 105C/20T (105W) Max Mem 2.33MHzDual Xeon E5-269SV314- Core 2.36H2 35MB L3 Cache 9.6GT/S QPL Turbo, HT, 105C/20T (105W) Max Mem 2.33MHzAC Input VoltageAuto-switching 100-240VAuto-switching 100-240VAC Power50 Watts (maximum)10-5 AmpsPower Supply UnitsDual Hot Swap 550WDual Hot Swap 750WPrequency-40°F tot 190° F (-40°C to 65° C) with a maximum temperature gradation of 20° per hour-40°F tot 190° F (-40°C to 65° C) with a maximum temperature gradation of 20° per hourDD (behind front panel FRUs)PERC H730 Rai Controller s ATA 3050P3 35m Hot-plug Hard Drive, 136 a 35m Hot-plug Hard Drive, 136Au0e tot 180° CAOC to 650 C) s And 5 S HDO FUS Cond GB SA SHot-Swap 2 S HDO FUS Cond GB SA SHot-Swap 2 S HDO FUS	Dimensions (WxHxD)	18.99 x 1.68 x 23.9 in (48.24 x 4.28 x 60.7 cm), 1U	17.49 x 3.44 x 26.92 in (44.42 x 8.73 x 68.37 cm), 2U
Management Interface (eth0)(1) 10/100/1000BASE-T copper Gigabit Ethernet port(1) 10/100/1000BASE-T copper Gigabit Ethernet portMonitoring Interface (eth1) (Not relevant for core devices)(1 reserved) 1000BASE-T copper Gigabit 	Enclosure	19" rack	19" rack
Monitoring Interface (eth1) (Not relevant for core devices): (I reserved) 1000BASE-T copper Gigabit Ethernet ports: Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional)Alternate Analysis Engine Exhaust Interface (eth2): 1000BASE-T copper Gigabit Ethernet port optional): Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional): Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional)CPU CPUIntel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional, not relevant for Collector or AWS devices): Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional, not relevant for Collector or AWS devices)CPU AC Input VoltageIntel Xeon E5-2650 v3 2.3GHz, Z5M Cache, 9.6GGT/S QPI, Turbo, HT, 10C/2UT (105W) Max Mem 2133MHzDual Xeon E5-2695V3 14- Core 2.3GH2 35MB L3 Cache 9.6GT/S QPI Socket- LGA201-3120WAC Input VoltageAuto-switching 100-240VAuto-switching 100-240VAC Input VoltageNuto-switching 100-240VAuto-switching 100-240VAC Power500 Watts (maximum)750 Watts (maximum)Power Supply UnitsDual Hot Swap 750W50-60 HzFrequency-60-61 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUS)PERC H730 Raid Controller +1x 500GB 72K RPM SATA 350ps 35.in Hot-plug Hard Drive, 136 35.in Hot-plug Hard Drive, 136 35.in Hot-plug Hard Drive, 136 35.in Hot-plug Hard Drive, 136 35.in Hot-plug Hard Drive, 136PLA PT 1 GB 01 DUAI POT 10 GB <td>Management Interface (eth0)</td> <td>(1) 10/100/1000BASE-T copper Gigabit Ethernet port</td> <td>(1) 10/100/1000BASE-T copper Gigabit Ethernet port</td>	Management Interface (eth0)	(1) 10/100/1000BASE-T copper Gigabit Ethernet port	(1) 10/100/1000BASE-T copper Gigabit Ethernet port
Alternate Analysis Engine Exhaust Interface (eth2)· 1000BASE-T copper Gigabit Ethernet por (optional)· 1000BASE-T copper Gigabit Ethernet por (optional)Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional; not relevant for Collector or AWS devices)· Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional; not relevant for 	Monitoring Interface (eth1) (Not relevant for core devices)	 (1 reserved) 1000BASE-T copper Gigabit Ethernet port Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional) 	 10/100/1000BASE-T copper Gigabit Ethernet ports Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional)
CPUIntel Xeon E5-2650 v3Dual Xeon E5-2695V3 14- Core 2.3GHZ 35MB L3 Cache 9.6GT/S QPI Socket- LGA2011-3120WAC Input VoltageAuto-switching 100-240VAuto-switching 100-240VAC Input Current74-3.7 Amps10-5 AmpsAC Power550 Watts (maximum)750 Watts (maximum)Power Supply UnitsDual Hot Swap 550WDual Hot Swap 750WFrequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller -1 x 500GB 72K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1GB1 Dual Port 1GB1 Dual Port 1GB or 1 Dual Port 10 GB	Alternate Analysis Engine Exhaust Interface (eth2)	 1000BASE-T copper Gigabit Ethernet port (optional) Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional; not relevant for Collector or AWS devices) 	 1000BASE-T copper Gigabit Ethernet port (optional) Intel Ethernet X520 DP 10Gb DA/SFP+ Server Adapter (optional; not relevant for Collector or AWS devices)
AC Input VoltageAuto-switching 100-240VAuto-switching 100-240VAC Input Current7.4-3.7 Amps10-5 AmpsAC Power550 Watts (maximum)750 Watts (maximum)Power Supply UnitsDual Hot Swap 550WDual Hot Swap 750WFrequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUS)PERC H730 Raid Controller - 1 x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13G 2.5 THDD FRUSPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUS RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB1 Dual Port 10 GB	CPU	Intel Xeon E5-2650 v3 2.3GHz, 25M Cache, 9.60GT/s QPI, Turbo, HT, 10C/20T (105W) Max Mem 2133MHz	Dual Xeon E5-2695V3 14- Core 2.3GHZ 35MB L3 Cache 9.6GT/S QPI Socket- LGA2011-3 120W
AC Input Current74-3.7 Amps10-5 AmpsAC Power550 Watts (maximum)750 Watts (maximum)Power Supply UnitsDual Hot Swap 550WDual Hot Swap 750WFrequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller - 1x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 136 .5in Hot-plug Hard Drive, 136PERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB1 Dual Port 1 0 GB	AC Input Voltage	Auto-switching 100-240V	Auto-switching 100-240V
AC Power550 Watts (maximum)750 Watts (maximum)Power Supply UnitsDual Hot Swap 550WDual Hot Swap 750WFrequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller - 1 x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13G + 2 x 2TB 7.2K RPM SATA 6Gbps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB1 Dual Port 1 0 GB	AC Input Current	7.4-3.7 Amps	10-5 Amps
Power Supply UnitsDual Hot Swap 550WDual Hot Swap 750WFrequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller -1 x 500 GB 7.2K RPM SATA 36bps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB1 Dual Port 1 0 GB	AC Power	550 Watts (maximum)	750 Watts (maximum)
Frequency50-60 Hz50-60 HzAmbient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller -1 x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB1 Dual Port 1 0 GB	Power Supply Units	Dual Hot Swap 550W	Dual Hot Swap 750W
Ambient Temperature-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hourHDD (behind front panel FRUs)PERC H730 Raid Controller - 1 x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13G + 2 x 2TB 7.2K RPM SATA 6Gbps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB	Frequency	50-60 Hz	50-60 Hz
HDD (behind front panel FRUs)PERC H730 Raid Controller - 1 × 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13G + 2 × 2TB 7.2K RPM SATA 6Gbps 3.5in Hot-plug Hard Drive, 13GPERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5Additional NIC1 Dual Port 1 GB1 Dual Port 1 GB	Ambient Temperature	-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour	-40°F to 149° F (-40°C to 65° C) with a maximum temperature gradation of 20° C per hour
Additional NIC 1 Dual Port 1 GB 1 Dual Port 1 GB or 1 Dual Port 10 GB	HDD (behind front panel FRUs)	PERC H730 Raid Controller - 1 x 500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive, 13G + 2 x 2TB 7.2K RPM SATA 6Gbps 3.5in Hot-plug Hard Drive, 13G	PERC H730 - 12 ea. 600 GB SAS Hot-Swap 2.5" HDD FRUs RAID 5
	Additional NIC	1 Dual Port 1 GB	1 Dual Port 1 GB or 1 Dual Port 10 GB

Ordering Information

The ATP Appliance offers subscription-based pricing. A summary of features and license options can be found in Table 1.

Table 1: ATP Appliance Feature and License Options

Standard Level (1 or 3 Years)	Enterprise Level (1 or 3 Years)	
 License by bandwidth and users, unlimited locations Combined Web, e-mail, file uploads, and advanced threat analytics Includes Windows, Mac 	 License by bandwidth and users, unlimited locations All Standard Level features and Advanced e-mail Lateral spread detection across all locations Unlimited scale for e-mail and advanced threat analytics 	

For additional ordering information, please contact your Juniper sales representative.



Find authenticated court documents without watermarks at docketalarm.com.

DOCKET



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

