

Amended

Exhibit 10

Exhibit 10

Claim 7 of U.S. Patent No. 10,44

"7. A mobile device in a wireless packet system using a frame structure of multiple frames for transmission, each frame comprising a plurality of time intervals, each time interval comprising a plurality of orthogonal frequency division multiplexing (OFDM) symbols, and each OFDM symbol containing a plurality of frequency subcarriers, the mobile device configured to"

7. A mobile device in a wireless packet system using a frame structure of multiple frames for transmission, each frame comprising a plurality of time intervals, each time interval comprising a plurality of orthogonal frequency division multiplexing (OFDM) symbols, and each OFDM symbol containing a plurality of frequency subcarriers, the mobile device configured to:

Ford's Accused Products include vehicles equipped with components and/or services used in connection with access to 4G/LTE networks and services, including services sold and provided by Ford.

To the extent the preamble is considered a limitation, Ford's Accused Products do not infringe the claims of the patent. *E.g.*,

For clarity, release 8 of the 3GPP specifications was frozen in December 2008 and used as the basis for the first wave of LTE equipment. The LTE marketplaces have released releases from Release 8 through Release 17. Though for ease of review releases cited below, the same or functionally identical content exists in each corresponding release.

5 Physical Layer for E-UTRA

Downlink and uplink transmissions are organized into radio frames with 10 ms duration. Two radio frame structures are supported:

- Type 1, applicable to FDD,
- Type 2, applicable to TDD.

Frame structure Type 1 is illustrated in Figure 5.1-1. Each 10 ms radio frame is divided into ten equal subframes. Each sub-frame consists of two equally sized slots. For FDD, 10 subframes are available for downlink transmission and 10 subframes are available for uplink transmissions in each 10 ms interval. Uplink and downlink transmissions are separated in the frequency domain.




Figure 5.1-1: Frame structure type 1

Frame structure Type 2 is illustrated in Figure 5.1-2. Each 10 ms radio frame consists of two half-frames. Each half-frame consists of eight slots of length 0.5 ms and three special fields: DwPTS, GP and UpPTS. DwPTS and UpPTS is configurable subject to the total length of DwPTS, GP and UpPTS being equal to 3 ms. 1.5 ms and 10ms switch-point periodicity are supported. Subframe 1 in all configurations and subframe 6 in configurations with 1.5 ms switch-point periodicity consist of DwPTS, GP and UpPTS. Subframe 6 in configurations with 10ms switch-point periodicity consists of DwPTS only. All other subframes consist of two equally sized slots.

For TDD, GP is reserved for downlink to uplink transition. Other Subframes/Fields are assigned

"7. A mobile device in a wireless packet system using a frame structure of multiple frames for transmission, each frame comprising a plurality of time intervals, each time interval comprising a plurality of orthogonal frequency division multiplexing (OFDM) symbols, and each OFDM symbol comprising a plurality of frequency subcarriers, the mobile device configured to"

See e.g., 3GPP TS 36.300 V8.12.0 at pg. 23.

The LTE downlink uses orthogonal frequency division multiplexing (OFDM). In the downlink, OFDM symbols are transmitted.

5.1 Downlink Transmission Scheme

5.1.1 Basic transmission scheme based on OFDM

The downlink transmission scheme is based on conventional OFDM using a cyclic prefix. The sub-carrier spacing is $\Delta f = 15$ kHz. 12 consecutive sub-carriers during one slot correspond to one downlink OFDM symbol in the frequency domain, the number of resource blocks, N_{RB} , can range from $N_{RB-min} = 6$ to N_{RB-max} .

In addition there is also a reduced sub-carrier spacing $\Delta f_{low} = 7.5$ kHz, only for MBMS-dedicated channels.

In the case of 15 kHz sub-carrier spacing there are two cyclic-prefix lengths, corresponding to normal and extended cyclic prefix OFDM symbols per slot respectively.

- Normal cyclic prefix: $T_{CP} = 160 \times T_s$ (OFDM symbol #0), $T_{CP} = 144 \times T_s$ (OFDM symbol #1-11)

See e.g., 3GPP TS 36.300 V8.12.0 at pg. 25.

A subframe contains two slots, and in each slot multiple OFDM symbols are transmitted. Each OFDM symbol includes a plurality of subcarriers.

"7. A mobile device in a wireless packet system using a frame structure of multiple frames for transmission, each frame comprising a plurality of time intervals, each time interval comprising a plurality of orthogonal frequency division multiplexing (OFDM) symbols, and each OFDM symbol comprising a plurality of frequency subcarriers, the mobile device configured to"

	<p>6.2 Slot structure and physical resource elements</p> <p>6.2.1 Resource grid</p> <p>The transmitted signal in each slot is described by a resource grid of $N_{RB}^{DL} N_{sc}^{RB}$ subcarriers and N_{sc}^{DL} OFDM symbols.</p> <p>The resource grid structure is illustrated in Figure 6.2.2-1. The quantity N_{RB}^{DL} depends on the bandwidth configured in the cell and shall fulfil</p> $N_{RB}^{min,DL} \leq N_{RB}^{DL} \leq N_{RB}^{max,DL}$ <p>where $N_{RB}^{min,DL} = 6$ and $N_{RB}^{max,DL} = 110$ are the smallest and largest downlink bandwidth, respectively, in the current version of this specification.</p> <p><i>See e.g., 3GPP TS 36.211 V8.9.0 at pg. 45.</i></p>
--	--

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.