

EXHIBIT G

Example Asserted Claims¹ of U.S. Patent No. 8,467,366

Claim 1 of the '366 Patent	Claim 17 of the '366 Patent
In a multi-cell orthogonal frequency division multiple access (OFDMA) wireless communication system comprising a plurality of base stations and mobile stations, a mobile station configured to communicate with a serving base station in a cell via a communication channel, the mobile station comprising:	In an orthogonal frequency division multiple access (OFDMA) wireless communication system, a method for signal transmission by a mobile station to a serving base station via a communication channel, the method comprising:
an apparatus configured to transmit a data signal to the serving base station in the cell over a data subchannel, wherein the data subchannel comprises a plurality of adjacent or non-adjacent subcarriers within the communication channel; and	transmitting a data signal over a data subchannel to the serving base station, wherein the data subchannel comprises a plurality of adjacent or non-adjacent subcarriers within the communication channel; and
an apparatus configured to transmit a ranging signal to the serving base station in the cell over a ranging subchannel for random access, wherein:	transmitting a ranging signal over a ranging subchannel to the serving base station for random access, wherein:
the ranging signal is formed from a ranging sequence selected from a set of ranging sequences associated with the cell for identifying the mobile station;	the ranging signal is formed from a ranging sequence selected from a set of ranging sequences for identifying the mobile station;
the ranging signal lasts over a period of one or multiple orthogonal frequency division multiplexing (OFDM) symbols and the ranging signal exhibits a low peak-to-average power ratio in the time domain; and	the ranging signal lasts over a period of one or multiple orthogonal frequency division multiplexing (OFDM) symbols and the ranging signal exhibits a low peak-to-average power ratio in the time domain; and
the ranging subchannel comprises at least one block of subcarriers within the communication channel and power levels of subcarriers at both ends of a block are set to zero.	the ranging subchannel comprises at least one block of subcarriers within the communication channel and power levels of subcarriers at both ends of a block are set to zero.

¹ Neo asserts the following claims of the '366 Patent: 1, 2, 3, 4, 5, 17, 20, 21.

Claim 4 of the '366 Patent	Claim 20 of the '366 Patent
The mobile station of claim 1, wherein subcarriers in a block are contiguous in frequency.	The method of claim 17, wherein subcarriers in a block are contiguous in frequency.

Claim 5 of the '366 Patent	Claim 21 of the '366 Patent
The mobile station of claim 1, further comprising an apparatus configured to control a transmission power of the ranging signal using an open-loop power control method by:	The method of claim 17, further comprising controlling a transmission power of the ranging signal using an open-loop power control method by:
estimating a path loss between the serving base station and the mobile station based on a received downlink signal;	estimating a path loss between the serving base station and the mobile station based on a received downlink signal;
setting the transmission power of the ranging signal based on the path loss; and	setting the transmission power of the ranging signal based on the path loss; and
increasing the transmission power of the ranging signal for retransmission.	increasing the transmission power of the ranging signal for retransmission.

Example Asserted Claims² of U.S. Patent No. 10,075,941

Claim 8 of the '941 Patent	Claim 13 of the '941 Patent
A link adaptation method by a mobile station served by a serving base station in an Orthogonal Frequency Division Multiplexing (OFDM) communication system, the communication system utilizing a transmission structure with time slots in the time domain and frequency subchannels in the frequency domain, the method comprising:	A mobile station served by a serving base station in an Orthogonal Frequency Division Multiplexing (OFDM) communication system, the communication system utilizing a transmission structure with time slots in the time domain and frequency subchannels in the frequency domain, the mobile station comprising a receiver configured to:
receiving a control message from the serving base station over a control channel, wherein:	receive a control message from the serving base station over a control channel, wherein:
the control message contains transmission parameters specific to the mobile station for a subsequent transmission by the serving base station over a frequency subchannel to the mobile station in a time slot; and	the control message contains transmission parameters specific to the mobile station for a subsequent transmission by the serving base station over a frequency subchannel to the mobile station in a time slot; and
the mobile station-specific transmission parameters indicate an antenna transmission scheme and a corresponding subchannel configuration, the antenna transmission scheme comprising a transmission diversity scheme or a multiple-input multiple-output (MIMO) scheme and the corresponding subchannel configuration characterized by distributed subcarriers or localized subcarriers in the frequency domain; and	the mobile station-specific transmission parameters indicate an antenna transmission scheme and a corresponding subchannel configuration, the antenna transmission scheme comprising a transmission diversity scheme or a multiple-input multiple-output (MIMO) scheme and the corresponding subchannel configuration characterized by distributed subcarriers or localized subcarriers in the frequency domain; and
receiving a data packet transmitted by the serving base station using the mobile station-specific transmission parameters over the frequency subchannel.	receive a data packet transmitted by the serving base station using the mobile station-specific transmission parameters over the frequency subchannel.

² Neo asserts the following claims of the '941 Patent: 8, 10, 12, 13, 14.

Example Asserted Claims³ of U.S. Patent No. 10,447,450 Patent

Claim 8 of the '450 Patent	Claim 10 of the '450 Patent
The mobile device of claim 7, wherein the starting time-frequency coordinate indicates a starting OFDM symbol of the segment of time-frequency resource.	The mobile device of claim 7, wherein the starting time-frequency coordinate indicates a starting group of subcarriers of the segment of time-frequency resource.

³ Neo asserts the following claims of the '450 Patent: 7, 8, 10, 11.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.