

AX.25 Amateur Packet-Radio Link-Layer Protocol

| Contents | | Page |
|-----------|---|------|
| 2.3.4 | Control Field Coding for Commands and Responses | 12 |
| 2.3.4.1 | Information Command Frame Control Field | 13 |
| 2.3.4.2 | Supervisory Frame Control Field | 13 |
| 2.3.4.2.1 | Receive Ready (RR) Command and Response | 13 |
| 2.3.4.2.2 | Receive Not Ready (RNR) Command and Response | 14 |
| 2.3.4.2.3 | Reject (REJ) Command and Response | 14 |
| 2.3.4.3 | Unnumbered Frame Control Fields | 14 |
| 2.3.4.3.1 | Set Asynchronous Balanced Mode (SABM) Command | 15 |
| 2.3.4.3.2 | Disconnect (DISC) Command | 15 |
| 2.3.4.3.3 | Frame Reject (FRMR) Response | 16 |
| 2.3.4.3.4 | Unnumbered Acknowledge (UA) Response | 17 |
| 2.3.4.3.5 | Disconnected Mode (DM) Response | 18 |
| 2.3.4.3.6 | Unnumbered Information (UI) Frame | 18 |
| 2.3.5 | Link Error Reporting and Recovery | 18 |
| 2.3.5.1 | DXE Busy Condition | 18 |
| 2.3.5.2 | Send Sequence Number Error | 18 |
| 2.3.5.3 | Reject (REJ) Recovery | 19 |
| 2.3.5.4 | Time-out Error Recovery | 19 |
| 2.3.5.4.1 | T1 Timer Recovery | 19 |
| 2.3.5.4.2 | Timer T3 Recovery | 19 |
| 2.3.5.5 | Invalid Frame or FCS Error | 19 |
| 2.3.5.6 | Frame Rejection Condition | 19 |
| 2.4 | Description of AX.25 Procedures | 20 |
| 2.4.1 | Address Field Operation | 20 |
| 2.4.1.1 | Address Information | 20 |
| 2.4.1.2 | Command/Response Procedure | 20 |
| 2.4.2 | P/F Bit Procedures | 21 |
| 2.4.3 | Procedures For Link Set-Up and Disconnection | 21 |
| 2.4.3.1 | LAPB Link Connection Establishment | 21 |
| 2.4.3.2 | Information-Transfer Phase | 22 |
| 2.4.3.3 | Link Disconnection | 22 |
| 2.4.3.4 | Disconnected State | 22 |
| 2.4.3.5 | Collision Recovery | 23 |
| 2.4.3.5.1 | Collisions in a Half-Duplex Environment | 23 |
| 2.4.3.5.2 | Collisions of Unnumbered Commands | 23 |
| 2.4.3.5.3 | Collision of a DM with a SABM or DISC | 23 |
| 2.4.3.6 | Connectionless Operation | 23 |

AX.25 Amateur Packet-Radio Link-Layer Protocol

| Contents | Page |
|---|------|
| 2.4.4 Procedures for Information Transfer | 24 |
| 2.4.4.1 Sending I Frames | 24 |
| 2.4.4.2 Receiving I Frames | 24 |
| 2.4.4.3 Reception of Out of Sequence Frames | 25 |
| 2.4.4.4 Reception of Incorrect Frames | 25 |
| 2.4.4.5 Receiving Acknowledgement | 25 |
| 2.4.4.6 Receiving Reject | 26 |
| 2.4.4.7 Receiving a RNR Frame | 26 |
| 2.4.4.8 Sending a Busy Indication | 26 |
| 2.4.4.9 Waiting Acknowledgement | 27 |
| 2.4.5 Frame Rejection Conditions | 27 |
| 2.4.6 Resetting Procedure | 27 |
| 2.4.7 List of System Defined Parameters | 28 |
| 2.4.7.1 Timers | 28 |
| 2.4.7.1.1 Acknowledgement Timer T1 | 28 |
| 2.4.7.1.2 Response Delay Timer T2 | 29 |
| 2.4.7.1.3 Inactive Link Timer T3 | 29 |
| 2.4.7.2 Maximum Number of Retries (N2) | 29 |
| 2.4.7.3 Maximum Number of Octets in an I Field (N1) | 29 |
| 2.4.7.4 Maximum Number of I Frames Outstanding (k) | 29 |
| Appendix A Glossary | 31 |
| Appendix B References | 34 |
| Appendix C Implementation Notes | 35 |
| Appendix D State Tables | 36 |

