



Standard Frac Plug

Wireline Set

The Standard Frac Plug provides an economical means of a temporary zone isolation for fracturing or other treatments. The plug can be set on different types of wireline pressure setting tools.

The Standard Frac Plug is supplied with a shear ring to give an accurate and secure set. Also supplied is a ball that will seat on the top of frac plug during a fracturing operation. This plug sustains moderate pressures and temperatures.

FEATURES:

- Electric wireline set
- Drillable
- Cast iron construction
- One piece slips - hardened to depth of wicker only
- Sets in any grade casing including P-110
- Bottom set with shear ring
- For temporary or permanent service
- Ratcheting lock ring holds setting force
- Small O.D.'s for speed and safety when running

SPECIFICATIONS

CASING		PLUG		SETTING RANGE		SETTING TOOL	
OD	WT. (LBS/FT)	PART NO.	O.D.	MIN.	MAX.	BAKER	GO
4 1/2	9.5 - 16.6	002-3500-000	3.50	3.826	4.090	10	3 1/2
4 1/2	9.5 - 13.5	002-3710-000	3.71	3.920	4.560	10	3 1/2
5	11.5 - 21	002-3710-000	3.71	3.920	4.560	10	3 1/2
5 1/2	13 - 25	002-4240-000	4.24	4.580	5.047	20	3 1/2
5 3/4	22.5 - 25.2	002-4240-000	4.24	4.580	5.047	20	3 1/2
6 5/8	17 - 22	002-5610-000	5.61	5.989	6.655	20	3 1/2
7	17 - 35	002-5610-000	5.61	5.989	6.655	20	3 1/2



This illustration does not reflect all sizes