



U.S. PATENT APPLICATION

SERIAL NUMBER

08/725,643

FILING DATE

10/15/96

CLASS

455

GROUP ART UNIT

2611

APPLICANT

ALEX K. RAITH, DURHAM, NC; JAMES RAGSDALE, RALEIGH, NC; JOHN DIACHINA, GARNER, NC.

CONTINUING DATA***
VERIFIED

FOREIGN/PCT APPLICATIONS***
VERIFIED

FOREIGN FILING LICENSE GRANTED 01/29/97

STATE OR
COUNTRY

NC

SHEETS
DRAWING

8

TOTAL
CLAIMS

66

INDEPENDENT
CLAIMS

12

FILING FEE
RECEIVED

\$2,632.00

ATTORNEY DOCKET NO.

027555-801

ADDRESS

RONALD L GRUDZIECKI
BURNS DOANE SWECKER & MATHIS
P O BOX 1404
ALEXANDRIA VA 22313-1404

TITLE

MULTI-RATE RADIOCOMMUNICATION SYSTEMS AND TERMINALS

This is to certify that annexed hereto is a true copy from the records of the United States Patent and Trademark Office of the application which is identified above.

By authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS

Date

Certifying Officer

ABSTRACT

Variances in bandwidth used by a radiocommunication connection are adapted to by changing the type of information being transmitted. For example, in a TDMA environment, a first downlink time slot associated with a double- or triple-rate connection may have a first format, while a second time slot associated with the same connection may have a second format different from the first format. Bandwidth in the second (or third) time slot can be used to carry information in a fast out-of-band channel (FOC). The FOC may provide information relating to the same connection as the payload or data field in that time slot, e.g., a service type identifier which informs the mobile or base station of the type of information (e.g., voice, video or data) being conveyed in the payload. Alternatively, the FOC information may be associated with a connection or connections which are different from that supported by the payload or data field containing the FOC.

APPLICATION FOR UNITED STATES LETTERS PATENT

by

Krister Raith, James Ragsdale and John Diachina

for

MULTI-RATE RADIOCOMMUNICATION SYSTEMS AND TERMINALS

BURNS, DOANE, SWECKER & MATHIS, L.L.P.
Post Office Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Attorney's Docket No. 027555-801

MULTI-RATE RADIOCOMMUNICATION SYSTEMS AND TERMINALS

RELATED APPLICATION

This application is related to U.S. Patent Application Serial No. 08/1730,300⁷⁰,
entitled "Radiocommunication Systems and Terminals with Increased Payload
5 Bandwidth", which application was filed on the same date as this application.

BACKGROUND

Applicant's invention relates generally to radiocommunication systems,
e.g., cellular or satellite systems, that use digital traffic channels in a multiple
access scheme, e.g., time division multiple access (TDMA) or code division
10 multiple access (CDMA).

The growth of commercial radiocommunications and, in particular, the
explosive growth of cellular radiotelephone systems have compelled system
designers to search for ways to increase system capacity without reducing
communication quality beyond consumer tolerance thresholds. One way to
15 increase capacity is to use digital communication and multiple access techniques
such as TDMA, in which several users are assigned respective time slots on a
single radio carrier frequency.

In North America, these features are currently provided by a digital
cellular radiotelephone system called the digital advanced mobile phone service
20 (D-AMPS), some of the characteristics of which are specified in the interim
standard IS-54B, "Dual-Mode Mobile Station-Base Station Compatibility
Standard", published by the Electronic Industries Association and
Telecommunications Industry Association (EIA/TIA). Because of a large
existing consumer base of equipment operating only in the analog domain with
25 frequency-division multiple access (FDMA), IS-54B is a dual-mode (analog and
digital) standard, providing for analog compatibility in tandem with digital
communication capability. For example, the IS-54B standard provides for both

FDMA analog voice channels (AVC) and TDMA digital traffic channels (DTC), and the system operator can dynamically replace one type with the other to accommodate fluctuating traffic patterns among analog and digital users. The AVCs and DTCs are implemented by frequency modulating radio carrier signals, which have frequencies near 800 megahertz (MHz) such that each radio channel has a spectral width of 30 kilohertz (KHz). A subsequent standard, referred to as IS-136, adds specifications for digital control channels. This standard document, in particular the version identified as PN-3474.1, dated December 15, 1995 and published by EIA/TIA, is incorporated here by reference.

In a TDMA cellular radiotelephone system, each radio channel is divided into a series of time slots, each of which contains a burst of information from a data source, e.g., a digitally encoded portion of a voice conversation. The time slots are grouped into successive TDMA frames having a predetermined duration. According to IS-54B and IS-136, each TDMA frame consists of six consecutive time slots and has a duration of 40 milliseconds (msec). Thus, each frame can carry from one to six traffic channels (e.g., one to six radio connections). The number of connections which can be supported by each TDMA frame depends on the desired information transmission rate. For example, if the connections are used to support the transmission of voice information, the number of slots used per channel depends on the source rates of the speech coder/decoders (codecs) used to digitally encode the conversations. Such speech codecs can operate at either full-rate or half-rate, with full-rate codecs being expected to be used until half-rate codecs that produce acceptable speech quality are developed.

Thus, a full-rate DTC requires twice as many time slots in a given time period as a half-rate DTC, and in IS-54B, each radio channel can carry up to three full-rate DTCs or up to six half-rate DTCs. Each full-rate DTC uses two slots of each TDMA frame, i.e., the first and fourth, second and fifth, or third and sixth of a TDMA frame's six slots. Each half-rate DTC uses one time slot of each TDMA frame. During each DTC time slot, 324 bits are transmitted, of

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.