

US PATENT & TRADEMARK OFFICE

PATENT APPLICATION FULL TEXT AND IMAGE DATABASE



(1 of 1)

United States Patent Application

20110251675

Kind Code

A1

Dwork; Joshua

October 13, 2011

Transcatheter Prosthetic Heart Valve Delivery Device With Partial Deployment and Release Features and Methods

Abstract

A delivery device for percutaneously deploying a stented prosthetic heart valve, including a delivery sheath, an inner shaft, and a spindle. The inner shaft is slidably disposed within a lumen of the delivery sheath. The spindle is attached to the shaft and includes a hub defining at least one longitudinal slot sized to slidably receive a post of the stented valve. An outer surface of the hub forms a curved proximal segment. The device provides a loaded state in which the delivery sheath retains the stented valve over the inner shaft and coupled to the spindle via the slot. In a deployed state, the distal end of the delivery sheath is withdrawn from the prosthesis to permit the stented valve to release from the slot, sliding along the curved outer surface of the hub.

Inventors: **Dwork; Joshua**; (*Santa Rosa, CA*)

Assignee: **Medtronic, Inc.**
Minneapolis
MN

Family ID: **44761494**

Appl. No.: **12/757088**

Filed: **April 9, 2010**

Current U.S. Class:

623/1.23 ; 623/1.26

Current CPC Class:

A61F 2/2418 20130101; A61F 2/2436 20130101; A61F 2002/9665 20130101

Class at Publication:

623/1.23 ; 623/1.26

International Class:

A61F 2/84

US PATENT & TRADEMARK OFFICE

PATENT APPLICATION FULL TEXT AND IMAGE DATABASE



(1 of 1)

United States Patent Application

20110251675

Kind Code

A1

Dwork; Joshua

October 13, 2011

Transcatheter Prosthetic Heart Valve Delivery Device With Partial Deployment and Release Features and Methods

Abstract

A delivery device for percutaneously deploying a stented prosthetic heart valve, including a delivery sheath, an inner shaft, and a spindle. The inner shaft is slidably disposed within a lumen of the delivery sheath. The spindle is attached to the shaft and includes a hub defining at least one longitudinal slot sized to slidably receive a post of the stented valve. An outer surface of the hub forms a curved proximal segment. The device provides a loaded state in which the delivery sheath retains the stented valve over the inner shaft and coupled to the spindle via the slot. In a deployed state, the distal end of the delivery sheath is withdrawn from the prosthesis to permit the stented valve to release from the slot, sliding along the curved outer surface of the hub.

Inventors: **Dwork; Joshua**; (*Santa Rosa, CA*)

Assignee: **Medtronic, Inc.**
Minneapolis
MN

Family ID: **44761494**

Appl. No.: **12/757088**

Filed: **April 9, 2010**

Current U.S. Class:

623/1.23 ; 623/1.26

Current CPC Class:

A61F 2/2418 20130101; A61F 2/2436 20130101; A61F 2002/9665 20130101

Class at Publication:

623/1.23 ; 623/1.26

International Class:

A61F 2/84 20060101 A61F002/84; A61F 2/82 20060101
A61F002/82

1. A delivery device for percutaneously deploying a stented prosthetic heart valve including a stent frame to which a valve structure is attached, the device comprising: a delivery sheath assembly terminating at a distal end and defining a lumen; an inner shaft slidably disposed within the lumen; and a spindle attached to the shaft, the spindle including: a tubular base, a hub projecting radially outwardly relative to the base, wherein: the hub defines at least one longitudinal slot sized to slidably receive a corresponding post of a prosthetic heart valve stent frame, an outer surface of the hub forms a proximal segment and a distal segment, the proximal segment being curved in extension toward the distal segment; wherein the device is configured to provide a loaded state in which the delivery sheath assembly retains a stented prosthetic heart valve over the inner shaft and coupled to the spindle via the at least one slot, and a deployment state in which the distal end of the delivery sheath assembly is withdrawn from the prosthetic heart valve to permit the prosthetic heart valve to release from the at least one longitudinal slot.
2. The delivery device of claim 1, wherein the at least one longitudinal slot includes a plurality of circumferentially spaced longitudinal slots formed in the hub.
3. The delivery device of claim 2, wherein the plurality of longitudinal slots are equidistantly spaced from one another about a circumference of the hub.
4. The delivery device of claim 1, wherein the proximal segment defines a proximal face of the hub and the distal segment defines a distal face of the hub, and further wherein the at least one longitudinal slot is open at the proximal and distal faces.
5. The delivery device of claim 4, wherein the at least one longitudinal slot is defined by opposing side walls and a floor, and further wherein the tubular base includes a ring immediately proximal the hub, the ring having a surface aligned with the floor.
6. The delivery device of claim 5, wherein the spindle further includes a flange projecting radially outwardly relative to the base and proximally spaced from the hub by the ring.
7. The delivery device of claim 6, wherein an outer diameter of the flange approximates a maximum outer diameter of the hub.
8. The delivery device of claim 1, wherein the outer surface defines a convex curve in longitudinal extension along the proximal segment.
9. The delivery device of claim 1, wherein the outer surface, as collectively defined by the proximal and distal segments, approximates a semi-circle in longitudinal extension.
10. The delivery device of claim 1, further comprising: a release sheath assembly disposed between the delivery sheath assembly and the spindle in the loaded state, the release sheath assembly including a release sheath slidably received over at least the proximal segment of the hub in the loaded state.
11. The delivery device of claim 10, wherein the release sheath assembly is configured to proximally retract the release sheath relative to the hub with proximal retraction of the delivery sheath distal end from the release sheath.

12. The delivery device of claim 10, wherein the release sheath forms at least one longitudinal notch extending from a distal end of the release sheath, and further wherein upon final assembly in the loaded state, the at least one notch is longitudinally aligned with the at least one slot.
13. The delivery device of claim 12, wherein the at least one longitudinal slot includes a plurality of circumferentially spaced longitudinal slots, and the at least one notch includes a plurality of circumferentially spaced notches, and further wherein each of the slots is longitudinally aligned with a respective one of the notches.
14. The delivery device of claim 13, wherein the spindle further forms a circumferential trough between the hub and a flange formed proximal the hub, and further wherein the release sheath includes a plurality of fingers spaced from one another by the plurality of notches, and further wherein the loaded state includes the fingers extending across the circumferential trough.
15. A system for repairing a defective heart valve of a patient, the system comprising: a prosthetic heart valve having a stent frame and a valve structure attached to the stent frame, the stent frame defining a distal region and a proximal region, the proximal region forming at least one post; and a delivery device comprising: a delivery sheath assembly terminating at a distal end and defining a lumen, an inner shaft slidably disposed within the lumen, a spindle attached to the inner shaft, the spindle including: a tubular base, a hub projecting radially outwardly relative to the base and defining at least one longitudinal slot sized to slidably receive the at least one post, wherein the outer surface of the hub forms a proximal segment and a distal segment, the proximal segment being curved in extension toward the distal segment; wherein the system is configured to provide a loaded condition in which the prosthetic heart valve is retained between the delivery sheath assembly and the inner shaft, including the at least one post slidably captured within the at least one longitudinal slot.
16. The system of claim 15, wherein the at least one longitudinal slot includes a plurality of circumferentially spaced longitudinal slots, and further wherein the at least one post includes a plurality of posts corresponding with the plurality of longitudinal slots.
17. The system of claim 15, wherein the spindle further includes a flange projecting radially outwardly relative to the base and proximally spaced from the hub to define a circumferential trough.
18. The system of claim 17, wherein the at least one post includes a proximal shoulder and a distal head, the shoulder sized to slidably nest within the longitudinal slot and the head sized to slidably nest within the trough.
19. The system of claim 18, wherein a circumferential width of the head is larger than a circumferential width of the shoulder.
20. The system of claim 19, wherein the shoulder and the head collectively define a T-like shape.
21. The system of claim 15, wherein the system is further configured to provide a deployment condition in which the distal end of the delivery sheath assembly is proximal the hub to permit the post to release from the slot, including a head of the post sliding along the curved proximal segment of the hub outer surface.
22. The system of claim 21, wherein the stent frame is configured to radially self-expand from a compressed arrangement to a normal arrangement, and further wherein the loaded condition that includes the delivery sheath assembly compressively retaining the prosthetic heart valve in the compressed arrangement.

23. The system of claim 22, wherein the deployment condition includes the stent frame self-expanding to the normal arrangement.
24. The system of claim 15, wherein the delivery device further includes: a release sheath assembly disposed between the delivery sheath assembly and the spindle in the loaded state, the release sheath assembly including a release sheath slidably received over at least the proximal segment of the hub in the loaded state.
25. The system of claim 24, wherein the release sheath forms at least one longitudinal notch extending from a distal end of the release sheath, and further wherein upon final assembly in the loaded condition, the at least one notch is longitudinally aligned with the at least one slot.
26. The system of claim 25, wherein the system is further configured to provide a deployment condition includes the release sheath proximally retracted from the hub and the at least one post self-pivoting through the at least one slot and the at least one notch.
27. The system of claim 26, wherein the at least one post includes a distal shoulder and a proximal head, and further wherein the spindle forms a circumferential trough proximal the hub such that the loaded condition includes the shoulder disposed within the slot and the head disposed within the trough, the head being releasably captured within the trough by the release sheath.
28. A method of percutaneously deploying a stented prosthetic heart valve to an implantation site of a patient, the method comprising: receiving a delivery device loaded with a radially expandable prosthetic heart valve having a stent frame to which a valve structure is attached, the delivery device including a delivery sheath assembly containing the prosthetic heart valve in a compressed arrangement over an inner shaft in a loaded state of the device, and a spindle attached to the shaft, the spindle including: a tubular base, a hub projecting radially outwardly relative to the base and defining at least one longitudinal slot and an outer surface forming a proximal segment and a distal segment, the proximal segment being curved in extension toward the distal segment, wherein a post of the stent frame is slidably captured within the at least one slot in the loaded state; delivering the prosthetic heart valve in the compressed arrangement through a bodily lumen of the patient and to the implantation site via the delivery device in the loaded state; proximally retracting the delivery sheath assembly from the prosthetic heart valve; and permitting the post to release from the at least one slot, including a surface of the post sliding along the curved proximal segment of the hub outer surface such that the prosthetic heart valve deploys from the delivery device.
29. The method of claim 28, wherein the at least one longitudinal slot includes a plurality of circumferentially spaced longitudinal slots, and further wherein the at least one post includes a plurality of posts corresponding with the plurality of longitudinal slots.
30. The method of claim 28, wherein the stent frame is configured to radially self-expand from a compressed arrangement to a normal arrangement, and further wherein the loaded state includes the delivery sheath assembly compressively retaining the prosthetic heart valve in the compressed arrangement.
31. The method of claim 28, wherein the delivery device further includes: a release sheath assembly disposed between the delivery sheath assembly and the spindle in the loaded state, the release sheath assembly including a release sheath slidably received over at least the proximal segment of the hub.
32. The method of claim 31, wherein the release sheath forms at least one longitudinal notch extending from a distal end of the release sheath, and further wherein permitting the post to release from the at least one slot includes the post pivoting relative to the spindle such that a portion of the post moves through the at least one slot and a corresponding one of the at least one notch

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.