\sim	
S m	ntn
ЭШ	

[45] Reissued Nov. 29, 1983

[54]	METHOD AND	STRUCTURE FOR FLOW	3.044,302 7/1962	Knauth 73/434
[54]	MEASUREMEN			Alspach et al
	MEASUREME	N1	3,049,919 8/1962	Roth 73/228
[75]	Inventor: Jam	es E. Smith, Boulder, Colo.	3,080,750 3/1963	Wiley et al
• •			3,087,325 4/1963	Roth 73/3
[73]	Assignee: Mic	ro Motion, Inc., Boulder, Colo.	3,096,646 7/1963	Peirce 73/228
[21]	A1 No. 249	071	3,108,475 10/1963	Henderson .
[21]	Appl. No.: 348,	0/1	3,132,512 5/1964	Roth .
[22]	Filed: Feb.	. 11, 1982	3,138,955 6/1964	Uttley .
£,		•		Karlby et al
Related U.S. Patent Documents		3,167,691 1/1965	Halista 317/157	
	Relateu C	5. I atent Documents	3,218,851 11/1965	•
Reiss	sue of:		3,232,110 2/1966	
[64]	Patent No.:	4,187,721		Cushing 73/861.63 X
• •	Issued:	Feb. 12, 1980	3,261,205 7/1966	
	Appl. No.:	926,468	3,276,257 10/1966	
	Filed:	Jul. 20, 1978	3,276,258 10/1966	Rowley .
	I iioo.	541. 45, 25. 5	3,298,221 1/1967	
U.S.	Applications:		3,303,705 2/1967	
[63]	Continuation-in-	part of Ser. No. 818,475, Jul. 25, 1977,		Banks 73/32
• •	abandoned.		3,329,019 7/1967	•
	- 63.1	CO1E 1/96	3,339,400 9/1967	
[51]			3,344,666 10/1967	Rilett .
[52]			3,349,004 10/1907	T:
[58]	Field of Search	73/32 A, 434, 505, 861.18,	3,350,936 11/1967 3,355,944 12/1967	
		73/861.35, 861.37, 861.38	3,385,104 5/1968	•
[54]	Da	ferences Cited	3,396,579 8/1968	
• •		3,449,940 6/1969		
	U.S. PAT	ENT DOCUMENTS	3,449,941 6/1969	
	2 (24 109 1 /1052	Pearson .	3,456,491 7/1969	
		Poole et al 73/32	3,481,509 12/1969	
	2,033,402 4/1933	Barnaby et al	3,485,098 12/1969	
		Poole et al	3,533,285 10/1970	•
		Brown 73/228	3,555,900 1/1971	
	2,811,854 11/1957		3,575,052 4/1971	
	2,813,423 11/1957			Shiba .
	2,821,084 1/1958		3,589,178 6/1971	Germann .
	2,831,349 4/1958	Altfillisch et al	3,608,374 9/1971	
	2,834,209 5/1958		3,613,451 10/1971	
	2,865,201 12/1958		3,625,055 12/1971	
	2,877,649 3/1959	Powers .	3,677,086 7/1977	
	2,889,702 6/1959			Arutunian et al
	2,897,672 8/1959	Glasbrenner et al 73/228	3,728,893 4/1973	Janssen 73/32
	2,914,945 12/1959	Cleveland .	3,740,586 6/1973	
	2,923,154 2/1960		3,762,217 10/1973	
	2,934,951 5/1960	Li.	3,839,915 10/1974	
	2,943,476 7/1960	Bernstein 73/32	3,842,681 10/1974	
	2,943,487 7/1960	Potter .	3,876,927 4/1975	
	2,956,431 10/1960	Westerheim 73/32		Pratt, Jr. et al
	3,039,310 6/1962	Copland et al 73/434	3,927,565 12/1975	r i aviiii ct ai

3,955,401	5/1976	Catherall 73/32			
4,051,723	10/1977	Head et al			
4.056,976	11/1977	Hildebrand .			
4,109,524	8/1978	Smith .			
4,127,028	11/1978	Cox et al 73/861.			
FOREIGN PATENT DOCUMENTS					
2249269	4/1974	Fed. Rep. of Germany .			
2145387	2/1975	France.			
32-6595	8/1957	Japan .			
44-18531	8/1969	Japan .			
46-19827	6/1971	Japan .			
117091	5/1958	U.S.S.R			
146982	4/1961	U.S.S.R			
149900	11/1961	U.S.S.R			
159678	12/1963	U.S.S.R.			
171651	5/1965	U.S.S.R			
400838	10/1973	U.S.S.R			
426170	4/1974	U.S.S.R			
486247	9/1975	U.S.S.R			
	OTHER	PURI ICATIONS			

OTHER PUBLICATIONS

A. Treatise; Continuous Measurement of Unsteady Flow, by G. P. Katys, translated from the Russian by D. P. Barrett, MacMillan Company, New York, 1964.


Primary Examiner—Jerry W. Myracle Attorney, Agent, or Firm—Irons & Sears

[57] ABSTRACT


Apparatus and method for mass flow measurement utilizing a substantially "U" shaped conduit mounted in a cantilever manner at the legs thereof, [means for oscillating the conduit, and means for measuring 3 so that, when the conduit is oscillated, sensors mounted on the conduit can measure the Coriolis force by measurement of the force moment or the angular motion of the conduit around an axis substantially symmetrical to the legs of the conduit. The force moment is measured by sensing incipient movement around the axis, and generating and measuring a nulling force. In preferred embodiments, the oscillating means are mounted on a spring arm having a natural frequency substantially equal to that of the "U" shaped conduit, and in a particularly preferred [displacement] embodiment the measuring [means are sensors] sensors are mounted on the "U" shaped conduit and adapted to measure, with proper direction sense, the time differential between the leading and trailing portions of the "U" shaped conduit passing through the plane of the "U" shaped conduit at substantially midpoint of the oscillation thereof.

55 Claims, 14 Drawing Figures

Nov. 29, 1983



U.S. Patent








Fig. 10

DOCKET A L A R M

Explore Litigation Insights



Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

