

MODERN
DICTIONARY
of
ELECTRONICS


SIXTH EDITION

REVISED AND UPDATED

Rudolf F. Graf


Newnes is an imprint of Butterworth-Heinemann

Copyright © 1997 by Butterworth-Heinemann

 A member of the Reed Elsevier group

All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

 Recognizing the importance of preserving what has been written, Butterworth-Heinemann prints its books on acid-free paper whenever possible.

Library of Congress Cataloging-in-Publication Data

Graf, Rudolf F.

Modern dictionary of electronics / by Rudolf F. Graf. — 6th ed.

p. cm.

Reprint. Originally published: Indianapolis, Ind. : H.W. Sams,

© 1984.

ISBN 0-7506-9870-5

1. Electronics—Dictionaries.

TK7804.G67 1996

621.381'03—dc 20

96-25894

CIP

British Library Cataloguing-in-Publication Data

A catalogue record for this book is available from the British Library.

The publisher offers special discounts on bulk orders of this book.

For information, please contact:

Manager of Special Sales

Butterworth-Heinemann

313 Washington Street

Newton, MA 02158-1626

Tel: 617-928-2500

Fax: 617-928-2620

For information on all Newnes electronics publications available, contact our World Wide Web home page at: <http://www.bh.com/bh>

Edited by: *Charlie Buffington* and *Jack Davis*

Illustrated by: *T.R. Emrick*

Printed in the United States of America

10 9 8 7 6 5 4 3 2

We are
advances
To keep
reflect the
ics. It mu
explain to
quely suit

Those
effectivel
tion. Orig
definition
actual use

Every
of the el
electronic
municatio
which its
a clear an
level of c
prise that
probably
contains
and relate
fifth editi
filled the
were revi
enhance t
definition
updated, :

While t
the field o
evolve an
ings. The
periodical
welcomed

tone. In telegraphy service, the carrier is keyed to produce the modulation.

modulated light—Light whose intensity has been made to vary in accordance with variations in an audio-frequency or code signal.

modulated oscillator—An oscillator the output frequency of which is varied by an input signal.

modulated photoelectric alarm system—A photoelectric alarm system in which the transmitted light beam is modulated in a predetermined manner and in which the receiving equipment will signal an alarm unless it receives the properly modulated light.

modulated signal generator—A device which produces an output signal that may be changed in amplitude and/or frequency according to a desired pattern. It is calibrated in units of both power (or voltage) and frequency.

modulated stage—The radio-frequency stage to which the modulator is coupled and in which the continuous wave (carrier wave) is modulated, in accordance with the system of modulation and the characteristics of the modulating wave.

modulated wave—A carrier wave in which the amplitude, frequency, or phase varies in accordance with intelligence signal being transmitted.

modulating amplifier using variable reactance—A very-high-frequency electron-beam parametric amplifier with bandpass characteristics that are independent of gain, and which is unconditionally stable.

modulating electrode—In a cathode-ray tube, an electrode to which a potential is applied to control the magnitude of the beam current.

modulating signal—See Modulating Wave.

modulating wave—Also called modulating signal, or simply signal. A wave which varies some characteristic (i.e., frequency, amplitude, phase) of the carrier.

modulation—1. The process of modifying some characteristic of a wave (called a carrier) so that it varies in step with the instantaneous value of another wave (called a modulating wave or signal). The carrier can be a direct current, an alternating current (provided its frequency is above the highest frequency component in the modulating wave), or a series of regularly repeating, uniform pulses called a pulse chain (provided their repetition rate is at least twice that of the highest frequency to be transmitted). 2. The controlled variation of frequency, phase and/or amplitude of a carrier wave of any frequency in order to transmit a message.

method may be either pulse modulation (digital) or intensity modulation (analog).

4. The process of varying one signal with another. 5. The imposing of a signal on some type of transmission or storage medium, such as a radio carrier or magnetic tape. 6. The process, or results of the process, whereby some characteristic of one signal is varied in accordance with another signal. The modulated signal is called the carrier and may be modulated in three fundamental ways: by varying the amplitude (amplitude modulation) by varying the frequency (frequency modulation) or by varying the phase (phase modulation).


modulation capability—The maximum percentage of modulation possible without objectionable distortion.

modulation code—A code used to cause variations in a signal in accordance with a predetermined scheme; normally used to alter or modulate a carrier wave to transmit data.

modulation distortion—Distortion occurring in the radio-frequency amplifier tube of a receiver when the operating point is at the bend of the grid-voltage/plate-current characteristic curve. As a result, the plate-current changes are greater on positive than on negative half-cycles. The effect is equivalent to an increase in the percent of modulation.

modulation envelope—A curve, drawn through the peaks of a graph, showing how the waveform of a modulated carrier represents the waveform of the intelligence carried by the signal. The modulation envelope is the intelligence waveform.

INTELLIGENCE (MODULATION ENVELOPE)



CARRIER

Modulation envelope.

modulation factor—In an amplitude-modulated wave, the ratio of half the difference between the maximum and minimum amplitudes to the average amplitude. This ratio is multiplied by 100 to obtain the percentage of modulation.

modulation frequency—That signal which causes the output frequency of an oscillator to be modulated.

modulation index—1. In frequency modulation with a sinusoidal modulating wave, the ratio of the frequency deviation