

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:	Chistyakov	GROUP NO.:	1795
SERIAL NO.:	10/897,257	EXAMINER:	Rodney Glenn McDonald
FILING DATE:	July 22, 2004		
TITLE:	METHODS AND APPARATUS FOR GENERATING HIGH-DENSITY PLASMA		

Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

AMENDMENT AND RESPONSE

Sir:

The following remarks are responsive to the Office Action mailed on March 27, 2008 in the above-identified patent application. Consideration of the following remarks, and allowance of the claims, as presented, is respectfully requested. A Petition for a three month extension of time, up to and including September 27, 2008 is submitted herewith. Authorization to charge Attorney's charge card for the extension fee and any other proper fees was given in the EFS-Web filing submission papers.

Amendments to the claims begin on page 2 of this paper.

Remarks are on page 9 of this paper.

INTEL 1108

Amendments to the Claims

Please amend claims 45, 58, 70, and 78 as follows:

45. (Currently Amended): An apparatus for generating a strongly-ionized plasma, the apparatus comprising:

- a. an ionization source that generates a weakly-ionized plasma from a feed gas contained in a chamber, the weakly-ionized plasma ~~reducing~~ substantially eliminating the probability of developing an electrical breakdown condition in the chamber; and
- b. a power supply that supplies power to the weakly-ionized plasma through an electrical pulse that is applied across the weakly-ionized plasma, the electrical pulse having at least one of a magnitude and a rise-time that is sufficient to transform the weakly-ionized plasma to a strongly-ionized plasma without developing an electrical breakdown condition in the chamber.

46. (Original): The apparatus of claim 45 wherein the pulsed power supply is a component in the ionization source.

47. (Original): The apparatus of claim 45 wherein the ionization source is chosen from the group comprising an electrode coupled to a DC power supply, an electrode coupled to an AC power supply, a UV source, an X-ray source, an electron beam source, an ion beam source, an inductively coupled plasma source, a capacitively coupled plasma source, and a microwave plasma source.

48. (Original): The apparatus of claim 45 wherein the power supply generates a constant power.
49. (Original): The apparatus of claim 45 wherein the power supply generates a constant voltage.
50. (Original): The apparatus of claim 45 wherein the power supply supplies power to the weakly ionized plasma at a time that is between about fifty microsecond and five second after the ionization source generates the weakly-ionized plasma.
51. (Original): The apparatus of claim 45 wherein the power supply supplies power to the weakly ionized plasma for a duration that is sufficient to generate a quasi-static electric field across the weakly-ionized plasma.
52. (Original): The apparatus of claim 45 wherein the cathode is generally formed in the shape of at least one circular disk.
53. (Original): The apparatus of claim 45 wherein the ionization source generates the weakly-ionized plasma from a reactive feed gas contained in a chamber.
54. (Original): The apparatus of claim 45 further comprising a magnet that is positioned to generate a magnetic field proximate to the weakly-ionized plasma, the magnetic field trapping electrons in the weakly-ionized plasma.
55. (Original): The apparatus of claim 54 wherein the magnet generates a magnetic field that is shaped to trap secondary electrons that are produced by ion bombardment.

56. (Original): The apparatus of claim 45 further comprising a gas line that is coupled to the chamber, the gas line supplying feed gas to the strongly-ionized plasma that transports the strongly-ionized plasma by a rapid volume exchange.
57. (Original): The apparatus of claim 56 wherein the gas volume exchange permits additional power to be absorbed by the strongly-ionized plasma.
58. (Currently Amended): A method for generating a strongly-ionized plasma, the method comprising:
- a. ionizing a feed gas in a chamber to form a weakly-ionized plasma that ~~reduces~~ substantially eliminates the probability of developing an electrical breakdown condition in the chamber; and
 - b. supplying an electrical pulse across the weakly-ionized plasma that excites atoms in the weakly-ionized plasma, thereby generating a strongly-ionized plasma without developing an electrical breakdown condition in the chamber.
59. (Original): The method of claim 58 wherein the ionizing the feed gas comprises exposing the feed gas to one of a static electric field, an pulsed electric field, UV radiation, X-ray radiation, electron beam radiation, and an ion beam.
60. (Original): The method of claim 58 wherein at least one of a rise time and magnitude of the electrical pulse supplied across the weakly-ionized plasma is selected to increase a density of the weakly-ionized plasma.

61. (Original): The method of claim 58 wherein at least one of a rise time and magnitude of the electrical pulse supplied across the weakly-ionized plasma is selected to excite atoms in the weakly-ionized plasma to generate secondary electrons that increase an ionization rate of the weakly-ionized plasma.
62. (Original): The method of claim 58 wherein at least one of a rise time and magnitude of the electrical pulse supplied across the weakly-ionized plasma is selected to improve uniformity of the strongly-ionized plasma.
63. (Original): The method of claim 58 further comprising supplying feed gas to the strongly-ionized plasma to transport the strongly-ionized plasma by a rapid volume exchange.
64. (Original): The method of claim 63 wherein the transport of the strongly-ionized plasma by the rapid volume exchange permits additional power to be absorbed by the strongly-ionized plasma.
65. (Original): The method of claim 58 wherein the supplying the electrical pulse comprises applying a quasi-static electric field across the weakly-ionized plasma.
66. (Original): The method of claim 58 wherein the electrical pulse comprises a rise time that is between about 0.1 microsecond and 10 seconds.
67. (Original): The method of claim 58 wherein a peak plasma density of the weakly-ionized plasma is less than about 10^{12} cm^{-3} .

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.