## EXHIBIT 1013

**DOCKET A L A R M** Find authenticated court documents without watermarks at <u>docketalarm.com</u>. >

Network Working Group Request for Comments: 1541 Obsoletes: 1531 Category: Standards Track R. Droms Bucknell University October 1993

#### Dynamic Host Configuration Protocol

Status of this memo

This RFC specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" for the standardization state and status of this protocol. Distribution of this memo is unlimited.

#### Abstract

The Dynamic Host Configuration Protocol (DHCP) provides a framework for passing configuration information to hosts on a TCP/IP network. DHCP is based on the Bootstrap Protocol (BOOTP) [7], adding the capability of automatic allocation of reusable network addresses and additional configuration options [19]. DHCP captures the behavior of BOOTP relay agents [7, 23], and DHCP participants can interoperate with BOOTP participants [9]. Due to some errors introduced into RFC 1531 in the editorial process, this memo is reissued as RFC 1541.

#### Table of Contents

1.	Introduction		2
1.1	Related Work		4
1.2	Problem definition and issues		4
1.3	Requirements		5
1.4	Terminology		6
1.5	Design goals		6
	rotocol Summary		
2.1	Configuration parameters repository		10
2.2	Dynamic allocation of network addresses		11
З. 1	he Client-Server Protocol	•	11
3.1	Client-server interaction - allocating a network address		12
3.2	Client-server interaction - reusing a previously allocated		
	network address		17
3.3	Interpretation and representation of time values		19
3.4	Host parameters in DHCP		19
3.5	Use of DHCP in clients with multiple interfaces		20
3.6	When clients should use DHCP		20
4. 5	pecification of the DHCP client-server protocol		21

DOCKE.

[Page 1]

10/17/0010

10/17/0010

	Dynamic Host	Configuration	Protocol	October 19
<pre>4.2 DHCP serv 4.3 DHCP serv 4.3.1 DHCPDIS 4.3.2 DHCPREQ 4.3.3 DHCPDEC 4.3.4 DHCPREI 4.4 DHCP clie 4.4.1 Initial 4.4.2 Initial 4.4.3 Initial 4.4.4 Reacqui 4.4.5 DHCPREI 5. Acknowledg 6. References 7. Security C 8. Author's A</pre>	ing and sending er administration COVER message. UEST message . LINE message . EASE message . it behavior. ization and all ization with a sition and expi EASE ments considerations. ddress guration Parame	lve controls .	cwork address ddress cver address	.       .
List of Figures	J			
<ol> <li>Format of</li> <li>Timeline of servers wh</li> <li>Timeline of servers wh</li> </ol>	a DHCP message the 'flags' fie liagram of messa en allocating a liagram of messa en reusing a pr sition diagram	eld	between DHCP address between DHCP cated network	1 client and 1 client and address 1
List of Tables				
2. DHCP messa 3. Fields and	n of fields in ges options used k options used k		· · · · · · · ·	· · · · · · 1 · · · · · 2
1. Introduction				
parameters to	ost Configurati			
	o a host and a	-specific conf	figuration pa	rameters from
DHCP server t addresses to DHCP is built hosts allocat to dynamicall	o a host and a	specific conf mechanism for erver model, wh esses and deliv osts. Througho	figuration pa allocation o here designation ver configura but the remain	rameters from f network ed DHCP serve tion paramete nder of this
DHCP server t addresses to DHCP is built hosts allocat to dynamicall	o a host and a hosts. on a client-se e network addre y configured ho	specific conf mechanism for erver model, wh esses and deliv osts. Througho	figuration pa allocation o here designation ver configura but the remain	rameters from f network ed DHCP serve tion paramete nder of this
DHCP server t addresses to DHCP is built hosts allocat to dynamicall document, the	o a host and a hosts. on a client-se e network addre y configured ho term "server"	specific conf mechanism for erver model, wh esses and deliv osts. Througho	figuration pa allocation o here designativer configura but the remained ost providing	rameters from f network ed DHCP serve tion paramete nder of this initializati

CITE CITE AT 1

1 / - - -

/٣

10 - 4 - 4

10/17/0010

requesting initialization parameters from a DHCP server.

A host should not act as a DHCP server unless explicitly configured to do so by a system administrator. The diversity of hardware and protocol implementations in the Internet would preclude reliable operation if random hosts were allowed to respond to DHCP requests. For example, IP requires the setting of many parameters within the protocol implementation software. Because IP can be used on many dissimilar kinds of network hardware, values for those parameters cannot be guessed or assumed to have correct defaults. Also, distributed address allocation schemes depend on a polling/defense mechanism for discovery of addresses that are already in use. IP hosts may not always be able to defend their network addresses, so that such a distributed address allocation scheme cannot be guaranteed to avoid allocation of duplicate network addresses.

DHCP supports three mechanisms for IP address allocation. In "automatic allocation", DHCP assigns a permanent IP address to a host. In "dynamic allocation", DHCP assigns an IP address to a host for a limited period of time (or until the host explicitly relinquishes the address). In "manual allocation", a host's IP address is assigned by the network administrator, and DHCP is used simply to convey the assigned address to the host. A particular network will use one or more of these mechanisms, depending on the policies of the network administrator.

Dynamic allocation is the only one of the three mechanisms that allows automatic reuse of an address that is no longer needed by the host to which it was assigned. Thus, dynamic allocation is particularly useful for assigning an address to a host that will be connected to the network only temporarily or for sharing a limited pool of IP addresses among a group of hosts that do not need permanent IP addresses. Dynamic allocation may also be a good choice for assigning an IP address to a new host being permanently connected to a network where IP addresses are sufficiently scarce that it is important to reclaim them when old hosts are retired. Manual allocation allows DHCP to be used to eliminate the error-prone process of manually configuring hosts with IP addresses in environments where (for whatever reasons) it is desirable to manage IP address assignment outside of the DHCP mechanisms.

The format of DHCP messages is based on the format of BOOTP messages, to capture the BOOTP relay agent behavior described as part of the BOOTP specification [7, 23] and to allow interoperability of existing BOOTP clients with DHCP servers. Using BOOTP relaying agents eliminates the necessity of having a DHCP server on each physical network segment.

Droms [Page 3] RFC 1541 Dynamic Host Configuration Protocol October 1993

#### 1.1 Related Work

DOCKE.

There are several Internet protocols and related mechanisms that address some parts of the dynamic host configuration problem. The Reverse Address Resolution Protocol (RARP) [10] (through the

1/70

extensions defined in the Dynamic RARP (DRARP) [5]) explicitly addresses the problem of network address discovery, and includes an automatic IP address assignment mechanism. The Trivial File Transfer Protocol (TFTP) [20] provides for transport of a boot image from a boot server. The Internet Control Message Protocol (ICMP) [16] provides for informing hosts of additional routers via "ICMP redirect" messages. ICMP also can provide subnet mask information through the "ICMP mask request" message and other information through the (obsolete) "ICMP information request" message. Hosts can locate routers through the ICMP router discovery mechanism [8].

BOOTP is a transport mechanism for a collection of configuration information. BOOTP is also extensible, and official extensions [17] have been defined for several configuration parameters. Morgan has proposed extensions to BOOTP for dynamic IP address assignment [15]. The Network Information Protocol (NIP), used by the Athena project at MIT, is a distributed mechanism for dynamic IP address assignment [19]. The Resource Location Protocol RLP [1] provides for location of higher level services. Sun Microsystems diskless workstations use a boot procedure that employs RARP, TFTP and an RPC mechanism called "bootparams" to deliver configuration information and operating system code to diskless hosts. (Sun Microsystems, Sun Workstation and SunOS are trademarks of Sun Microsystems, Inc.) Some Sun networks also use DRARP and an auto-installation mechanism to automate the configuration of new hosts in an existing network.

In other related work, the path minimum transmission unit (MTU) discovery algorithm can determine the MTU of an arbitrary internet path [14]. Comer and Droms have proposed the use of the Address Resolution Protocol (ARP) as a transport protocol for resource location and selection [6]. Finally, the Host Requirements RFCs [3, 4] mention specific requirements for host reconfiguration and suggest a scenario for initial configuration of diskless hosts.

1.2 Problem definition and issues

DHCP is designed to supply hosts with the configuration parameters defined in the Host Requirements RFCs. After obtaining parameters via DHCP, a host should be able to exchange packets with any other host in the Internet. The parameters supplied by DHCP are listed in Appendix A.

[Page 4] Dynamic Host Configuration Protocol October 1993

Not all of these parameters are required for a newly initialized host. A client and server may negotiate for the transmission of only those parameters required by the client or specific to a particular subnet.

DHCP allows but does not require the configuration of host parameters not directly related to the IP protocol. DHCP also does not address registration of newly configured hosts with the Domain Name System (DNS) [12, 13].

IT INTERNALL.

Droms

DOCKE.

#### RFC 1541

10/17/0010

## DOCKET A L A R M



# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## **Real-Time Litigation Alerts**



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## **Advanced Docket Research**



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## **Analytics At Your Fingertips**



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

### LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

### FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.