

070805



17169 U.S. PTO

PTO/SB/16 (07-05)

Approved for use through 07/31/2006. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. ED 866827955 US

113564 U.S. PTO
68/697613



070805

INVENTOR(S)		
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
Luben	Hristov	Southampton, Hampshire, GB
Additional inventors are being named on the _____ separately numbered sheets attached hereto		
TITLE OF THE INVENTION (500 characters max):		
Two Dimensional Position Sensor		
Direct all correspondence to: CORRESPONDENCE ADDRESS		
<input checked="" type="checkbox"/> The address corresponding to Customer Number:	<input type="text" value="20191"/>	
OR		
<input type="checkbox"/> Firm or Individual Name		
Address		
City	State	Zip
Country	Telephone	Email
ENCLOSED APPLICATION PARTS (check all that apply)		
<input checked="" type="checkbox"/> Application Data Sheet. See 37 CFR 1.76	<input type="checkbox"/> CD(s), Number of CDs _____	
<input checked="" type="checkbox"/> Specification Number of Pages <u>25 26</u>	<input type="checkbox"/> Other (specify) <u>Return post card</u>	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets <u>8 8</u>		
Fees Due: Filing Fee of \$200 (\$100 for small entity). If the specification and drawings exceed 100 sheets of paper, an application size fee is also due, which is \$250 (\$125 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).		
METHOD OF PAYMENT OF FILING FEES AND APPLICATION SIZE FEE FOR THIS PROVISIONAL APPLICATION FOR PATENT		
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.		
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fee and application size fee (if applicable).	<input type="text" value="100"/>	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached	TOTAL FEE AMOUNT (\$)	
<input checked="" type="checkbox"/> The Director is hereby authorized to charge the filing fee and application size fee (if applicable) or credit any overpayment to Deposit Account Number: <u>50 1012</u> . A duplicative copy of this form is enclosed for fee processing.		
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.		
<input checked="" type="checkbox"/> No.		
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____		

SIGNATURE

TYPED or PRINTED NAME David Kiewit

TELEPHONE 727 866 0669

Date July 08, 2005

REGISTRATION NO. 34640
(if appropriate)

Docket Number: P2D

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

TITLE OF THE INVENTION

TWO-DIMENSIONAL POSITION SENSOR

BACKGROUND OF THE INVENTION

5 The invention relates to a capacitive position sensor for determining the position of an object within a two-dimensional sensing area.

 The use of two-dimensional touch-sensitive position sensors is becoming more common. Examples include the use of position sensors in laptop computers in place of mouse pointing devices, as control panels for receiving user inputs to control an
10 appliance, or particularly as a glass touchscreen apparatus having an X-Y coordinate output. Some applications require a clear sensing layer so that a display can be viewed beneath the screen, while others only require an opaque touch surface, for example for a keypanel on a kitchen appliance or a PC peripheral.

 Touch-sensitive position sensors are frequently preferred to mechanical
15 devices because they provide for a more robust interface and are often considered to be more aesthetically pleasing. Furthermore, because touch-sensitive position sensors require no moving parts to be accessible to a user, they are less prone to wear than their mechanical counterparts and can be provided within a sealed outer surface. This makes their use where there is a danger of dirt or fluids entering a device being
20 controlled particularly attractive.

 There exists a large body of art involving 2D touchpanels and screens. They can be generally divided into two classifications: those that report an X-Y coordinate of a more or less continuous nature ('XY' type), and those that have a discrete sensing surface ('discrete' type) having predefined key areas that are fixed by physical
25 geometry. The XY type find dominant use over LCD or other display types while the latter find use in fixed function key panels. There are exceptions to this, for example touchpad surfaces on laptops report XY position but are opaque. XY types invariably involve a sensing surface on the user-side or 'first surface' of the touch area. For example, both continuous resistive and capacitive touch screens involve a sensing
30 layer that must be either physically depressed by the user or touched almost directly,

or at most through a thin layer of insulation (as in mouse touchpads). These types require that the product have a bezel opening to allow direct or near-direct contact by the user with the sensing layer. A significant disadvantage of these types is that there has to be an opening in the panel, which requires sealing against moisture and dirt and hence is expensive to mount. Furthermore the sensing layer is directly exposed to abuse and can be easily damaged by sharp objects or abrasion. While robust capacitive types are known which have buried wires inside a glass layer (e.g. US 5,844,506 [1]), these still require a bezel opening in a panel which must be sealed, and require two sensing layers as a matrix due to the need to cross X and Y conductors. Furthermore these screens are very expensive to produce and in fact cannot be produced on a mass scale; additionally the sensing circuitry is known to be complex and expensive.

In the field of discrete touch buttons, it has been known for some time that capacitive keys can be placed behind a solid surface having no requirement for a bezel opening. However these types only provide for limited resolution, as predefined by the location of discrete electrode shapes. An example of this can be found in US 4,954,823 [2], Figures 4 and 6. While it is well known that these electrodes can be made of a single layer of clear conductor such as Indium Tin Oxide ('ITO') to allow placement over a bezel-less display, for example by the application of the layer as a film on the back of a subsection of a panel, nevertheless the technology is limited to discrete touch areas based on the number, size, and placement of discrete electrodes.

Figure 1 schematically shows in plan view a touch pad 2 of the type described in US 4,954,823 [2], but laid out in an orthogonal array. The touch pad 2 comprises a grid of discrete electrodes 4 mounted on an insulating substrate 6. Each electrode is connected to a channel of capacitance measurement circuitry in a controller 8. US 5,463,388 [3] describes this geometry in passing in conjunction with its Figure 1, to show how such an array can be used to determine a position of an object proximate the sensing layer via a method of determining a centroid of the signals from each pad. However US 5,463,388 fails to show how to implement such a design and describes instead a matrix of conductors along with a centroidal calculation of continuous X-Y position. In fact it is not practical to have so many sensing channels as one per sense pad, and a matrix arrangement is much more efficient as described below.

Figure 2 schematically shows a position sensor 12 based on a matrix of conductors as described in US 5,463,388 [3]. The position sensor 12 comprises a number of vertically aligned strip electrodes (columns) 14 mounted on an upper surface of an insulating substrate 16 and a number of horizontally aligned strip electrodes (rows) 15 mounted on an opposing lower surface of the insulating substrate. Each vertical strip electrode is connected to a channel of capacitance measurement circuitry in a controller 18. Thus, this type of position sensor allows an X-Y coordinate output of a continuous nature by means of calculation of a centroid of capacitance among the rows and columns rather than among discrete pads. However this type requires two sensing layers so that the matrix traces can be routed, and does not allow the use of optically clear materials.

The ideal touch surface would eliminate the need for a bezel opening (or at least, make it optional), have an inexpensive sensing surface that is applied to the rear of the panel surface that can project through a reasonable thickness of panel material (e.g. up to 4mm of glass or plastic), optionally require only one sensing layer with no crossovers in the sensing region, be usable with clear sensing layers such as ITO, have an XY type of output, and have a compact, inexpensive driver circuit. This set of ideal goals has not been achieved with any known prior art.

SUMMARY OF THE INVENTION

According to a first aspect of the invention there is provided a capacitive position sensor for determining the position of an object in a sensing area, the sensor comprising a substrate having a surface with an arrangement of electrodes mounted thereon, wherein the electrodes define an array of sensing cells arranged in columns and rows to form the sensing area, each sensing cell including a column sensing electrode and a row sensing electrode, the column sensing electrodes of sensing cells in the same column being electrically coupled together and the row sensing electrodes of sensing cells in the same row being electrically coupled together, wherein row sensing electrodes of sensing cells at opposing ends of at least one of the rows are electrically coupled to one another by respective row wrap-around connections made outside of the sensing area.

Thus a position sensor having electrodes on only a single layer of a substrate can be provided. Furthermore, because the position sensor employs an intersecting array of columns and rows of sensing electrodes (i.e. a matrix), fewer measurement channels are required than with sensors based on an array of discrete electrodes.

Because the position sensor is based on sensing electrodes on only a single surface, it can be cheaper to manufacture than known double-sided position sensors. This also means the sensing electrodes can be deposited directly onto a surface for which the opposing surface is inaccessible (e.g. a display screen). The sensing electrodes can also be deposited on an inside surface of a device housing, thus removing the need for any protective covering that might be required if electrodes were also required to be on the outer surface.

The electrical row wrap-around connections may comprise a conductive trace mounted on the substrate. This allows the connection outside of the sensing area to be made in the same processing step as the sensing electrodes within it. Alternatively, the row wrap-around connections may be made by a free wire appropriately connected to the respective row sensing electrodes.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.