


DOCKET A L A R M



Ensure Windows Compatibility with Sealevel ISA and PCI COM: Ports

Introducing the Ultra™ and COMM+™ series -- The Ideal Windows COM: ports

Sealevel, the leader in PC communications, now introduces two new lines of serial I/O cards for Windows. ISA and PCI Bus RS-232 and RS-485/422 products are available.



Features Include:

- Multiport RS-232 and RS-422/485 Adapters
- Data Rates Supported up to 460K bps
- 10 Interrupts to Choose From
- Interrupt Status Port for Windows Flexibility
- 16550 UARTs Standard / 16650 Optional · Includes Windows 95 INF Files, our Windows NT Configuration Utility and
- Help Files to Simplify Installation · Excellent Technical Support
- · Made in U.S.A.



VERSA COMM+4/EX







Sealevel Systems, Inc. P.O. Box 830 • Liberty, SC 29657 864.843.4343 • www.sealevel.com

All trademarks are the sole property of their respective owners

CIRCLE NO. 4



EDN. 275 Washington St, Newton, MA 02158. www.ednmag.com. Phone 1-617-964-3030; fax 1-617-558-4470. Address changes or subscription inquiries: phone 1-303-470-4445; fax 1-303-470-4280; cahners.subs@denver.cahners.com. Cahners Publishing, 8773 S Ridgeline Blvd, Highland Ranch, CO 80126. Include your mailing label.

PUBLISHING DIRECTOR, EDN WORLDWIDE Tim Tobeck 1-617-558-4454; ttobeck@edn.cahners.com **EDITORIAL DIRECTOR, EDN WORLDWIDE** Michael C Markowitz 1-617-558-4214;

ednmarkowitz@mcimail.com or m.markowitz@cahners.com

EXECUTIVE EDITOR

Gary Legg 1-617-558-4404; gary.legg@edn.cahners.com **MANAGING EDITOR**

Joan Lynch 1-617-558-4215; jlynch@edn.cahners.com. CONTACT FOR CONTRIBUTED TECHNICAL ARTICLES

TEST & MEASUREMENT: DAN STRASSBERG, SENIOR TECHNICAL EDITOR 1-617-558-4205; fax: 1-617-558-4470; ednstrassberg@

COMPONENTS, INTERCONNECT & POWER SUPPLIES: BILL TRAVIS, SENIOR TECHNICAL EDITOR; 1-617-558-4471; fax: 1-617-558-4470; b.travis@cahners.com

FPGAs, PLDs, Memories: Brian Dipert, Technical Editor 1-916-454-5242; fax: 1-916 454-5101; edndipert@worldnet.

DIGITAL ICS, COMMUNICATIONS: STEPHEN KEMPAINEN, TECHNICAL EDITOR; 1-415-643-1760; fax: 1-415-643-9513; ednkempainen@ worldnet.att.net

MICROPROCESSORS, DSPs: MARKUS LEVY, TECHNICAL EDITOR 1-916-939-1642; fax: 1-916-939-1650; markus.levy@worldnet.

EDA, ASICs: Jim Lipman, Technical Editor; 1-510-606-1370; fax: 1-510-606-1563; ednlipman@mcimail.com

Analog & Power ICs, RF Communications: Bill Schweber, **TECHNICAL EDITOR;** 1-617-558-4484; fax: 1-617-558-4470; bill.schweber@cahners.com

EMBEDDED SYSTEMS: WARREN WEBB, TECHNICAL EDITOR 1-619-513-3713; fax: 1-619-486-3646; www.ebb@cts.com

COMPUTER DESIGN, PERIPHERALS: MAURY WRIGHT, TECHNICAL EDITOR 1-619-748-6785; fax: 1-619-679-1861; mwright@abac.com

LEADING EDGE: FRANCES T GRANVILLE, SENIOR ASSOCIATE EDITOR 1-617-558-4344; f.granville@edn.cahners.com

ASK EDN, SIGNALS AND NOISE: BETH MORRISON, ASSOCIATE EDITOR 1-617-558-4333; bmorrison@edn.cahners.com

LITERATURE, CALENDAR: KASEY CLARK, ASSOCIATE EDITOR 1-617-558-4324; kase@cahners.com

EDITORIAL AND ART PRODUCTION

Diane Malone, Manager 1-617-558-4303 Ken Racicot, Senior Art Director 1-617-558-4708 Chinsoo Chung, Associate Art Director 1-617-558-4446 Patricia Shaughnessy, Production Editor 1-617-558-4206

WEBMASTER

Millie Gutierrez; millie@edn.cahners.com

CONTRIBUTING TECHNICAL EDITORS

David Brubaker, Jack Ganssle, Debora Grosse, Clive Maxfield, Robert Pease, Anne Watson Swager, Ron Mancini, Wolfram Blume, Howard Johnson, PhD

Assistant to Editorial Director, EDN Worldwide Kathy Leonard 1-617-558-4405; kathy.leonard@edn.cahners.com

EDITORIAL SECRETARY Cathy Greland 1-617-558-4681; cgreland@edn.cahners.com

PRODUCTION

Andrew Jantz, Group Manager 1-617-558-4372 Karen Banks, Production Manager 1-617-558-4441 Christian Adanalian, Production Assistant 1-617-558-4601

EDN EuropeBrian Kerridge, *Editor*, PO Box 377, Norwich NR14 6UQ, UK; +44
1508-528435; fax +44 1508-528430; ednkerridge@mcimail.com

EDN ASIA/EDN CHINA

Cahners Asia Ltd,19th Floor, Eight Commercial Tower, 8 Sun Yip St, Chai Wan, Hong Kong, Phone +852 2965-1555; fax +852 2976-0706. Chris Everett, *Publisher/Editor in Chief, EDN Asia*, chriseverett@rebi.com.hk Simon Lian, Assistant Technical Editor, EDN China, simonlian@rebi.com.hk

A member of the Reed Elsevier group

Win

Dee

High

High

HUI

This material may be protected by Copyright law (Title 17 U.S. Code)

LEADING EDGE

WHAT'S HOT IN THE DESIGN COMMUNITY

EDITED BY FRAN GRANVILLE

IC changes course of USB enumeration procedure



the

ol solution

tors and

Itage (5V)

hat lets you

hone sensi-

eble, bass,

ation into

All through

onder also

eamp. The

ntrol muting

d. A battery-

a "loop out"

ur designs,

omer® audio


ortable, it's v crank it up. The EZ-USB family of ICs from Anchor Chips integrates a high-performance microcontroller, includes hardware support for low-level USB signaling, and takes a new tack to maximize flexibility in the USB enumeration procedure. These features differentiate

Anchor's ICs from most other USB ICs and provide a singlechip USB implementation that can serve in applications ranging from cost-sensitive peripherals, such as pointing devices, to high-end devices, such as scanners.

The IC incorporates an 8051-compatible core with support from a legion of software-development tools from multiple vendors. Moreover, the core offers a fivefold boost in performance over off-the-shelf 8051 ICs. In addition, although most manufacturers minimize prices by using the microcontroller to handle low-level signal handshakes, the EZ-USB ICs include state machines that offload these task from the microcontroller. The hardware signaling leaves the microcontroller free to handle more peripheral functions and, therefore, allows designers to use the IC in more complex devices.

The ICs also use an enumeration scheme to maximize flexibility in peripherals via downloadable control firmware. The USB standard specifies that a peripheral must go through an enumeration procedure whenever the peripheral connects to the bus. During this procedure, the host assigns the peripheral a unique ID, and the peripheral provides the host with device descriptors that indicate the peripheral's capabilities.

In contrast, the EZ-USB ICs go through this enumeration procedure and establish a baseline configuration. The ICs then download new firmware from the host, simulate a disconnect/reconnect cycle, and repeat the enumeration, providing updated descriptors to the host. This software-based configuration scheme offers several advantages. For example, it simplifies software updates to peripherals, a feature that can be important in a new interface, such as USB. The



The EZ-USB family of ICs integrates an 8051 microcontroller with a USB interface that's handles all USB signaling. The IC supports postage-stamp-sized designs.

software-based configuration also enables you to develop multifunction peripherals. A DSP-based peripheral could take on the role of a modem during one session, for example, and an audio synthesizer during another session.

The company offers three versions of the EZ-USB. The AN2131S integrates 8 kbytes of RAM and 16 I/O lines and costs \$6.36 (10,000). The AN2131Q adds eight more I/O lines and costs \$7.31 (10,000), and the AN2141Q increases memory to 16 kbytes of RAM for \$8.72 (10,000). Anchor also offers an EZ-USB Xcelerator development kit for \$495. The kit includes a development board, an 8051 compiler, a general-purpose USB device driver, and sample firmware and driver code.—by Maury Wright

Anchor Chips, San Diego, CA. 1-619-613-7900, www. anchorchips.com. **Circle No. 520**

Firewire VXI slot-zero controller is first, fast, and low-cost

Hewlett-Packard's C-size E8491A slotzero controller and host-computer interface may be the first IEEE 1394 (Firewire) test-and-measurement hardware. The device transfers data bursts at 400 Mbps (50 Mbytes/sec). This speed accommodates the VXI bus' 40-Mbyte/sec transfer rate. Although observers call Firewire fast and elegant but costly, the E8491A costs only \$2500. HP claims that the E8491A makes the cost of Firewire only \$300 higher than that of products employ-

ing IEEE 488, whose transfer rate is less than 2% that of Firewire's. Compared with the MXI bus, which has become the standard for linking VXI cages to external host PCs, Firewire is both less expensive (the savings over HP's MXI interface can exceed \$3500) and faster (50 vs 32 Mbytes/sec).

Cabling is another advantage of the

www.ednmag.com

Evhibit 2060 Dago 03 of 03

EDN MARCH 2 1998 = 11

