



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : G06F 13/10</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/01820</p>
		<p>(43) International Publication Date: 14 January 1999 (14.01.99)</p>
<p>(21) International Application Number: PCT/US98/13397 (22) International Filing Date: 26 June 1998 (26.06.98) (30) Priority Data: 08/886,923 2 July 1997 (02.07.97) US (71) Applicant: ANCHOR CHIPS INCORPORATED [US/US]; Suite 212, 12396 World Trade Drive, San Diego, CA 92128 (US). (72) Inventors: SARTORE, Ronald, H.; 11511 Eastridge Place, San Diego, CA 92131 (US). LARKY, Steven, P.; 314 Del Mar Heights Road, Del Mar, CA 92014 (US). (74) Agent: LOHSE, Timothy, W.; Gray Cary Ware & Freiedenrich, 400 Hamilton Avenue, Palo Alto, CA 94301 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. With amended claims.</p>	

(54) Title: BUS INTERFACE SYSTEM AND METHOD

(57) Abstract

A system and method for reconfiguring a peripheral device (54) connected by a computer bus (60) and port to a host (52) from a first generic configuration to a second manufacturer specific configuration is provided in which the configuration of a peripheral device may be electronically reset. A peripheral interface device (76) for a standardized computer peripheral device bus and port is also provided in which a physical disconnection and reconnection of the peripheral device is emulated to reconfigure the bus and port for a particular peripheral device.




EXHIBIT 1009

IPR Petition for U.S. Patent No. 6,493,770

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

BUS INTERFACE SYSTEM AND METHOD

Background of the Invention

This invention relates generally to a system and method for connecting a computer system to a computer bus and in particular to a system and method for interfacing a computer system to a standard universal serial peripheral device bus.

In a typical computer system, a computer having a microprocessor may be connected to a plurality of peripheral devices, such as a printer or a modem, by one or more electrical buses and several different communications ports. Different peripheral devices have interfaces with different form factors and electrical characteristics, and these communications ports are used for a variety of different peripheral devices. A typical desktop computer may have a modem, a printer, a keyboard and a mouse connected to it. The modem may be connected to a serial port, the printer may be connected to a parallel port, the keyboard may be connected to a dedicated keyboard port and the mouse may be connected to a dedicated mouse port. Each of these communication ports may have different electrical characteristics, require different connectors and each has a different cable that runs from the peripheral device to the connector which connects to the computer communications port. For example, the serial port, the parallel port, the keyboard port and the mouse port all have different

characteristics, cables and different connectors. The result is a large number of diverse interfaces and cables that must be used. In addition, the electrical design of these communications ports typically requires that the computer be turned off before connecting and/or disconnecting a peripheral device from the port because the port may be permanently damaged otherwise. This prompted the design of a single standardized peripheral interface connection system which reduces the need for multiple connectors and cables, and permits the connection and disconnection of a peripheral device while the computer is turned on.

A new emerging technology called the Universal Serial Bus (USB) is a system intended to create a single standardized peripheral device connection system. The USB makes the task of connecting peripheral devices to computers easier and more reliable since it uses a standardized connector and form factor, and makes operating those peripheral devices with the computer, easier and more reliable than with the various different types of communication ports. The computer to which these peripheral devices are connected by the USB is known as the “host computer”. The USB replaces the multiple cable and connector types with a single standardized connection system. The USB also permits the connection and disconnection of USB compatible peripheral devices while the computer is turned on which eliminates the typical turning off and rebooting of the computer in order to connect or disconnect a peripheral device to the computer.

When a peripheral device is first connected to the USB and the host computer through a standard USB communications port, the presence of the connected peripheral device is detected and a configuration process of the USB for the connected peripheral device, known as device enumeration, begins. The enumeration process assigns a unique USB address to the connected peripheral device, queries the connected peripheral device about its requirements and capabilities, writes data about the connected peripheral device into the host computer's operating system, and loads the appropriate software device driver from a storage location into the host computer's operating system. During the query, a data table stored in the peripheral device, which contains the particular peripheral device's configuration information, is read from the peripheral device into the host computer's memory. Upon completion of the enumeration process, the connected peripheral device is recognized by the host computer's operating system and may be used by application software being executed by the microprocessor of the host computer. The association of the device with the software device driver cannot be subsequently changed.

In a serial bus system, such as the USB, the only opportunity for associating software device drivers with a peripheral device is at the time when the peripheral device is plugged into the USB and the enumeration process occurs. Thus, to alter the configuration or personality of a peripheral device, such as downloading new code or

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.