

**Digital cellular telecommunications system (Phase 2+);
General Packet Radio Service (GPRS);
Mobile Station - Serving GPRS Support Node (MS-SGSN)
Logical Link Control (LLC) layer specification
(GSM 04.64 version 6.1.0 Release 1997)**



Reference

DTS/SMG-030464Q6 (cic030c3.PDF)

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)
GPRS

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
<http://www.etsi.fr>
<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

ETSI

Contents

Intellectual Property Rights.....	7
Foreword	7
1 Scope.....	8
2 Normative references	8
3 Definitions and abbreviations	10
3.1 Definitions	10
3.2 Abbreviations.....	10
4 Overview description of LLC functions and procedures	11
4.1 Reference model	12
4.2 General description of the LLC protocol	12
4.2.1 Services required by the lower layers.....	13
4.3 Unacknowledged operation.....	13
4.4 Acknowledged operation	13
4.5 Establishment of information transfer modes.....	13
4.5.1 Data link connection identification.....	13
4.5.2 Logical link states.....	14
4.5.3 TLLI assignment	14
4.5.4 Establishment of ABM operation	14
4.6 Data confidentiality.....	14
4.7 LLC layer structure	15
4.7.1 Logical Link Entity	15
4.7.2 Multiplex procedure	16
4.7.3 Logical Link Management.....	16
4.8 GPRS Mobility Management.....	16
4.9 Short Message Service.....	16
5 Frame structure	16
5.1 General.....	16
5.2 Address field.....	17
5.3 Control field.....	17
5.4 Information field.....	17
5.5 Frame Check Sequence (FCS) field.....	17
5.6 Transparency.....	18
5.6.1 Bit transparency	18
5.6.2 Information protection.....	18
5.6.3 Octet alignment.....	18
5.7 Format convention	18
5.7.1 Numbering convention	18
5.7.2 Order of transmission	18
5.7.3 Field mapping convention.....	19
5.8 Invalid frames	19
6 Elements of procedures and formats of fields.....	19
6.1 General.....	19
6.2 Address field format and variables	20
6.2.1 Protocol Discriminator bit (PD)	20
6.2.2 Command/Response bit (C/R).....	20
6.2.3 Service Access Point Identifier (SAPI).....	20
6.3 Control field formats, parameters, and variables	21
6.3.1 Information transfer format - I.....	22
6.3.2 Supervisory format - S	23
6.3.3 Unconfirmed Information format - UI.....	23
6.3.4 Unnumbered format - U	23
6.3.5 Control field parameters and associated state variables	23

ETSI

6.3.5.1	Poll/Final bit (P/F).....	23
6.3.5.2	Acknowledgement request bit (A).....	23
6.3.5.3	Modulus.....	23
6.3.5.4	ABM Variables and sequence numbers.....	24
6.3.5.4.1	Send state variable V(S).....	24
6.3.5.4.2	Acknowledge state variable V(A).....	24
6.3.5.4.3	Send sequence number N(S).....	24
6.3.5.4.4	Receive state variable V(R).....	24
6.3.5.4.5	Receive sequence number N(R).....	24
6.3.5.4.6	SACK bitmap R(n).....	24
6.3.5.4.7	I frame buffer variable B.....	25
6.3.5.4.8	Other parameters and variables.....	25
6.3.5.5	Unacknowledged operation variables and parameters.....	25
6.3.5.5.1	Encryption mode bit (E).....	25
6.3.5.5.2	Protected mode bit (PM).....	25
6.3.5.5.3	Unconfirmed send state variable V(U).....	25
6.3.5.5.4	Unconfirmed sequence number N(U).....	25
6.3.5.5.5	Unconfirmed receive state variable V(UR).....	25
6.3.5.5.6	Other parameters and variables.....	25
6.4	Commands and responses.....	26
6.4.1	Unnumbered (U) frames.....	26
6.4.1.1	Set asynchronous balanced mode (SABM) command.....	26
6.4.1.2	Disconnect (DISC) command.....	26
6.4.1.3	Unnumbered Acknowledgement (UA) response.....	27
6.4.1.4	Disconnected Mode (DM) response.....	27
6.4.1.5	Frame Reject (FRMR) Response.....	27
6.4.1.6	Exchange Identification (XID) command/response.....	28
6.4.2	Unconfirmed Information (UI) frame.....	29
6.4.2.1	Unconfirmed Information (UI) command.....	29
6.4.3	Combined Information (I) and Supervisory (S) frames.....	29
6.4.3.1	Receive Ready (RR) command / response.....	30
6.4.3.2	Acknowledgement (ACK) command / response.....	30
6.4.3.3	Selective Acknowledgement (SACK) command / response.....	30
6.4.3.4	Receive not ready (RNR) command / response.....	30
7	Elements for layer-to-layer communication.....	31
7.1	Definition of service primitives and parameters.....	31
7.1.1	Primitives types.....	31
7.1.1.1	Request.....	31
7.1.1.2	Indication.....	31
7.1.1.3	Response.....	31
7.1.1.4	Confirm.....	31
7.1.2	Generic names.....	32
7.2	Primitive procedures.....	32
7.2.1	GMM - LLC primitives.....	32
7.2.1.1	LLGMM-ASSIGN.....	32
7.2.1.2	LLGMM-TRIGGER.....	33
7.2.1.3	LLGMM-SUSPEND.....	33
7.2.1.4	LLGMM-RESUME.....	34
7.2.1.5	LLGMM-PAGE.....	34
7.2.1.6	LLGMM-WINDOW.....	34
7.2.1.7	LLGMM-IOV.....	34
7.2.1.8	LLGMM-STATUS.....	34
7.2.2	Layer 3 - LL primitives.....	34
7.2.2.1	LL-ESTABLISH.....	34
7.2.2.2	LL-RELEASE.....	34
7.2.2.3	LL-XID.....	35
7.2.2.4	LL-DATA.....	35
7.2.2.5	LL-DATASENT.....	35
7.2.2.6	LL-UNITDATA.....	35
7.2.3	LL - RLC/MAC primitives.....	35

ETSI

7.2.3.1	GRR-DATA.....	35
7.2.3.2	GRR-UNITDATA.....	35
7.2.3.3	GRR-STATUS.....	36
7.2.4	LL - BSSGP primitives.....	36
7.2.4.1	BSSGP-UNITDATA.....	36
7.2.4.2	BSSGP-STATUS.....	36
7.2.5	LLM - LL primitives.....	36
8	Definition of the LLC peer-to-peer protocol.....	36
8.1	General.....	36
8.2	Procedure for the use of the P/F bit.....	37
8.3	TLLI assignment procedures.....	37
8.3.1	TLLI assignment.....	37
8.3.2	TLLI change.....	38
8.3.3	TLLI unassignment.....	38
8.4	Procedures for unacknowledged information transfer.....	38
8.4.1	Transmission of unacknowledged information.....	38
8.4.2	Receipt of unacknowledged information.....	38
8.5	Procedures for establishment and release of ABM operation.....	39
8.5.1	Establishment of ABM operation.....	39
8.5.1.1	General.....	39
8.5.1.2	Establishment procedures.....	39
8.5.1.3	Procedure on expiry of timer T200.....	40
8.5.2	Termination of ABM operation.....	40
8.5.2.1	General.....	40
8.5.2.2	Release procedure.....	41
8.5.2.3	Procedure on expiry of timer T200.....	41
8.5.3	Automatic negotiation of LLC layer and layer-3 parameters.....	41
8.5.3.1	Negotiation of parameter m.....	42
8.5.3.2	Unsuccessful XID negotiation.....	43
8.5.3.3	Procedure on expiry of timer T200.....	43
8.5.4	TLLI Assigned / ADM state.....	43
8.5.5	Collision of unnumbered commands and responses.....	44
8.5.5.1	Identical transmitted and received commands.....	44
8.5.5.2	Different transmitted and received commands.....	44
8.5.6	Unsolicited DM response and SABM or DISC command.....	44
8.6	Procedures for information transfer in ABM operation.....	44
8.6.1	Transmitting I frames.....	45
8.6.2	Receiving I frames.....	46
8.6.3	Sending and receiving acknowledgements.....	46
8.6.3.1	Sending acknowledgements.....	46
8.6.3.2	Receiving acknowledgements.....	46
8.6.3.3	Requesting acknowledgements.....	47
8.6.4	Peer receiver busy condition.....	47
8.6.4.1	Supervisory frame selection.....	48
8.6.5	Own receiver busy condition.....	48
8.6.6	Waiting for acknowledgement.....	48
8.7	Re-establishment of ABM operation.....	48
8.7.1	Criteria for re-establishment.....	48
8.7.2	Procedures.....	49
8.8	Exception condition reporting and recovery.....	49
8.8.1	Invalid frame condition.....	49
8.8.2	Frame rejection condition.....	49
8.8.3	Receipt of a FRMR response frame.....	49
8.8.4	Unsolicited response frames.....	49
8.8.5	Multiple assignment of TLLI value.....	50
8.9	List of LLC layer parameters.....	50
8.9.1	LLC version number (Version).....	50
8.9.2	Input Offset Value (IOV).....	50
8.9.3	Retransmission timer (T200).....	50
8.9.4	Maximum number of retransmissions (N200).....	50

ETSI

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.