

**3rd Generation Partnership Project;
Technical Specification Group Services and Systems Aspects;
Architectural Requirements for Release 1999
(3G TS 23.121 version 3.0.0)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organisational Partners' Publications Offices.

Reference

DTS/TSGSA-0221121U

Keywords

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

ETSI

Contents

Foreword	5
1 Scope 6	
2 References	6
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Working assumptions	7
4.1 General	7
4.2 Iu Interface	7
4.2.1 Iu Control Plane	8
4.2.1.1 Iu control plane for CS domain	8
4.2.1.2 Iu control plane for PD domain	8
4.2.2 Iu User plane	9
4.2.2.1 Principles of User Data Retrieve in UMTS and at GSM-UMTS Hand-Over for PS Domain	10
4.2.2.1.1 Requirements for Data retrieve at GPRS/UMTS handover	10
4.2.2.1.2 Adopted solution for data retrieve at GPRS-UMTS handover	10
4.2.2.1.3 Requirements for data retrieve in UMTS	11
4.2.2.1.4 Adopted solution for data retrieve in UMTS	12
4.2.2.1.5 User plane protocol stacks for UMTS data retrieve	13
4.2.2.1.6 User plane protocol stacks for data retrieve between UTRAN and 2G-SGSN	13
4.2.2.2 Packet buffering in SRNC and transmission of not yet acknowledged downstream packets at SRNC relocation	13
4.2.2.3 Load sharing	14
4.3 UMTS Mobility Management (UMM)	14
4.3.1 Location Management and Mobility Management concept overview	14
4.3.1.1 Use of combined procedures for UMTS	17
4.3.2 Description of the Location Management and Mobility Management Concept	18
4.3.2.1 Area concepts	18
4.3.2.1.1 Location areas	18
4.3.2.1.2 Routing areas	18
4.3.2.1.3 UTRAN internal areas	18
4.3.2.1.4 Relationship between the different areas	18
4.3.3 MM functionality in different UE service states	19
4.3.4 The RRC state machine	20
4.3.5 Relationship between CS and PS service states and RRC state for an UE	21
4.3.6 Service registration and location update	22
4.3.6.1 Location area update	23
4.3.6.2 Routing area update	23
4.3.6.3 Combined updates	23
4.3.7 Paging initiated by CN	23
4.3.8 Signalling connection establishment	23
4.3.9 Relations between SRNS relocation and Location registration	24
4.3.10 Requirements on Identifiers for UMTS and GSM	25
4.3.11 Use of TMSI signature	26
4.3.11.1 IMSI attach	26
4.3.11.2 Location Area update	27
4.3.11.3 MM System Information	28
4.3.11.4 IMSI detach procedure	28
4.3.12 Signalling procedures	28
4.3.12.1 Idle mode procedures	28

ETSI

4.3.12.1.1	Location Area update.....	28
4.3.12.1.2	Routing Area update.....	30
4.3.12.1.3	Periodic Registration towards both CN nodes without use of Gs.....	31
4.3.12.1.4	Periodic Registration with use of Gs/UMSC.....	33
4.3.12.1.5	UE initiated Combined Detach Procedure when using Gs/UMSC.....	33
4.3.12.2	SRNS Relocation.....	33
4.3.12.2.1	SRNS relocation principles.....	33
4.3.12.2.2	SRNS relocation (UE connected to a single CN node, 3G_MSC/VLR) followed by Location Registration in new Routing Area.....	34
4.3.12.2.3	SRNS relocation (UE connected to a single CN node, 3G_SGSN) followed by Location Registration in new Location Area.....	36
4.3.12.3	Comparison between UMTS and GSM.....	41
4.3.12.3.1	PS -idle state.....	42
4.3.12.3.2	PS -connected state.....	42
4.3.12.4	Issues for further study.....	42
4.3.13	Combined update towards the HLR for a combined 3G-(MSC/VLR+SGSN) configuration.....	43
4.3.13.1	Motivation.....	43
4.3.13.2	Technical description.....	43
4.3.13.3	Requirements on UTRAN.....	44
4.3.13.4	List of MAP services for location management between the HLR and MSC-VLR/SGSN for GSM/GPRS.....	44
4.3.13.5	Signalling procedures for combined update towards HLR.....	45
4.3.13.6	Combined attach case where the previous attach was towards 2 CN elements.....	45
4.3.13.7	Combined location/routing area update where the previous LA/RA belonged to a 2 CN element.....	46
4.4	UMTS call control.....	47
4.4.1	Technical Requirements.....	47
4.4.2	Typical Scenarios for Multimedia Control and User Plane.....	48
4.4.2.1	H.324M to H.324M Call.....	48
4.4.2.2	IMT-2000 H.323 to H.323 call.....	50
4.5	Core network layer 3.....	51
4.6	Structure of radio interface layer 3.....	52
4.7	Alternate Access technologies to UTRAN.....	52
4.7.1	Advantages of attaching HIPERLAN 2 to UMTS.....	52
4.7.2	HIPERLAN 2 UMTS Interworking.....	53
4.7.3	Related Actions.....	53
4.8	Location of the IP compression function in UMTS.....	53
4.8.1	Functional role of SNDCP/ L3CE.....	53
4.8.2	Position for header compression.....	54
4.8.3	Implied protocol stack.....	54
4.9	Short Message Service for UMTS.....	55
4.9.1	Protocols and architecture.....	55
4.10	Mobile IP for UMTS/GPRS End Users, revised version.....	55
4.10.1	Mobile IP for UMTS/GPRS End Users.....	55
4.10.1.1	Alterations of and Additions to Current GPRS Standards.....	58
References	58
History	59

ETSI

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version 3.y.z

where:

x the first digit:

1 presented to TSG for information;

2 presented to TSG for approval;

3 Indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the specification;

ETSI

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.