United States Patent [19]

Nishikawa et al.

- [54] INTER-VEHICLE DISTANCE CONTROL SYSTEM FOR VEHICLES
- [75] Inventors: Masao Nishikawa, Tokyo; Takashi Aoki, Saitama, both of Japan
- [73] Assignee: Honda Giken Kogyo Kabushiki Kaisha, Tokyo, Japan
- [21] Appl. No.: 288,033
- [22] Filed: Jul. 29, 1981
- [30] Foreign Application Priority Data
- Aug. 4, 1980 [JP] Japan 55-106949

[11] Patent Number: 4,628,317

[45] Date of Patent: Dec. 9, 1986

References Cited

U.S. PATENT DOCUMENTS

3,778,826	12/1973	Flannery et al 343/7 V	Μ
3,786,507	1/1974	Hurd, Jr 343/7 V	Μ
3,921,749	11/1975	Kawada 343/7 VM	х
3,952,301	4/1976	Sorkin 343/7 V	Μ

Primary Examiner—T. H. Tubbesing

Assistant Examiner-Gilberto Barrón, Jr.

Attorney, Agent, or Firm-Irving M. Weiner; Joseph P. Carrier; Pamela S. Burt

[57] ABSTRACT

[56]

An inter-vehicle distance control system for a vehicle wherein the distance between the vehicle and a preceding object and a relative velocity therebetween are detected by a detection system such as a radar system, and when this distance has become shorter than a predetermined value, a reaction force is imparted to a throttling operation member such as a throttling pedal. The vehicle operator is effectively advised of this fact.

11 Claims, 3 Drawing Figures



DOCKET ALARM Find authenticated court documents without watermarks at <u>docketalarm.com</u>.



FIG.2 10 24 28 27 Ź5 28 26





Α R М Find authenticated court documents without watermarks at docketalarm.com. 5

INTER-VEHICLE DISTANCE CONTROL SYSTEM FOR VEHICLES

FIELD OF THE INVENTION

The present invention relates to an inter-vehicle distance control system for a vehicle for safely maintaining the distance between the vehicle and an object such as another vehicle travelling ahead thereof, by detecting the distance from the object and the relative speed by the utilization of electromagnetic waves, ultrasonic waves, or the like.

RELEVANT ART

In recent years, an increased number of vehicles and increased driving speeds have been giving rise to a correspondingly sharp increase in the number of rearend collision accidents, and this problem is now a social problem. In an effort to solve this problem there have 20 been proposed many automatic control systems for vehicles wherein the distance from a preceding vehicle and a relative speed are measured at all times by the utilization of a radar system and when the measured values exceed predetermined levels braking is actuated 25 automatically.

However, such conventional systems involve the following problems.

First, since the radar system merely detects whether or not there is an object ahead, it is difficult to judge 30 whether the detected object will cause a danger. In the event that the detected signal is a false signal, an unnecessarily actuated braking may cause a danger of being hit from the rear by a succeeding vehicle, and this is not desirable from the standpoint of safety. 35

Such a false signal may be generated for example where there is a viaduct or road sign, where rain is falling heavily, or where the vehicle is passing a sharp valley constituting of an upward slope and a downward slope.

Secondly, there sometimes occurs the case where the braking action by the automatic braking system and the intended driving of the vehicle operator are different from each other. There are three means for avoiding a vehicle collision, namely, braking, steering and acceler- 45 ation. Therefore, even when a vehicle is travelling ahead, collision is avoidable by a by-passing operation consisting of steering and acceleration if there is enough of an inter-vehicle distance still remaining. In such a case, it is unsuitable in the actual driving situation to 50 completely disregard the driver's will and have the braking system operated only automatically.

Because of the above-mentioned problems, the conventional systems of such type have not been acceptable. As to the second problem mentioned above, there 55 has been proposed the concept of changing the measuring range with the angle of rotation of the steering wheel as a parameter, but such an idea is still incomplete technically.

The present invention effectively solves the above 60 problems.

It is an object of the present invention to provide an inter-vehicle distance control system for a vehicle wherein the distance from a preceding object and a relative velocity therebetween are detected by a detec-55 tion system such as a radar system, and when this distance has become shorter than a predetermined value, a reaction force is imparted to a throttling operation

member such as a throttling pedal, thereby advising the vehicle operator of this fact.

It is another object of the present invention to provide an inter-vehicle distance control system for a vehicle constructed such that when the vehicle has come abnormally close to a preceding object, thus giving rise to an increased danger, an automatic braking system is immediately actuated to mitigate a possible collision for minimizing the damage of a potential accident, while in principle the driver's will has priority in response to a reaction force generated at a throttling operation member such as a throttling pedal.

It is a further object of the present invention to provide an inter-vehicle distance control system for a vehi-15 cle wherein the detecting capability of a detection system such as a radar system for detecting interfering objects may be maintained at a high level without the need to narrow its detection range, and even if a false signal is issued there is assured a smooth driving condi-20 tion with priority given to the driver's will.

A preferred embodiment of the present invention will be described in detail hereinbelow with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an inter-vehicle distance control system according to an embodiment of the present invention.

FIG. 2 shows an example of a throttling control unit. FIG. 3 shows another example of a throttling control unit.

DETAILED DESCRIPTION OF THE INVENTION

In FIG. 1, the reference symbol A designates a detection system of a vehicle for detecting the distance between the vehicle and a preceding vehicle and a relative speed therebetween and for comparing respective thus detected values with predetermined ones; the symbol B designates a braking control system of the vehicle comprising a braking pedal and a device for automatically controlling it; the symbol C designates a throttling control system comprising a throttling pedal and a device for automatically controlling it; and the symbol D designates a braking lamp disposed on the rear of the vehicle.

Referring now to the detection system A, there is employed a FM-CW radar system, wherein oscillatory waves generated at an oscillator 1 are modulated by a modulator 2 and output therefrom is divided by a directional coupler 3 into two groups of waves, one being sent through circulator 4 to an antenna 5 from which they are radiated as radio waves toward a preceding object and the other being sent to a mixer 6. Reflected waves from the object are received by the antenna 5, and sent through the circulator 4 to the mixer 6, where these waves are mixed with those waves directly transmitted from the directional coupler 3 to create a signal of beat frequency. This beat frequency signal is weak, and amplified up to a required voltage level by a video amplifier 7, then this amplified signal is transmitted to a frequency counter 8 where the frequency is read-out, and this read-out value of beat frequency is provided to a signal processing circuit 9.

In the signal processing circuit 9 there is calculated a distance X between the vehicle and the object and a relative velocity V_R therebetween on the basis of the beat frequency value, and there is determined a proper

Find authenticated court documents without watermarks at docketalarm.com.

5

distance X_S from the object at that time by using a velocity signal V_S sent from the speedometer in the vehicle and the relative speed V_R , according to a predetermined proper distance characteristic function. Then, the proper distance X_S is compared with the actual distance X, and on the basis of a difference XS-X the following output signals are produced.

Where the difference X_S -X is larger than a predetermined maximum reference value, a (first) signal is generated through an output line 10, whereby the stop lamp 10 tling control element 11 for providing the spring 24 D is lit at a luminance proportional to that signal level, and at the same time an element 11 in the throttling control unit C is operated to urge a throttling pedal 14 toward its idle position side.

If the value X_S-X continues increasing and becomes 15 larger than a predetermined intermediate reference value notwithstanding the provision of the aforesaid throttling action, the signal processing circuit 9 issues another (third) signal through an output line 12 with a limit switch 15, in order to operate an automatic braking 20 element 13 in the braking control system B. However, since the limit switch 15 is provided at an intermediate point of the output line 12 so as to be turned on or off according to the position of the throttling pedal 14, the intended signal transmission is not effected except when 25 element 11 comprises a screw 26 mounted on an output the limit switch 15 is closed.

Furthermore, when the distance from the object has become smaller and reached a predetermined minimum reference value presumably indicative of unavoidable collision, the signal processing circuit 9 generates still 30 another (second) signal through an output line 16 whereby the automatic braking element 13 is directly operated to effect the braking and at the same time a throttle retarder 17 is operated to hold the pedal 14 at 35 the idle position without fail.

Referring now to the braking control system B, a braking pedal 18 is adapted to rotate about a pivot point 19 in the vehicle body, and this pivotal motion allows a master cylinder 21 to be operated through a push rod 20. Preferably, between the master cylinder 21 and the 40 push rod 20 there is provided a vacuum booster (not shown). The braking pedal 18 can be moved to its operating position not only by a treading force of the operator but also by the automatic braking element 13 according to what has previously been noted.

The automatic braking element 13 used in this embodiment is of such a type that a force indicated by an arrow 13a is applied to the pedal 18 by means of a hydraulic cylinder or the like. In the automatic braking element 13, the force for actuating the master cylinder 50 21 in response to the signal on the output line 12 and the actuating force for the same cylinder in response to the signal on the output line 16 are desirably not the same; that is, the element 13 may be constructed such that the braking force based on the signal on the output line 16 55 is stronger than that based on the signal on the output line 12.

If the vacuum booster is included between the master cylinder 21 and the push rod 20, the automatic braking element 13 may be constructed so as to utilize this 60 booster for actuation of the master cylinder. Even in this case, as mentioned above, the braking forces caused by the output lines 12 and 16 may preferably be made different.

Referring now to the throttling control system C, the 65 throttling pedal 14 is mounted so as to be pivotable about a pivot point 22 with respect to the vehicle body, and when it is moved pivotally in a clockwise direction

DOCKE

in FIG. 1 by virtue of a treading force applied at the lower end of the pedal 14 by the vehicle operator, a butterfly valve (not shown) of a carburetor (not shown) is opened through a throttling wire whereby an accelerating force can be exerted on the vehicle. On the other hand, when the throttling pedal 14 is returned in the opposite direction by a spring 24, an engine braking is effected to decelerate the vehicle.

Engaged with the throttling pedal 14 are: the throtwith a variation of resiliency according to the intensity of the signal on the output line 10 from the signal processing circuit 9 thereby urging the pedal 14 to its idle position side; the foregoing limit switch 15 adapted to be closed when the throttling pedal 14 is in its idle position; and the retarder 17 for holding the throtting pedal 14 in its idle position in response to the signal on the output line 16.

For the retarder 17 there may be used a hydraulic or pneumatic cylinder which functions to push the throttling pedal 14 back to the idle position with a minimum time lag in response to the signal on the output line 16.

Regarding the throttling control element 11, a particular example thereof is shown in FIG. 2, in which the shaft of a pulse motor 25, a nut 27 fitted over the screw 26, and two rails 28 for preventing the rotation of the nut 27. The pulse motor 25 is fixed to the vehicle body, and when it rotates the screw 26 in response to the signal on the output line 10, the nut 27 is moved to the left in the figure, so that a variation of resiliency proportional to the signal can be imparted to the spring 24.

Referring now to the braking lamp D, there may be used an existing braking lamp, provided its luminance is not fixed but rather is variable in proportion to the intensity of the signal on the output line 10. The operation of the above construction is described hereinbelow.

Even when there is an interfering object such as a vehicle ahead, if the object is so far away that the radar detection system A does not detect any danger, the signal processing circuit 9 provides no signal on any of the output lines 10, 12 and 16, so that the vehicle operation can be performed on the basis of the driver's judgment only. In such state, the vehicle driver can effect 45 the engine braking by releasing his foot from the throttling pedal 14, or he can actuate the brakes any time by treading the braking pedal 18.

When the object approaches and the radar detection system A detects the possibility of collision and provides a signal through the output line 10, the throttling control element 11 operates to apply a force to the throttling pedal 14 so as to return the latter to its idle position. The vehicle driver is warned by feeling the weight of the pedal 14 based on the reaction force. At the same time, the braking lamp D is lit whereby a succeeding vehicle is advised of a possible impending actuation of the brakes.

In the above case, the reaction force transmitted as a warning to the vehicle driver through the pedal 14 is proportional to the intensity of the signal on the output line 10, so the vehicle driver can fully recognize the degree of the possibility of collision with the interfering object. In case the vehicle driver continues to tread the throttle pedal 14 in opposition to the above reaction force, there will be no sudden actuation of the brakes for the vehicle against the driver's will, nor will a decelerated state occur. Conversely, when the vehicle driver anticipated a danger, he may slacken the treading force

DOCKET



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

