EXHIBIT 1109

PCT PUB. NO. WO 93/11631, PUBLISHED JUNE 10, 1993

("DENYER")

TRW Automotive U.S. LLC: EXHIBIT 1109 PETITION FOR *INTER PARTES* REVIEW OF U.S. PATENT NUMBER 8,599,001

DOCKET A L A R M Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

D	~	T.
Г	C	L

1

1 1 1 WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

51) International Patent Classification ⁵ :		(11) International Publication Number:	WO 93/11631
H04N 5/335, 9/097, 5/225	A1	(43) International Publication Date:	10 June 1993 (10.06.93
21) International Application Number: PCT/GI 22) International Filing Date: 4 December 1992		CH, DE, DK, ES, FR, GB, C	European patent (AT, BI 3R, IE, IT, LU, MC, NI
30) Priority data: 9125954.9 6 December 1991 (06.12	.91) (Published 3B With international search report Before the expiration of the tinclaims and to be republished in	me limit for amending th
71) Applicant (for all designated States except US): SION LIMITED [GB/GB]; Technology Tran tre, King's Buildings, Mayfield Road, Edinb 3JL (GB).	nsfer Co	/I- <i>amendments.</i>	i inc crem of the receipt of
 72) Inventor; and 75) Inventor/Applicant (for US only) : DENYER, Performance [GB/GB]; 91 Colinton Road, Edinburgh E (GB). 	eter, Bri H10 51	an DF	
74) Agents: McCALLUM, William, Potter et al.; C and Fairweather, 19 Royal Exchange Square G1 3AE (GB).	Cruiksha , Glasg	nk ow	
54) Title: SOLID STATE SENSOR ARRANGEM	ENT F	DR VIDEO CAMERA	
54) Title: SOLID STATE SENSOR ARRANGEM	ENT F	DR VIDEO CAMERA	
54) Title: SOLID STATE SENSOR ARRANGEM			
54) Title: SOLID STATE SENSOR ARRANGEM			
54) Title: SOLID STATE SENSOR ARRANGEM			
54) Title: SOLID STATE SENSOR ARRANGEM			

DOCKET ALARM Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria
ÁU	Australia
BB	Barbados
BE	Belgium
BF	Burkina Faso
BG	Bulgaria
BJ	Benin
BR	Brazil
CA	Canada
CF	Central African Republic
CG	Congo
CH	Switzerland
CI	Côte d'Ivoire
СМ	Cameroon
CS	Czechoslovakia
CZ	Czech Republic
DE	Germany
DK	Denmark
ES	Spain
FI	Finland

DOO

Δ

FR	France
GA	Gabon
GB	United Kingdom
GN	Guinca
GR	Greece
HU	Hungary
1E	Ireland
IT	Italy
JP	Japan
КР	Democratic People's Republic
	of Korea
KR	Republic of Korea
КZ	Kazakhstan
LI	Liechtenstein
LK	Sri Lanka
LU	Luxembourg
мс	Monaco
MG	Madagascar
MI.	Mali
MN	Mongolia

MR	Mauritania
MW	Malawi
NL	Netherlands
NO	Norway
NZ	New Zealand
PL	Poland
РТ	Portugal
RO	Romanía
RU	Russian Federation
SD	Sudan
SE	Sweden
SK	Slovak Republic
SN	Senegal
SU	Soviet Union
TD	Chad
TG	Togo
UA	Ukraine
US	United States of America
VN	Viet Nam

1

£.

۴

2

4

<u>ا</u>

DOCKET

PCT/GB92/02260

SOLID STATE SENSOR ARRANGEMENT FOR VIDEO CAMERA The present invention relates to electronic cameras including electronic colour cameras.

- 1

It is well known that colour sensors can be produced by discriminating three images of the primary colours (blue, green, red) of the scene. All colours can be analysed and synthesised via these primaries (or other complementary triples like cyan, magenta, yellow). Conventional electronic cameras classically use one of two approaches for forming the separate colour images.

- 10 3-tube cameras use a single lens followed by a prism which forms three separate r.g.b images. Three sensors are used simultaneously to detect these three images. If the sensors are accurately aligned the resulting picture is of very high quality. However the sensors
- 15 are separated in space and orientation and their assembly and alignment with the prism and lens is difficult for a volume manufacturing process. This technique is therefore used exclusively for expensive broadcast-quality equipment. Colour-Mosaic Cameras use
- 20 a single lens and sensor, but the sensor surface is covered with a high-resolution mosaic or grid of colour filters, with the pattern dimension equal to the pixel-pitch for a semiconductor CCD or MOS sensor array. Pixels of different colours are demultiplexed at
- 25 the sensor output and interpolated to form synchronous parallel colour signals. This is well-suited to volume production as the surface colour mosaic can be fabricated as an extension of the semiconductor wafer fabrication process. The techniques for mosaic
- 30 fabrication are restricted to relatively few companies worldwide who supply the colour sensor market and thus they are not commonly available. Furthermore, associated with this technique there are technical problems concerned with resolution and aliasing. Much

DOCKET

4

work has been done to correct these effects, but usually at some cost in image-processing hardware.

- 2

It is an object of the present invention to avoid or minimise one or more of the above disadvantages.

5 In one of its broadest aspects, the present invention provides an image capture system comprising a solid state image capture device which device comprises an integrated circuit having at least two sensor arrays, each said array having an image sensing surface and a 10 respective lens system associated therewith.

Thus in effect the present invention provides two or more cameras on one chip each with its own lens system and sensor array. With such an arrangement the problem of alignment is greatly reduced by the fabrication of

- 15 the various sensors required one one chip. This ensures that the sensors all lie in the same plane and have the same rotational orientation, and this is an important advantage. Assuming lenses can be accurately assembled in a parallel plane (see below), the only alignment
- 20 errors which are likely to occur are simple orthogonal translations in the form of vertical and horizontal errors in the centres of the optical axes. It is relatively easy though to calibrate these cameras after assembly and electronically to correct for these
- 25 translations. Whilst the inevitable lateral off-set between the cameras at even the closest dispositions of the cameras on the chip, will of course give rise to a degree of parallax error, it has now been found that with a preferred system of the present invention with
- 30 generally adjacent sensor arrays, the degree of error in producing a single composite image (i.e. a single image produced by the more or less accurately aligned super imposition of two or more corresponding images e.g. at

DOCKET A L A R M



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.