HANDBOOK OF INDUSTRIAL MIXING SCIENCE AND PRACTICE

Edited by

Edward L. Paul

Merck & Co., Inc. Rahway, New Jersey

Victor A. Atiemo-Obeng

The Dow Chemical Company. Midland, Michigan

Suzanne M. Kresta

University of Alberta Edmonton, Canada



DOCKE.

R

Δ

Sponsored by the North American Mixing Forum



A JOHN WILEY & SONS, INC., PUBLICATION

CO₂ Solutions Inc. Exhibit 2014

Find authenticated court documents without watermarks at docketalarm.com.

Cover: The jet image is courtesy of Chiharu Fukushima and Jerry Westerweel, of the Laboratory for Aero and Hydrodynamics, Delft University of Technology, The Netherlands.

Copyright © 2004 by John Wiley & Sons, Inc. All rights reserved.

Published by John Wiley & Sons, Inc., Hoboken, New Jersey. Published simultaneously in Canada.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning, or otherwise, except as permitted under Section 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, 978-750-8400, fax 978-750-4470, or on the web at www.copyright.com. Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 111 River Street, Hoboken, NJ 07030, (201) 748-6011, fax (201) 748-6008, e-mail: permreq@wiley.com.

Limit of Liability/Disclaimer of Warranty: While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. No warranty may be created or extended by sales representatives or written sales materials. The advice and strategies contained herein may not be suitable for your situation. You should consult with a professional where appropriate. Neither the publisher nor author shall be liable for any loss of profit or any other commercial damages, including but not limited to special, incidental, consequential, or other damages.

For general information on our other products and services please contact our Customer Care Department within the U.S. at 877-762-2974, outside the U.S. at 317-572-3993 or fax 317-572-4002.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print, however, may not be available in electronic format.

Library of Congress Cataloging-in-Publication Data:

Paul, Edward L.
Handbook of industrial mixing : science and practice / Edward L. Paul,
Victor A. Atiemo-Obeng, Suzanne M. Kresta

p. cm.

"Sponsored by the North American Mixing Forum."
Includes bibliographical references and index.
ISBN 0-471-26919-0 (cloth : alk. paper)
1. Mixing—Handbooks, manuals, etc. I. Atiemo-Obeng, Victor A. II.
Kresta, Suzanne M. III. Title.

TP156,M5K74 2003 660'.284292—dc21

2003007731

Printed in the United States of America.

10 9 8 7 6 5 4 3 2 1

DOCKET

548 SOLID-LIQUID MIXING

- What happens to the suspension when agitation is increased? Most solid-liquid mixing operations operate above the minimum speed for suspension. A higher agitation speed improves the degree of suspension and enhances mass transfer rates. The higher speed also translates into higher turbulence as well as local and average shear rates, which for some processes may cause undesirable particle attrition. Obviously, there is also a practical economic limit on the maximum speed of agitation.
- What effect does vessel geometry have on the process? The geometry of the vessel, in particular the shape of the vessel base, affects the location of dead zones or regions where solids tend to congregate. It also influences the minimum agitation speed required to suspend all particles from the bottom of the vessel. In flat-bottomed vessels, dead zones and thus "fillet formation" tend to occur in the corner between the tank base and the tank wall, whereas in dished heads the solids tend to settle beneath the impeller or midway between the center and the periphery of the base. The minimum agitation speed is typically 10 to 20% higher in a flat-bottomed vessel than in one with a dished head. Both the minimum agitation speed and the extent of fillet formation are also a function of impeller type, ratio of impeller diameter to tank diameter, and location of the impeller from the vessel bottom. In general, a dished-head vessel is preferred to a flatbottomed vessel for solid-liquid mixing operations. There is little or no difference between ASME dished, elliptical, or even hemispherical dished heads as far as solid-liquid mixing is concerned. However, elliptical heads are preferred for higher-pressure applications.
- What is the appropriate material of construction for the process vessel? The main issue here is that, for steel or alloy vessels, the standard four wallmounted baffles provide a better environment for solid-liquid mixing. The standard glass-lined vessels are usually underbaffled because of a deficiency of nozzles from which to mount baffles.

10-2 HYDRODYNAMICS OF SOLID SUSPENSION AND DISTRIBUTION

DOCKE.

Solid suspension requires the input of mechanical energy into the fluid-solid system by some mode of agitation. The input energy creates a turbulent flow field in which solid particles are lifted from the vessel base and subsequently dispersed and distributed throughout the liquid. Nienow (1985) discusses in some detail the complex hydrodynamic interactions between solid particles and the fluid in mechanically agitated vessels. Recent measurements (Guiraud et al., 1997; Pettersson and Rasmuson, 1998) of the 3D velocity of both the fluid and the suspension confirm the complexity.

Solids pickup from the vessel base is achieved by a combination of the drag and lift forces of the moving fluid on the solid particles and the bursts of turbulent eddies originating from the bulk flow in the vessel. This is clearly evident in Publisher's Note: Permission to reproduce this image online was not granted by the copyright holder. Readers are kindly requested to refer to the printed version of this article.

Figure 10-1 Sudden pickup of solids by turbulent burst (Cleaver and Yates, 1973).

visual observations of agitated solid suspensions as in the video clip included on the accompanying CD ROM. Solids settled at the vessel base mostly swirl and roll around there, but occasionally, particles are suddenly and intermittently lifted up as a tornado might lift an object from the ground. An illustration of sudden pickup by turbulent bursts is shown in Figure 10-1.

The distribution and magnitude of the mean fluid velocities and large anisotropic turbulent eddies generated by a given agitator determine to what degree solid suspension may be achieved. Thus, different agitator designs achieve different degrees of suspensions at similar energy input. Also for any given impeller the degree of suspension will vary with D/T as well as C/T at constant power input. One of the video clips on the accompanying CD ROM shows the effect of D/T on solid suspension for a pitched blade impeller at constant power input.

For small solid particles whose density is approximately equal to that of the liquid, once suspended they continue to move with the liquid. The suspension behaves like a single-phase liquid at low solid concentrations; the mixing operation is more like blending than solid suspension. For heavier solid particles, their velocities will be different from that of the liquid. The drag force on the particles caused by the liquid motion must be sufficient and directed upward to counteract the tendency of the particles to settle by the action of gravity.

The properties of both the liquid and the solid particles influence the fluid-particle hydrodynamics and thus the suspension. Also important are vessel geometry and agitation parameters. The important fluid and solid properties and operational parameters include:

- 1. Physical properties of the liquid, such as:
 - a. Liquid density, ρ_l (lb/ft³ or kg/m³)
 - b. Density difference, $\rho_s \rho_l \ (lb/ft^3 \text{ or } kg/m^3)$
 - c. Liquid viscosity, μ_1 (cP or Pa · s)
- 2. Physical properties of the solid, such as:
 - a. Solid density, ρ_s (lb/ft³ or kg/m³)
 - b. Particle size, d_p (ft or m)

DOCKE

550 SOLID-LIQUID MIXING

- c. Particle shape or sphericity, ψ (dimensionless factor defined by the ratio of surface area of a spherical particle of the same volume to that of a nonspherical particle)
- d. Wetting characteristics of the solid
- e. Tendency to entrap air or headspace gas
- f. Agglomerating tendencies of the solid
- g. Hardness and friability characteristics of the solid
- 3. Process operating conditions, such as:
 - a. Liquid depth in vessel, Z (ft or m)
 - b. Solids concentration, X (lb solid/lb liquid or kg solid/kg liquid)
 - c. Volume fraction of solid, ϕ
 - d. Presence or absence of gas bubbles
- 4. Geometric parameters, such as:
 - a. Vessel diameter, T (ft or m)
 - b. Bottom head geometry: flat, dished, or cone-shaped
 - c. Impeller type and geometry
 - d. Impeller diameter, D (ft or m)
 - e. Impeller clearance from the bottom of the vessel, C (ft or m)
 - f. Liquid coverage above the impeller, CV (ft or m)
 - g. Baffle type and geometry and number of baffles
- 5 Agitation conditions, such as:
 - a. Impeller speed, N (rps)
 - b. Impeller power, P (hp or W)
 - c. Impeller tip speed (ft/s or m/s)
 - d. Level of suspension achieved
 - e. Liquid flow pattern

DOCKE.

f. Distribution of turbulence intensity in the vessel

10-2.1 Settling Velocity and Drag Coefficient

A dense solid particle placed in a quiescent fluid will accelerate to a steady-state settling velocity. This velocity, often called the *free* or *still-fluid settling velocity*, occurs when the drag force balances the buoyancy and gravitational force of the fluid on the particle. In an agitated solid suspension, because of the complex turbulent hydrodynamic field, including solid–solid interactions, it is difficult to clearly define and/or measure a particle settling velocity. However, the particle settling velocity in an agitated solid suspension is a function of the free settling velocity and is always less than the free settling velocity (Guiraud et al., 1997).

The magnitude of the free settling velocity has proven useful in characterizing solid suspension problems into easy, moderate, or difficult categories (see Table 10-2). It is also used in solid–liquid mixing correlations, as described below.