

- PRODUCTS
- POWER
- ANALOG
- INTERFACE
- COMMUNICATIONS
- DIGITAL**
- INDUSTRIES
- ALL
- WHAT'S NEW
- SOLUTIONS
- DESIGN
- ORDER
- SUPPORT
- ABOUT US

Maxim › Products › Digital › Memory Products › DS1996

DS1996

iButton 64Kb Memory

 Data Sheet  Subscribe  Active: In Production.

- OVERVIEW**
- KEY SPECS
- DESIGN RESOURCES
- ORDER

Description

The iButton® 64Kb memory (DS1996) is a rugged read/write data carrier that acts as a localized database that can be easily accessed with minimal hardware. The nonvolatile memory offers a simple solution to storing and retrieving vital information pertaining to the object to which the iButton device is attached. Data is transferred serially via the 1-Wire® protocol which requires only a single data lead and a ground return. The scratchpad is an additional page that acts as a buffer when writing to memory. Data is first written to the scratchpad where it can be read back. After the data has been verified, a copy scratchpad command will transfer the data to memory. This process ensures data integrity when modifying the memory. A 48-bit serial number is factory lasered into each DS1996 to provide a guaranteed unique identity which allows for absolute traceability. The durable MicroCan package is highly resistant to environmental hazards such as dirt, moisture, and shock. Its compact button-shaped profile is self-aligning with mating receptacles, allowing the DS1996 to be easily used by human operators. Accessories permit the DS1996 to be mounted on almost any surface including plastic key fobs, photo-ID badges and printed circuit boards. Applications include access control, work-in-progress tracking, electronic travelers, storage of calibration constants, and debit tokens.

Key Features



Enlarge+

Twitter

Facebook
Related Resources

Google

LinkedIn
NEW PRODUCTS

Pinterest

Gmail
RELATED PACKAGING

Email

Print
TECHNICAL DOCS

AddThis
REFERENCE DESIGNS

- 65,536 bits of read/write nonvolatile memory
- Overdrive mode boosts communication speed to 142 kbits per second
- 256-bit scratchpad ensures integrity of data transfer
- Memory partitioned into 256-bit pages for packetizing data
- Data integrity assured with strict read/write protocols
- Operating temperature range from -40°C to +70°C
- Over 10 years of data retention

© 2015 Maxim Integrated | [Contact us](#) | [Careers](#) | [Legal](#) | [Privacy](#) | [Cookie Policy](#) | [Site Map](#)