

The Ultimate Computer Reference



The Comprehensive Standard for Business, School, Library, and Home





Microsoft Press Computer Dictionary
Third Computer Third Computer Computer

- Over 300 illustrations and diagrams
- Extensive Internet coverage
- Featured in Microsoft® Bookshelf®
- Covers software, hardware, concepts, and more!

Qualcomm Incorporated

Microsoft Press



PUBLISHED BY
Microsoft Press
A Division of Microsoft Corporation
One Microsoft Way
Redmond, Washington 98052-6399

Copyright © 1997 by Microsoft Corporation

All rights reserved. No part of the contents of this book may be reproduced or transmitted in any form or by any means without the written permission of the publisher.

Library of Congress Cataloging-in-Publication Data Microsoft Press Computer Dictionary. -- 3rd ed.

p. cm. ISBN 1-57231-446-X

1. Computers--Dictionaries. 2. Microcomputers--Dictionaries.

I. Microsoft Press. QA76.15.M54 1997 004'.03--dc21

97-15489

CIP

Printed and bound in the United States of America.

3 4 5 6 7 8 9 QMQM 2 1 0 9 8

Distributed to the book trade in Canada by Macmillan of Canada, a division of Canada Publishing Corporation.

A CIP catalogue record for this book is available from the British Library.

Microsoft Press books are available through booksellers and distributors worldwide. For further information about international editions, contact your local Microsoft Corporation office. Or contact Microsoft Press International directly at fax (425) 936-7329.

Macintosh, Power Macintosh, QuickTime, and TrueType are registered trademarks of Apple Computer, Inc. Intel is a registered trademark of Intel Corporation. DirectInput, DirectX, Microsoft, Microsoft Press, MS-DOS, Visual Basic, Visual C++, Win32, Win32s, Windows, Windows NT, and XENIX are registered trademarks and ActiveMovie, ActiveX, and Visual J++ are trademarks of Microsoft Corporation. Java is a trademark of Sun Microsystems, Inc. Other product and company names mentioned herein may be the trademarks of their respective owners.

Acquisitions Editor: Kim Fryer

Project Editor: Maureen Williams Zimmerman, Anne Taussig

Technical Editors: Dail Magee Jr., Gary Nelson, Jean Ross, Jim Fuchs, John Conrow, Kurt Meyer,

Robert Lyon, Roslyn Lutsch



Contents

Introduction

Dictionary of Computer Terms

Appendix A

ASCII Character Set

Appendix R

IBM Extended Character Set

Appendix C

Apple Macintosh Extended Character Set

Appendix D

EBCDIC Character Set

Appendix E

Numeric Equivalents
534



change, so as to keep the phosphors irradiated. **2.** To recharge dynamic random access memory chips (DRAMs) so that they continue to retain the information stored in them. Circuitry on the memory board automatically performs this function. *See also* refresh cycle.

refreshable \rə-fresh´ə-bl\ adj. In programming, referring to a program module capable of being replaced in memory without affecting processing of the program or the information being used by the program.

refresh cycle \rə-fresh´ sī kl\ n. The process in which controller circuitry provides repeated electric pulses to dynamic random access memory chips in order to renew the stored electric charges in those locations that contain binary 1. Each pulse is one refresh cycle. Without constant refreshing, dynamic semiconductor RAM loses any information stored in it—as it does when the computer is turned off or when the power fails. See also dynamic RAM, static RAM.

refresh rate \ro-fresh' rāt\\ n. In reference to video hardware, the frequency with which the entire screen is redrawn to maintain a constant, flicker-free image. On TV screens and raster-scan monitors, the electron beam that lights the phosphor coating on the inner surface of the screen typically refreshes the entire image area at a rate of about 60 hertz, or 60 times per second. (Interlaced monitors, which redraw alternate lines during each sweep of the electron beam, actually refresh any particular line only 30 times per second. Because odd and even lines are refreshed on successive sweeps, however, the effective refresh rate is 60 times per second.)

REGEDIT \rej^ed`it\ n. See Registry Editor.

regenerate \re-jen´ər-āt\ vb. See rewrite.

regeneration buffer $\ \bar{a} = -\bar{a}$ shən buf ər $\ n$. *See* video buffer.

regenerator $\bar{a} \to n$. See repeater.

region \ref jen\ n. 1. An area dedicated to or reserved for a particular purpose. 2. In video programming, a contiguous group of pixels that are treated as a unit. On the Apple Macintosh, for example, a region is an area in a grafPort that can be defined and manipulated as an entity. The vis-

ible working area within a window is an example of a region. *See also* grafPort.

region fill \re jən fil\\ n. In computer graphics, the technique of filling a defined region on the screen with a selected color, pattern, or other attribute. *See also* region.

register \rej'i-stər`\ n. A set of bits of high-speed memory within a microprocessor or other electronic device, used to hold data for a particular purpose. Each register in a central processing unit is referred to in assembly language programs by a name such as AX (the register that contains the results of arithmetic operations in an Intel 80x86 processor) or SP (the register that contains the memory address of the top of the stack in various processors).

registration \rej\end{a}-stra\shan\ n. The process of precisely aligning elements or superimposing layers in a document or a graphic so that everything will print in the correct relative position. *See also* registration marks.

registration marks \rej-a-strā´shən märks`\ *n*. Marks placed on a page so that in printing, the elements or layers in a document can be arranged correctly with respect to each other. Each element to be assembled contains its own registration marks; when the marks are precisely superimposed, the elements are in the correct position. See the illustration.



Registration marks.

Registry or **registry** \rej'is-trē\\ n. A central hierarchical database in Windows 95 and Windows NT used to store information necessary to configure the system for one or more users, applications, and hardware devices. The Registry contains information that Windows 95 and Windows NT continually reference during operation, such as profiles for each user, the applications installed on the computer and the types of documents each can create, property sheet settings for folders and application icons, what hardware exists on the system, and which ports are being used. The Registry

