



US007484264B2

(12) **United States Patent**
Kraemer et al.

(10) **Patent No.:** **US 7,484,264 B2**
(45) **Date of Patent:** ***Feb. 3, 2009**

(54) **AUTOMOBILE WINDSHIELD WIPER BLADE**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Godelieve Kraemer**, Huegelsheim (DE);
Juergen Mayer, Gaggenau (DE)

DE 1028896 4/1958

(73) Assignee: **Robert Bosch LLC**, Broadview, IL (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

International Search Report dated Aug. 19, 2002, European Patent Office, International Application No. PCT/DE02/01336 published Jul. 11, 2002.

(21) Appl. No.: **11/760,394**

Primary Examiner—Gary K Graham

(22) Filed: **Jun. 8, 2007**

(74) *Attorney, Agent, or Firm*—Michael Best & Friedrich LLP

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2007/0226941 A1 Oct. 4, 2007

Related U.S. Application Data

(62) Division of application No. 10/312,279, filed as application No. PCT/DE02/01336 on Apr. 11, 2002, now Pat. No. 7,228,588.

(30) **Foreign Application Priority Data**

Apr. 26, 2001 (DE) 101 20 467

(51) **Int. Cl.**
B60S 1/38 (2006.01)

(52) **U.S. Cl.** **15/250.201**; 15/250.43;
15/250.48

(58) **Field of Classification Search** 15/250.43,
15/250.44, 250.201, 250.451, 250.452, 250.48,
15/250.361

See application file for complete search history.

(56) **References Cited**



U.S. PATENT DOCUMENTS

2,687,544 A 8/1954 Scinta

(Continued)

A wiper blade that cleans panes, in particular of motor vehicles. The wiper blade (10) comprises a strip-shaped, elongated, elastically resilient support element (12), the lower strip surface of which faces the pane (14) and is provided with an elongated, elastic wiper strip (24) running parallel to the longitudinal axis. The upper strip surface (16) of the element is provided with a wind deflector strip (42), which consists of an elastic material, extends in the longitudinal direction of the support element and has an oncoming stream surface (54) that faces the principal flow direction, (arrow 52), of the air stream. A particularly advantageous wiper blade, which is cost-effective to produce, can be achieved if the wind deflector strip, (when viewed in cross-section), comprises two limbs (48, 50), diverging from a common base (46) but mutually attached thereto, the free ends of said limbs facing the pane (14) and being supported on the wiper blade, and if in addition, the oncoming stream surface (54) is configured on the external face of one limb (50) and the cross-sectional profile of the wind deflector strip is the same over its entire length.

6 Claims, 2 Drawing Sheets



US 7,484,264 B2

U.S. PATENT DOCUMENTS					
			DE	1505357	5/1969
			DE	2336271	7/1973
			DE	2344876	9/1973
2,814,820	A	12/1957 Elliott et al.	DE	2440179	8/1974
2,983,945	A	5/1961 De Pew	DE	2311293	9/1974
3,084,372	A	4/1963 Krohm	DE	2839587	A1 3/1980
3,088,155	A	5/1963 Smithers	DE	29611722	7/1996
3,107,384	A	10/1963 Wise	DE	19627114	1/1998
3,116,507	A	1/1964 Scinta	DE	19627115	1/1998
3,116,509	A	1/1964 Contant et al.	DE	19650159	6/1998
3,121,133	A	2/1964 Mathues	DE	19734843	2/1999
3,317,945	A	5/1967 Ludwig	DE	19736368	2/1999
3,418,679	A	12/1968 Barth et al.	DE	19802451	7/1999
3,427,637	A	2/1969 Quinlan et al.	DE	19856300	A1 6/2000
3,626,544	A	12/1971 Lopez et al.	DE	10000373	A1 8/2001
3,636,583	A	1/1972 Rosen	EP	0316114	5/1989
3,785,002	A	1/1974 Quinlan et al.	EP	0624133	2/1993
3,879,793	A	4/1975 Schlegel et al.	EP	0646507	4/1995
3,881,214	A	5/1975 Palu	EP	0930990	7/1999
3,958,295	A	5/1976 Green et al.	EP	2199302	5/1974
4,360,943	A	11/1982 Thompson et al.	FR	2679185	1/1993
4,683,606	A	8/1987 Sharp	FR	1222648	2/1971
5,052,072	A	10/1991 Chen	GB	1269993	4/1972
5,493,750	A	2/1996 Bollen et al.	GB	1429820	3/1976
5,546,627	A	8/1996 Chen	GB	2036547	7/1980
5,933,910	A	8/1999 Buechele et al.	GB	2106775	4/1983
6,192,546	B1	2/2001 Kotlarski	GB	2336293	10/1999
6,292,974	B1	9/2001 Merkel et al.	GB	2346318	A 9/2000
6,588,048	B2*	7/2003 Ohyama 15/250.43	JP	6219467	2/1987
6,675,434	B1	1/2004 Wilhelm et al.	JP	6222172	2/1987
6,944,905	B2	9/2005 De Block et al.	JP	2001502638	T 2/2001
6,978,512	B2	12/2005 Dietrich et al.	JP	9850261	11/1998
7,228,588	B2*	6/2007 Kraemer et al. 15/250.201	WO	9902383	1/1999
2003/0014828	A1	1/2003 Edner-Walter et al.	WO	0034090	6/2000
			WO	0149537	7/2001
			WO	0192073	A1 12/2001
FOREIGN PATENT DOCUMENTS					
DE	1077540	3/1960			
DE	1247161	8/1967			

* cited by examiner






Fig. 1



AUTOMOBILE WINDSHIELD WIPER BLADE

RELATED APPLICATION

This application is a divisional of U.S. application Ser. No. 10/312,279, filed Jul. 29, 2003, now U.S. Pat. No. 7,228,588 the entire content of which is incorporated herein by reference.

BACKGROUND

In wiper blades with a spring-action support element, the support element is intended to guarantee as even a distribution of wiper blade pressure onto the windshield issued from the wiper arm as possible, and over the entire wipe field swept by the wiper blade. By appropriately bending the un-loaded support element into shape—the unloaded state being when only the two ends of the wiper blade sit against the windshield—the ends of the wiper strip, which sits completely against the windshield when the wiper blade is in operation, are pushed toward the windshield by the loaded support element, even if the radii of curvature of spherically curved vehicle windshields change with the wiper blade position. The curvature of the wiper blade must therefore be somewhat greater than the maximum curvature measured within the wipe field on the windshield to be wiped. This is because during wiping, the wiper strip, or its wiping lip that sits against the windshield, must be continuously pressed against the windshield with a specific force. The support element thus replaces the expensive stirrup design with two flexible rails located in the wiper strip, as is practiced in conventional wiper blades (DE-OS 15 05 257) since the support element provides the necessary cross-stiffening of the elastic rubber wiper strip in addition to providing a distribution of pressure. Specifically, in the known wiper blade the contact force directed toward the windshield that is exerted by a wiper arm onto a main stirrup is conveyed to two claw-like stirrups and distributed from these onto the elastic rubber wiper strip via four claws. The two flexible rails of this wiper blade mainly provide a cross-stiffening of the wiper strip between the claws when the wiper blade is pushed across the windshield perpendicular to its longitudinal length.

SUMMARY OF THE INVENTION

In a prior art wiper blade of this type (DE 197 36 368.7), the wiper blade is provided with a so-called wind deflection strip in order to produce a force component directed toward the windshield to counteract the tendency of the wiper blade to lift off of the windshield due to the airflow at high vehicle speeds. To this end, the wind deflection strip has a leading edge during the pendulum wiping motion that is mainly impacted by the driving wind, said leading edge being designed as an incident surface. The cross section of the wind deflection strip has approximately the shape of a right triangle, one leg of which directly opposite the support element and the hypotenuse of which represents the incident surface. This makes a sharp angle with the pendulum-like plane of motion of the wiper blade and with the surface of the windshield. The triangle profile used requires a relatively large amount of material to manufacture the wind deflection strip, which is reflected in the costs of the wiper blade. Moreover, the weight of the wiper blade becomes undesirably high. Specifically, the increased mass to be accelerated in the pendulum wiping motion requires a more powerful drive system

wiper blade can be adversely affected by the bending stiffness, which depends on its profile, of a wind deflection strip thus formed.

In the wiper blade according to the invention, the weight of the wind deflection strip is considerably reduced due to the cross sectional structure of an angular profile. Moreover, in addition to the material savings, there is a reduction in the moving mass along with the advantages with respect to the design of the drive system and the pendulum gear as a result. Also, the bending stiffness of the wind deflection strip is reduced, thus considerably reducing its influence on the bending and spring behavior of the wiper blade support element. For more detailed shapes, this wind deflection strip can be manufactured both as an injection molded part as well as using the simple, and thus cost effective, extrusion process.

In a further development of the invention, at least one support means is placed between the two sides of the wind deflection strip at a distance from their common base point, said support means stabilizing the sides. This provides a certain degree of stiffening even when using a relatively soft material for the manufacture of the wind deflection strip, which provides the necessary form stability of the wind deflection strip even at a high wind loads.

What is helpful here is that the support means is made up of a wall that extends in the longitudinal direction of the wind deflection strip that is connected to both sides, said wall extending along the entire length of the wind deflection strip, if necessary.

If the support element is made up of two flexible rails, each of which sits in a longitudinal notch associated with it, respectively, said longitudinal notches being open toward the opposite lateral sides of the wiper strip, and if the outer strip edges of each of said flexible rails extend out of these notches, the support means are positioned at a distance from the support element. This results in a space between the wiper strip and the support means into which the area of the wiper strip located above the support element can extend. By correspondingly dimensioning this space, undesired friction between the wiper strip and the wind deflection strip is prevented.

In another embodiment of the concept of the invention, the free ends of the sides of the wind deflection strip are provided, respectively, with claw-like extensions that grip tightly around these exterior strip edges of the support element at least in sections. This provides the ability to snap the wind deflection strip onto the exterior edge or to push it onto this edge in the longitudinal direction. This makes it possible to do away with a glued connection between the wind deflection strip and the support element. A glued connection of this type can limit the flexibility of the support element needed to attain a satisfactory wipe result due to its stiffness.

In the process, it can be advantageous if the wind deflection strip is designed as a binary component whose longitudinal area provided with the claw-like extensions is made of a harder material than the longitudinal area lying closer to the base. In this way, the longitudinal area of the wind deflection strip provided with the extensions can be manufactured from a material that is well suited for the purposes of securing the wind deflection strip to the support element, whereas the area of the wind deflection strip provided with the incident surface can be made of a material that accounts for the further requirements on the wind deflection strip.

In a wiper blade designed in this way, it can be advantageous if the transition from the harder longitudinal area to the softer longitudinal area occurs near the wall.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.