# **DECLARATION OF SCOTT ANDREWS**

- I, Scott Andrews, declare as follows:
- 1. I hold a B.Sc. degree in Electrical Engineering from University of California–Irvine and a M.Sc. degree in Electronic Engineering from Stanford University. In various positions at, among others, TRW and Toyota, I have been responsible for research and development projects relating to, among others, numerous vehicle navigation systems, information systems, and user interface systems. My qualifications are further set forth in my *curriculum vitae* (Exhibit A). I have been retained by Volkswagen Group of America, Inc. in connection with its petition for *inter partes* review of U.S. Patent No. 8,781,839 (the "'839 patent"). I have over 35 years of experience in fields relevant to the '839 patent, including telecommunications systems and navigation systems.
- 2. I have reviewed the '839 patent, as well as its prosecution history and the prior art cited during its prosecution. I have also reviewed U.S. Patent No. 6,249,740 ("Ito"), U.S. Patent No. 6,201,544 ("Ezaki"), U.S. Patent No. 6,091,956 ("Hollenberg"), U.S. Patent No. 5,574,443 ("Hsieh"), U.S. Patent No. 6,064,323 ("Ishii"), U.S. Patent No. 4,558,300 ("Goldman"), U.S. Patent No. 6,211,777 ("Greenwood"), and "Plaintiff and Counter-Defendant West View Research, LLC's Revised Disclosure of Asserted Claims and Infringement Contentions,

Pursuant to Patent L.R. 3.1 and the June 10, 2015 Court Order" ("Infringement Contentions"), dated June 26, 2015.

### The '839 Patent

3. The '839 patent describes an interactive display in an elevator that is responsive to verbal commands. '839 patent, col. 7, lines 5 to 27. Signals captured by a microphone 118 as part of a speech recognition module 104 are digitized by an analog to digital converter 141 and processed using a speech recognition algorithm to produce digital representations of the user's speech. '839 patent, col. 7, lines 59 to 63. The digital representations are compared to a speech library to identify known words and the desired functionality is implemented. '839 patent, col. 7, line 63 to col. 8, line 2. The display device includes a touch screen display 113 that "generates a variety of different messages or display formats" based on the user's input and query. '839 patent, col. 8, lines 45 to 47. For example, one such message or display format includes a building directory. '839 patent, col. 9, line 37 to col. 11, line 37. The user can speak the specific name of the party the user wishes to find, the speech recognition module 104 converts the detected speech to a digital format, and the digitized speech is compared to the contents of a directory file to find any matches. '839 patent, col. 10, lines 9 to 19.

# The Disclosures of Ito, Ezaki, and Hollenberg – Claims 1, 10, 11, 16, 22, 23, and 35

Ito, Ezaki, and Hollenberg disclose a "[c]omputerized apparatus useful for 4. locating an organization or entity, the organization or entity being disposed within a building or structure" as claimed in claim 1 and a "[c]omputerized apparatus" as claimed in claim 35. For example, Ito discloses an apparatus that includes both a processing section and a display. Ito, col. 9, lines 51 to 67. The display in Ito is a touch panel display, which is located in the vehicle. *Id.* at col. 10, lines 39 to 45. Ito also discloses a "processing section 101" with "a CPU as its main component" and a "program storage section 102" that "serves as a memory for storing programs which will be executed by a processing section." Ito, col. 9, lines 51 to 67. Ito discloses that the user operates an input section 105 to "input information about the destination, such as the facility name." Id. at col. 15, lines 50 to 54. And Ito describes, for example, displaying maps on a display device, including a recommended route to the selected destination on an output display. Ito, col. 10, lines 39 to 50, col. 16, lines 24 to 27. Ezaki discloses a navigation apparatus which displays a detailed map, including the visual display of "the floor number of a floor, in a building, on which a target institution is located." Ezaki, col. 2, lines 62 to 65. The "target institution" Ezaki's navigation apparatus is an "organization or entity." Additionally, Ezaki's navigation apparatus is computerized, as element 18 in Figure 2 is a CPU. Hollenberg also discloses a navigation system that includes

"at least one mobile computer" that can be used for location finding in areas "enclosed within buildings, such as shopping malls." Hollenberg, col. 5, lines 13 to 28.

- 5. Ito and Hollenberg disclose "a wireless interface" as claimed in claims 1 and 35. For example, Ito discloses that the transmitting and receiving section "includes devices such as a modem and the like" for communicating wirelessly with the base station. Ito, col. 10, lines 51 to 57. Ito also discloses that car phones, portable phones, PHS, and the like may be used to connect the navigation apparatus and the base station. Ito, col. 10, lines 51 to 57. The transmitting and receiving section 108 interfaces with these wireless systems. Additionally, Hollenberg discloses a wireless system for providing information to "mobile computers" and that these mobile computers have "multiple transmitters and receivers," including "a transceiver for wireless voice and data telecommunications." Hollenberg, Abstract, col. 5, lines 13 to 28.
- 6. Ito, Ezaki, and Hollenberg disclose a "data processing apparatus" as claimed in claims 1 and 35. For example, Ito discloses a CPU as the main component of the processing section 101. Ito, col. 9, lines 51 to 67; Fig. 1. Additionally, Ezaki discloses a processor (CPU) for controlling the navigation apparatus. Ezaki, col. 5, lines 10 to 11. Hollenberg discloses a computer including a "computer central processing unit" and a "DSP unit." Hollenberg, col. 6, lines 22 to 26.

- 7. Ito and Hollenberg disclose "a touch-screen input and display device" as claimed in claims 1 and 35. Ito discloses a display 106 that includes a liquid crystal display or CRT that is equipped with a touch panel as a data input device. Ito, col. 10, lines 39 to 50. A user "can use a finger or the like to touch an icon or the like displayed on the screen of the display 106." Ito, col. 10, lines 39 to 50. Hollenberg discloses "a touch-screen graphical display unit 4a" that displays menus or icons. Hollenberg, col. 12, lines 13 to 40.
- 8. Ito discloses "a speech digitization apparatus in data communication with the data processing apparatus" as claimed in claims 1 and "a speech recognition apparatus in data communication with the data processing apparatus" as claimed in claim 35. Ito discloses that the input section 105 may be "a data input device using voice recognition," in which the user uses his or her voice to input data and commands. Ito, col. 10, lines 39 to 47. The input 105, as shown in Figure 1, is connected to, and therefore in data communication with, the processing section 101 (i.e., the data processing apparatus). West view has acknowledged (and I agree) that "all speech recognition systems inherently digitize the speaker's analog voice." Infringement Contentions, p. 729.
- 9. Ito, Ezaki, and Hollenberg also disclose "a storage apparatus in data communication with the data processing apparatus, said storage apparatus comprising at least one computer program" as claimed in claims 1 and 35. Ito

discloses a "program storage section 102" which serves as a memory for storing programs executed by the processing section. Ito, col. 9, lines 51 to 67. As shown in Figure 1, the program storage section is connected to in data communication with the processing section. Ezaki discloses a navigation apparatus which includes "a ROM for storing various types of programs" such as for "guide route" searching." Ezaki, col. 5, lines 10 to 22. The ROM 19 is connected to the CPU 18 via a bus 28. Ezaki, Fig. 2. Hollenberg discloses the necessary memory ("storage, drives, and RAM units") and computer programs to "provide for efficient situation information exchange." Hollenberg, col. 5, lines 13 to 28. These computer programs include a "user's computer control program" by which the mobile computer "requests information and services and subsequently processes the information communicated from the service provider." Hollenberg, col. 23, line 64 to col. 24, line 3.

10. Ito discloses "at least one program being configured to ... receive a digitized speech input via the speech digitization apparatus, the input relating to an organization or entity which a user wishes to locate" as claimed in claim 1; Ito discloses "at least one program being configured to ... receive a digitized speech input via the speech recognition apparatus," and Ezaki and Hollenberg disclose "the input relating to an organization or entity disposed within a building or structure which a user wishes to locate," as claimed in claim 35. Ito discloses that,

among the inputs that the user may make to the input 105 (which uses voice recognition), are "information about the destination, such as the facility name, telephone number and address thereof, and a route search request." Ito, col. 15, lines 47 to 58. This input is related to an organization or entity that a user wishes to locate. Ezaki discloses a system that allows the user to cause a search of a yellow pages directory or institution database and, in response, the apparatus "calculates a user name list (object list) of a building ... from the building database stored in the Yellow Page data memory." Ezaki, col. 6, lines 49 to 58. Therefore, Ezaki discloses that an organization or entity the user wishes to locate can be disposed within a building. Hollenberg discloses a system that includes capabilities for location finding in areas such as "those enclosed within buildings, such as shopping malls." Hollenberg, col. 5, lines 13 to 28.

11. Ito discloses "based at least in part on the input, causing recognition of at least one word therein relating to the organization or entity" as claimed in claim 1. The programs in Ito can receive input of data and commands from "a data input device using voice recognition." Ito, col. 10, lines 39 to 47. Information about the destination, e.g., a facility name, can be input. The information includes a least one word relating to a facility. Additionally, as described, for example, in Ishii, col. 3, lines 11 to 18, it is obvious that in voice recognition systems, software programs process a representation of speech in order to identify a spoken word or phrase.

- 12. Ito, Ezaki, and Hollenberg disclose "identification of a location associated with the organization or entity based at least in part on the at least one recognized word, the location being inside of the building or structure" as claimed in claim 1. Ito discloses that the user inputs are used to search a database of navigation data, which uses the inputs to extract a position of the destination, or "facility position." Ito, col. 11, lines 1 to 30, col. 15, lines 50 to 67. Ezaki discloses a navigation apparatus for a vehicle that displays a detailed map that provides directions to a target destination. Ezaki, col. 1, line 58 to col. 2, line 19. The displayed map includes the shapes of buildings and roads, and visually displays "the floor number of a floor, in a building, on which a target institution is located to reliably guide a user to the target institution." Ezaki, col. 2, lines 62 to 65. Hollenberg also discloses a system that identifies a location inside a building or structure, such as a shopping mall. Hollenberg, col. 5, lines 13 to 28.
- 13. Ito, Ezaki, and Hollenberg disclose at least one computer program configured to "provide a graphical or visual representation of the location on the touch screen input and display device in order to aid a user in finding the organization or entity" as claimed in claims 1 and 35. Ito discloses a display device that displays detailed maps, including a recommended route to the selected destination. Ito, col. 16, lines 24 to 27. An exemplary map showing destination PA is shown in Figure 9(A). Ezaki discloses a display device for displaying a map

and/or menu image. Ezaki, col. 5, lines 10 to 23. The displayed map displays the shapes of buildings and roads, and visually displays "the floor number of a floor, in a building, on which a target institution is located to reliably guide a user to the target institution." Ezaki, col. 2, lines 62 to 65. This map, shown in Figure 1, "displays the floor by an L-shaped mark FL." Hollenberg discloses a graphical display, on which maps can be displayed. Hollenberg, col. 7, lines 31 to 40. Figure 2 of Hollenberg depicts an "exemplary retail store floor plan," that displays items of interest near the user's current location. Hollenberg, col. 10, lines 52 to 55; Fig. 2.

14. Ito, Ezaki, and Hollenberg disclose "the graphical or visual representation of the location also comprising a graphical or visual representation of at least the immediate surroundings of the organization or entity" as claimed in claim 1, and "the graphical or visual representation of the location comprising a map graphic showing the location of the organization or entity relative to other organizations or entities proximate thereto inside of the building or structure" as claimed in claim 35. Ito discloses displaying area guidance for the area surrounding the destination point. As shown in Figure 9(A) of Ito, a graphical representation of the immediate surroundings of the destination is displayed. Ito, Fig. 9(A). An exemplary map of the area surrounding the departure point ("PD") is shown in Figure 9(B). See Ito, col. 17, lines 4 to 19. Although Figure 9(B) illustrates a departure point, Ito

discloses that destination points are treated in generally the same manner (id., 14:19-38), describing that when "the vehicle has entered the surrounding area A3 of the destination PA ... a map thereof is displayed on the display 106" and "an enlarged view of the destination PA may be displayed when the vehicle comes within a prescribed distance to the destination PA." Ito, col. 18, lines 36 to 52. The maps shown in Figures 40(C) and 44, for example, of Ito include a department store, a fire station, and a bank shown relative to each other. The maps disclosed by Ito include graphical representation of immediate surroundings, and also a graphical representation of a map graphic in which the immediate surroundings of an entity or organization are displayed. Ezaki discloses a display device 27 in a navigation apparatus for displaying a map and/or menu image. Ezaki, col. 5, lines 10 to 23. The detailed map information in Ezaki includes neighboring buildings of a "target location" displayed by an indicator shown in Figure 5. Ezaki, col. 5, line 66 to col. 6, line 3. Ezaki also displays a "user name list of the building," or tenant list, which is "a visual representation of the immediate surroundings within the building of the entity" and also a graphical representation of a "map graphic" on which the "immediate surroundings" or an entity or organization are displayed. Hollenberg also discloses, in Figure 2, a graphical display showing "an exemplary retail-store floor plan" and "floor plan details" such as the locations of nearby exit doors or an escalator, both of which are around the user's location. Hollenberg,

- Fig. 2, col. 10, lines 52 to 55, col. 13, lines 22 to 46. Figure 4 also discloses an "urban plan" with organizations (3e, 3f) near the user's current location. Hollenberg, col. 10, lines 60 to 64, col. 14, line 65 to col. 15, line 8.
- 15. Hollenberg and Ezaki disclose "the immediate surroundings being inside the building or structure" as claimed in claim 1. Hollenberg describes a mobile computer for location finding within buildings including by providing users with maps and floor plan details to "help find their way around the store or shopping mall." Hollenberg, col. 5, lines 13 to 28; col. 7, lines 31 to 40; col. 13, lines 22 to 45. Figure 2 depicts a "graphical display showing an exemplary retail-store floor plan" showing "floor plan details" such as the locations of a near exit (3b) or an escalator (3d) around a user's location (6a). Hollenberg, Fig. 2 and col. 10, lines 52 to 55, col. 13, lines 22 to 46. As described above, Ezaki displays "a user name list of the building" on a part of the display screen with the map information; the user name list of the tenants in the building is a visual representation of the immediate surroundings within the building of the entity. Ezaki, col. 2, lines 62 to 65, col. 3, lines 21 to 24.
- 16. Ito and Hollenberg disclose "the computerized apparatus is mounted on or proximate to a surface of a land-mobile transport apparatus such that an operator of the transport apparatus can view and access a touch screen of the touch screen input and display device, and make input to the speech digitization apparatus,

while operating the transport apparatus" as claimed in claim 10. Ito discloses that the vehicle navigation apparatus 100 may be "mounted in a vehicle as a movable body." Ito, col. 8, lines 11 to 16. Ito describes an input 105 of the navigation apparatus includes a touch panel display 106 such that the user (e.g., the driver of the vehicle) "can use a finger or the like to touch an icon or the like displayed on the screen of the display 106" and a data input device using voice recognition so that the user (e.g., the driver) can use his/her voice to input corresponding data and commands." Ito, col. 10, lines 39 to 47; col. 14, lines 19 to 38. In order for a driver to be able to view the detailed guidance provided on the display and to input commands via the touch screen or voice recognition, both the voice input device (e.g., a microphone) and touch screen display are accessible to the driver and the navigation apparatus is mounted on or proximate to some surface of the vehicle ("a land-mobile transport apparatus") accessible to the driver. Hollenberg describes a mobile computer having a graphical display unit for location finding that can be mounted in an automobile. Hollenberg, col. 6, lines 31 to 54. Figs. 7 and 8 of Hollenberg illustrate a bracket that can be used for installing and mounting the mobile computer in a vehicle, "for example, device 2d may be inserted into bracket 40 mounted in a vehicle for greater operative mobility and used for networking with vehicular systems." Hollenberg, col. 19, line 61 to col. 20, line 51. When used in a vehicle, the display can provide local information, for example traffic

congestion information. Hollenberg, col. 6, lines 31 to 54. In order for a driver of a vehicle to be able to view the information provided on the graphical display, the mobile computer is mounted on or proximate to some surface of the automobile ("a land-mobile transport apparatus") accessible to the driver.

Ito and Hollenberg disclose that "the identification of the location comprises 17. accessing a remote server via a network in data communication with the computerized apparatus via the wireless interface" as claimed in claim 11. Ito discloses that the user inputs are used to search a remote network entity, which is a database of navigation data that is not located in the vehicle, and that the vehicle receives position information related to the destination, or an intersection close to the position of the destination. Ito, Fig. 1, col. 8, lines 28 to 40, col. 8, line 52 to col. 9, line 8. This information is received by the navigation apparatus 100 via the wireless interface. Ito, col. 10, line 64 to col. 11, line 30, col. 15, lines 30 to 37. Hollenberg discloses a mobile computer in communication with an "information service provider," which responds to user requests, for example, for "proximate situation information." Hollenberg, col. 5, lines 13 to 28; col. 11, lines 42 to 67; col. 18, line 57 to col. 19, line 14. Figure 1 shows a service provider, which includes network 30a and data 38a, is connected to a communications network 31a, and is also in communication with mobile computers 18a, 18b, and 18c via transceivers 14a, 14b, and 14c; the service provider transmits "proximate

information" and "requested information" from data 38, network 30a and communications network 31a to the mobile computers. Hollenberg, col. 13, lines 9 to 21. A remote server is accessed in order to receive information at the mobile computer.

Hollenberg discloses that "the computerized apparatus is further configured 18. to display advertising content selected by one or more remote servers accessed via a network in data communication with the computerized apparatus via the wireless interface" as claimed in claim 16. Hollenberg discloses the display of advertising content, in that its mobile computer can display "merchant's advertising messages" or "special offers to customers." Hollenberg, col. 9, lines 11 to 14; col. 9, lines 23 to 25. For example, referring to Figure 2, Hollenberg describes that "[a]s the user's location ... approaches within a selectable distance of proximate information station 3a, proximate station banner 6d ['Fragrances 1 hr. Special'] appears on display 4a, followed by proximate merchandise banner 6e ['Petite armure on sale 33.00'] to call user's attention to, for example, a short-term offer of merchandise." Hollenberg, col. 13, lines 22 to 45. Referring to Figure 4, Hollenberg further describes that as the user "approaches within a selectable distance of ... retail store site 3e ... an advertising message ... would appear on the display." Hollenberg, col. 16, lines 11 to 49. That information is retrieved by the above-discussed "service provider" from its network 30a and data 38a, or through communications

network 31a, and transmitted to the user's mobile computer; in discussing the "service provider computer control program," Hollenberg describes that "the service provider selects appropriate information from the system database (DB) specific to user information ... and this information is transmitted to the user." Hollenberg, col. 13, lines 9 to 21, col. 23, lines 9 to 18 and 48 to 54.

19. Ito discloses that "at least one computer program is further configured to generate on the touch-screen input and display device a plurality of soft function keys or icons" as claimed in claim 22. Ito discloses that the user can "touch an icon of a desired guidance area on the display 106 to select the guidance area" as shown in Figure 22. Ito, col. 30, lines 61 to 63. These buttons in Ito are soft function keys or icons. Additionally, Figures 23 to 25 of Ito describe various icons that assist the user with selecting various guidance options. Ito, col. 30, line 63 to col. 32, line 60. Hollenberg describes a mobile computer with a graphical display unit which displays various menus and icons that can be selected by a user; for example, the display can provide a service provider menu 6c, a device control icon 8a, a visit list control icon 5a, a look-ahead icon 8f, or a proximate information menu 6p. Hollenberg, col. 12, lines 13 to 40, col. 13, lines 46 to 63, col. 18, lines 1 to 18. Selecting a provided menu or icon will "caus[e] the computer to proceed in processing or executing the pertinent information or code." Hollenberg, col. 13, lines 60 to 63.

- 20. Ito and Hollenberg disclose "at least one of the soft function keys or icons having a function associated therewith relating to obtaining directions" as claimed in claim 22. Ito discloses that icons K1 to K5 have functions relating to obtaining directions; specifically, they are used to select the "desired guidance areas." Ito, col. 30, line 66 to col. 31, line 14, Fig. 22. Figures 23 and 24 of Ito shows further display screens with selectable icons ("Please touch desired item") providing options for obtaining directions. Ito, Figs. 23 and 24, col. 31, line 39 to col. 32, line 6. Hollenberg describes displaying various menus and icons that can be executably selected by a user. Hollenberg, col. 12, lines 13 to 40; col. 13, lines 46 to 63. As shown in Figure 2, the display in Hollenberg includes a menu option for displaying a floor map that can be used to orient oneself within the building or otherwise find proximate items of interest, such as exit doors or escalators. Hollenberg, Fig. 2, col. 13, lines 38 to 45. The floor map menu option is a soft function key which relates to obtaining directions.
- 21. Ito and Hollenberg disclose "at least one of the soft function keys having a function associated therewith relating to points of interest" as claimed in claim 22. Of the soft function keys described in relation to Figure 22 of Ito, one of the options the user can select includes "the icon K2 for 'surrounding area of destination." Ito, Fig. 22, col. 30, line 63 to col. 31, line 14. The "surrounding area of destination" soft key provides information on points of interest in the vicinity of

the destination, for example, "further in the case where the driver need to have information on the presence or absence of parking and various facilities in the area around the destination, it is convenient for the drive [sic] to have area guidance data around the destination." Ito, col. 31, lines 22 to 26. "Parking and various facilities" are points of interest. Hollenberg describes displaying various menus and icons that can be executably selected by a user; certain menus and icons relate to points of interest, such as, with reference to Figure 2, the "proximate station banner 6d" and "proximate merchandise banner 6e," both of which may be "mappable hypertext items that the user may executably select in order to receive additional information" (Hollenberg, col. 12, lines 13 to 40; col. 13, lines 46 to 63), or, with reference to Figure 6, "proximate information menu 6p," "proximate submenu 6q to provide user with information pertinent to the attractions located near the relatively approaching highway interchange," (Hollenberg, col. 19, lines 24 to 33). Additionally, Figure 6 shows the soft key "Visitor Sights," element 6p, and sub-menus soft keys 6q ("AguaVerde," "OldeManor," "Ville Dalfijn," "Yacht Basin") as points of interest. Hollenberg further describes a "look ahead icon 8f," which "selectably provides information for areas beyond user's current area;" upon selection, the display shows "map data of locations in advance of the mobile user's current location," including an airport, which is a point of interest. Hollenberg, Fig. 11, col. 19, lines 58 to 60, col. 21, lines 32 to 54.


22. Ito and Hollenberg disclose that "the at least one of the soft function keys or icons having a function associated therewith relating to directions comprises a function for obtaining directions from a current location of the user" as claimed in claim 23. Ito discloses that icons K1 to K5 have functions relating to obtaining directions; they are used to select the "desired guidance areas." Ito, col. 30, line 66 to col. 31, line 3. Figure 24 also shows options for selecting a recommended route from the departure point to the destination indicated by lines only or with detailed information. Ito, Fig. 24. The departure point is calculated from using GPS data obtained at the position measuring section 104 of the navigation apparatus to measure the current position of the vehicle so that the current position of the vehicle is the departure point. Ito, 15:47-58. Therefore, when the user requests guidance and directions from a departure point, including by displaying either an outline map or a detailed map for the recommended route, the request relates to directions from the current location of the vehicle and user. Hollenberg also discloses, in Figure 2, a display that includes a "device location and direction symbol 6a" that displays the current location of the user on a map. Hollenberg, col. 12, lines 22 to 40. This device location and direction symbol is a soft function key that relates to the current location of the user. The display in Hollenberg also includes a menu option for displaying a floor map that can be used to orient oneself and find proximate items of interest in relation to the user's current location.

Hollenberg, Fig. 2, col. 13, lines 38 to 45. Additionally, Hollenberg further describes a "look ahead icon 8f," which "selectably provides information for areas beyond user's current area;" upon selection, the display shows "map data of locations in advance of the mobile user's current location," including roads, airports, or towns, along with estimated travel times and mileages to them, and thereby provides directions from a current location of the user. Hollenberg, Fig. 11, col. 19, lines 58 to 60, col. 21, lines 32 to 54.

- 23. Ito discloses that "the digitized speech is generated based at least in part on user speech received via a microphone in communication with the speech recognition apparatus" as claimed in claim 35. Ito discloses that the input section 105 may be "a data input device using voice recognition," with which "the user can use his/her voice to input corresponding data and commands." Ito, col. 10, lines 39 to 47. Voice recognition systems rely on microphones for obtaining a user's voice input. Additionally, West View has acknowledged (and I agree) that "all speech recognition systems inherently digitize the speaker's analog voice." Infringement Contentions, at p. 729.
- 24. Ito discloses "the microphone being mounted within the computerized apparatus proximate the touch-screen input and display device so that the user can speak into the microphone while viewing the touch-screen input and display device" as claimed in claim 35. As discussed above, Ito discloses a vehicle

navigation apparatus that accepts voice commands; this apparatus is described as being mounted in a vehicle. In order for a driver of a vehicle to be able to view the detailed guidance provided on the display and to input commands via the touch screen or voice recognition, both the voice input device (e.g., a microphone) and touch screen display are accessible to the driver. Neither claim 35 nor the specification defines "proximate" in terms of how close the microphone and the touch-screen input and display device must be; since the microphone and touch-screen input and display device described, for example, by Ito are accessible to the driver of a vehicle, the microphone is located "proximate" the touch-screen input and display device.

25. Ito and Hollenberg disclose "the graphical representation of directions comprising the map graphic displayed on the touch-screen input and display device having at least one arrow showing the path for the user to follow inside of the building or structure" as claimed in claim 35. Figure 9(B) of Ito shows an example of a displayed map; as shown in Figure 9(B) (reproduced below), "a map for the area around the departure point PD is displayed on the display[]. In this displayed map, the road R1 is highlighted by markings MA, and in this way the searched route is indicated. Further, an arrow MB showing the direction of travel and a mark MC showing the vehicle position by map matching are also indicated." Ito, col. 17, lines 10 to 14, Fig. 9(B).



Arrows are also disclosed in Figs. 10(A), 10(B), 29(B), 30(B), 31(B), 32(B), and 40(A) to (C) of Ito, each illustrating a displayed map image having an arrow showing a path for the recommended route. The map displayed in Hollenberg includes a "device location and direction symbol 6a" that represents the current location of the user on the map. Hollenberg, col. 12, lines 22 to 40. As shown in Figure 2, the direction symbol includes an arrow.

26. Ito and Hollenberg disclose "an interface compliant with an IEEE 802.11 standard" as claimed in claim 35. For example, Ito discloses that the "transmitting and receiving section 108" in the vehicle navigation apparatus 100 communicates with the base station and "includes devices such as a modem and the like." Ito, col. 8, lines 51 to 57. Additionally, Ito discloses that the connection may "utilize systems such as car phones, portable phones PHS or the like." Id. Hollenberg discloses "at least one mobile computer with multiple transmitters and receivers," including "a transceiver wireless ... data telecommunications capability." Hollenberg, col. 5, lines 13 to 28. As described, for example, by Greenwood at col.

3, lines 11 to 17, it is obvious that an IEEE 802.11 wireless standard can be used for network communication in the vehicle systems disclosed by Ito and Hollenberg.

### The Level of Skill in the Art

- 27. Several years before the earliest filing date claimed as priority by the '839 patent, as well as contemporaneously with filing of the application for the '839 patent, other automotive industry companies had already developed, and were developing, vehicles with Internet connectivity (allowing users to, for example, retrieve information wirelessly from remote databases while inside their vehicles), speech-recognition functionality, and navigation functionality.
- 28. As described by Lind, the Network Vehicle was designed and developed by Delphi Delco Electronics Systems, IBM, Netscape Communication, and Sun Microsystems. The Network Vehicle developers loaded several computing and communications devices into a vehicle, to demonstrate that the technology could successfully be used in a variety of ways. The Network Vehicle included a roof-mounted antenna to provide a satellite connection to the Internet. Lind, page I21-2. The system associated with the Network Vehicle included an off-board network architecture, including, for example, a home/office computer and an IBM web server. Lind, page I21-2. As described by Lind, the Network Vehicle developers provided a Website for users of the Network Vehicle to remotely access the

computing systems located in the vehicle. The vehicle Website allowed users to "plan trips on the vehicle web site, then download them to your vehicle." Lind, page I21-7.

- 29. Lind also describes systems in which a user can receive various types of information inside the vehicle, including e-mail. The Network Vehicle was demonstrated at the Computer Dealer's Exhibits (COMDEX '97) conference in Las Vegas, Nevada on November 17-19, 1997. At this demonstration, the use of the Network Vehicle Website described by Lind, as noted above, was demonstrated to attendees of the conference.
- 30. I have reviewed screenshots of the Network Vehicle Website; those screenshots are attached as Exhibit B. I acquired these screenshots pursuant to my work as an expert witness engaged by Volkswagen Group of America, Inc. in connection with the litigation *Affinity Labs of Texas*, *LLC v. BMW North America*, *LLC*, et al., Case No. 9:08-cv-00164 (E.D. Tex.).
- 31. In 1997, I personally attended a demonstration of the Network Vehicle, conducted by Delphi and a Delphi supplier, at Toyota's headquarters in Toyota City, Japan. At that event, the features of the Network Vehicle were demonstrated and the system operation was explained.
- 32. Referring to Exhibit B, as illustrated on, e.g., the "Driver profile" page, the Network Vehicle maintained a set of profiles for each driver, including personal

data, entertainment preferences, information preferences, vehicle preferences, and a personal address book.

- 33. Referring to Exhibit C (*VW is working on a multimedia car*, Reuters AG, April 22, 1996), Volkswagen had also designed a "multimedia car" and presented that "Infotainment Car" at a conference in Hannover, Germany in 1996; the Infotainment Car included, for example, a PC with Internet connectivity.
- 34. In 1997, for example, in the Connected CarPC described in Exhibit D (*In-Car Computing and Communication Enables Entertainment, Productivity and Information*, Dedicated Conference on ATT/ITS Advances for Enhancing Passenger, Freight & Intermodal Transportation Systems, p. 411-417 (1997)), communication links were already available for use in automobiles to provide traffic information, Internet access to find hotels, restaurants, and travel guides, and to schedule maintenance, perform remote diagnostics and receive software updates. The "Connected CarPC environment" at that time included both speech recognition functionality and Internet access.
- 35. The Daimler-Benz Internet Multimedia on Wheels Concept Car, also referred to as the Internet Car, and described in Exhibit E (Jameel et al., *Internet Multimedia on Wheels: Connecting Cars to Cyberspace* (IEEE 1998)) and Exhibit F (Jameel et al., *Web on Wheels: Toward Internet-Enabled Cars* (IEEE January 1998)), included "an on-board, integrated wireless communication system and the

computing infrastructure to provide Internet connectivity from the car to any specific server on the Internet while stationary or in motion." The Internet Car included "Personal device (smart cards, HPCs) [to] be used to personalize car seats, climate, phone numbers, Internet services bookmarks, and computing man machine interface." The Internet Car also permitted drivers to "access ... voicemail, e-mail, and travel-related information such as restaurant guides and movie theater locations" "in a hands-free, eyes-free manner through voice commands and speech technology."

- 36. Microsoft's Auto PC, described in Exhibit G (Jost, *The car as a mobile-media platform*, Automotive Engineering International, pp. 49-53 (May 1998)), included "the benefits of interactive speech technology, connectivity, information on demand, and enhanced entertainment to the automobile."
- 37. Visteon's ICES system, described in Exhibit H, included a voice-activated control system that permitted "drivers to control vehicle functions that are usually operated manually," and "[t]hrough speech recognition, the driver can send e-mail, obtain turn-by-turn Global Positioning Satellite (GPS)-based navigation to a specific destination, ask for traffic and weather conditions, locate a restaurant or hotel, or change the musical selection on the stereo." Wireless Internet connectivity was included in Visteon's ICES system and "used for vehicle-to-roadside assistance or to receive e-mail and Internet information."

# Obviousness in View of Ito, Ezaki, and Hollenberg

- 38. The systems described in claims 1, 10, 11, 16, 22, 23, and 35 of the '839 patent were obvious from the disclosures of Ito, Ezaki, and Hollenberg.
- 39. Ito, Ezaki, and Hollenberg each describe navigation apparatuses, and it was obvious to use the guidance functions disclosed in Ezaki and Hollenberg in the vehicle computer and display system described by Ito in view of the known benefits of doing so, in order to provide "a communications navigation system which is able to carry out a satisfactory route guidance" (Ito, col. 2, lines 65 to 66), to provide information to "reliably guide a user to the target institution" (Ezaki, col. 2, lines 64 to 65), and to provide "time-critical information about places and events to mobile computers and their users" (Hollenberg, Abstract). Ito, Ezaki, and Hollenberg each address the same problem that the alleged inventions of the '839 patent purport to solve, e.g., allowing occupants to "use their time more efficiently and obtain needed information." '839 patent, col. 4, lines 8 to 9.
- 40. Ito discloses the necessary hardware to receive voice inputs, wirelessly connect to a remote database, and retrieve information from remote sources such as the Internet, including navigation information and maps. It is obvious to add the "target institution" disclosed in Ezaki and the navigation to locations within a building disclosed in Hollenberg to the system of Ito, as these are merely particular implementations of navigation functionality on a mobile unit. A person of ordinary

skill in the art would have found it desirable to add such implementations since they would give the user greater ability to determine location and related useful information.

# The Disclosures of Ito, Lind, Ezaki, Hollenberg, and Hsieh – Claim 29

41. Hsieh discloses a "video data apparatus in data communication with the processing apparatus and configured to enable video data to be generated and displayed on the display device" as claimed in claim 29. Hsieh discloses a "vehicle monitoring apparatus [that] includes a rear video camera" as well as "a television placed in the vehicle;" a video data apparatus that includes a "system control circuit 6" actuates a "rear video camera CCD1." Hsieh, Abstract, col. 2, lines 6 to 20. The video cameras disclosed in Hsieh are CCDs (charge coupled devices), which are the same types of cameras that are disclosed in the specification of the '839 patent. Hsieh, col. 2, lines 7 to 26; '839 patent, col. 17, lines 31 to 59. It was obvious that cameras can be integrated in computerized systems by placing the camera in data communication with a processor; for example, Hollenberg describes that a video camera may be provided in its information system. Hollenberg, col. 29, lines 6 to 19. The video data generated by the cameras in Hsieh is displayed on the display device. Hsieh, col. 1, lines 7 to 11.

Obviousness in View of Ito, Ezaki, Hollenberg, and Hsieh

It is obvious that the vehicle monitoring apparatus, rear view camera, and 42.

television disclosed by Hsieh may be used in the systems described in Ito, Ezaki,

and Hollenberg to "provide a vehicle monitoring apparatus" to display a picture on

a television placed inside the vehicle (Hsieh, page 1, lines 39 to 53), e.g., a backup

camera. Providing a known backup camera as disclosed in Hsieh in the

computerized information and display systems disclosed in Ito, Ezaki, and

Hollenberg would have required no major modifications to those systems, because

they already included displays capable of displaying video images generated by

CCD cameras, and would have provided only expected results.

I declare that all statements made herein of my own knowledge are true and

that all statements made on information and belief are believed to be true, and

further that these statements were made with the knowledge that willful false

statements and the like so made are punishable by fine or imprisonment, or both,

under §1001 of Title 18 of the United States Code.

Dated: \_ 11/16/2015

Scott Andrews

28

# **EXHIBIT A**

(650) 279-0242

915 Western Ave. Petaluma, CA 94952

# **Summary**

Creative, energetic, and innovative internationally recognized executive experienced in general management, systems engineering, advanced product development, advanced technology, business development, strategic planning, and program management

- Vehicle Electrical/Electronics Systems
- Vehicle Information Systems
- Communications Systems
- ITS and Related Industries
- Program and Project Management
- Enterprise Software
- Multimedia/Internet Computing
- Vehicle Safety and Control Systems
- Spacecraft Electronics
- Mobile Information Technology

# **Experience**

### 12/2001-Present Consultant

Systems engineering, business development and technical strategy consulting supporting automotive and information technology.

### **Current Engagements:**

- Technical consultant to ARINC for connected vehicle application systems engineering and development of high precision connected vehicle test bed for FHWA (Federal High Way Admin.)
- Technical consultant to Booz Allen for connected vehicle performance measures development project for NHTSA (National Highway Traffic Safety Admin.)
- Technical consultant to Booz Allen for connected vehicle standards for FHWA
- Technical consultant to American Association of State Highway Transportation Officials (AASHTO) for connected vehicle deployment analysis and strategy
- Technical consultant to Michigan State DOT (Enterprise Pooled Fund) to develop a system architecture and deployment strategy for Rural ITS
- Expert witness for Toyota in a case brought by American Vehicular Sciences (AVS)
- Expert witness for Toyota in a patent case brought by Affinity Labs
- Expert Witness for TomTom in a patent case brought by AVS
- Expert witness for Liberty Mutual, Geico and Hartford in a patent case brought by Progressive Insurance
- Expert witness for Ford in a patent case brought by Medius.
- Expert witness for Ford in a patent inventorship case brought by Berry.
- Expert witness for Ford and GM in a patent case brought by Affinity Labs
- Expert witness for M/A Com in a patent case against Laird
- Expert witness for VW/Audi in a patent case brought by Velocity
- Expert witness for VW/Audi in a case brought by Beacon, GmbH.
- Expert witness for Wasica in a patent case against Shrader and Continental

### **Recent Engagements:**

- Expert Witness for Samsung, Nokia, ZTE and Sony in an ITC patent case brought by Pragmatus
- Expert Witness for TomTom in a case brought by AOT/Adolph
- Expert Witness for TomTom in a case brought by Cuozzo
- Expert Witness for Navico in a case brought by Honeywell

- Expert witness for Bentley in a case brought by Cruise Control Technologies.
- Expert witness for Google in a case brought by Walker Digital
- Expert witness for Emtrac in a case brought by GTT (3M)
- Expert witness for Motorola in a case brought against Microsoft
- Co-Principal investigator for Integrated Advanced Transportation System; research program funded by FHWA
- Expert Witness for Volkswagen/Sirius-XM in patent infringement case relating to traffic information systems
- Expert Witness for Pioneer in patent infringement related International Trade Commission matter
- Expert Witness for Volkswagen in patent infringement case relating to the iPod interface
- Chief System Architect for the Vehicle Infrastructure Integration (VIIC) program (BMW, Chrysler, Daimler Benz, Ford, GM, Honda, Nissan, Toyota, VW);
- Expert Witness for Honda in patent infringement lawsuit); 14 asserted patents dealing with telematics equipment interfaces and functions
- Expert Witness for Alpine, Denso and Pioneer Corporation in patent infringement related International Trade Commission matter relating to navigation systems
- Telematics delivery architecture development for a Fortune 100 service provider
- Technical consultant to the Vehicle Safety Consortium developing Dedicated Short Range Communications (DSRC) standards for safety systems;
- Expert Witness for BMW in patent infringement lawsuit (American CalCar, Inc. v BMW) included prior art search, invalidity & non-infringement reports, rebuttals reports, depositions, etc for 12 patents with 200+ asserted claims.
- Toyota Motor Sales 10 year technology survey;
- Connected Vehicle Trade Association- Transferred AMI-C specifications to ISO TC 22, TC 204 AND OSGi. Developed OSGi Vehicle Interface Specification;
- Personal navigation device product feature and opportunity analyses for Thales-Magellan and Rand McNally

### 4/2000 to 12/2001 Cogenia, Inc.

President and Chief Executive Officer, Founder

Founded company in 2000 to develop enterprise class data management software system. Responsibilities included development of business concept and plan, corporate administration including financial and legal management, leadership of executive team in product development, fundraising, business development, organizational development, and investor relations. Raised \$2.2M between 8/00 and 5/01 from individuals and funds;

### 1996 to 4/2000 Toyota Motor Corporation, Japan

Project General Manager, R&D Management Division

Responsibilities included the conceptualization and development of multimedia and new technology products and services for Toyota's future generations of passenger vehicles in the United States and Europe, Heavy emphasis on strategy for information systems, and on development of technical concepts for computing and Internet oriented systems. Working under direction of Toyota board members, established the Automotive Multimedia Interface Collaboration (AMI-C), a partnership of the world's car makers to develop a uniform computing architecture for vehicle multimedia systems, and led all early technical, planning and legal work. Past responsibilities included leading Toyota's US Automated Highway Systems program, management of technical contracts with Carnegie Mellon University Robotics Lab (Image based collision warning systems), and the development of Toyota's position on the US Intelligent Vehicle Initiative.

### 1983 to 1996 TRW, Inc.

Held a series of increasingly responsible positions in program management, technology development and business development.

1993 to 1996 TRW Automotive Electronics Group

Director, Advanced Product Planning/Development

Specific responsibilities included leadership and overall management of advanced development programs such as Automotive Radar, Adaptive Cruise Control, Occupant Sensing, In Vehicle Information Systems, and other emerging transportation products; Managed remotely located advanced development laboratory performing approximately \$6M in annual development projects.

1983 to 1993 TRW Space & Electronics Group

Manager, MMIC Products Organization

Developed TRW's commercial GaAs MMIC business. Responsibilities included development of business strategy and business plan, and overall management of customer and R&D programs. Developed extensive international business base and took operation from start-up to \$5M sales per year in under two years. Developed the first single chip 94 GHz Radar (Used for automotive cruise control and anti collision systems).

### 1979-1983 Teledyne Microwave

Developed high reliability microwave components. Developed CAD tools.

# 1977-1979 Ford Aerospace, Advanced Development Operation

Designed, tested and delivered microwave radar receiver systems

## **Education**

MSEE Stanford University, 1982 BSEE University of CA, Irvine 1977 TRW Senior Leadership Program 1992

### **Publications**

- Two Dimensional Vehicle Control for Obstacle Avoidance in Multi-Lane Traffic Environments; Published in the proceedings of the 1998 IEEE International Conference on Intelligent Vehicles.
- 2. Automotive Multimedia Interface Collaboration; Briefing Presented to the 9<sup>th</sup> VERTIS Symposium, April 1999, Tokyo Japan.
- 3. Privacy and Authenticity in Telematics Systems; Published in the Proceedings of the Society of Automotive Engineers World Congress, 1999
- Automated Highway Systems Acceptance and Liability; Briefing presented to the Automated Vehicle Guidance Demo 98 Conference, Rinjwoude, The Netherlands, June1998.
- What is Telematics? Briefing presented at IIR Telematics Conference Scottsdale,
   AZ, December 2001

- 6. Advanced Telematics Services: A Hard Look at Reality; Briefing presented at IIR Telematics Conference Scottsdale, AZ, December 2001
- 7. Consumer Electronics and Telematics; Briefing presented at Eye For Auto Telematics Update Conference Las Vegas, NV, January 2003
- 8. The Automotive Multimedia Interface Collaboration Software and Network Architecture: Extending the Concept of Platform Independent Computing; Briefing Presented to the Future Generation Software Architectures in the Automotive Domain Conference, San Diego, CA, January 2004
- Quality, Choice and Value: How New Architectures are Changing the Vehicle
   Lifecycle; Briefing presented at IEEE Convergence Conference, October 2004
- Critical Standards for the Next Generation of Telematics Systems and Services;
   Briefing presented at the Telematics Update Conference, December 2004
- 11. VII System Overview; Briefing presented To Transportation Research Board, ITS and V-HA Committees 2007 Mid-Year Meeting; July 2007
- Testing and Development of In-Vehicle Equipment and
   Private Applications (P08-1634); Briefing presented to the Transportation
   Research Board Annual Meeting, Washington, DC, January 2008
- 13. A Comparison of Communications Systems for VII; Presented at the ITS World Congress, New York, NY, October, 2008
- Vehicle Infrastructure Integration Systems Overview; Presented at the ITS
   America Annual Meeting, June 1 2009, National Harbor, Maryland
- 15. Telematics Standards: Logical Next Steps; ITS International, August 2009
- 16. IntelliDrive<sup>SM</sup> Overview; ITS International, May 2009
- 17. Time Synchronization and Positioning Accuracy in Cooperative IntelliDrive<sup>SM</sup> Systems; Presented at the 2010 ITS America Annual Meeting, June 2010, Houston, Texas


### **Patents**

- Mobile Body Reporting Device And Its System; Patent Number: JP11118902;
   4/30/1999
- Multiformat Auto-Handoff Communications Handset; Patent Number: US5649308; 07/15/1997

- 3. A Communications Terminal Device, A Communications System, And A Storing Medium For Storing A Program To Control Data Processing By The Communications Terminal Device; Patent Number: EP0867850, A3; 09/30/1998
- Communication System For Controlling Data Processing According To A State
   Of A Communication Terminal Device; Patent Number: US 6122682 3/23/1998
- 5. Method And Apparatus For Controlling An Adjustable Device; Patent Number: US5864105; 01/26/1999
- 6. Automatic Brake Device; Patent Number: JP2000108866; 4/18/2000
- 7. Visual Field Base Display System; Patent Number: JP2000029618; 01/28/2000
- 8. Intersection Warning System; Patent Number: US5926114; 07/20/1999
- 9. Security For Anonymous Vehicular Broadcast Messages; Patent Number: US 7742603 3/27/2006
- 10. Digital Certificate Pool; Patent Number: US7734050 3/27/2006
- System, Method And Computer Program Product For Sharing Information In A
   Distributed Framework; Patent Number: US 7802263 12/15/2003

# **EXHIBIT B**

# 







































































52
















58




















67









## **EXHIBIT C**

3:45 P.M. Apr 22 VW < VOWG.F > is working on a multimedia car

Hanover(Reuter) - Engineers of the Volkswagen company are working on a multimedia car. In addition to the traffic radio that today is considered standard equipment already, the vehicle, which is filled with high-tech components, will be fitted with CD player, video recorder, telephone, navigation system, a notebook computer, as well as external cameras, according to the manager of Electronic Research, Ralf Bergholz, speaking on Monday at the Hanover fair. The Wolfsburg company presented an "infotainment car" based on a "Sharan" at the trade show, which is equipped with monitors for the front seat passenger and the rear seats.

Each passenger was said to be able to select an individual program in the vehicle and listen to it with headphones. Available as image sources are a TV receiver, a video recorder, a CD player as well as a PC with Internet connection. Only the driver is prevented from watching TV, for reasons of safety. Instead, an on-board computer informs him about vehicle data such as the gas level, speed, or the engine's rotational speed. If desired, a navigation system may be displayed on the screen instead of the engine speed. Two cameras in each bumper also make it easier to park in small parking spaces.\

According to information from Bergholz, there are currently no specific plans for a market introduction of the multimedia car with the "feel of a living room". However, VW is assuming that such a vehicle could exist in certain market areas.

sei/fgc

\*For related news, double click:

[DE][AUT]

\*For additional company news, double click:

[VOWG.F]

\*For stock quotes and prices, double click:

<VOWG.F>

Monday, April 22 1996 3:45:28 P.M. ENDS [nFJ2200797]



#### DECLARATION

I, Judith E. Taddeo, declare that I am well qualified as a translator of German to English and that I have carefully prepared the attached English language translation from the original document:

VW arbeitet an Multimedia-Auto

[VW is Working on A Multimedia Car]

written in German and that the attached translation is an accurate English version of such original to the best of my knowledge and belief.

I certify under penalty of perjury that the foregoing is true and correct.

Date: 9/22/2015 Signature Man Judith E. TASSEO

#### REUTERS AG

Monday, 22 April 1996 15:58:11

15:45 22 Apr VW < VOWG.F > arbeitet an Multimedia-Auto

Hannover (Reuter) - Ingenieure des Volkswagen-Konzerns arbeiten an einem Multimedia-Auto. Das mit High-Tech vollgestopfte Gefährt solle über die bereits heute üblichen Verkehrsfunkradios hinaus mit CD-Player, Videorecorder, Telefon, Navigatonssystem, einem Notebook-Computer sowie Außenkameras ausgestattet sein, sagte der Leiter der VW-Elektronikforschung, Ralf Bergholz, am Montag auf der Hannover Messe. Die Wolfsburger präsentieren auf der Industrieschau ein "Infotalnment Car" auf der Basis eines "Sharan", das mit Monitoren für den Beifahrer und die hinteren Sitzreihen ausgestattet ist.

In dem Fahrzeug könne jeder Passagier individuell ein Programm wählen und mit Kopfhörern abhören. Als Bildquellen stünden ein Fernsehempfänger, ein Videorecorder, ein CD-Player sowie ein PC mit Internetanschluß zur Verfügung. Nur dem Fahrer sei es aus Sicherheitsgründen verwehrt, dem Fernsehen zu frönen. Dafür werde er über einen Bordcomputer mit Fahrzeugdaten wie Tankinhalt, Geschwindigkeit oder Motordrehzahl informiert. Auf Wunsch könne statt der Drehzahl ein Navigationssystem eingeblendet werden. Jeweils zwei Kameras in den Stoßstangen erleichterten zudem das Einparken in engen Parklücken.

Nach Bergholz' Angaben gibt as bisher keine konkreten Pläne zur Markteinführung des multimedialen Autos mit dem "Ambiente eines Wohnzimmers". VW gehe allerdings davon aus, daß ein solches Gefährt in bestimmten Marktbereichen bestehen könne.

sei/fgc

\* Für verwandte Nachrichten, Doppelklick auf: IDEI[AUT]

\* Für weitere Firmenmeldungen, Doppelklick auf: IVOWG.FI

\* Für Kurse und Preise, Doppelklick auf:

<VOWG.F>

Monday, 22 April 1996 15:45:28 ENDS [nFJ2200797]



## **EXHIBIT D**

#### Edited by:

#### Prof. Dr. Dieter Roller

Institut für Informatik Universität Stuttgart Chairman, ISATA Scientific Programme Committee.

Published by:

Automotive Automation Limited 32A Queen Street Croydon CR0 1SY England

Tel: +44 181 681 3069 Telefax: +44 181 686 1490 ail: 100270.1263@compuserye

E.Mail: 100270.1263@compuserve.com Website: http://www.isata.com þ

37652001 UKM

TL 285 .154

#### DEDICATED CONFERENCE ON ATT/ITS ADVANCES FOR ENHANCIN PASSENGER, FREIGHT & INTERMODAL TRANSPORTATION SYSTEMS

#### CO-SPONSORED BY ITS FOCUS, UK

#### PROGRAMME COMMITTEE CHAIR

Dr K Thirumalai, IDEA Program Manager, Transportation Research Board, National Research Council, USA

#### PROGRAMME COMMITTEE MEMBERS

Dr B C Abernethy, Kimley-Horn & Associates Inc. USA

Professor H Adeli, Ohio State University, USA

Dr S Cassidy, University of Nottingham, UK

Professor P R G Cunningham, East Carolina University, USA

Mr J G Davis, International Maritime Industries Forum. UK

Mr M Gendreau, Université de Montréal, Canada

Mr G Gynnerstadt, Royal Institute of Technology, Sweden

Mrs S Harvey, ITS Focus, UK

Dr P Hidas, The University of New South Wales, Australia

Professor A M Khan, Carleton University, Canada

Dr R S Levine, Associate Clinical Professor, USA

Dr J Luk, ARRB Transport Research, Australia

Mr Y Mashiyama, Matsushita, Japan

Dr J D Nelson, University of Newcastle-Upon-Tyne, UK

Dr R Rajagopalan, Concordia University, Canada

Dr J Stewart, Royal Military College, Canada

T.S. LIBRARY
LIBRARY
DEC 6 1999
DEC CONTROPONTANIA

		Page
Generation V		11
Professor D 8	perling, Director, University of California-Davis, USA	
Safety and En	orecasts in Motor Vehicle Kilometrage, Road vironmental Quality ustra, SWOV Institute for Road Safety Research, The Netherlands	21
•	Coatings - Dedicated to Car Lifetime berts Automotive Systems, Germany	33
Meeting the N Industry	leeds of a Changing Population - The Challenges for the Automotive	45
Ms Ann Frye,	Head of Mobility Unit, Department of Transport, UK	
APPLICATI	ONS TO INTERMODAL SYSTEMS PRACTICE	
97ATT003	The Design of a Ticketless Parking Revenue Collection and Management System Dr B Abernethy, Kimley Horn and Associates Inc, USA	53
97ATT042	An Intermodal Transportation Simulation System for the 21st Century Dr C Berkowitz and Dr C Bragdon, National Aviation and Transportation Center at Dowling College, USA	61
97ATT062	Flexible and Intermediate Forms of Transport as part of a package of Transport Demand Measures Dr J D Nelson and Dr W Saleh, University of Newcastle upon Tyne, UK	67
97ATT076	Inter-Modal Economic Comparison: Where are the Resource Differences? Mr P Foyer, Peter Foyer Consulting Engineers, UK	<b>75</b> ;
ITS FOR TR	ANSIT SERVICES ,	. ?
97ATT001	Using Travel Surveys and Experiments to Explore the Potential Impact of Transit Information Systems on Mode Choice Professor M A Abdel-Aty, University of Central Florida, USA	' 81

		Page
97ATT060	Making the Full Use of Vehicle Fleets: Demand Responsive Transport Services (DRTS) in SAMPO Project Mr A Lumiaho, MTC Sampo Office, Finland	89
97ATT064	Demand Responsive Transport Services - The User Requirements Mr B Finn, European Transport Telematics Systems Ltd, Ireland	97
ITS CONTI	RIBUTIONS TO SUSTAINABLE TRANSPORTATION	
97ATT006	AHS/MAGLEV - A Supply-Side Approach to Sustainable Development Professor D Drew, Mr D Sohn, Mr K Kirn, Virginia Polytechnic Institute and State University, USA	105
97ATT008	The GreenTrip Toolkit - Sustainable Transportation Via Intelligent Vehicle Routing Systems Dr G Hasle, SINTEF Applied Mathematics, Norway and Mr A Concialini, Pirelli SpA, Italy	113
97ATT032	Implications of a Car Culture for the Development of Sustainable Highway Transport Dr D S Evans, Professor A W Smyth, and Mr R J Harron, University of Ulster, UK	123
97ATT057	Sustaining ITS Deployment in Advanced Traveler Information Systems (ATIS) in the New York City Metropolitan Region Dr J C Falcocchio and Mr E C Serafin, Polytechnic University, USA	131
97ATT058	Using ITS to Alleviate Environmental Concerns Mrs S Harvey, ITS Focus, UK	141
TRAFFIC &	& TRAVEL MANAGEMENT	
97ATT009	Automated Processing Of Video License Plate Images For Traffic Data Acquisition And Analysis Professor P W Shuldiner, University of Massachusetts Amherst, Mr J B Woodson and Mr S A D'Agustino, Transformation Systems Inc., USA	151

		Page
TRAFFIC I	MODELLING	
97ATT017	Models for Real-Time Traffic Adaptive Signal Control Professor A.G.R. Bullen, University of Pittsburgh, USA and Dr G Q Memon, Royal Saudi Airforce, Kingdom of Saudi Arabia	159
97ATT020	Application of Neutral Networks Incident Detection Mr A Aburahmah, Manatee County Government, Mr S Weerasuriya, Center for Urban Transportation Research, USA	167
97ATT055	Chaos in a Car-Following Model with a Desired Headway Time Dr D Low and Dr P Addison, Napier University, UK	175
TRAFFIC I	NFORMATION MANAGEMENT	
97ATT048	Incident Detection Based On Real-Time Travel Time Dr E C P Chang, Texas Transportation Institute, USA	183
97ATT045	A Fast FH-SS Random Access Data System for the Road Informatics - system performances under simultaneous multi- users Dr J Horikoshi and Mr N Hayashi, Gunma University, Japan	. 191
97ATT035	Detector System Design for Meeting its Requirements Dr E C-P Chang, Texas Transportation System, USA	199
SPECIAL S	ESSION ON INTELLIGENT VEHICLES	
97ATT049	An Overtaking Model and the Determination of Safe Passing Sight Distance for Cars and Trucks Dr M P Cartmell, University of Edinburgh and Dr Y Wang, Heriot-Watt University, UK	207
DRIVER SA	FETY ENHANCEMENT	
97ATT031	Eye Closure Detection Using Eyelid Motion Mr S Katahara and Professor M Aoki, Seikei University, Japan	215

		Page
97ATT013	A System For Detection of Driver Impairment and Emergency Handling Dr E Bekiaris, TRD S.A., Greece, Dr K Brookhuis and Mr D Waard, Traffic Research Center, The Netherlands	223
97ATT014	In-Vehicle System For Detection of Violations and Impairment Dr K Brookhuis, Mr D Waard, Traffic Research Centre, The Netherlands	231
97ATT029	Driver's Behavioural Simulation in the Long Distance Path Choice Dr U Crisalli, University of Rome, Italy	239
ITS SAFETY	SYSTEMS	
97 <b>A</b> TT010	Safety Impacts of Transport Telematics in Road Traffic Mr V A W J Marchau and Professor R E C M Van Der Heijden, Delft University of Technology, The Netherlands	247
97ATT046	On-Line Data Analysis of a Microwave Radar Intended for Obstacle, Detection in Automotive Applications Ms M Wahl, Mr M Dang, LSR-IMAG, and Mr D Georges, LAG-ELESA, France	255
97ATT024	Dynamic Analysis of Mini Bus Considering Flexible Body Modes Mr G H Lee, Mr K H Nam, Hyundai Motor Co., and Mr T W Park, Ajou University, South Korea	263
COMMERC	IAL OPERATIONS	
97ATT002	Rural ITS Technology and ITS Benefits to Commercial Vehicle Operations Dr B Abernethy, Kimley Horn and Associates Inc, USA	271
97ATT067	Preliminary Guidelines for Development of Advanced Traveler Information Systems for the Driving Tourist: Route Guidance Features Ms L J Molnar and Dr D W Eby, University of Michigan Transportation Research Institute, USA	279

		Page
97ATT061	The Challenge to the Vehicle Industry: Flexible & Intermediate Forms of Transport Mr T Korsisaari, Korsisaari Group, Finland	287
FREIGHT	TRANSPORTATION SYSTEMS	
97ATT015	New Information Technologies and Freight Transportation Dr J Roy, Dr Y Bigras, Dr T Crainic, Université du Québec- at Montreal and Trois-Rivieres, Canada	291
97ATT038	Customized Transportation & Logistics Solutions for the Automotive Industry Mrs C Stoddard, Emery Worldwide, USA	299
97ATT012	ITS For Managing Commercial Vehicle Operations On Airport Grounds and Improving Airport Ground Transportation Mr A Kanaan and Mr D Sims, IBI Group, USA	305
ITS IMPLE	MENTATIONS	
97AȚT021	City-Logistics with ITS Professor Dr U KÖhler, University of Kassel, Germany	313
97ATT053	ITS Applications on the I-81 Corridor in Virginia Mr S Ahn, The Korean Transport Institute, Korea	321
97ATT040	Protecting The "I" In ITS  Mr J Alexander, International Road Dynamics Inc, and Dr  B Abernethy, Kimley-Horn & Associates, USA	329
97ATT052	AUTOGUIA: An Intelligent Highway System Professor A Alonso, Professor Lopez, Mr R Homero, and Mr J P de Castro, University of Valladolid, Spain	337
AUTOMAT	ED VEHICLE AND HIGHWAY SYSTEMS	
97ATT011	Possible Roles of Stakeholders towards Developments of advanced Vehicle Control Systems  Mr V.A.W.J. Marchau and Professor R.E.C.M. Van Der Heijden. Delft University of Technology. The Netherlands	<b>345</b>

		Page
97ATT016	United States/Germany Collaborative Research Program on Autonomous Navigation (AUTONAV) Mr R Phelps, Army Research Laboratory, Dr. P Burt, David Sarnoff Research Centre, Mr Maris Juberts, National Institute of Standards and Technology, USA, and Mr M Bartha, Dornier GmbH, Dr E Dickmanns, Universitat der Bundeswehr Munchen, and Mr I Postler, Bundesamt füer Wehrtechnik und Beschaffung, Germany	353
97ATT074	Intersection Collision Avoidance by Means of Decentralized Security and Communication Management of Autonomous Vehicles Mr R Naumann, Mr R Rasche, University of Paderborn, Germany	361
97ATT075	Satellite Navigation-Positioning Systems in Roundwood Tranportation: Experiences From Finland Mr J Sauna-aho, Ministry of Transport & Communications, Mr S Tolkki, Enson Ltd, Mr J Laitinen, Metsäliitto Osuuskunta, and Mr H Parkkonen, Forest Branch Transport Entrepeneurs, Finland	369
97ATT037	An Infrastructure Diagnostic Vehicle for Automated .Highway Systems Dr T A Lasky and Professor B Ravani, Advanced Highway Maintenance and Construction Technology Research Center, USA	377
97 <b>ATT</b> 077	An Adaptive Selection Method for Positioning In Car Navigation System Mr T H Kang, Dr J H Lee, Mr J S Kim, Systems Engineering Research Institute, Mr W Y Lee, Hyundai Electronics Industries Company Ltd, Korea	385
ITS INTEG	RATION	
97ATT028	Development of Traffic Simulation and an Applied Example Mr R Nakagawa, Mr H Oshika, Toyota Motor Corporation, Japan	395
97ATT071	Single-Trip Ridesharing with the Matching Computer Accessed by Wireless Pocket Phones Mr E W Walbridge RAA Inc. USA	401

		Page
97ATT073	In-Car Computing and Communication Enables Entertainment, Productivity and Information Mr J Altnether, Intel Corporation, USA	411
97 <b>ATT</b> 059	Advanced Information System Using DARC FM Data Multiplexing Mr S Ibara, Mr K Miyake, Mr S Gohda, and Mr K Sakagami, Daihatsu Motor Company Limited, Japan	419

## IN-CAR COMPUTING AND COMMUNICATION ENABLES ENTERTAINMENT, PRODUCTIVITY AND INFORMATION

Mr JAltnether, Intel Corporation, USA

97ATT073

Abstract: PC technology and applications continue to expand at an exponential rate. Many of these elements can be adapted to the automobile to provide new levels of entertainment, productivity and communication. In addition, new application requirements for the automobile such as navigation and real time traffic information are rapidly evolving. A system incorporating the Intel architecture provides the performance and flexibility to implement these functions. Examined in this paper are the architectural requirements and how they can be satisfied with the established Intel Architecture. Other factors, such as tools, and existing applications that can be utilised for quick development time and time-to-market will also be investigated.

Introduction: A number new applications and appliances are beginning to find their way into the automobile. Some of them are portable, allowing their use within the automobile. Each is a stand alone unit offering a dedicated service with little or no interaction with the other appliances. This not only limits the functionality but increases the cost because many of the functions are duplicated within each unit. For example, each usually has an embedded processor and a man-machine-interface such as a display.

The first is the cellular telephone. According to Datatquest, approximately 60 million cellular phones will be shipped in 1997 with a 22% CAGR. This is fueled by the decreasing costs of equipment and air time. In the beginning, standard personal cellular were used in the automobile. This provided both business and personal communication and is also used for emergency services. Currently cellular telephones are being integrated into the automobile with hands free operation. With services such as GSM, both voice and data can be transmitted, but few applications currently exist for digital data communication. This will change dramatically over the next few years.

Navigation systems are also beginning to be integrated into automobiles. Based on GPS technology many systems incorporate accelerometers or gyros to augment the accuracy of the GPS. In Europe alone this segment has grown at a 36% CAGR since 1993 (source: Dataquest). Navigation has two components: location and route planning. Location defines where the car is and establishes the beginning point for navigation. In addition, the location can be used as part of the safety component. Emergency road service would also require this information, as could the theft monitoring.

Today, route planning is static. This feature is available with a number of GPS system or navigation systems such as the "Never lost" system in Hertz rental automobiles. The assumption is that the stored information is current and no changes have occurred in the physical streets. If road construction closes a road and forces the automobile to deviate from the system's expected route, a new route will be recalculated usually through the same closed road. Real time information is required to eliminate this problem. Here is the beginning of integrating functionality. Information is received through the communication link. Real time traffic information is provided via one of the communication links. Information has a broader meaning than traffic information. Both voice

411

and data information are required. Voice for the normal human communications and messaging and data for a variety of functions: traffic information, internet access to find hotels, restaurants, travel guides and electronic forms of communication such as faxes. At another level, the data communication channel can be used by the automobile to schedule maintenance, perform remote diagnostics and receive software updates for various components.

Another application that is being incorporated within the automobile is entertainment capability. This in the form of games, movies and television. Systems by Clarion and Fujitsu Ten are already on the market. These are proving indispensable on long trips or to occupy children.

In vehicle applications are comprised of four segments: information, safety, infotainment and productivity. Information includes trip guidance, route planning, points of interest and congestion avoidance. Safety comprehends: emergency location, vehicle immobilization, operator identification, and weather information. Infotainment for the driver provides user delectable news and music on demand; while for the passenger there are PC games, movies, news and internet surfing. Productivity is provided by hands free phone, FAX/modem, voice and email messaging and personal itinerary.

Discussion: All of these applications and functions can be satisfied with a PC. Several environmental trends are validating this. First there is a decreasing cost for communication and computing. PCs that one year ago cost \$4000 now sell for \$2000 with twice the performance. Secondly, there is a universal acceptance of portable computing. This segment is growing faster than the desktop. Next, there is a convergence of computing and communication. All new PCs sold now contain a modem, cellular phone interface or a wire connection. Finally, the information services available via internet continues to accelerate. The cost, mobility, communication and portability of PCs can be effectively used in the automobile to meet the emerging requirements. The PC technology offers a number of reasons to be migrated into the automobile: established base easy to integrate existing hardware and software, existing hardware and software standards, existing relationship between home and office PCs, ever expanding market that can be followed for low cost advantage, and existing tools and development environment.

The PC began as a tool to enhance productivity in the office and business environment. Many of the application suites were developed to provide word processing, document control, financial analysis and inventory control. Made possible by the PC was distributed processing, which made the PC a tool of individuals increasing their productivity. This individual productivity was carried into the home both as a spill-over from work and because the home is a small business and can take advantage of the office applications. Because the PC is not 100% utilised at home, entertainment's such as games were a natural filler for this free time. Today a link exists between the home and office computers and the natural extension is into the automobile.

The automobile did not participate in the PC revolution because the applications required were different that those of the office and home environment and required higher performance and functionality. Also, the simultaneous operation of two machines (the automobile and the personal computer) that each required attention was thought of as a safety hazard. Personal computers and their software have advanced to a stage where they can meet the automotive requirements.

The advent and enthusiastic acceptance of the personal computer has enabled information on demand, both processed or communicated information. The populace has accepted this, and is recognizing the necessity for this functionality in the automobile. The automobile has been the last bastion of unstructured time. The necessity for these functions is becoming apparent in four types of applications which are evolving: navigation, information, entertainment and safety.

412

A number of valid reasons have kept the PC from entering the automobile environment, but the primary reasons were limited technology capability and lack of application software. The technology and software exists today to implement such a system. There are a number of compelling reasons to draw from the PC and adapt technology and software to the automobile both from the stand point of technology and business.

By today's standards the first Personal Computers were primitive machines. They were 8-bit machines operating at 5 Mhz providing .33 MIPS. By contrast today's machines are 32- or 64-bit machines operating at 200+ Mhz and execute 220 MIPS. What the early systems did was to provide were platform standards. An open architecture fueled a plethora of applications and hardware peripherals enhancements. Standards emerged providing a number of advantages: low risk for the manufacturer, increased market size and market growth.

At this point in time there are no standards for the "computer platform" in the automobile. Several are being discussed in committees such as ITS but have not been ratified. In the meantime, the market is ripening and could be ready before the standards. One method to safeguard investment is to embrace existing popular standards. The Personal Computer offers such a standard. In addition, there is an existing infrastructure of hardware and software to be applied.

The size of the PC market continues to grow at an 18-20% per anum rate with no reasons to abate. As shown in Figure 1, as of 1996 there are over 250 million PCs installed. As of 1996 there are 250 million PCs installed and over 65% of those are Pentium® processor based.




Figure 1. Installed PCs


Software too, advanced. The growth in personal computer performance is coupled to a correspondingly evolution in S/W and OS making them easy to use and efficient. The hardware and software exist in a constantly expanding upward spiral. Software pushes the hardware to its limits and new hardware is created to handle the increasing s/w requirements. Again, new s/w will stretch the limits of this new hardware on an ever upward spiral. In the beginning, what little software there was, had a clumsy man-machine interface (MMI). Often it required arcane commands to perform functions. Rather than requiring many hours to study manuals, hardware has become self-installing

90

Source Dataquest 1/96

and programs are intuitive in their operation. Added to this is the capability to perform applications once thought of as exotic such as speech recognition, full motion video and high speed communications. As a result, the computers have moved from the domain of the highly skilled users to that of everyday unsophisticated users.

Here again, standards play an important role. Operating systems such as Microsoft Windows\* 95 or NT are shipped with almost every PC. Any application that wants market acceptance or any peripheral expecting to be used, has the interface and drivers for this most popular operating system. As shown in Figure 2 this is the de facto standard and it runs on the Intel Architecture.



Source: Instat Inc., 1995

\*\* Other brands and trademarks are the property of their respective owners includes Windows 3.1, Windows 95 and Windows NT

Figure 2 Operating systems

Because the PC has become a standard tool all development tools have been designed to run on the PC. This is true from Microsoft Developers Network to Psoft, to QNX to C and C++ compilers. Many of these tools have tracked the development of the PC and are very mature and stable. Another advantage of using the PC platform in the automobile is that the target is also the development platform, permitting native debugging.

The question then becomes, "How to integrate the PC to the automobile space?" To answer this, we must look at the automobile architecture. At present it is a multiprocessor distributed system on a bus such as CAN. To provide functions to the driver and the passengers, the PC functionality will be distributed also. The GPS, radio, wireless communication, displays, and all of the MMI will be distributed throughout the automobile. The PC bus will be a separate bus to avoid any interference with the functions on the CAN bus. On the CAN bus, many dedicated processors perform their local functions such as ABS, engine control, etc. and communicate to the other components via the bus. All of the information here should be considered mission critical and not disturbed. The system operates in real time and must be deterministic. This precludes using this bus for the PC system in the car. There is however information on this bus that is of interest and a gateway should be provided. Information such as wheel speed and engine performance can be monitored as well as sending information to the devices on the CAN bus

Attaching the peripherals to the PC platform and defining two bus structures, the system takes shape as in Figure 3. While the previous discussion mention two buses, this system provides for three: CAN/J1850, a USB for the PC peripherals and 1394 for high speed data transfers such as full motion video.




Figure 3. Connected CarPC Platform

USB is selected because it has become a standard on PCs. USB propagates a 12M/s differential data stream over a shielded twisted pair. Many peripherals are USB ready. Windows 95 supports hot plug-and-play of peripherals. This permits using existing peripherals in the automobile. For example, if one of the children has a favorite joystick, it can be used at any station without rebooting the system to recognise the peripheral. Because Windows 95 recognises USB, most if not all application programs can be used. USB is also used to interface to the car environment such as seat sensors, window and door controls. Slow data, level signals, switches and lamps are best interfaced to microcontroller rather than tying up valuable processor resources. Each element of the automobile should be thought of as a module, for example the driver's door. Intel offers the 8x930Ax microcontroller that has USB capability. Thus, the door locks, door ajar sensor, window controls and sensors and even the mirror can be interfaced to the microcontroller and it interfaces to the processor via USB. Up to 256 such modules can be incorporated. The 1394 bus is included to provide future high speed transmissions. This will permit full motion video (for movies) to be displayed at all passenger stations.

The PC platform is built around the Intel Architecture for technical reasons as well as the business reasons previously discussed. It provides continuous performance enhancements on a well defined road map. Each new generation offers greater that 2:1 performance enhancements. The product rich roadmap permits the platform architecture to be scaleable from low end price and performance to high end leading edge performance. Platforms can be scaled from i486® processor through Pentium processors up to the current generation Pentium Pro processor. This provides an order of magnitude range in the performance of systems. In addition, they bring with them complementary

415

technology to further enhance the system performance. Two such examples are USB bus and MMX<sup>TM</sup> technology. MMX technology is a single instruction, multiple data operation. The latest version of the Pentium processor incorporated 57 new instructions to implement MMX technology. As a result, high performance digital signal processing is feasible on the Pentium processor. In the Connected CarPC environment, this could be used for image processing - MPEG2 decoding of movies, noise cancellation, soft communication devices to name a few uses.

This scalability of the architecture permits a range of systems for the automobile. As an example, three systems are shown: a navigation system, an internet system and a multimedia system. These systems are shown in Figures 4-6. The Navigation system is built around the Intel i486 processor and provides: position, navigation, vehicle control, audio entertainment. The Internet system uses a Pentium processor with MMX technology and provides: position, navigation, vehicle control and audio entertainment as does the navigation system but it also includes: speech recognition, communications. The Multimedia system provides all of the functionality of the Internet system but also adds: multimedia and games. This enhancement is due primarily to the salability of the processor that allows upgrading to a Pentium processor with MMX technology.




Figure 4 Navigation system

As can be seen in the two systems built around the Pentium processor, there is a large degree of commonality between the systems. The primary difference is in the performance and features of the Pentium processor. The Internet system uses a 133 MHz processor while the Multimedia system incorporates a 166 MHz Pentium Processor with MMX technology. Systems can easily be differentiated on performance and features while retaining commonality over a family of systems. This core platform can be expanded and extended in the future as more performance and features are required from the system. It is designed to follow the high volume PC components for upgradability and protection for legacy issues. The designer has the choice to incorporate higher speed Pentium processors as they become available or to incorporate the Pentium Pro processor.




Figure 5 Internet system




Figure 6 Multimedia System

Conclusion: In addition to the technical advantages, Intel Architecture provides a number of business advantages. These are quick time-to-market and low investment costs. Quick time to market is possible because the architecture is established and familiar. There are time proven, familiar, robust hardware and software packages available. Native debugging is accomplished on the PC. The solutions are low cost because they use the same high volume processors that are used in the desk top and laptop computers. PC peripheral components are widely available, eliminating the need to develop new peripherals. The tools are low cost and off-the shelf O/S and application software exist.

<sup>\*</sup>Other brands and trademarks are the property of their respective owners.

## **EXHIBIT E**

## INTERNET MULTIMEDIA ON WHEELS: CONNECTING CARS TO CYBERSPACE

Akhtar Jameel, Axel Fuchs, and Matthias Stuempfle
Daimler-Benz Research and Technology North America
Research and Technology Center, Palo Alto
{jameel, fuchs, stuempfle}@rtna.daimlerbenz.com

Keywords: Mobile Communication, Road vehicles, Internet, and Multimedia systems

#### **ABSTRACT**

An integrated solution to seamless connectivity and innovative in-trip services is being researched at the Daimler-Benz Research and Technology Center in Palo Alto. The Internet Multimedia on Wheels Concept Car has an onboard, integrated wireless communication system and the computing infrastructure to provide Internet connectivity from the car to any specific server on the Internet while stationary or in motion. Essentially, the car is like any other node on the Internet with a unique Internet Protocol (IP) address such as the Vehicle Identification Number (VIN). Thus, an entirely new type of services can be delivered to cars in an efficient and secure way through increasingly less expensive wireless data connectivity over the Internet.

#### INTRODUCTION

With the advancement of the computing and communications revolution, the Internet is becoming more and more part of our daily life. We send e-mail, check our bank account, read newspapers, and "surf" the net just for fun. New multimedia applications even allow us to listen to "Internet-Radio," watch "Internet make phone calls, and do videoconferencing over the Internet. By contrast, this communications revolution has yet to reach the automobile. Drivers and passengers in cars typically enjoy access only to radio broadcasts and occasionally television. To reduce the unproductive driving time, people use their cellphone for voice communication. Moreover, today information cannot be personalized or adapted to the driver's and passenger's needs. The challenge is to provide the Internet's multimedia capability in the automobile environment with varying and limited bandwidth, thereby, enable a whole new class of services to and from the car.

At the same time, there is a strong effort in the Intelligent Transportation Systems community to stimulate research and industry to build an infrastructure which will lead to better traffic and transit resources management and enhanced safety. From cost and reusability perspectives, it is necessary that a single infrastructure provides most of the functionality building a separate instead of infrastructure for each service. Internet has the potential to be such an infrastructure. The car is essentially a probe in this model collecting and sending data to service centers, which in case of future navigation systems will be used for building dynamic real-time traffic models that would be used for on-demand route guidance by individual vehicles.

#### VISION

First we define the term "Internet Car":

An Internet Car is one which is like any other node on the Internet. Although it is highly mobile, it uses standard TCP/IP protocols to communicate with the other nodes on the Internet. An Internet car can be an Internet client as well as an Internet server. The car in essence becomes an open platform for services to be delivered over the Internet.

Some scenarios where the Internet car would be useful for drivers and passengers are:

- Services from Internet service providers e.g. safety, security, news, stock, city guide, navigation, email, and movies.
- Seamless access to office or home computer from the car.
- Personal devices (smart cards, HPCs) can be used to personalize car seats, climate, phone numbers, Internet services bookmarks, and computing man machine interface.
- Interactive audio/video games over the Internet for passengers.
- Personalized Internet based services e.g. "my" commute traffic information.

- Geo-specific information access on demand e.g. "nearest" Chinese restaurant.
- Internet based roadside assistance and remote diagnostics.

It is an open question what impact Internet content will have on the car, but it is our belief that ultimately it will be used to optimize the safety and security of the car along with comfort and convenience. Figure 1 illustrates a systems view of the Internet Multimedia on Wheels concept including a number of components that may be included in a full implementation.




Figure 1: A systems view of the Internet Multimedia on Wheels concept.

There are a number of ways to bring the Internet connectivity and content into a car. These methods differ widely in terms of functionality, connectivity, in-car infrastructure and system requirements. The strength of connectivity to the Internet may range from a fully connected model where data and services are available all the time down to a disconnected model which requires the drivers/passengers to bring Internet data on a storage media with them.

#### MAJOR CHALLENGES

An overarching challenge for connecting cars to the Internet is to define a system architecture with flexible distribution of computing power and communication between the automobiles and the infrastructure. The answer may be as simple as the cost of wireless communication. At one end, the car may only have the input/output devices and a modem to request and receive information. On the other hand, the car may have state-of-the-art computing power with on-board storage media to receive raw data, and to process it. Clearly, the form of the final architecture will depend on costs and business models. In all cases it will always be necessary to maintain the integrity, security, reliability and speed of communication.

Wireless communication is expensive and the bandwidth is quite restrictive for applications requiring transfer of other than a few hundred bytes of text data. There are a number of wireless service providers using different flavors of communication protocols and bandwidth to support the Internet protocol e.g., the frequency hopping spread spectrum Ricochet network, Cellular Digital Packet Data (CDPD), and Personal Communication Services (PCS). The challenge is to provide the basic infrastructure that can provide national or global coverage without employing a whole array of modems.

The presence of multimedia information in a moving vehicle can be a potential hazard to safety of the car. It is essential that the software architecture is open for development of new services and benefits from being easily adaptable to new and evolving Internet technologies. At the same time a metric that will define what services are deliverable to drivers under what mobility conditions, and which services can be used by passengers should be established to optimize the safety in the car.

#### BENEFITS

Automobile access to the Internet opens up a wide range of new opportunities for drivers, passengers, and customer assistance centers. It also increases the security and safety of the car. The quality of travel can be improved by personalized route plans delivered to the car with up to the minute road and traffic information.

Drivers will be able to access their voice-mail, e-mail, and travel-related information such as restaurant guides and movie theater locations. The driver will have access to these services in a hands-free, eyes-free manner through voice commands and speech technology.

Passengers can additionally access richer interactive applications such as on-board or Internet games, audio-on-demand, and web surfing. They can access information about cities and historical places during a drive as they pass them.

Drivers and passengers can also use their personal devices like Smart Phones, Personal Digital Assistants (PDAs), Hand-held PCs (HPCs), etc., in an integrated fashion. Also, by integrating GPS and mapping technologies, the Internet car becomes "location aware" which will be used for a new class of services that will go well beyond classical navigation.

For the customer assistance centers that currently rely on a "telephony-based" service, the Internet car will provide a richer "datacentric" multimedia environment to deliver new services including operator's help manuals and intelligent roadside travel assistance. For these new services, user interfaces will be designed that

allow easy and safe handling of the interactive media.

By grounding the concept and architecture of information technology for a car around the Internet and open standards, the Internet car can take full advantage of the tidal wave of Internet based services, technologies, and devices for many years to come, thereby transforming driving and riding into a completely new experience.

#### MOBILE SYSTEMS DESIGN

Inherently, the design of a system to provide access to Internet from cars must take into account the mobility aspect. Mobility in the system needs to be handled at two places. First, at the point of attachment (for example, at home or office), and secondly, during the time of travel. There are standardization efforts in this area already in the Internet community such as the Mobile IP proposal [1,2] along with the IPv6 proposal to Internet Engineering Task Force (IETF). In summary, Mobile IP assigns temporary care-off addresses to visiting hosts and directs Internet packets addressed to them at the home location to be forwarded to the point of attachment when a mobile (in this case the car) moves from one subnet to another.

Networking may be carried out using a variety of wireless technologies. Metricom, CDPD and Satellite based systems are the most attractive technologies in the US for connectivity to the Internet from the road. The 19.2 kbit/s bandwidth, CDPD wireless data service is already available in nearly 80 cities and may be used in conjunction with Circuit Switched CDPD to provide national coverage. Code Division Multiple Access (CDMA) is still being tested as a viable alternative for wireless Internet access. For short range data transaction, high bandwidth is typically the primary requirement. WaveLAN, IR or RF based solutions are most appropriate here. Finally, the new Java based smart card technologies will link personal information to cars. They will, in essence, provide a new way to communicate the identity of drivers/occupants to the car in an unobtrusive manner over the Internet. This information may then be used by the car to provide personalization of the seat position, climate, user interface in the car. The ramifications of such personalization features would include improved safety while driving, because mundane information for access to information services can be individually filtered Internet communication is based on standard TCP/IP stack. However, TCP [3] does not have any special provisions to work over wireless connections. It's congestion control algorithm assumes that a time-out in transmission is due to congestion but not to the loss of a packet. So, when a timer goes off, TCP slows down and sends less packets to avoid the congestion. In wireless networks it is very likely that the timer went off because of the loss of the packet, so the proper way to deal with this problem would be to send the packet again as soon as possible. Currently there are two major ways to improve the performance of TCP over wireless [7]:

- Indirect TCP [4] splits the TCP connection into two separate connections. The first connection goes from the sender to the base station and the second from base to mobile station over the wireless link. The drawback of this scheme is that the semantics of TCP as an end-to-end protocol are hurt. The base station acknowledges (Ack) each received packet in the usual way but this is no guarantee for the sender that the packet has reached the receiver.
- Snooping Agents [5,6]. The basic idea behind this agent is that it observes and caches TCP segments going out to the mobile host and Acks coming back from it. Therefore, it sits in the link layer of the base station. When it sees a packet going out to the mobile host but sees no Ack coming back in a relatively short time, it just retransmits the packet without telling the source sender that it is doing so. When it sees a duplicate Ack from the mobile host going by, it also generates a retransmission meaning that the mobile host has missed something. The duplicate Acks are discarded to avoid a source of misinterpretation by the sender as being a sign of congestion. One drawback of this solution is that the system is implicitly aware that TCP is used as the transport protocol. Also, when the link is very lossy, it will run into the same problems as without the system. This can be fixed by a selective repeat mechanism which is applied when the base station notices a gap in the inbound sequence numbers. It requests a selective repeat of the missing bytes using a TCP option. The findings in [6] strongly suggest that such a TCP aware link layer algorithm improves the throughput and the goodput over wireless links substantially without compromising the end-to-end semantics of TCP.

Our research would focus on the questions, whether the snoop agent can be placed anywhere in the network and how this would change the performance of snooping.

#### **IMPLEMENTATION**

In the first implementation of the Internet Multimedia on Wheels concept, we have designed multimedia units for two different zones with the user interfaces as shown in the following figures. In these units, there is a color screen, channel select buttons, IrDA (Infrared) transceiver to support hand-held devices, and an audio outlet.

The access to applications is different in these two zones. The driver and the navigator have access to a single multimedia unit in the front (Figure 2), and the passengers in the back seat have access to individual multimedia units (Figure 3). The applications in the front zone are more traffic and navigation driven. In the rear zone, there is access to navigation, office applications, interactive games, and infotainment.

The driver has access to the navigation system and local or Internet based services. He will be able to use voice commands to access these services from the Internet.

The passengers in the rear can enjoy a richer multimedia environment on their multimedia sets for navigation, games, stereo, or Internet access. The built-in IrDA transceivers will allow HPCs/PDAs to interact with the systems in the car.

In addition, the hand-rest in the driver's zone has a slot for a personal device to enable the driver to bring in personal preferences to the car.

#### **TODAY'S RESEARCH SCENARIOS**

Drivers and passengers will use the Internet car for both fun and productivity. The Internet based navigation unit will plan a route which takes into account real-time traffic information and traffic history. Drivers will access news, voice mail, email, stock quotes, weather information all through a hands-free, eyes-free audio interface. Co-passengers will access rich multimedia information from various domains work, as infotainment, office such entertainment. The car will empower the driver and passengers to choose the way they would like to spend their time from a large selection of options and services.




Figure 2: The E 420 Internet Multimedia on Wheels Concept Car and the front multimedia zone.



Figure 3: The rear passengers multimedia units with screens, channel selectors for games, computer, navigation, IrDA and Audio outlets

Furthermore, safety and security will be enhanced because Customer Assistance Centers will be always connected to the car. Services such as remote door unlocking, warning for bad road conditions, weather, accidents, and remote diagnostics, will add to the safety and security of cars.

#### THE FUTURE

Having an Internet address, the car becomes an integral part of cyberspace. Not only can

passengers request information but also fleet owners and customer assistance centers can request information from the car or even modify the car's behavior. This ultimately leads to a network-centric solution where the car can be continuously monitored, and where in essence every Electronic Control Unit (ECU) will be addressable through the Internet protocols. In fact, the very concept turns every car into a probe with vast implications for traffic guidance and control.

It will be possible to analyze driving habits and optimize engine performance. Customer assistance technicians can download code to the vehicle to perform diagnostic tasks or upgrade the software version.

ECU's can use external data from the infrastructure to adapt in an optimal way to weather conditions, road conditions, and traffic to provide new safety services.

#### **REFERENCES**

- [1] Perkins, C.; "Mobile IP", *IEEE Communications Magazine*, pp. 84 ff., May 1997.
- [2] Perkins, C. ed.; "IPv4 Mobility Support", *RFC* 2002, Oct .1996.
- [3] Stevens, W.R.; *TCP/IP Illustrated*, Vol. 1 The Protocols, Addison Wesley, 1996.
- [4] Bakre, A.; Badrinath, B.R.: "I-TCP: Indirect TCP for Mobile Hosts", *Proc. 15 Intl. Conf. on Distributed Comp. Systems*, IEEE, pp.136 ff, 1995.
- [5] Balakrishnan, H.; Seshan, S.; Katz, R.: "Improving Reliable Transport and Handoff Performance in Cellular Wireless Networks", *Proc. of ACM Mobile Computing and Networking Conf.*, ACM, pp. 2 ff, 1995.
- [6] Balakrishnan, H.; Padmanabhan, V.N. et al: "A Comparison of Mechanisms for Improving TCP Performance over Wireless Links", Department of EECS, University of California at Berkeley, 1997.

[7] Tanenbaum, A.S.: Computer Networks, Prentice-Hall, 3rd ed. 1997

#### **AUTHORS**

Akhtar Jameel is the principal researcher and manager for the Internet Multimedia on Wheels project. He joined the Research and Technology Center in Palo Alto in June 1996. He holds a Ph.D. in Computer Science.

Matthias Stuempfle is a research scientist at the Research and Technology Center with a major interest in communication protocols and architectural issues. He received a Diploma in Electrical Engineering and expects his Ph.D. in summer '98 from the University of Stuttgart. He is a member of VDE & IEEE.

Axel Fuchs is the head of the Transportation and Mobility Group. He joined Daimler-Benz in 1991 and has been with the Research and Technology Center in Palo Alto since its start in 1995. He holds a Ph.D. in Electrical Engineering.

## **EXHIBIT F**



## Web on Wheels: Toward Internet-Enabled Cars

An open system that conforms to standard Internet protocols for communication to and from automobiles could greatly enhance driving. Existing Internet resources can be leveraged to integrate a car into the Internet. Service providers will subsequently produce innovative services for drivers and passengers that will improve safety and security as well as provide infotainment.

Akhtar Jameel Matthias Stuempfle Daniel Jiang Axel Fuchs

Daimler-Benz Research and Technology, North America

he services provided to customers through the Internet can be extended to the automobile. Early versions of Internet-enabled cars might hit the road in five years or less. Portions of the technology could be available to customers in as little as two years as an after-sales solution. Indeed, such integration could become essential, given the constant access to information our just-in-time world seems to require. Integration could also be two-way: Your car might also provide information to the Internet for the purposes of remote diagnostics, among other things. Unlike the portable method of accessing the Internet with a laptop computer, an Internet-integrated vehicle is truly mobile. Mobility serves as both a challenge and a distinguishing factor in the design of our communication and service architecture.

With the advancement of the Global Positioning System (GPS) and other position-tracking technologies, *location awareness* emerges as a distinctive characteristic of combining mobile computing and automobiles. This knowledge will be used to build communication and service architectures. For example, a service could provide information about the nearest gas station or restaurant.

A safe and easy-to-use human interface for drivers and passengers must be designed to bring Internet-based services to moving vehicles. For example, an email service must not require that drivers take their eyes off the road. We employ various alternatives, such as speech-based technologies, to address safety concerns.

#### **SCENARIOS**

Our overall goal is to provide "telematik" (telecommunications and computer science) services to drivers and passengers. What types of services are interesting

to our customers and how we serve them are open questions. The Internet appears to be the most appropriate infrastructure through which to conduct car-based services.

Services range from the obvious to the innovative, and include the following:

- Integration of personal data to the car using personal devices such as smart cards and handheld personal computers.
- · Interactive audio and video games for passengers.
- Personalized services on demand, for example, personalized commuting information.
- Location-based information on demand, for example, the nearest Chinese restaurant.
- Seamless access to office or home computers.
- · Roadside assistance and remote diagnostics.


These services can be grouped as generic and location based. Generic services, for example, real-time stock quotes, are not directly car-related but are of interest to drivers and passengers. In general, the infrastructure for such services can be supported in the same way as a desktop environment.

Location-based services directly relate to the car-driving experience. Because the car moves, its location changes and thus brings new demands for services: Where is the nearest gas station? Location-based services are possible because a car's position can be known at all times with current GPS technology.

An Internet car is similar to any other node on the Internet. Although highly mobile, an Internet car can use the standard transmission-control protocol/Internet protocol (TCP/IP) to communicate with other nodes on the Internet. The Internet car can be a client and a server, and in essence becomes an open platform for services to be delivered over the Internet.

0018-9162/98/\$10.00 © 1998 IEEE January 1998

Figure 1. The Interneton-wheels concept car integrates a mobile vehicle with services available on the Internet



#### **CHALLENGES**

The design of Internet access for automobiles involves three major issues: mobile wireless communications, system architecture, and user interface design.

#### Mobile wireless communications

Networking requires a variety of wireless technologies.

In a local area, infrared (IR) and radio frequency (RF) technologies generally provide high-speed wireless access of several megabits per second at relatively small or no cost.

At the metropolitan level, technologies such as Metricom's Ricochet network are capable of access speeds of tens of kilobits per second with a flat monthly fee.

For a wide area, cellular digital packet data (CDPD) and emerging standards, such as the General Packet Radio System (GPRS), achieve speeds of about 10 kilobits per second at a higher cost. Furthermore, a plethora of new satellite-based systems are proposed. When realized, these satellite systems will deliver globally from a few kilobits per second up to one megabit per second at a premium. Of course, when all else fails, the wireless modem over the Advanced Mobile Phone System (AMPS) cellular system is still available.

These technologies provide the basic infrastructure for maintaining access to and from a vehicle. The main challenge lies in selecting the appropriate technology according to such factors as cost, performance, and availability.

#### System architecture

In connecting cars to the Internet, a system architecture must provide a flexible distribution of computing power and communication between the automobile and the infrastructure. Basically, a car could be treated as either a thin or thick client. Cars with only input/output devices and a modem to request and receive information are thin clients; cars with state-of-the-art computing power and onboard storage media to receive raw data and to process it are thick clients. The key factor influencing this overall architectural choice is the cost of wireless communication.

The form of the final architecture will be determined by technologies and business models. In any case, the integrity, security, reliability, and speed of communication must be maintained. The software architecture should also allow for the development of new services and benefits that adapt easily to new and evolving Internet technologies.

#### **User interface**

Introducing multimedia information in a moving vehicle creates a potential hazard. A human interface both safe and convenient while mobile at vehicular speeds significantly challenges the utility of services to be delivered over the Internet to drivers. The requirements for a safe human interface also have a drastic impact on the design of services for vehicles.

#### SYSTEM DESIGN

The initial intent of the project was to design a system to meet the challenges of wireless communication and the issues relating to a user interface in a car. At the same time, the growth of the Internet and the Web brought to the fore a new way of network computing. The design that emerged from these factors led to the concept of total integration of vehicle functions, personal data, position awareness, seamless access, and Internet-based services. Figure 1 shows this concept, which we call Internet-on-wheels.

Our system design has three major components: the communication layer, the service infrastructure, and the user interface. The reliability, security, performance, and scalability of the system are also essential aspects of our design but are beyond the scope of our discussion here.

#### **Communication layer**

The communication layer must be both open and convenient:

- Openness. In today's networking world, TCP/IP is the de facto standard for communication. Most applications use TCP/IP for communication, and many resources and services available on networks are accessible through TCP/IP, including the Web. It therefore must be used in any open networking solution. TCP/IP enables the use of many of today's existing applications, provides access to numerous resources, and encourages new service development. Furthermore, it does not make sense to require the current servers on the Internet to change their software or hardware.
- Convenience. Many wireless data communication technologies exist and more are coming. We need to support these technologies without additional burden. First, we need to work with the availability of a technology in a particular geographical region. Second, customers should not have to change the technology they currently use. For example, a user might be a Global Standard for Mobile Communications (GSM) subscriber, in which case the GSM handset should plug into the user's car to enable communication through the GSM network. To provide connectivity anywhere and to account for the coverage of different technologies, one wireless network should be able to hand off to another. We cannot expect a customer to have the technical understanding to manage the handoff, nor can we expect a driver to have the time or attention to deal with such details. Furthermore, a constant identity needs to be maintained. Therefore, the necessary handoff among various wireless networks must be seamless and transparent.




Figure 2. A typical Mobile IP communication network has a virtual home address.




Figure 3. The basic Mobile IP architecture seamlessly hands off among interfaces.

We omit performance as a basic requirement of the communication layer. Although we want as much networking performance as possible, our ability to provide this in the communication layer is limited by available technologies and wireless service providers. So we try to provide an architecture that supports as many existing or emerging wireless technologies as possible, but we cannot dictate the performance of those wireless channels directly. Therefore, the application design should adapt to the communication layer's capabilities rather than the other way around. Of course, we will try to improve the networking performance as much as possible in our capacity.

Basic communication architecture. With augmented handoff support, the Mobile IP's capability of maintaining the same identity over various network access points provides a natural solution. <sup>1,2</sup> Mobile IP supports

Services for an Internet car are bidirectional. In the more common services, the car acts as a client and the service infrastructure supports such services.

a seamless handoff among multiple wireless interfaces in a manner that is transparent to the higher layers.

Figures 2 and 3 show the workings of the proposed Mobile IP. As Figure 2 shows, the vehicle has a virtual home IP address. Any service provider or corresponding host would always see the vehicle at that IP address, which is connected to the Internet at large via a home agent.

The vehicle connects through a particular wireless network and an Internet service provider (ISP) and uses an IP address issued by the ISP. The vehicle registers its current address with a stationary host known as its *home agent*. In communicating with a service provider, the incoming IP traffic from the service provider would be intercepted by the home agent and

forwarded to the current address of the vehicle. Likewise, all traffic to the service provider would be sent to the home agent before being forwarded to the service provider.

In the event of a handoff from one wireless network or ISP to another, the actual IP address of the vehicle changes. Such a change would be reported to the home agent, and all subsequent IP traffic would be routed to the vehicle at the new address. None of these activities is visible from the applications that use the communication layer.

**Communication performance**. Two issues affect performance in this environment: TCP performance over wireless links and the handoff from one wireless network provider to another.

TCP³ was designed to work for the wire-line-based Internet, which rarely creates errors in the transmission of IP packets. In such an environment, TCP assumes that failure to receive a packet results from congestion. In the event of a packet loss, TCP slows and sends fewer packets to lessen the congestion. Such an algorithm works well in the wire-line network, but not so well over the wireless link. However, when a TCP connection includes a wireless link, packet loss is far more likely to be caused by errors in a wireless channel. Consequently, TCP data should be sent faster, not slower.

The networking research community has done much to improve performance over lossy wireless links. In general, the proposed solutions fall into three groups:

- An end-to-end connection is intended to improve TCP performance relative to that of wireless communication.
- A split TCP connection divides a TCP connection into two end-to-end parts.
- The reliable link layer has some knowledge of the TCP.<sup>4</sup>

The end-to-end and link-layer solutions work com-

paratively well. However, any end-to-end solution requires changes at the TCP layers of both the sender and the receiver. All servers on the Internet that our customers might contact cannot be expected to upgrade their TCP software, leaving the link-layer solution as the most feasible measure for improving TCP performance.

One link-layer solution employs a *snooping agent*.<sup>5</sup> A snooping-agent observes and caches the TCP packets going out to the mobile host on the wireless link. When the agent senses that some packets are lost (by monitoring the acknowledgment packets coming back from the mobile host), it retransmits the cached TCP packets. In this way, the snooping agent effectively prevents the effect of packet loss on the wireless link from being propagated to the TCP sender and triggering a TCP slowdown.

The snooping-agent method works well in a wireless local area network (LAN), in which the snooping agent sits in the wireless base station. For wireless wide area networks (WANs), the snooping agent must be placed a little further away from the wireless link. The logical location would be that of the home agent through which all traffic goes. Our research will focus on the snooping agent's impact on performance relative to its distance from the vehicle.

The issues concerning handoffs and their effect on communication performance are twofold. First, handoffs exist among cells in a wireless network infrastructure. Although transparent to the mobile host, the handoff's impact on the communication layer performance is unclear. Second, the handoff from one wireless network provider to another has a much larger effect. During the change of an actual IP address, the registering of the change to the home agent, and finally the rerouting of traffic to reflect the change, some IP packets might be lost.

The impact of such a handoff could be lessened by holding onto the existing wireless connection and simultaneously routing the same packets to the new address as well as the existing one. With the new connection fully operational, the previous connection closes. The vehicle has the advantage of knowing where it is and where it is going to be and at what time.

Combining such information with the knowledge of where the coverage of a wireless network begins and ends, a new connection can be preestablished before the current connection runs out of coverage. Such information might be cached by the vehicle through the experience of driving in a familiar region, for example, a daily commute from home to work, or it could be provided by service providers that measure and collect the coverage of various wireless data networks.

**In-car network.** Most of the automotive industry supports some types of bus architectures for control

Service register and locator

Ouery and response of services

Service information registration and update

Service transactions

Service provider

Figure 4. The service architecture design contains these high-level components.

and data transmission. A bus system with bandwidth large enough to support multiple video and audio channels is needed to support the Internet-based multimedia information in the car. The Universal Serial Bus (USB), the IEEE 1394 standard Firewire, or the Intelligent Transportation System Data Bus (IDB-I and IDB-II) could be considered for such a task.

Multiple inputs and outputs—such as screens, control units, and audio channels—must be available for use by all occupants in a car without any interference with each other. This flexibility is relatively easily achieved for screens and control units, but it is harder to separate audio sources without using headphones.

Merging the in-car network with Internet communication services will provide an integrated internal and external environment for the occupants. A multimedia infrastructure in a vehicular environment challenges the design. The storage media is an essential component of an Internet information-based multimedia environment in a car. At a basic level, the media might be just a cache or simply a readable media such as the minidisc or digital video disc, but the ultimate solution will be a hard-disk-like unit for storing large amounts of data that can be dynamically changed.

Docking of personal devices has wide acceptance in the personal computing arena. People will likely use devices such as smart phones, smart cards, and personal digital assistants (PDAs) to integrate with the car's multimedia system. These devices might also be a means through which to exchange personal information between the occupants and the car for seat adjustment, climate, and computer interface.

#### Service infrastructure

Services for an Internet car are bidirectional. In the more common services, the car acts as a client and the service infrastructure supports such services.

Service infrastructure functions. The service infra-

structure has four main functions: It must search for service providers, manage the user profile, deliver the service, and use the service. Here we will not discuss issues like billing and so on.

A location-indexed database is necessary if the car occupants are to easily search geographical location-based services. The database must contain things like service providers, Web pages, and other information, indexed by the relevant geographical area. The vehicle's location determines the scope of the search.

A service profile specifies what and how services will be delivered to the customers in an Internet car. The service infrastructure provides storage and management of a customer's service profile.

After selecting a service provider, the communication layer offers data transport functions. However, the ability of the devices in the car to use the service content must be determined. For example, large images of a Web page cannot be displayed on a tiny PDA screen. Service delivery also needs to adapt to wireless link capabilities. A service proxy works well in such a situation. By doing data transformation at the well-connected side of the Internet, the data load can be reduced and something easy to present can be created. By symmetry, a car-side proxy for the vehicle must act as a server in certain applications like remote diagnostics.

The need to support ad hoc service types and service providers means that we need to support automated downloading, installation, and update of client software for future, unknown services.

Service architecture design. Figure 4 diagrams the high-level components in the service architecture. The service register and locator is essentially the location-indexed database. This database accepts and responds to queries from the vehicle for services and service providers. Once a customer finds a service provider, services can be requested and transactions begun. Such service transactions might go through a proxy.

Figure 5. The front multimedia zone of the Internet car is accessible to both the driver and the navigator.



Figure 6. The rear passengers have access to multimedia units that contain screens, channel selectors for games, a computer, navigation tools, infrared transceivers, and audio outlets.



Placement of the user profile and determination of the component responsible for the profile management must be determined. This is essentially the issue of how to distribute the intelligence in the system.

#### User interface design

There is no precedent for the user interface of a Web car. Obviously, there are safety issues involved in the placement of screens, hand control units, hands-free phones, and buttons.

User interfaces can range from a simple one-touch operation to a fully interactive audio and video experience. Clearly, the driver, navigator, and passengers have differing circumstances when the vehicle is parked or in motion. A taxonomy of the driver, navigator, and passengers with different human interface needs is a good starting point to understand the basic differences in the design of interfaces for these positions.<sup>9</sup>

Drivers might find a primarily speech-driven interface most suitable, whereas passengers and navigators can use a richer and more interactive interface. We expect that a conversational, dialogue-based speech system will be used in the future.

Large speech-recognition systems, especially those that support natural-language processing, are expensive and difficult to support in cars. Therefore, a network-based solution makes sense. Such a solution is well suited to a dynamic, on-the-fly vocabulary, and conversational natural-language processing approach, and it is cheaper to maintain and upgrade. A hybrid between in-car recognition for the car controls and a network-based approach for external informationbased services would be ideal.

The type of user interface chosen will be closely tied with the nature and type of services that can be delivered to drivers and passengers. Mobility is no longer only driving the car but incorporates also the states of being at home, in the garage, on the road, and at the destination. A driver's *safety* depends on the state of *mobility*, the *time* available, and the driver's *goals*. We intend to define a metric on the basis of the relationship between these four human factors and the services that can be delivered to car drivers and passengers. This metric will be used to define user interfaces that are safe and match the measures used by Mercedes-Benz, the Society of Automotive Engineers, or similar established safety standards. See Figures 5 and 6.

The presentation and user interface architecture shown in Figure 7 assumes that content providers supply the data and the semantics to describe the architecture's structure. The presenter uses this information along with the user input and status information (vehicle speed, user being the driver or passenger) to render and deliver content to appropriate output devices.

#### **CONCEPT DEMONSTRATION**

In the first implementation of the Internet-on-wheels concept car, <sup>10</sup> we designed multimedia units for two different zones (*drivers* and *passengers*) with the user interfaces as shown in Figures 5 and 6. Each of these has a color screen, channel select buttons, an infrared transceiver to support handheld devices, and an audio outlet.

Access to applications differs in these two zones. The driver and the navigator have access to a single multimedia unit in the front (Figure 5), and the passengers in the back seat have access to individual multimedia units (Figure 6). The demonstrative applications in the front zone access information related to traffic and navigation. In the rear zone, access expands to include navigation tools, office applications, interactive games, and infotainment.

Drivers can access voice-mail, e-mail, and travel-related information such as restaurant guides and movie theater locations. By integrating the GPS and mapping technologies, the Internet car becomes location-aware, which allows for a new class of services that go well beyond classical navigation. The driver will have access to these services in a hands-free, eyesfree manner through voice commands and speech technology. In addition, the armrest in the driver's zone has a slot for a personal device to enable the driver to bring in personal preferences.

Passengers can access richer interactive applications such as onboard or Internet games, audio-on-demand, and the Web. They can access information about cities




Figure 7. Content providers define the data and semantics for the presentation and user interface architecture.

and historical places during a drive as they pass them. Passengers can also enjoy an enhanced multimedia environment for navigation, stereo, or streaming audio and video. The built-in infrared transceivers will allow PDAs, handheld PCs (HPCs), and smart phones to interact with the systems in the car and the Internet. For these new services, user interfaces will allow easy and safe handling of the interactive media.

For the customer assistance centers that currently rely on telephony-based service, the Internet car provides an expanded datacentric multimedia environment to deliver new services, including operator's help manuals, intelligent roadside travel assistance, and remote diagnostics.

he intelligent transportation systems community intends to stimulate research and industry to build an infrastructure that will lead to better traffic and transit resource management and enhanced safety. From the perspectives of cost and reusability, a single infrastructure must provide most of the functionality as opposed to a separate infrastructure for each service. The Internet has the potential to be such an infrastructure. The car acts essentially as a probe in this model, collecting and sending data to service centers, which in future navigation systems will be used to build dynamic real-time traffic models for on-demand route guidance for individual vehicles.

The spectrum of service possibilities ranges from a highly integrated, PC-like environment to a fully autonomous network computer-like system. A safe and convenient human interface design will leverage the vast pool of potential services from the Internet for drivers and passengers.

Our research aims to investigate and prototype future Internet-based services for cars. By grounding the concept and architecture of information technology for a car around the Internet and open standards, the Internet car can take full advantage of the tidal wave of Internet-based services, technologies, and devices for many years to come. ��

#### Acknowledgments

We thank Paul Mehring for his vision in supporting this research. Many thanks to Klaus Eitzenberger and Peter Stiess from Daimler-Benz in Stuttgart whose research and ideas have helped us in this project.

#### References

- M. Stemm and R. Katz, "Vertical Handoffs in Wireless Overlay Networks," ACM Mobile Networking, Fall 1997.
- C. Perkins, "Mobile IP," *IEEE Comm.*, May 1997, pp. 84-99.
- W.R. Stevens, TCP/IP Illustrated: The Protocols, Addison Wesley Longman, Reading, Mass., 1996.
- H. Balakrishnan et al., "A Comparison of Mechanisms for Improving TCP Performance over Wireless Links," *Proc. ACM SIGCOMM Conf.*, ACM Press, New York, 1996.
- H. Balakrishnan, S. Seshan, and R. Katz, "Improving Reliable Transport and Hand-off Performance in Cellular Wireless Networks," Proc. ACM Mobile Computing & Networking Conf., ACM Press, New York, 1995.
- 6. A. Fox and E.A. Brewer, "Reducing WWW Latency and Bandwidth Requirements via Real-Time Distillation," *Proc. Fifth Int'l World Wide Web Conf.*, 1996.

- M. Stuempfle, D. Jiang, and A. Jameel, "Aspects of an IP-Based Communication and Service Architecture Using Wireless Networks," RTC Report 31, DB-RTNA, 1997.
- D. Jiang, M. Stuempfle, and A. Jameel, "Service Architecture for Internet-Enabled Automobiles," RTC Report 32. DB-RTNA. 1997.
- M. Tschudy, M. Braun, and A. Jameel, "MB-Browser Technologies," RTC Report 33, DB-RTNA, 1997.
- A. Jameel, A. Fuchs, and M. Stuempfle, "Internet Multimedia on Wheels: Connecting Cars to Cyberspace," Proc. IEEE ITS Conf., IEEE Press, Piscataway, N.J., 1997, p. 291.

Akhtar Jameel is the principal researcher and manager for the Internet Multimedia on Wheels project at Daimler-Benz's Research and Technology Center. He received a PhD in computer science from Tulane University, New Orleans.

Matthias Stuempfle is a research scientist at Daimler-Benz's Research and Technology Center with a major interest in communication architectures and software engineering. He finished the research toward his PhD and has submitted the thesis to the faculty of EE at the University of Stuttgart. He is a member of Verein Deutscher Elektrotechniker and the IEEE Computer Society.

Daniel Jiang is a research scientist at Daimler-Benz's Research and Technology Center. He received a BS in computer science from Rutgers University and is an MS candidate in computer science from the University of California at Berkeley.

**Axel Fuchs** heads the Transportation and Mobility Group at Daimler-Benz's Research and Technology Center. He received a PhD in electrical engineering from the University of Darmstadt.

Contact the authors at Daimler-Benz Research and Technology North America, Palo Alto, CA 94304; {jameel, stuempfle, jiang, fuchs}@rtna.daimlerbenz.com.



#### CALL FOR PAPERS

#### IW-MMDBMS'98

#### 1998 International Workshop on Multimedia Data Base Management Systems August 5-7, 1998, Holiday Inn, Dayton/Fairborn, Ohio, USA.



Sponsored by IEEE Computer Society, Information Technology Res. Institute (ITRI), Wright State Univ., Dayton, Ohio Incooperation with IEEE TC on Multimedia Computing, IEEE TC on Data Engineering, ACM SIG Multimedia\*.

ACM SIG Management of Data\*, and the Data Management Specialty Group of the MITRE Corp.

Objectives: IW-MMDBMS'98 is an international technical forum for active researchers and practitioners who are involved in various aspects of multimedia database management issues. The workshop will emphasis issues relevant to designing, developing,
and utilizing multimedia database management systems. The paper presentations, panel, and working group discussions will
address the following issues as they relate to multimedia database management:- Multimedia Database Modeling - Decomposition/Organization Techniques - Storage Structures and Techniques - Distributed Multimedia DBMS - Data Transmission - Meta
Data Management - Performance Evaluation - Multimedia Network Protocols and Infrastructures - Access Security Issues - Multimedia Database Applications - Multimedia Data Synchronization - Query Language Designs, Specification, and Optimization OS Issues - QoS Delivery/Presentation Issues - Retrieval Techniques and Algorithms - Access Methods, Browsing, and Indexing
Techniques - OO Paradigms - System, Schema, and Functional Architectures - Image Processing, etc.

General Chair: P. Bruce Berra (ITRI, Wright State Univ.) Vice General Chair: Erich Neuhold (GMD-IPSI)

Program Chairs: Kingsley C. Nwosu (Lucent Tech.), Bhavani Thuraisingham (Mitre); Publications: R. Kannan (Monmouth U.)
Program Co-chairs: Cyril Orji (Lucent Tech.), Donald Adjeroh (Chinese Univ., Hong Kong);

Program Committee: M. Adiba (IMAG-LGI), A. Asthana (Lucent Tech), J. Buford (U. Mass. Lowell), Son Dao (Hughes Res. Lab.), M. Escobar-Molano (Univ. S. Florida), B. Furite (Florida Atlantic U.), A. Ghafoor (Purdue U.), S. Ghandeharizadeh (USC), F. Golshani (Arizona St. U.), W. Grosky (Wayne St. U.), Le Gruenwald (U. Oklahoma), R. Jain (UC-San Diego), K. Jeffay (UNC), W. Klas (GMD-IPSI), C. Leung (Victoria U. Tech.), R. Mehrotra (U. Missouri), P. Mitkas (Colorado St. Univ.), T. Ozsoyoglu (Case W. Res. Univ.), P. Prabhakaran (National U. Singapore), P. Venkat Rangan (UC-San Diego), R. Rastogi (Lucent Tech.), O. R.. Sheng (Hong Kong US&T), W. Sterling (NCR), V. S. Subrahmanian (Univ. Maryland), D. Szafron (Univ. Alberta), P. Yu (IBM), H-J. Zhang (HP Labs), A. Zhang (SUNY, Buffalo, HongJiang Zhang (HP Res. Lab.). Information for Authors: Each paper must not exceed 25 double-spaced pages. Submit postscript or Microsoft Word files electronically by March 15, 1998 to knwosu@lucent.com or send 4 copies of each paper to: Dr. Kingsley C. Nwosu, Lucent Technologies, 67 Whippany Rd., RM 2E-223A, Whippany, NJ 07981-0903. Phone: (201)386-4211, Fax: (201)386-6235.

URL: http://andromeda.rutgers.edu/~nwosu/mmdbms98/

## **EXHIBIT G**

# The car as a mobile-media platform



by Kevin Jost, Associate Editor

Vehicle and computer
technologies are merging as
the automotive industry
scrambles to provide
consumers with PC
functionality in their
vehicles.

The average automobile user spends about seven hours per week of largely unproductive time behind the wheel. Automakers are looking at this as an opportunity, anticipating driver needs by providing information technology to extend the electronic environment of the home and office to the automobile. Industry engineers are designing systems that provide safe, affordable, and valuable information, communication, entertainment, and security features. However, their ability to do this is dependent on building the right hardware and software infrastructure.

One of the chief proponents of such offerings is Microsoft. In January, the company announced the Auto PC, the latest member of its PC Companion line of products powered by the Windows CE operating system. It brings the benefits of interactive speech technology, connectivity, information on demand, and enhanced entertainment to the automobile.

Microsoft's interactive-speech technology user interface enables the Auto PC to respond to oral commands and communicate information to drivers, allowing them to keep their hands on the wheel and eyes on the road. Microsoft expects the technology to become widely accepted as the primary way of interacting with automotive computing devices.

The Auto PC displayed by Microsoft is the size of a car stereo system, so it can be easily installed in the instrument panel. It provides drivers access to personal information and driving directions as well as wireless services such as e-mail, paging, and traffic alerts; a digital audio system; an AM/FM radio; and a CD player. PC Companion devices are designed to work together, so users can share information between their Auto PC and Handheld and Palm PCs.

The Auto PC platform is expandable and upgradeable. The latest example, version 2.0, allows a variety of third-party applications such as enhanced navigation, wireless data capabilities, cellular telephone integration, and vehicle diagnostics.

The list of automotive manufacturers, suppliers, and aftermarket electronics vendors supporting the Auto PC platform includes Alpine, Clarion Corp., Daewoo Telecom, Hyundai Electronics Industries Company, IAV GmbH, Infinity Systems, JBL, Magneti Marelli, MD-Co., Nissan Motor Corp. U.S.A., PSA Peugeot Citroen, Samsung Electronics Company, United Technologies Automotive, Visteon, and

Volkswagen AG. The first units on the market are expected to be from electronic aftermarket companies in the second quarter of 1998.

#### Clarion to market first unit

Clarion Corp. of America is expected to be the first car audio manufacturer to bring the Auto PC platform to market this spring or summer (see sidebar). In early February, the Clarion AutoPC was showcased in an Infiniti concept car called the I30 Executive Luxury Special Edition (ELSE). The concept-car unit takes the core Windows CE 2.0 operating system and adds speech recognition, a car-stereosized visual interface, and other car-oriented features to create an information and entertainment device for the car.

The Clarion AutoPC fits within a car's instrument panel. It allows drivers to keep their eyes on the road and their hands on the wheel while receiving e-mail alerts, dialing a cell phone, navigating to a specific destination, locating a restaurant or hotel, accessing traffic and weather conditions, or changing the musical selection on the stereo.

"Microsoft's open, expandable Auto PC platform will bring a new level of excitement and opportunity to the in-vehicle systems market," said James Minarik, president, Clarion Sales Corp. "Clarion is bringing to market the first product in this category, the Clarion AutoPC, demonstrating our commitment to developing mobile multimedia products that converge car audio and personal computing — allowing consumers to drive smarter and safer."

#### OEM suppliers develop production Auto PCs

A number of automotive original equipment suppliers have announced plans for development of Auto PCs, including UT Automotive, Visteon, and Delphi.

UT Automotive announced in November that it would use the Windows CE operating system to develop an architecture for in-vehicle use, starting with multimedia, information, communication, and entertainment (MICE) applications. The development agreement with Microsoft will help UT Automotive influence and pioneer product development, expand its product lines, and position the company to be the preferred supplier in the future for in-vehicle operating platforms, according to Roch Basson, UT Automotive's vice president of electrical and electronic products. Development of a computer operating system is being driven by the number of comfort and convenience functions being offered in automobiles, Basson said.

In January, Visteon Automotive Systems announced it was joining forces with Microsoft and Intel to develop a computing platform for vehicles designed to "keep drivers safely connected to the information they need and want on the road." The platform is based on the Microsoft Windows CE operating system and Intel Architecture microprocessors. Visteon expects to be first-to-market with its version of Auto PC technology in a production vehicle and will pilot a dealerinstalled version of the system this summer.

At the 1998 SAE International Congress and Exposition, Visteon unveiled its Auto PC-based multimedia system. Called ICES, the electronics infrastructure hardware and software architecture supports information, communication, entertainment, safety, and security features. Visteon says that ICES extends the electronic environment of the home and office to the vehicle, delivering Internet access, an emergency service, and other features such as a cell phone, climate control, high-quality audio, and even movies for rear-seat passengers.

By using state-of-the-art voice and navigation technology, ICES can tell a driver about traffic snarls as they occur and suggest time-saving alternate routes. More importantly, the system can also listen to and understand the driver's requests to map new routes.

"Our research shows that customers want the time in their vehicles to be productive, entertaining, and, most of all, safe," says Charles W. Szuluk, President, Visteon. "With ICES we've answered the customer's call. Drive time will never be downtime again."

Safety was an important consideration

for the ICES development team. For instance, drivers will be able to retrieve and respond to e-mail, voice mail, and pages using simple voice commands.

ICES is powered by Intel Architecture microprocessors and the Microsoft Windows CE operating system. By maximizing integration, Visteon engineers developed a system that is said to offer automotive manufacturers significant cost savings and a compact, lightweight package that is easy to install.

Drivers will be able to tailor ICES to the features they want and add more features by installing new software — as they do with their home and office PCs. Key technologies of Visteon's system include a voice-activated control system and a Remote Emergency Satellite Cellular Unit (RESCU).

The voice-activated system allows drivers to control vehicle functions that are usually operated manually — such as climate control and audio — with simple voice commands to help alleviate distractions while driving. The voice system recognizes natural language commands, including a wide range of voices, languages, and dialects.

Visteon's RESCU is a factory-installed system that combines Global Positioning System (GPS) technology and the cellular telephone network to aid drivers in distress. It activates automatically upon air bag deployment and includes new convenience features such as route assistance and concierge services.

Also at SAE '98, Delphi and Saab introduced a Saab 9-5 concept called the Personal Productivity Vehicle said to feature the most advanced mobile office technology — including communication, entertainment, and computer desktop functions. Developed at Delphi Delco Electronics System's Mecel AB subsidiary in Goteburg, Sweden, the Personal Productivity Vehicle uses the Microsoft Windows CE-based Auto PC platform. It integrates an AM/FM receiver, CD-ROM, IrDA, serial port interface, universal serial bus, COMPACTFLASH expansion slot, and a high-resolution display.

The vehicle features steering wheel controls, interactive speech technology to respond to driver commands, and speech synthesis to communicate text information - again "allowing drivers to keep their hands on the wheel and eyes on the road." Through speech recognition, the driver can send e-mail, obtain turn-byturn Global Positioning Satellite (GPS)based navigation to a specific destination, ask for traffic and weather conditions, locate a restaurant or hotel, or change the musical selection on the stereo. The concept vehicle also offers wireless features in which a cellular modem connection can be used for vehicle-to-roadside assistance or to receive e-mail and Internet information. An infrared data link connects to Windows CE-based devices, such as Handheld and Palm PCs or another personal handheld Data Assistant, for transferring data to and from the vehicle.


High-bandwidth connectivity is achieved in the vehicle with a unique, ultra-high-speed, fiber-optic serial data link called Mobile Media Link (MML), which



Visteon's Windows CE-based ICES multimedia system has information, communication, entertainment, safety, and security features.







The Delphi/Saab Personal Productivity Vehicle uses the Microsoft Windows CE-based Auto PC platform.

is capable of providing multiple-channel digital audio and video. MML also can connect and control inputs and outputs to facilitate a variety of consumer electronic products such as head-up display, television antenna and tuner, DVD player, compact disc player, digital stereo audio, and digital speaker amplifiers.

Data are transmitted and distributed from network nodes via a plastic-optical-fiber physical layer, passive star, and optoelectronic devices developed by Delphi Packard Electric Systems. Delphi Delco Electronics Systems provided the hardware, standard link protocol, and integrated circuit design. The MML fiber-optic bus is capable of signal transmissions rates of up to 110 Mb/s and can support up to 50 channels of audio and 20 channels of TV-quality compressed video.

"Because the fiber-optic cable is immune to electromagnetic interference (EMI) and generates no emissions, MML provides vehicle occupants with crystal-clear audio and video without negatively affecting other vehicle systems increasing functional reliability," said Jim Crouse, director of engineering at Delphi Packard Electric Systems. Compared with other systems, MML also can provide higher performance. While other fiber-optic

systems currently feature only audio capability, MML offers both audio and video.

#### Delphi and others offer alternative

In addition to the Windows CE-based Personal Productivity Vehicle, at SAE '98 Delphi introduced another technology initiative concept called a Network Vehicle that it is working on with IBM, Sun Microsystems, and Netscape. With the concept, the four companies demonstrated how existing hardware and software technology — including wireless communications, global positioning via satellite, head-up displays, voice recognition, Java technology, microprocessors, Web access and collaboration, and other Internet/intranet features — can be integrated.

"Much of the technology to do this, including our head-up displays, steering wheel-mounted controls, and man-machine interface in the passenger compartment, exists today," said Dave Wohleen, general director of engineering for Delphi Delco Electronics Systems. "Working with vehicle manufacturers, these technologies could be integrated into all types of vehicles."

The Network Vehicle receives direct broadcast reception from Hughes DirecTV and DirecPC satellites by use of an innovative flat antenna embedded in its roof, which provides the driver and passengers with route and travel information, to movies and real-time stock quotes. Existing services that could be integrated in the future include theft-deterrent technologies and the ability to contact emergency services. Future features include dictating and electronic distribution of memos; setting work schedules; listening to, and dictating a response to, faxes; and viewing videos.

#### The Clarion AutoPC


At the Consumer Electronics Show in January, Clarion Corp. of America introduced the first Auto PC. The 1-DIN unit fits in an automobile's instrument panel and is built on an open architecture platform powered by the Microsoft Windows CE operating system. It integrates car audio, computing functions, navigation, and wireless communications via hands-free voice activation.

A key innovation of the Clarion AutoPC is its use of Universal Serial Bus (USB) architecture, allowing for compatibility with other USB products. This provides numerous opportunities for hardware and software developers to create and market customized products for consumers.

speech application, the AutoPC can provide status information and assistance, such as turn-by-turn directions or e-mail alerts, through speech synthesis and text information presented on the unit's display. To make finding destinations easier, the Clarion AutoPC comes standard with a basic point-to-point navigation system that provides route calculation from a user-specified starting location and destination, as well as accurate turn-by-turn directions. Other built-in applications include an address book, mileage log, and a hands-free voice memo feature.

The unit supports an optional compact flash memory card that can be used to exwhen lost and pinpointing the location of a 911 call for immediate assistance. Using wireless "push" technology, the Clarion AutoPC's wireless receiver option allows consumers to receive an array of customized information, such as real-time traffic, news updates, numeric paging, voice and email alerts — all using text-to-speech technology.

To protect the car and Clarion AutoPC inside it, an optional Clarion/Ungo security system is under development. This system has USB connectivity and provides consumers with all the features found in other high-end Ungo security products such as Electronic Logicsensor and Motion/Impact



The Clarion AutoPC is a high-powered AM/FM stereo with integrated digital signal processing (DSP) equalization and a built-in 35 W x 4-channel amplifier. It comes with a Hitachi SH3 processor, 8 MB DRAM/8 MB ROM, and the first in-dash Clarion quality USB CD audio and CD-ROM drive, which supports an optional six-disc CD/CD-ROM changer. The backlit, 8-color LCD screen provides consumers with an easy-to-read, icon-driven user interface.

The AutoPC unit recognizes over 200 simple voice commands, allowing consumers to interact with the unit without taking their eyes from the road. With its text-to-

pand the onboard memory as well as provide an interface for other products such as paging and hardware accessories. Also included is an infrared data port, enabling easy exchange of data to and from a handheld PC.

A number of hardware accessories will also be available. The optional Global Positioning System (GPS) receiver works in conjunction with the built-in navigation system to provide automatic starting point identification and location updates. The GPS accessory, coupled with the cellular phone interface, enables access to roadside emergency services, such as providing directions

detector. When combined with the cellular telephone interface and GPS, this system also provides easy tracking of stolen vehicles.

The Clarion AutoPC will be shipping in limited quantities in spring 1998, with mass production beginning in June 1998. Suggested retail price for the base unit is \$1299. Clarion also announced at the Consumer Electronics Show that it would supply the new mobile-media product to Citroen, which will be the first in Europe to offer the Clarion AutoPC.

For more information, circle 103





These "smart" features are enabled in large measure by the real-time data-streaming capabilities over a wireless network made possible through IBM's Java-based technology. Java enables the rapid development and prototyping of applications that run within the vehicle. With the technology, automakers also have the flexibility to create a Network Vehicle using a variety of hardware and operating system platforms.


The Network Vehicle has voice-recognition technology for drivers and passengers to request and listen to e-mail messages, locate a restaurant or hotel, receive navigation help or specific music and sports scores, and use voice-activated telephone services — all without interfering with driving. Drivers can use a Delphi head-up display projected

onto the windshield to navigate while keeping their eyes on the road. Passengers using individual terminals next to their seats can use the Internet, watch high-resolution television, or play computer games.

The use of Java allows for an open, scalable platform to deploy cutting-edge content and applications in vehicles, according to Jim Mitchell, vice president of technology and architecture at JavaSoft, a business unit of Sun Microsystems, Inc.

"As Internet-based services add new dimensions to the daily lives and work of millions of people, we see great value in extending network access beyond the home, classroom, or office by making it easily accessible from anywhere," said Netscape's vice president of technology, Mike McCue. "Our participation

#### **On-Board Architecture**



Delphi collaborated with IBM, Sun Microsystems, and Netscape on the Network Vehicle, which uses Java-based technology.

in this technology initiative underscores our vision of a network world where our products run across computing platforms and the new portable devices that serve a mobile lifestyle. Access will be from anywhere — including vehicles."

Interesting? Circle 17 Not interesting? Circle 18