
Development of a New Hybrid System - Dual System

**Kozo Yamaguchi, Shuzo Moroto, Koji Kobayashi,
Mutsumi Kawamoto, and Yoshinori Miyaishi**
Equos Research Co., Ltd.

**Reprinted from: Strategies in Electric and Hybrid Vehicle Design
(SP-1156)**

DTX 636

Paice LLP v. Toyota Motor
Corp. et al.
04-cv-00211 (DF)

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL

**International Congress & Exposition
Detroit, Michigan
February 26-29, 1996**

The appearance of the ISSN code at the bottom of this page indicates SAE's consent that copies of the paper may be made for personal or internal use of specific clients. This consent is given on the condition however, that the copier pay a \$7.00 per article copy fee through the Copyright Clearance Center, Inc. Operations Center, 222 Rosewood Drive, Danvers, MA 01923 for copying beyond that permitted by Sections 107 or 108 of U.S. Copyright Law. This consent does not extend to other kinds of copying such as copying for general distribution, for advertising or promotional purposes, for creating new collective works, or for resale.

SAE routinely stocks printed papers for a period of three years following date of publication. Direct your orders to SAE Customer Sales and Satisfaction Department.

Quantity reprint rates can be obtained from the Customer Sales and Satisfaction Department.

To request permission to reprint a technical paper or permission to use copyrighted SAE publications in other works, contact the SAE Publications Group.



GLOBAL MOBILITY DATABASE

All SAE papers, standards, and selected books are abstracted and indexed in the Global Mobility Database.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

ISSN 0148-7191

Copyright 1996 Society of Automotive Engineers, Inc.

Positions and opinions advanced in this paper are those of the author(s) and not necessarily those of SAE. The author is solely responsible for the content of the paper. A process is available by which discussions will be printed with the paper if it is published in SAE Transactions. For permission to publish this paper in full or in part, contact the SAE Publications Group.

Persons wishing to submit papers to be considered for presentation or publication through SAE should send the manuscript or a 300 word abstract of a proposed manuscript to: Secretary, Engineering Meetings Board, SAE.

Printed in USA

95-0048

Development of a New Hybrid System - Dual System

Kozo Yamaguchi, Shuzo Moroto, Koji Kobayashi,
Mutsumi Kawamoto, and Yoshinori Miyaishi
Equos Research Co., Ltd.

Copyright 1996 Society of Automotive Engineers, Inc.

ABSTRACT

A new hybrid vehicle system has been developed, the Dual System, which combines the series and parallel hybrid systems.

Combination with a motor has reduced the engine size, only using the most efficient range of the engine. A transaxle employing a generator motor and a traction motor in one compact package is applicable to currently produced vehicles with little modification. Use of the generator as a motor realizes multiple control functions.

A prototype vehicle with this new Dual System was built and tested. Its driving performance and the fuel economy were measured, and the fuel economy results were analyzed.

INTRODUCTION

Toward the 21st century, energy conservation has keen global interest due to an expected sharp increase in energy demands according to ever increasing population and global warming caused by an increasing volume of generated CO₂. To decrease the energy used for vehicles, there are activities in various countries to find ways to greatly reduce the fuel consumption of vehicles, such as the "80 mpg Super Car Concept" in the U.S. It is required to adapt a completely new system, not just make a simple modification to the current system, to realize a dramatic improvement in fuel economy. It is recognized that one promising field is hybrid systems.

Both series and parallel hybrid systems are well known. This paper discusses a new hybrid system based on the "split" system which splits energy from the engine using a planetary gear [1] [2] [3], the new system being called the Dual System.

COMPARISON OF VARIOUS HYBRID SYSTEMS

Not only used as a range extender of electric vehicles, the hybrid system, employing both an engine and an electric motor, can improve fuel economy using the engine through

its combination with the motor [4]. The hybrid system can improve fuel economy in light of the following:

1. Operation of the engine in optimum efficiency range
2. Transmission efficiency between the engine and the driving wheels is improved
3. Regeneration of deceleration energy


Figure 1 shows the four different hybrid systems.

(A) **SERIES SYSTEM** - This system supplements electricity generated by the engine. It is most commonly used as a range extender for electric vehicles. Since the engine is not mechanically connected to the drive wheels, this system has an advantage of controlling the engine independently of the driving conditions. Accordingly, the engine is used in its optimum efficiency and low emission range. This system is particularly suited to engines which are hard to mechanically connect to the drive wheels such as gas turbine engines.

Disadvantages, however, include large energy conversion losses because of the necessity of full electricity conversion of the engine output. Further, a generator large enough to convert the maximum engine output is required.

(B) **PARALLEL SYSTEM** - With the parallel system, an electric motor which supplements the engine torque, is added to the conventional driveline system of the engine and transmission. Accordingly, operations of the engine are quite similar to those of an engine in a normal vehicle. This system requires no generator, and there is a direct mechanical connection between the engine and the drive wheels, providing an advantage of less energy being lost through conversion to electricity.

On the other hand, this system requires a transmission because no speed adjustment mechanism is installed, though the motor supplements the torque. When an automatic transmission is used, a torque converter, oil pump, and other auxiliary components can reduce the transmission efficiency. Although the engine torque can be controlled by the motor, the engine speed is determined by gear ratios like a



— Mechanical Connection
 - - - - - Electrical Connection
 EG: Engine G: Generator M: Motor B: Battery
 TM: Transmission C: Clutch PG: Planetary Gear

Figure 1: Four Different Hybrid Systems

conventional vehicle. Accordingly, the engine operation is linked to the driving conditions.

(C) SERIES-PARALLEL COMBINED SYSTEM - This combined type, having a generator and a motor, features characteristics of both the series and parallel systems, and the following two systems are possible:

(C-1) SWITCHING SYSTEM - Application and release of the clutch switches between the series and parallel systems. For driving as by the series system, the clutch is released, separating the engine and the generator from the driving wheels. For driving with the parallel system, the clutch is engaged, connecting the engine with the driving wheels.

For example, since city driving requires low loads for driving and low emissions, the series system is selected with the clutch released. For high speed driving where the series system would not work efficiently due to higher drive loads and consequently higher engine output is required, the parallel system is selected with the clutch applied.

(C-2) SPLIT SYSTEM - This system acts as the series and parallel systems at all times. The engine output energy is split by the planetary gear into the series path (from the engine to the generator) and the parallel path (from the engine to the driving wheels). It can control the engine speed under variable control of the series path by the generator while maintaining the mechanical connection of the engine and the driving wheels through the parallel path.

Correlation between the vehicle speed V and the engine speed NE is shown in Figure 2. When the engine is operating at a relatively constant torque in an optimum efficiency range, the energy from the engine is almost proportional to the engine speed NE . Accordingly, Figure 2 also indicates correlation between the vehicle speed and the engine output energy. In Figure 2, the engine speed NE is

$$NE = NEP + NES$$

where NEP is the engine speed by the parallel path and NES the engine speed by the series path. As the parallel path engine speed NEP increases in proportion to the vehicle speed, the output energy from the engine increases as the vehicle speed becomes higher. The higher the speed, the more energy is required for driving, it being appropriate that the parallel path energy becomes larger for higher speeds. For high speed




Figure 2: Engine Speeds in Split Hybrid System

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.