UNITED STATES PATENT AND TRADEMARK OFFICE

BEFORE THE PATENT TRIAL AND APPEAL BOARD

LAM RESEARCH CORP., Petitioner,

v.

DANIEL L. FLAMM, Patent Owner.

Case IPR2016-00466 Patent 5,711,849

Before DONNA M. PRAISS, CHRISTOPHER L. CRUMBLEY, and JO-ANNE M. KOKOSKI, *Administrative Patent Judges*.

KOKOSKI, Administrative Patent Judge.

DOCKET

DECISION Denying Institution of *Inter Partes* Review 37 C.F.R. § 42.108

I. INTRODUCTION

Lam Research Corp. ("Petitioner") filed a Petition ("Pet.") to institute an *inter partes* review of claims 1–29 of U.S. Patent No. 5,711,849 ("the '849 patent," Ex. 1001). Paper 1. Daniel L. Flamm ("Patent Owner") filed a Preliminary Response ("Prelim. Resp."). Paper 5. We have jurisdiction under 35 U.S.C. § 314.

Upon consideration of the Petition, Preliminary Response, and the evidence of record, we determine that Petitioner has not established a reasonable likelihood of prevailing with respect to any of the challenged claims of the '849 patent. Accordingly, we deny the Petition and do not institute an *inter partes* review.

A. Related Proceedings

The parties identify two proceedings in which the '849 patent is being asserted: (1) *Lam Research Corp. v. Daniel L. Flamm*, Case 5:15-cv-01277-BLF (N.D. Cal.), and (2) *Daniel L. Flamm v. Samsung Electronics Co., Ltd.*, Case No. 1:15-cv-00613-LY (W.D. Tex.). Pet. 3; Paper 4, 1.

B. The '849 Patent

The '849 patent, titled "Process Optimization in Gas Phase Dry Etching," is directed to "a plasma etching method that includes determining a reaction rate coefficient based upon etch profile data." Ex. 1001, 1:51–53. The method "includes steps of providing a plasma etching apparatus having a substrate therein[,]" where the substrate has a film overlaying the top surface, and the film has a top film surface. *Id.* at 1:59–63. It "also includes chemically etching the top film surface to define an etching profile on the film, and defining etch rate data which includes an etch rate and a spatial coordinate from an etching profile." *Id.* at 1:63–67. Steps of extracting a

2

reaction rate constant from the etch rate data, and using the reaction rate constant to adjust the plasma etching apparatus are also described. *Id.* at 1:67–2:2. According to the '849 patent, the method "provides for an easy and cost effective way to select appropriate etching parameters such as reactor dimensions, temperature, pressure, radio frequency (rf) power, flow rate and the like by way of the etch profile data." *Id.* at 1:53–57.

Figure 1A of the '849 patent is reproduced below:



Figure 1A is an example of an etched substrate. *Id.* at 3:66–67. Substrate 21 includes bottom surface 23, sides 25, and top surface film 27, and is defined in spatial coordinates z and r. *Id.* at 3:67–4:2. "[T]op surface film [27] includes a convex region, or etching profile." *Id.* at 4:3–4. "The etching profile occurs by way of different etch rates along the r-direction of [substrate 21], corresponding to different etchant species concentrations." *Id.* at 4:4–6. Concentration profile $n_o(r,z)$ shows that "the greatest concentration of reactant species exists at the outer periphery of [] top surface film [27]." *Id.* at 4:6–9.

The '849 patent describes an embodiment of a method of extracting an etch rate constant in which a substrate with an overlying film is placed into a plasma etching apparatus, and the plasma etching step occurs at

3

constant pressure, and, preferably, isothermally. *Id.* at 5:11–19. Plasma etching of the film stops before etching into an etch stop layer underneath the overlying film "in order to define a 'clean' etching profile." *Id.* at 5:24–26. The plasma etching step produces an etching profile, which "converts into a relative etch rate, relative concentration ratio, a relative etch depth and the like at selected spatial coordinates." *Id.* at 5:28–32.

Using x-y-z coordinates, the relative etch rate is in the z-direction, and x-y are the spatial coordinates. *Id.* at 5:38–40. "The etching profile is thereby characterized as a relative etch rate u, [an] x-location, and a y-location u, (x, y)," and an array of data points in the x-y coordinates define the etching profile. *Id.* at 5:40–41, 45–47. An etch constant over diffusivity (k_{vo} /D) and an etch rate at the substrate edge is then calculated, where "[t]he etch constant over diffusivity correlates with data points representing the etch rate profile." *Id.* at 5:62–65. After the etch rate constant k_{vo} is extracted, the surface reaction rate constant k_s can be determined using the formula $k_s = (k_{vo})d_{gap}$, where d_{gap} is the space above the substrate, between the substrate and the adjacent substrate. *Id.* at 3:35–36, 6:58–62, 9:27–29, Fig 7.

C. Illustrative Claim

Petitioner challenges claims 1–29 of the '849 patent. Claims 1, 10, 20, 22, and 26 are independent. Claim 1 is illustrative, and reads as follows:

providing a plasma etching apparatus comprising a substrate therein, said substrate comprising a top surface and a film overlying said top surface, said film comprising a top film surface;

^{1.} A device fabrication method comprising the steps of:

- etching said top film surface to define a relatively non-uniform etching profile on said film, and defining etch rate data comprising an etch rate and a spatial coordinate which defines a position within said relatively non-uniform etching profile on said substrate, said etching comprising a reaction between a gas phase etchant and said film; and
- extracting a surface reaction rate constant from said etch rate data, and using said surface reaction rate constant in the fabrication of a device.
- Ex. 1001, 17:35–50.
- D. The Prior Art

Reference	Description	Date	Exhibit No.
Sawin	US 5,450,205	Sept. 12, 1995	1004
Galewski	Modeling of a High Throughput Hot-Wall Reactor for Selective Epitaxial Growth of Silicon, IEEE Transaction on Semiconductor Manufacturing, Vol. 5, No. 3 (1992) 169–179	Aug. 1992	1003
Battey	The Effects of Geometry on Diffusion-Controlled Chemical Reaction Rates in a Plasma, J. Electrochem. Soc.: Solid-State Science and Technology, Vol. 124, No. 3 (1977) 437–441	March 1977	1002

Petitioner relies on the following prior art references:

E. The Asserted Grounds of Unpatentability

Petitioner challenges the patentability of claims 1–29 of

the '849 patent on the following grounds:

DOCKET



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

