

TITLE

AUTOMATIC DIRECTIONAL CONTROL
SYSTEM FOR VEHICLE HEADLIGHTS

5

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of United States Provisional Application Nos. 60/335,409, filed October 31, 2001; 60/356,703, filed February 13, 2002; and 60/369,447, filed April 2, 2002, the disclosures of which are incorporated herein by
10 reference.

BACKGROUND OF THE INVENTION

This invention relates in general to headlights that are provided on vehicles for illuminating dark road surfaces or other areas in the path of movement. In particular,
15 this invention relates to an automatic directional control system for such vehicle headlights.

Virtually all land vehicles, and many other types of vehicles (such as boats and airplanes, for example), are provided with one or more headlights that are adapted to illuminate a portion of a dark road surface or other area in the path of movement of the
20 vehicle to facilitate safe travel thereon. Typically, each headlight is mounted on or near the front end of the vehicle and is oriented in such a manner that a beam of light is projected forwardly therefrom. The angle at which the beam of light projects from the headlight can, for example, be characterized in a variety of ways, including (1) up and down relative to a horizontal reference position or plane and (2) left and right
25 relative to a vertical reference position or plane. Such directional aiming angles are usually set at the time of assembly of the headlight into the vehicle so as to illuminate a predetermined portion of the road surface or other area in the path of movement of the vehicle.

In the past, these headlights have been mounted on the vehicle in fixed
30 positions relative thereto such that the beams of light are projected therefrom at

of suspension height of the vehicle. A controller is responsive to the sensor signal for generating an output signal. An actuator is adapted to be connected to the headlight to effect movement thereof in accordance with the output signal. The controller can include a table that relates values of sensed operating condition to values of the output signal. The controller is responsive to the sensor signal for looking up the output signal in the table.

Various objects and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the preferred embodiments, when read in light of the accompanying drawings.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of an automatic directional control system for a vehicle headlight in accordance with this invention.

Fig. 2 is a flow chart of an algorithm for calibrating the automatic directional control system illustrated in Fig. 1 so as to define an initial reference position for the headlight from which the headlight directional controller can implement directional angle adjustments.

Fig. 3 is a flow chart of an algorithm for generating a table that relates one or more sensed vehicle operating condition values to one or more headlight directional angle adjustment factors and for storing such table in the headlight directional controller illustrated in Fig. 1.

Fig. 4 is an example of a table that can be generated and stored in the headlight directional controller in accordance with the table generating algorithm illustrated in Fig. 3.

Fig. 5 is a flow chart of an algorithm for operating the headlight directional controller illustrated in Fig. 1 to automatically implement directional angle adjustments in accordance with sensed condition values.

Fig. 6 is a flow chart of an algorithm for operating the headlight directional controller illustrated in Fig. 1 to automatically implement directional angle

adjustments in accordance with the rate of change of one or more of the sensed condition values.

Fig. 7 is a flow chart of an algorithm for operating the headlight directional controller illustrated in Fig. 1 to automatically implement directional angle adjustments, but only when the rate of change of one or more of the sensed condition values is less than (or greater than) a predetermined value.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, there is illustrated in Fig. 1 an automatic directional control system, indicated generally at 10, for a vehicle headlight 11 in accordance with this invention. The illustrated headlight 11 is, of itself, conventional in the art and is intended to be representative of any device that can be supported on any type of vehicle for the purpose of illuminating any area, such as an area in the path of movement of the vehicle. The headlight 11 is typically mounted on or near the front end of a vehicle (not shown) and is oriented in such a manner that a beam of light is projected therefrom. In a manner that is well known in the art, the headlight 11 is adapted to illuminate a portion of a dark road surface or other area in the path of movement of the vehicle to facilitate safe travel thereon.

The headlight 11 is adjustably mounted on the vehicle such that the directional orientation at which the beam of light projects therefrom can be adjusted relative to the vehicle. Any desired mounting structure can be provided to accomplish this.

Typically, the headlight 11 is mounted on the vehicle such that the angle at which the beam of light projects therefrom can be adjusted both (1) up and down relative to a horizontal reference position or plane and (2) left and right relative to a vertical reference position or plane. Although this invention will be described and illustrated in the context of a headlight that is adjustable in both the up/down direction and the left/right direction, it will be appreciated that this invention may be practiced with any headlight 11 that is adjustable in any single direction or multiple directions of movement, whether up/down, left/right, or any other direction.

To effect movement of the illustrated headlight 11 relative to the vehicle, an up/down actuator 12 and a left/right actuator 13 are provided. The actuators 12 and 13 are conventional in the art and may, for example, be embodied as servo motors, step motors, or any other electronically controlled mechanical actuators. It has been found to be desirable to use microstepping motors for the actuators 12 and 13. Such microstepping motors are known in the art and consist of conventional step motors that have appropriate hardware (i.e., driver integrated circuits) and software that allow the step motors to be operated in fractional step increments. The use of such microstepping motors has been found to be desirable because they can effect movements of the headlights in a somewhat faster, smoother, and quieter manner than conventional step motors, and further permit more precise positioning of the headlights 11. In the illustrated embodiment, the up/down actuator 12 is mechanically connected to the headlight 11 such that the headlight 11 can be selectively adjusted up and down relative to a horizontal reference position or plane. Similarly, the illustrated left/right actuator 13 is mechanically connected to the headlight 11 such that the headlight 11 can be selectively adjusted left and right relative to a vertical reference position or plane.

A headlight directional controller 14 is provided for controlling the operations of the up/down actuator 12 and the left/right actuator 13 and, therefore, the angle at which the beam of light projects from the headlight 11 relative to the vehicle. The headlight directional controller 14 can be embodied as any control system, such as a microprocessor or programmable electronic controller, that is responsive to one or more sensed operating conditions of the vehicle for selectively operating the up/down actuator 12 and the left/right actuator 13. To accomplish this, the automatic directional control system 10 can include, for example, a pair of condition sensors 15 and 16 that are connected to the headlight directional controller 14. The condition sensors 15 and 16 are conventional in the art and are responsive to respective sensed operating conditions of the vehicle for generating electrical signals to the headlight directional controller 14. However, if desired, only a single one of the condition sensors 15 and 16 need be provided. Alternatively, additional condition sensors (not

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.