



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C08J 3/00, 3/03, 3/12, 5/18	A1	(11) International Publication Number: WO 00/02955 (43) International Publication Date: 20 January 2000 (20.01.00)
<p>(21) International Application Number: PCT/US99/15396</p> <p>(22) International Filing Date: 8 July 1999 (08.07.99)</p> <p>(30) Priority Data: 09/113,778 10 July 1998 (10.07.98) US</p> <p>(71) Applicant: KIMBERLY-CLARK WORLDWIDE, INC. [US/US]; 401 North Lake Street, Neenah, WI 54956 (US).</p> <p>(72) Inventors: WANG, James, H.; 1325 East Overland Road, Appleton, WI 54915 (US). TOPOLKARAEV, Vasily; 1730 South Lee Street, Appleton, WI 54915 (US).</p> <p>(74) Agents: PRIOR, Kimberly, J.; Jones & Askew, LLP, 2400 Monarch Tower, 3424 Peachtree Road, Atlanta, GA 30326 (US) et al.</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
<p>(54) Title: WATER SOLUBLE POLYETHYLENE OXIDE FILMS</p> <p>(57) Abstract</p> <p>The invention relates to blends of a polyethylene oxide (PEO) resin and a latex emulsion. The blends are formed by mixing or coating a PEO powder resin with a latex emulsion and melt blending the powder. The blends have improved processibility and toughness which are beneficial in the manufacture of PEO-based films and fibers. The films composed of the PEO/latex blend have improved toughness, breathability, and tear resistance and are useful for the manufacture of disposable, flushable medical and personal care products, such as diapers, tampons, feminine napkins, and bladder control pads.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

WATER SOLUBLE POLYETHYLENE OXIDE FILMS

10

FIELD OF THE INVENTION

15

The present invention relates generally to polymeric films, processes for their manufacture, and their use in flushable medical and personal care products. More specifically, the invention relates to the modification and processing of polyethylene oxide (PEO) resins to make films for the production of such flushable products which have the advantages of improved toughness, softness, and tear resistance.

BACKGROUND OF THE INVENTION

20

25

Disposable personal care products, such as panti-liners, diapers, and tampons, are a great convenience, as are disposable medical care products, such as drapes, gowns, head coverings, and face masks. These products provide the benefit and convenience of one time, sanitary use. However, disposal of many of these products is a concern due to limited landfill space. Incineration of such products is not desirable because of increasing concerns about air quality and because of the costs and difficulty associated with separating these products from other disposed articles that cannot be incinerated. Consequently, there is a need for disposable products which may be quickly and conveniently disposed of without dumping or incineration.

30

35

It has been proposed to dispose of such products in municipal and private sewage systems. Ideally, the products would be degradable in conventional sewage systems. Products suited for disposal in sewage systems which can be flushed down conventional toilets and are dispersed or disintegrated in water are termed "flushable." Disposal in this manner is simple, convenient, and sanitary.

Personal care and medical care products must have sufficient strength to maintain integrity under the environmental conditions in which they will be used. They must also be able to withstand the elevated

temperature and humidity conditions encountered during use and storage and still lose integrity upon contact with water in the toilet. Therefore, a water-disintegrable material which is capable of thermal processing into a thin film having mechanical integrity is desirable.


5 Currently, thin films are typically made from water-insoluble polymers or polymer blends. Frequently used polymers include amorphous polymers, epoxy resins, and semicrystalline polymers. Examples of amorphous polymers are polystyrene (PS), styrene-acrylonitrile copolymers, polycarbonate, and poly(vinyl chloride) (PVC).
10 Examples of semicrystalline polymers are polyethylene (PE), polyamide (PA), polybutadiene (PB), and polypropylene (PP). The most commonly used polymers are polypropylene, and polyethylene.

 The thin films composed of these polymers are formed by extrusion casting or melt blowing processes. Conventional film extrusion
15 involves mixing commercially available pellets of the desired polymers at increased temperatures, followed by extruding the mixture in a single screw extruder through a slit die to form a film. The film is then cooled by passing it through a series of chilled rolls. Films made in this manner from such water-insoluble polymers are unsuitable for use in "flushable"
20 personal care and medical care products because they do not possess the desired characteristics, e.g., they will not degrade in conventional sewage systems and consequently form blockage in the sewer lines.

 Polyethylene oxide (hereinafter PEO) is a hydrophilic, water-soluble polymer,



that is produced from the ring opening polymerization of ethylene oxide,



30 It is available in widely varying molecular weights in the form of a powder from a number of sources, for example, Union Carbide Corp. (Danbury, CT) PEO is currently used as a flocculant to enhance the deposition of colloidal particles onto wood pulp fiber in the paper-making process. It is
35 also used as an additive to modify such properties as the aggregation state, sedimentation behavior, and rheology of polymers employed as paints and

adhesives. PEO is also used to modify and stabilize polymer lattices, for example, by grafting PEO chains to a polystyrene lattice.

5 Due to its unique interaction with water and body fluids, the present inventors are considering it as a component material for flushable and personal care products. However, currently available PEO resins are not practical for the formation of thin films by melt extrusion or for personal care product applications for a number of reasons.

10 For example, while low molecular weight PEO resins have desirable melt viscosity and melt pressure properties for extrusion processing, they have low melt strength and low melt elasticity which limit their ability to be drawn into films having a thickness of less than about 2 mil. Films produced from low molecular weight PEO also have low tensile strength, low ductility, and are too brittle for commercial use.

15 High molecular weight PEO resins, on the other hand, should produce films having improved mechanical properties compared to those produced from low molecular weight PEO. High molecular weight PEO, however, has poor processibility and poor melt drawability due to its high melt viscosity. Melt pressure and melt temperature must be significantly elevated during melt extrusion of high molecular weight PEO, resulting in PEO degradation and severe melt fracture. Therefore, only very thick
20 films of about 7 mil or greater in thickness can be made from high molecular weight PEO. Films this thick are not practical for flushable applications.

25 Attempts to melt extrude PEO often result in severe degradation of the PEO. Even when a film can be formed, the PEO undergoes morphological changes such as crystallization and aging, when it is cooled from the melt and exposed to the ambient environment. These changes affect the mechanical properties of the film, resulting in a film that is weak and brittle, having very low elongation-at-break and tear
30 resistance, and, thus, not suitable for the production of personal care products. What is needed in the art, therefore, is a means to overcome the difficulties in melt processing of PEO resins and to improve the resultant ductility and toughness of the thin films formed therefrom.

35 It is known in the art to modify water-insoluble polymer resins, such as polystyrene and polypropylene, by incorporating soft rubber particles into the polymeric structure to improve the toughness of the polymer, to reduce its modulus, and to improve the softness and flexibility of the resulting material. The modifier can be a rubber-like elastomer, a core-shell modifier, or another polymer, such as styrene

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.