Internet Engineering Task Force Internet Draft William Bressler NORTEL Networks

Expires in Six Months

January 1999

SS7 Level Two over IP <draft-bressler-sigtran-ipss712-00.txt>

Status of this Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a "working draft" or "work in progress".

To learn the current status of any Internet-Draft, please check the lid-abstracts.txt listing contained in the Internet-Drafts Shadow Directories on ds.internic.net, nic.nordu.net, ftp.isi.edu, or munnari.oz.au.

1 Abstract

This document proposes the use of TCP/IP as the transport protocol for common channel signaling, Signaling System #7 (SS7).

The migration from the current 56k/64k physical layer to an IP based transport will reduce the cost associated with dedicated trunk based link. Also, the current signaling point (SP) network using quasi-associated architecture will be maintained to make the transition as seamless as possible.

2 Scope

This draft defines the encapsulation of SS7 signal units (SU) in a TCP packet. The concept of a physical link will be maintained, which will emulate the current SS7 links and link control mechanisms.

2.1 Quasi-associated Network Architecture

The scope of network architecture in this recommendation is limited to

L A R M Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

itself as a cost effective, reliable alternative. Using the current quasi-associated SS7 networks also decreases the number of hops between SP's and the number of endpoints to a minimum. Each SP would have two IP addresss (two IPlinks) in addition to its current point code(s).

Bressler

DOCKET A L A R M Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

2.2 IP Signaling Link (IPlink)

The scope of IP signaling link, IPlink, in this Recommendation includes the following:

- A link will be identified by an IP address
- The link alignment procedure.
- The emergency link alignment procedure.
- The link Basic Error Rate (BER) monitor.
- The link Alignment Error Rate (AER) monitor.
- Either software or hardware shall calculate SU CRC-16 checksums.
- Preventative Cyclic Retransmission (PCR) shall be the default
- forward error correction.
- Signaling message handling.
- MSU load sharing.

3 Quasi-associated Network

A quasi-associated network between a signaling service point (SSP) and a signaling transfer point (STP) is shown below. Currently, SS7 messaging traverse from SSP through the STP to another SSP using T1 trunking, which is very reliable, and is configured for redundancy (not shown). If the IP network is to be a viable alternative to T1 trunking, it must be able to demonstrate at least equal reliability and alternate routing capabilty.





3.1 Network Nodes

Current network topology should be unchanged. SSP, STP, signaling control point (SCP), authentication centers (AC), customer service centers (CSC), home location register (HLR), visiting location register (VLR), etc., will all be accessible.

3.2 Signaling Link

DOCKE

Each link will have it's own IP address and processor. This will maintain the current link concepts intact for reliability, redundency, alignment, changeover/changeback, load sharing, etc.

IPlinks should have the same behaviour as the current SS7 links to gain acceptance into the existing network architecture. SS7 <-> IP-SS7 interworking should be as transparent as possible.

Bressler

DOCKET A L A R M Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

4 TCP encapsulation

The current SS7 protocol is to be used as is. It provides a high reliability transport for telephony information. TCP packets will be used to carry the current SS7 messaging. This greatly reduces the risk of IP-SS7 by eliminating the need for new protocols. Telephony vendors already offer IP connectivity on their STP products. The largest MSU allowed, 272 octets, easily fits in a TCP packet.

тср	Header	SS7	SU

5 SS7 CRC-16 Checksum

The reliability of the SS7 network is due in large part to the use of a CRC-16 checksum, calculated by hardware. This same reliability must be used in IPlink. Currently, existing hardware will most likely not support the encapsulation of the SS7 packet after the checksum has been calculated. The CRC-16, while cumbersome, will have to be performed in software. This can be speeded up greatly by the use of table driven calculations.

6 L2 Timers

Since the CRC-16 is computed in software, the L2 timers for IPlink have been extended.

т1	(aligned/ready)	20	Sec
т2	(not aligned)	30	Sec
т3	(aligned)	20	Sec
т4	(Pn)	5	Sec
т4	(Pe)	2	Sec
т5	(SIB)	500	ms
т6	(remote congestion)	6	Sec
т7	(ACK delay)	2	Sec

7 FISU Transmitting

DOCKET

Currently, SS7 links will send fill-in SUs (FISU) continuously, separated only by an HDLC flag (value 7E hex). To reduce processing overhead in IPlink, FISU's will be transmitted under the following conditions:

- A FISU will be transmitted every 20 ms (Tfs) while the links are aligned.
- A FISU may be sent at any time to ACK/NACK MSU's.

The FISU transmit timer is reset to Tfs after the transmission of any SU (FISU, LSSU, MSU).

DOCKET



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

