

NOVEMBER 1981 Founded in 1872/Vol. 219, No.5



HIGHLIGHTS

THIS ISSUE

New personal computers—now the big guns have arrived

IBM, Xerox, and others may at last detonate the small-computer explosion. PAGE 93

Missile killers . . . top-secret race to develop beam weapons Laser or particle-beam guns in orbit could blast targets 7,000 miles away. PAGE 75

New age for airships? Workhorse copter-blimps

Hell-Stat, to be used for heavy lifting, may bring dirigibles out of limbo. PAGE 72

Faster than bullets or rockets: electromagnetic launchers

No longer a dream, space-age slings can fire objects at five times rifle speed. PAGE 78

All-out energy audits-how the pros spot heat leaks

House doctors measure all kinds of heat losses and recommend cures. PAGE 50

COVER PHOTO BY JOHN KEATING

40-mpg diesel for GM's mid-size cars	
	4
Mercedes' steering-wheel air bag . PS car test: three little wagons	2
for small families	3
Toyota restyles sporty coupes	4
Beechcraft's LNG car	45
Turbo cycle uses computer- controlled fuel injection	60
Success at last for 40-year-old	
stratified-charge engine?	82
Transmission shifts like an	
automatic, but saves fuel	92
NEW PROPERTY AND INVESTIGATION	
NEW PRODUCTS AND INVENTIONS	10
Double duty from a dual cassette.	
Double duty from a dual cassette . Light-sensing thermostat	25
Double duty from a dual cassette . Light-sensing thermostat Guide rail steers bus	
Double duty from a dual cassette . Light-sensing thermostat	29
Double duty from a dual cassette . Light-sensing thermostat Guide rail steers bus Down-to-earth moon boots	29
Double duty from a dual cassette . Light-sensing thermostat Guide rail stears bus . Down-to-earth moon boots NEW TECHNOLOGY Nuclear magnetic resonance New age for airships?	25 30 45
Double duty from a dual cassette . Light-sensing thermostat Guide rail stears bus	25 30 45 46

ENERGY NEWS	PS SPECIAL
Energy roof for sunless climes 12	HOME-ELECTRONICS SECTION
Insulating core for concrete walls . 14	New personal computers— now the big guns have arrived 93
All-out energy audits -how the pros spot heat leaks 50	For the '80's: a decade
Wind farm's first sprout 111	of wonder in home electronics 98
Insulating wall coverings-energy	Build a home computer center 100
savings with a decorator look 118	More channels, plummeting prices for new satellite-TV antennas 102
HOME AND YARD	The coming record revolution: digital discs
Leisure home: solarium kitchen 112 HIY concrete systems 123	New software makes your personal computer a workhorse 107
Announcing the sixth annual PS/APA Plywood Project Contest . 132	High-resolution TV-wide-screen, crystal-clear pictures 108
TOOLS AND TECHNIQUES	
Table-saw alignment 114	REGULAR FEATURES
Bench-saw lathe turning 122	PS readers talk back
Router case stores bits, too 124	Alternate-energy answers 10
	Detroit report 16
WhataNew DIGEST	Science newsfront
Rugged bus 84	Calcu-letter
NASA remotely piloted vehicle 85	"Say, Smokey-"
Passive prefab	Recreation roundup 68
What's new in photography 87	PS/What's news
What's new in tools	Wordless workshop 121
What's new in home improvement 89	Shop talk
What's new in electronics 90	Taking care of your car 130
What's new for your car 91	PS readers' product information 163

EDITORIAL OFFICES 380 Medison Avenue, New York, N.Y. 10017 Published monthly by TIMES MIRROR MAGAZINES, INC., 380 Medison Avenue, New York, N.Y. 10017

SUBSCRIPTION SERVICE. (Only mail regarding subscriptions should be sent to Boulder, Colo., address below.) New or renewal orders: Send to Popular Science Subscription Department, Boulder, Colo. 80302. In U.S. and its possessions, one year \$13.94, two years \$24.97, three years \$34.97; in Canada and elsewhere, one year \$17.94, two years \$32.97, three years, \$46.97. Subscription orders processed electronically. For all subscription adjustments, write to Robert Hartan. Popular Science, P.O. Box 2871, Boulder, Colo. 80302. For change of address allow eight weeks; please give both old and new addresses. Postmatter: Please send notices of undelivered copies (Form 3579) to Mr. Hartan. Controlled-circulation post-

age paid at New York, N. Y., and additional mailing offices, publication number 483730. Popular Science is entered as second-class matter at the P.O. Dept., Canada. Microfilm editions are available from University Microfilms, Ann Arbor, Mich. 48106. ADVERTISING OFFICES. New York: 380 Madison Ave. (19017), Tel. 212-887-3900; Chicago: 875 N. Michigan Ave. (69611), Tel. 312-337-7717; Detroit: 19075 W. 10 Mile Rd., Southfield, Mich. (48075), Tel. 313-356-333; Los Angelles Pacific West Coast): 3550 Wilshire Blvd., Sulta 908 (90005), Tel. 213-380-1936. Mechanics and Handwart & Popular Science & Copyright © 1981 by Times Mirror Magazines, Inc. All rights reserved. Printed in U.S.A.

NOVEMBER 1981 1 1 material



PS SPECIAL HOME FLECTRONICS

Highresolution TV

 here come wide-screen crystal-clear pictures

New video components speed TV systems that match 35-mm-film fidelity

By JOHN FREE

WASHINGTON, D.C.

For several days, groups of government officials, politicians, and journalists crowded into a darkened room at CBS's offices here. We'd come to view a rare, one-time collection of video gear. "What we are going to show you," CBS's Joseph Flaherty, vice-president of engineering development, told my group, "is a combination of high-resolution TV, stereo sound, wide-screen TV, and enhanced-color TV."

During the next hour I watched a variety of amazing TV images that had extraordinary clarity—more than five times the detail of television pictures you see on conventional home receivers. The high-resolution pictures, a dazzling match for sharpfocus 35-mm slides, were shown on special "Cinerama-type" direct-view sets and a large-screen projection TV. Other equipment used by CBS, such as microelectronic encoding circuits and a Sony-built digital video recorder, may have a key role—in improved forms—in delivering this new type of TV to you during the 1980's.

Actually, so-called high-definition TV (HDTV) has been available for closed-circuit use in medical schools and business applications for a few years. But it has been limited to live transmissions using only cameras and TV monitors. Recently, professional videotape machines capable of recording HDTV were unveiled. As a result, Hollywood directors may soon put

high-resolution TV to work in producing movies, and broadcast networks will use it to enhance the quality of

standard programing.

CBS has still another reason for promoting HDTV. It and other broadcasters require transmission channels to get these super-fidelity pictures into your home. For reasons detailed below, high-resolution TV can't be carried easily on regular TV channels—and no one plans to disrupt today's standard TV programing based on the 525-line NTSC (National Television Standards Committee) format.

Standards Committee format.

But HDTV can be transmitted into homes by direct-broadcast satellite.

CBS is telling officials that it's vital to reserve HDTV frequencies on a new class of satellites slated for launch within a few years.

More pixels, better picture

How does HDTV differ technically from standard TV? Standard NTSC sets, functioning perfectly, can display 483 (not 525) horizontal scan lines created as electron beams paint TV pictures by sweeping back and forth over picture-tube phosphors. Each horizontal scan line can resolve, or display, 436 separate picture elements, called pixels—an NTSC picture can display 210,588 pixels.

In practice, new sets equipped with so-called comb filters IPS, Aug. 781 show only about 330 horizontal elements; most older sets average only about 250 picture elements per sean line. By contrast, although no firm standards have been set, a 1,125-line HDTV picture might contain not twice but some five times as many pixels ione million) compared with an ideal NTSC image. Each one of the high-resolution scanning lines carries more image detail, and each is longer

because of the wide-screen picture format. As a result, high-resolution TV requires more frequency space, or handwidth—typically, 30 MHz versus 4.2 MHz for standard NTSC TV.

"The NTSC system has given us very good service during the last 25 to 30 years," said Flaherty, "but we are pressing it to its maximum as pictures get larger and larger." A demonstration made this very apparent. Two cameras were set up in an adjacent room overlooking a street. One was a state-of-the-art CBS camera to display standard 525-line TV pictures. The other was a 1,125-line model made for Japan's public broadcasting corporation (NHK).

The 525-line camera piped its pictures to a Kloss projection TV before us with a six-foot-disgonal screen (and to regular TV studio monitors). The NHK HDTV camera sent its pictures to a Matsushita-built wide-format projection TV and wide-format monitors (see color pictures).

Pictures of a bowl of fruit were impressive on the 525-line Kloss and smaller monitors. But contrasted with the crystal-clear images on the HDTV sets, the limitations of NTSC pictures were dramatic. Training both cameras on the street below produced even sharper contrasts. I could read license plates and other vehicle lettering on HDTV sets that were a hopeless blur on 525-line receivers.

Why do today's sets have a squarish picture ratio four units wide and three high? "It was chosen for very simple reasons," said Flaherty, "First, it was all we could do [technologically], and it was the way films were made," he said, describing the 1940's monochrome-TV format.

An HDTV system unveiled by Sony

108 POPULAR SCIENCE

PMC3685199







Details from images on TV monitor screens contrast the Sony 1,125-line picture (above left) with a standard 525-line view.





Wide-screen high-resolution monitor developed by NHK and Matsushita has 30-inch-diagonal screen, 5:3 aspect ratio, Phosphor dots are much smaller than on conventional shadow mask tubes, and NHK uses a digital beam-convergence system.

Projection TV displayed by Matsushita at technology exhibit in Chicago this summer uses red, green, and blue projection tubes like conventional models, but displays high-definition 1,125-line images from TV camera. Screen is 55 inches diagonally.

NOVEMBER 1861 109

PMC3685200



last spring can show pictures in standard 4.3 format, the extra-wide Cinemascope format, or an intermediate picture width. The high-resolution sets at the CBS demonstration had a 5 picture-aspect ratio. In addition to letting you see most or all of the picture from wide-screen movies, sitting close to sharp, wide-screen HDTV images conveys more of the visual impact of a theater screen.

Digital demonstration

Warming up in another CBS office was a special type of videotape recorder completed by Sony just six weeks earlier. Bill Connolly, managing director of development for the CBS-TV network, prefaced another impressive demonstration: "Engineers today are generally agreed that digital techniques are the proper way to record this HDTV information and transmit it," he said [PS, March '78].

Connolly explained that with conventional TV, voltage is proportional to brightness. The brighter the scene at any given point on the screen, the higher the voltage. Since the voltage is analogous to what's on the screen, it's called an analog system.

"The digital system does something quite different," Connelly said. The voltage generated by the camera is constantly sampled or measured by digital circuits. Each of these samples is then assigned a binary number (zeros and ones) representing its intensity. This technique for each pixel on the scan lines requires considerably more bandwidth, or frequency spectrum, for storage and transmission. While this large-bandwidth requirement is a problem, major efforts are under way to shrink the frequency space needed for digital TV.

"One of the things we can do is reduce the number of bits [binary digits] necessary to describe a picture." Connolly said. He pointed to one of his "favorite symbols," a CBS eye glowing on monitors. Running his finger across one scan line on the eye, he explained that it carried about 150 black pixels, then 200 blue, and 150 black ones again.

"We waste a lot of [frequency] spectrum with analog TV because we transmit every one of those things using the whole bandwidth," Comolly said. With digital techniques, though, a single brief signal can be encoded that tells the digital circuits in the receiver to create 150 black pixels. This coding of the digital signal, requiring perhaps only a few dozen bits instead of hundreds of repetitive signals, cuts the rate at which bits must be transmitted—plus bandwidth requirements. Similar bit-rate-reduc-

tion coding can produce the 200 blue and 150 black pixels for an "eye" scan line.

John Rossi of the CBS Technology Center (Stamford, Conn.) demonstrated a CBS 4.1 bit-rate-reduction system with an analog videotape machine. An NTSC 525-line test pattern shown on monitors was created by a digitally coded signal that required only 28 megabits (million bits) per secord instead of the 144 megabits/sec. from the original digital sampling.

"This is a very simple bit-ratereduction technique," Rossi said. "The circuits can literally be held in the palm of your hand. This leads us to believe that with more-complex circuits much higher bit-rate reductions can be achieved."

can be achieved."
"Failing these bit-reduction schemes, HDTV will not be broadcastable," added Flaherty. He hopes to fit digitally compressed high-resolution TV into a normal or nearly normal TV channel. "Much work has yet to be done," he said, "but you can see we've achieved a 4:1 reduction in bits fairly well, transmitting a roughly equal-quality picture."

That test-pattern picture I saw had some noise but carried the fine detail indicating most of the image was getting through. For this demonstration, a normal 4.2-MHz, 525-line NTSC signal became a 114-megabit/sec. digital signal that was compressed into a 28-megabit/sec. signal. But that digital 525-line signal would require about four VHF channels on your TV set. An HDTV signal, even before it's digitally sampled, requires about five.

Pouring marbles

Why, if digital coding of a TV signal takes up so much more frequency spectrum, isn't high-resolution TV more feasible with analog signals? High-frequency noise is one reason. Noise, which can spoil standard TV images, devastates HDTV.

Connolly demonstrated another advantage of digital TV by first showing a 525-line analog-signal picture of a fruit bowl from tape. Then he showed the same picture after it had been rerecorded 10 times—a tenth-generation copy. The image was smeared, full of noise, and color values were shifted. For broadcasting, about five generations is the limit, he said.

But soenes that followed from tenthand even twentieth-generation digitally coded tapes seemed unaltered from the originals. Connolly compared analog taping to pouring water from one glass to others: Some water sticks to each glass; retaping, similarly, robs parts of the original signal with each generation. Digital signals, by contrast, are either the presence or absence of pulses on tape. They survive transmission and taping much better, and Connolly compared the digital technique to pouring marbles from glass to glass. The marbles (digital bits) get through unchanged.

CBS engineers were impressed with Sony's new digital recorder. "In just seven years there's been a 50:1 improvement in the ability to jam bits into a small area of tape," said Flaherty. "We went from under one million. We only need a 3:1 improvement over that to record [digital] HDTV."

CBS also presented an NTSC videotape made with stereo sound at a Kennedy Center concert. HDTV researchers believe stereo is needed to bring the realism of wide-screen movies and other programs into your home. During the demonstration of a Mozart operatic aria, repeated switching between stereo and monophonic modes made stereo's advantages obvious.

HDTV offers superior color, too. A future international high-resolution-TV standard will no doubt provide vivid hues that can't be obtained with NTSC color standards. Moreover, HDTV pictures can be transmitted with luminance (brightness) and color signals separated. Standard TV signals have combined these—disastrous for picture fidelity—to achieve compatibility between black-and-white and color receivers.

You may first encounter HDTV not on a TV receiver but displayed on a theater movie screen. Sony might lease its prototype HDTV gear within a year for Hollywood production work that would be converted to film. Videctaping offers advantages in economy and flexibility.

my and flexibility.

In a different application, CBS plans to use HDTV in about three years to enhance standard broadcasts. HDTV tapes would permit special production techniques, such as image enhancement and zooming without picture degradation, before conversion to regular NTSC recordings.

Also, cable TV and home videodiscs and tapes may bring HDTV to you in the 1980's. You would need a special receiver or player, but such sources could bypass the standards and regulatory problems of broadcast HDTV.

"The real question is whether this is going to be available to the general public or whether it will be something only for the videophile with the money to buy all these ancillaries," said Flaherty. Getting wide-band HDTV into broadcast channels, he said, "depends on the skill of the engineering community to make it fit."

116 POPULAR SCIENCE

PMC3685201

