



UNIX System Laboratories, Inc.  
A Subsidiary of AT&T

**UNIX<sup>®</sup> SYSTEM V  
RELEASE 4**  
*User's Guide*



Copyright 1990, 1989, 1988, 1987, 1986, 1985, 1984, 1983 AT&T  
All Rights Reserved  
Printed in USA

Published by Prentice-Hall, Inc.  
A Division of Simon & Schuster  
Englewood Cliffs, New Jersey 07632

No part of this publication may be reproduced or transmitted in any form or by any means—graphic, electronic, electrical, mechanical, or chemical, including photocopying, recording in any medium, taping, by any computer or information storage and retrieval systems, etc., without prior permissions in writing from AT&T.

#### IMPORTANT NOTE TO USERS

While every effort has been made to ensure the accuracy of all information in this document, AT&T assumes no liability to any party for any loss or damage caused by errors or omissions or by statements of any kind in this document, its updates, supplements, or special editions, whether such errors are omissions or statements resulting from negligence, accident, or any other cause. AT&T further assumes no liability arising out of the application or use of any product or system described herein; nor any liability for incidental or consequential damages arising from the use of this document. AT&T disclaims all warranties regarding the information contained herein, whether expressed, implied or statutory, *including implied warranties of merchantability or fitness for a particular purpose*. AT&T makes no representation that the interconnection of products in the manner described herein will not infringe on existing or future patent rights, nor do the descriptions contained herein imply the granting or license to make, use or sell equipment constructed in accordance with this description.

AT&T reserves the right to make changes without further notice to any products herein to improve reliability, function, or design.

#### TRADEMARKS

DOCUMENTER'S WORKBENCH is a registered trademark of UNIX System Laboratories, Inc.  
IBM is a registered trademark of International Business Machines.  
Teletype is a registered trademark of AT&T.  
UNIX is a registered trademark of UNIX System Laboratories, Inc.

10 9 8 7 6 5 4 3 2

ISBN 0-13-947052-2

**UNIX  
PRESS**  
A Prentice Hall Title



If the `-w` or `-c` option had been specified instead, the command would have reported the number of words or characters, respectively, in the file.

Figure 3-21 summarizes the syntax and capabilities of the `wc` command.

Figure 3-21: Summary of the `wc` Command

Command Recap		
<code>wc</code> - count lines, words, and characters in a file		
<i>command</i>	<i>options</i>	<i>arguments</i>
<code>wc</code>	<code>-l, -w, -c</code>	<i>file(s)</i>
Description:	<code>wc</code> counts lines, words, and characters in the specified file(s), keeping a total count of all tallies when more than one file is specified.	
Options	<ul style="list-style-type: none"> <li><code>-l</code> counts the number of lines in the specified file(s)</li> <li><code>-w</code> counts the number of words in the specified file(s)</li> <li><code>-c</code> counts the number of characters in the specified file(s)</li> </ul>	
Remarks:	When a file name is specified in the command line, it is printed with the count(s) requested.	

### Protecting Your Files: the `chmod` Command

The command `chmod` (short for change mode) allows you to decide who can read, write, and use your files and who cannot. Because the UNIX operating system is a multi-user system, you usually do not work alone in the file system. System users can follow path names to various directories and read and use files belonging to one another, as long as they have permission to do so.

If you own a file, you can decide who has the right to read it, write in it (make changes to it), or, if it is a program, to execute it. You can also restrict permissions for directories with the `chmod` command. When you grant execute permission for a directory, you allow the specified users to `cd` to it and list its contents with the `ls` command.

To assign these types of permissions, use the following three symbols:

- `r` allows system users to read a file or to copy its contents
- `w` allows system users to write changes into a file (or a copy of it)
- `x` allows system users to run an executable file

To specify the users to whom you are granting (or denying) these types of permission, use these three symbols:

- `u` you, the owner of your files and directories (`u` is short for user)
- `g` members of the group to which you belong (the group could consist of team members working on a project, members of a department, or a group arbitrarily designated by the person who set up your UNIX system account)
- `o` all other system users

When you create a file or a directory, the system automatically grants or denies permission to you, members of your group, and other system users. You can alter this automatic action by modifying your environment (see Chapter 9 for details). Moreover, regardless of how the permissions are granted when a file is created, as the owner of the file or directory you always have the option of changing them. For example, you may want to keep certain files private and reserve them for your exclusive use. You may want to grant permission to read and write changes into a file to members of your group and all other system users as well. Or you may share a program with members of your group by granting them permission to execute it.

### How to Determine Existing Permissions

You can determine what permissions are currently in effect on a file or a directory by using the command that produces a long listing of a directory's contents: `ls -l`. For example, typing `ls -l` and pressing the RETURN key while in the directory named `starship/bin` in the sample file system produces the following output:

```

$ ls -l<CR>
total 35
-rwxr-xr-x  1 starship  project   9346 Nov 1  08:06 display
-rw-r--r--  1 starship  project   6428 Dec 2  10:24 list
drwx--x--x  2 starship  project    32 Nov 8  15:32 tools
$

```

Permissions for the `display` and `list` files and the `tools` directory are shown on the left of the screen under the line `total 35`, and appear in this format:

```

-rwxr-xr-x  (for the display file)
-rw-r--r--  (for the list file)
drwx--x--x  (for the tools directory)

```

After the initial character, which describes the file type (for example, a `-` (dash) symbolizes a regular file and a `d` a directory), the other nine characters that set the permissions comprise three sets of three characters. The first set refers to permissions for the owner, the second set to permissions for group members, and the last set to permissions for all other system users. Within each set of characters, the `r`, `w`, and `x` show the permissions currently granted to each category. If a dash appears instead of an `r`, `w`, or `x`, permission to read, write, or execute is denied.

The following diagram summarizes this breakdown for the file named `display`.

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.