

JC900 U.S. PTO
08/10/00

08-11-00

A/prev

PATENT
AWR-047

Honorable Commissioner of Patents and Trademarks
Washington, DC 20231

NEW PROVISIONAL APPLICATION TRANSMITTAL LETTER

JC866 U.S. PTO
60/224308
08/10/00

Sir:

Transmitted herewith for filing is the Provisional Patent Application of Inventor(s):

Murat Belge

Residence: 36 Dartmouth Street
Pleasant PL #1004
Malden, MA 02148

Citizenship Turkey

Post Office Address: Same as above

Michael A. Tzannes

Residence: 17 Carley Road
Lexington, MA 02173

Citizenship United States

Post Office Address: Same as above

Halil Padir

Residence: 85 Carlton Lane
No. Andover, MA 01845

Citizenship United States

Post Office Address: Same as above

For: Characterization of Transmission Lines Using Broadband Signals In A Multi-Carrier DSL System

Enclosed are the following papers required to obtain a filing date under 37 C.F.R. §1.53(c):

—
33 Sheets of Informal Drawings
— Pages of Specification, Drawings & Tables
— Claims

The following papers, if indicated by an , are also enclosed:


A Declaration and Power of Attorney
 An Assignment of the invention
 An Information-Disclosure Statement, Form PTO-1449 and a copy of each cited reference
 A Small-Entity Declaration
 A Certificate of Express Mailing, Express Mail Label No. EE437022773US

Basic Fee: \$150

A check in the amount of \$150 is enclosed to cover the Filing Fee.

Please address all communications and telephone calls to the undersigned.

Respectfully submitted,


Gail Leonick
Aware, Inc.
40 Middlesex Turnpike
Bedford mass. 01730

References Cited

- [1] Provisional patent by D. Krinsky and R. Pizzano, "*Multicarrier Modulation System with Remote Transmission Mode*", serial no: 60/174,865, date filed: 1/7/2000.
- [2] Provisional patent by M. Belge, "*Estimation of the Loop Length and Bridged Tap Length of a Transmission Line*", serial no: 60/174,866, date filed: 1/7/2000.

1 Background of the Invention

Rapid developments in the computer industry and the availability of affordable hardware created the internet where any user having a communication link between his/her home and the computers in centralized locations can access publicly available information. Users of the internet are connected to the communication network through a link that includes a telephone line from the customer premises (CPE) to a telephone company central office (CO). A computer user requesting data transfer from an internet server is faced with the limited bandwidth of the connection between the his/her home and the central office. As more and more information is being created and stored in digital format, the demand from users to access large data files is increasing making it crucial to find new and faster ways of transferring data. One way of achieving faster data transmission is to increase the bandwidth of the transmission line between users and the CO by replacing the current metallic conductors with fiber or using better quality metallic conductors with increased bandwidth. But such an approach is costly and requires a substantial investment by the telephone companies.

Recent developments in digital signal processing and telecommunications have resulted in the digital subscriber line (DSL) technology enabling a high speed data link over existing twisted pair telephone lines. Although a couple of different DSL systems had been proposed multi-carrier systems have quickly gained popularity and been standardized. Multi-carrier DSL systems operate on the principle of frequency division multiplexing where separate frequency bands are used to transfer data from the CPE to the CO and vice versa. The portion of the bandwidth allocated for transmitting data from the user's computer to the CO is called the up-stream (US) channel and the portion of the bandwidth allocated for passing data from the CO to the user's computer is called the down-stream (DS) channel. Since in a typical internet session the amount of data being transmitted from the CO to the user's computer is much larger than the amount of data transmitted from the user's computer to the CO, the bandwidth allocated for the DS channel is usually much larger than the bandwidth allocated for the US channel (typical ratios are 4 to 1 or 8 to 1). The bandwidth allocated to the US and DS channels are partitioned into a large number of sub-bands which are sufficiently narrow so as to allow the distortions introduced by the line to be described as an attenuation and a phase shift. These parameters can be measured in a training session prior to establishing the data link by sending and receiving a predefined signal on each subband. The amount of data that can be sent in a sub-band is limited by the signal to noise ratio (SNR) in that sub-band which is the signal strength described by the line attenuation divided by the noise power. Each of the sub-bands in the multi-carrier DSL system is used to transmit data that is consistent with the SNR on that sub-band and maximum allowable error bit rate. Multi-carrier DSL

system operating with the described principles are able to achieve data rates as high as ten million bits per second.

Although the multi-carrier DSL systems are promising because they offer a cost effective way of opening current telephone lines to high speed data transmission traffic, there are important problems in the installation and maintenance phases of DSL deployment that prevents rapid wide spread deployment. Existing telephone lines were initially installed for voice only transmission which can be done by using only a small bandwidth. Multi-carrier DSL system require utilizing a bandwidth much larger than that required by the voice transmission. At high frequencies line conditions that don't affect the voice transmission become important factors limiting the digital data transmission rate. For example, the line attenuation is related to the loop length. The strength of the signals sent from either CO or user's computer decreases with distance. Small open circuited twisted pairs, called bridged taps (BT), connected in shunt with working twisted pairs, while not effecting voice transmission, cause periodic dips in the attenuation function of the line at certain sub-bands and hence degrade the performance of the DSL service. Telephone lines are usually bundled as 25 or 50 twisted pairs in a cable. Close proximity of the twisted pairs in the cable causes the signals generated by various DSL services carried by a specific telephone line to be picked up by the remaining telephone lines in the bundle. These signals are perceived as additive noise components because they are unpredictable and meaningless for all but one of the telephone lines carrying the service. The interference entering the telephone lines through some coupling path with other telephone lines are called crosstalk. There may be other sources of noise in a telephone line which are caused by the reception of electromagnetic (EM) waves transmitted by various sources such as AM stations or electrical devices such as hair dryers, dimmer switches, alarm systems etc. The most detrimental of these EM sources are generally AM stations. Since no two telephone lines are the same and the availability and the quality of a DSL link depend on the conditions of the line as described above, it is very important to be able to qualify telephone lines for DSL service and maintain the link once the service is established. It is a challenge to ease the installation and maintenance issues. To decrease the cost associated with service qualification and maintenance, it is preferable to qualify and maintain telephone lines remotely without sending a technician to the customer premises.

It is the object of the present invention to provide a system for the qualification, maintenance and monitoring of telephone lines for DSL service by taking advantage of the DSL transceivers in the CO and the CPE sites.

2 Summary of the Invention

Establishing a digital data link between the computer in user's home and the servers connected to the backbone of the central office requires DSL transceivers handling the data transmission with the basic principles outlined in the previous section. Each of the transceivers at either side of the link, the CO and the CPE, are called modems. The CO and the CPE modems consist of some analog hardware to perform analog signal transmission and reception and a digital section which consists of a digital signal processing (DSP) chip and

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.