

## Microlens array produced using hot embossing process

N.S. Ong\*, Y.H. Koh, Y.Q. Fu

*School of Mechanical and Production Engineering, Nanyang Technological University, Nanyang Avenue, Singapore 639798, Singapore*

Received 1 May 2001; accepted 30 August 2001

---

### Abstract

In this paper, the fabrication of molds that are suitable for the production of microlens arrays using the replication technique is discussed. Variation of parameters in the replication process were investigated. A focused ion beam was used to fabricate the microlens cavities on three materials, with silicon showing the best result. Hot embossing was used to produce replicated polycarbonate lens array. The temperature of the mold and the embossing force were the two parameters varied. The microlens array produced using the embossing replication process demonstrates the possibility of nanometre fabrication. © 2002 Elsevier Science B.V. All rights reserved.

*Keywords:* Microlens array; Focused ion beam; Hot embossing

---

### 1. Introduction

The increase in research into control-by-light systems has widened the market for the use of microlens array. Indeed, microlens array has a large field of application; for example high-speed photography, telecommunication industry that couple light in and out optical fiber waveguides and optical communication [1]. Also the use of optical control systems over their electrical counterparts offers a large number of advantages such as immunity to electromagnetic interference, safety in flammable areas, weight and cost savings, etc. Many methods of fabricating microlens were presented. Some examples are contactless embossing molding [2], the melted photoresist method [3] and microjet fabrication [4]. In this research, a focused ion beam is used to produce lens pattern on a mold material, which will then be used for embossing to produce microlens array.

Focused ion beam (FIB) technology is well known and widely used in semiconductor manufacturing. The FIB system uses liquid metal gallium as the ion source. In the ionization process, gallium

---

\*Corresponding author. Tel.: +65-799-55-37; fax: +65-791-18-59.  
*E-mail address:* mnsong@ntu.edu.sg (N.S. Ong).




Fig. 1. Steps involved in hot embossing process.

atoms tend to lose one electron, thus becoming singly-charged positive ions. Being charged particles, ions can be accelerated, focused and controlled by electrostatic fields. Their relatively high mass (compared with that of subatomic particles) allows them to be used to induce the milling and deposition effects. Factors affecting FIB milling such as beam limiting aperture size, neighbouring space of beam spot, dwell time and milling sequence were reported [5–7].

Fig. 1 shows the steps involved in hot embossing. A sheet of plastic foil/material is sandwiched between a mold (embossing tool) and an optically smooth backing plate was heated under pressure to a temperature (typically  $> 50^{\circ}\text{C}$ ) above the softening temperature ( $T_g$ ) of the plastic. Higher temperatures are favourable as the lower viscosity of the polymer facilitates the molding process. After molding, the polymer is cooled down to below the glass transition temperature. The molding force is maintained during cooling in order to preserve the polymer microstructures from distortion. Once the polymer is cooled to below  $T_g$  and the pressure is released, the plastic can be separated from the mold to give a high quality copy of the planar microstructure. No material shrinkage was found during the hot embossing process [8]. A simple filling mechanism governing the flow of polymer in hot embossing was described [9]. The factors governing hot embossing were reported [10]; temperature, embossing force and time were the three main factors. This technique works extremely well for shallow microstructures (relief depths less than  $1\ \mu\text{m}$ ). Deeper structures, where aspect ratio was as high as seven, were also reported [11]. Such an embossing technique can be carried out in the laboratory using a relatively unsophisticated hot press.

## 2. Fabrication of micro-molds

The manufacturing of the microlens array involved 2 steps. Firstly, FIB milling is done on a mold material. Once the pattern obtained on the mold is deemed satisfactory, it is then used as a mold to emboss the plastic lens array.

### 2.1. Focused ion beam milling

The material used for the mold must be polished to surface finish of below  $10\ \text{nm Ra}$ . This is because when the ion hits the surface of the material, the depth of material being removed will be affected if there are large surface irregularities. The material was ground by abrasives paper of grit size 180, 400, 800, 1000 progressively. The surface was then polished with 3- and  $1\text{-}\mu\text{m}$  sized




Fig. 2. Fabrication of microlens profile using FIB.

diamond paste at a rotating speed of 150 rpm. The polished material was then cleaned in an acetone ultrasonic bath.

Fig. 2 shows the lens profile generation. The inner circle path will be programmed with a higher ion dose while the ion dose in the outer circle path will be subsequently reduced. It is this variation in the ion dose that generates the depth of the lens profile. At a constant aperture, the depth increases as the ion dose increases. A higher ion dose indicates that there are a greater number of incident ions per unit area. Each of them removes particles from the material and thus generate a deeper feature. The sequence used in the fabrication of lens pattern was from periphery to the center of the profile. A 250- $\mu\text{m}$  aperture size was used for the FIB system. The dwell time was set at 5  $\mu\text{s}$ . Fig. 3 shows the design lens profile. The diameter is 70  $\mu\text{m}$  with a depth of 3.45  $\mu\text{m}$ .

Three different materials were used in the fabrication of the mold using FIB. As can be seen in Figs. 4 and 5, there are numerous small pitting holes on the mold surface. It is believed that one of the reasons for this problem is that the material is not homogenous. Another reason is because the grain




Fig. 3. Microlens profile.




Fig. 4. SEM picture of a lens profile on pure nickel.

structure for pure nickel and stainless steel materials were too big. This causes an uneven ‘tearing’ effect due to the bombardment of the ions during the ion milling process. A lens profile was also milled on a silicon wafer using FIB (see Fig. 6). A surface finish of around 7 nm Ra was obtained.




Fig. 5. SEM picture of a microlens profile on stainless steel.




Fig. 6. SEM picture of a microlens profile on silicon wafer.

Silicon was therefore selected for the lens array mold fabrication. Furthermore, it was noted that silicon has several advantages [12]. The silicon must be thick enough to withstand the force applied during the embossing process. A  $7 \times 5$  lens array was milled on a 9-mm thick silicon (see Fig. 7).

## 2.2. Hot embossing

In the embossing process, polycarbonate material was sandwiched between a flat nickel plate and the mold. Heat was applied to above the  $T_g$  temperature ( $148^\circ\text{C}$ ) of the polycarbonate material. Embossing force was applied and held for 20 min. The mold was subsequently cooled to  $26^\circ\text{C}$  with the force maintained to preserve the microstructures of the lens. Demolding was then performed. Demolding is the separation of the mold from the embossed polymer structure by a vertical movement of the mold.

## 3. Results and discussion

Fig. 8 shows a lens profile milled on the 9-mm thick silicon material. It can be seen that the surface profile was very well defined and the surface roughness was measured to be around 4 nm Ra.

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.