

THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE PATENT TRIAL AND APPEAL BOARD

OLYMPUS CORPORATION and OLYMPUS AMERICA INC.
Petitioners,

v.

PAPST LICENSING GMBH & CO. KG
Patent Owner.

Case No. IPR2017-01617
Patent No. 6,895,449

**DECLARATION OF KEVIN ALMEROOTH IN SUPPORT OF PETITION
FOR *INTER PARTES* REVIEW OF U.S. PATENT NO. 6,895,449: CLAIMS
1–10, 12, 13, AND 15–18**

TABLE OF CONTENTS

I.	Background and Qualifications	- 3 -
II.	Legal Standards and Background	- 13 -
A.	Person of Ordinary Skill in the Art	- 13 -
B.	Claim Construction	- 14 -
C.	Validity	- 14 -
III.	Overview of the '449 Patent	- 17 -
IV.	Level of Ordinary Skill	- 19 -
V.	Claim Construction	- 21 -
VI.	Analysis of Claims 1–10, 12, 13, 15–18	- 22 -
A.	Claims 1–3, 6–10, 12, 13, and 15–18 over Murata, Schmidt and MS-DOS Encyclopedia	- 22 -
1.	Rationale for Combining Murata, Schmidt and MS-DOS Encyclopedia	- 22 -
2.	Claim 1 [preamble] - “An interface device for communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device comprising the following features:”	- 26 -
3.	Claim 1 [1a] - “a processor;”	- 34 -
4.	Claim 1 [1b] - “a memory;”	- 34 -
5.	Claim 1 [1c] - “a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and”	- 35 -
6.	Claim 1 [1d] - “a second connecting device for interfacing the interface device with the data transmit/receive device,”	- 35 -

7. Claim 1 [1e] - “wherein the interface device is configured by the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached to the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is a storage device customary in a host device, whereupon the host device communicates with the interface device by means of the driver for the storage device customary in a host device, and” - 35 -
8. Claim 1 [1f] - “wherein the interface device is arranged for simulating a virtual file system to the host, the virtual file system including a directory structure.” - 42 -
9. Claim 2 - “An interface device in accordance with claim 1, in which the directory structure has a configuration file for setting and controlling functions of the interface device or an executable or a batch file for conducting a routine stored in the memory or a data file used for transferring data from the data transmit/receive device to the host device or a help file for giving help on handling the interface device.” - 45 -
10. Claim 3 - “An interface device in accordance with claim 2 wherein the configuration file is a text file.” - 45 -
11. Claim 6 - “An interface device in accordance with claim 1 wherein, in response to a request from the host to read a boot sequence, the processor is arranged to send a virtual boot sequence to the host.” - 46 -
12. Claim 7 - “An interface device in accordance with claim 6 wherein the virtual boot sequence includes a starting position and a length of a file allocation table, an indication of a type of the storage device or a number of sectors of the storage device.” - 47 -
13. Claim 8 - “An interface device in accordance with claim 7 wherein, in response to a request from the host to display a directory of the storage device, a processor is arranged for

transferring the file allocation table and the directory structure to the host.” - 49 -

14. Claim 9 - “An interface device in accordance with claim 1 wherein the file allocation table and the directory structure is transferred to the host in response to a request from the host to read data from or store data to the storage device.” - 51 -
15. Claim 10 - “An interface device in accordance with claim 1 wherein the directory structure includes a data file for transferring data from the data transmit/receive device to the host device wherein the processor is arranged to interpret a request from the host to read the data file as a request for a data transfer from the data transmit/receive device to the host, so that data is transmitted from the second connecting device to the first connecting device and to the host.” - 54 -
16. Claim 12 - “An interface device in accordance with claim 1 wherein the file allocation table includes information on numbers of blocks occupied by the data file wherein the interface device is arranged for receiving block numbers or a block number range from the host when the host wants to read the data file, and wherein the interface device is arranged to start a data transfer to the host, when the block numbers or the block number range is received from the host.” - 56 -
17. Claim 13 - “An interface device in accordance with claim 12 wherein the processor is arranged for formatting the data acquired by the second connecting device into blocks having a predetermined size, the predetermined size being suited for the storage device.” - 58 -
18. Claim 15 - “An interface device in accordance with claim 1 wherein the storage device is a hard disk.” - 59 -
19. Claim 16 - “An interface device in accordance with claim 1 wherein the memory has a data buffer for permitting independence in terms of time of the data transmit/receive device attachable to the second connecting device from the host device attachable to the first connecting device.” - 59 -

- 20. Claim 17 [preamble] - “An interface device for communication between a host device, which comprises a multi-purpose interface and a specific driver for this interface, and a data transmit/receive device comprising the following features:”- 60 -
- 21. Claim 17 [17a] - “a processor;” - 61 -
- 22. Claim 17 [17b] - “a memory;” - 61 -
- 23. Claim 17 [17c] - “a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and” - 62 -
- 24. Claim 17 [17d] - “a second connecting device for interfacing the interface device with the data transmit/receive device,”- 62 -
- 25. Claim 17 [17e] - “where the interface device is configured using the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached at the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is a storage device customary in a host device, whereupon the host device communicates with the interface device by means of the specific driver for the multi-purpose interface, and” - 62 -
- 26. Claim 17 [17f] - “wherein the interface device is arranged for simulating a virtual file system to the host, the virtual file system including a file allocation table and a directory structure.” - 63 -
- 27. Claim 18 [preamble] - “A method of communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device via an interface device comprising the following steps:” - 63 -

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.