

Ex. 1003

LOW PROFILE LIGHT AND ACCESSORY KIT FOR THE SAME

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part of U.S. Application Serial No. 12/775,310, filed May 6, 2010, which claims the benefit of U.S. Provisional Application Serial No. 61/248,665, filed October 5, 2009, both of which are incorporated herein by reference in their entirety.

BACKGROUND OF THE INVENTION

[0002] The present disclosure relates generally to lighting, particularly to low profile lighting, and more particularly to low profile downlighting for retrofit applications.

[0003] Light fixtures come in many shapes and sizes, with some being configured for new work installations while others are configured for old work installations. New work installations are not limited to as many constraints as old work installations, which must take into account the type of electrical fixture/enclosure or junction box existing behind a ceiling or wall panel material. With recessed ceiling lighting, sheet metal can-type light fixtures are typically used, while surface-mounted ceiling and wall lighting typically use metal or plastic junction boxes of a variety of sizes and depths. With the advent of LED (light emitting diode) lighting, there is a great need to not only provide new work LED light fixtures, but to also provide LED light fixtures that are suitable for old work applications, thereby enabling retrofit installations. One way of providing old work LED lighting is to configure an LED luminaire in such a manner as to utilize the volume of space available within an existing fixture (can-type fixture or junction box). However, such configurations typically result in unique designs for each type and size of fixture. Accordingly, there is a need in the art for an LED lighting apparatus that overcomes these drawbacks.

[0004] This background information is provided to reveal information believed by the applicant to be of possible relevance to the present invention. No admission is necessarily intended, nor should be construed, that any of the preceding information constitutes prior art against the present invention.

BRIEF DESCRIPTION OF THE INVENTION

[0005] An embodiment of the invention includes a luminaire having a heat spreader and a heat sink thermally coupled to and disposed diametrically outboard of the heat spreader, an outer optic securely retained relative to at least one of the heat spreader and the heat sink, and a light source disposed in thermal communication with the heat spreader, the light source having a plurality of light emitting diodes (LEDs). The heat spreader, the heat sink and the outer optic, in combination, have an overall height H and an overall outside dimension D such that the ratio of H/D is equal to or less than 0.25. The combination defined by the heat spreader, the heat sink and the outer optic, is so dimensioned as to: cover an opening defined by a nominally sized four-inch can light fixture; and, cover an opening defined by a nominally sized four-inch electrical junction box.

[0006] An embodiment of the invention includes a luminaire having a heat spreader and a heat sink thermally coupled to and disposed diametrically outboard of the heat spreader. An outer optic is securely retained relative to at least one of the heat spreader and the heat sink. A light source is disposed in thermal communication with the heat spreader, the light source having a plurality of light emitting diodes (LEDs). A power conditioner is disposed in electrical communication with the light source, the power conditioner being configured to receive AC voltage from an electrical supply line and to deliver DC voltage to the plurality of LEDs, the power conditioner being so dimensioned as to fit within at least one of: a nominally sized four-inch can light fixture; and, a nominally sized four-inch electrical junction box.

[0007] An embodiment of the invention includes a luminaire having a heat spreader, a heat sink thermally coupled to and disposed diametrically outboard of the heat spreader, an outer optic securely retained relative to at least one of the heat spreader and the heat sink, a light source disposed in thermal communication with the heat spreader, and an electrical supply line disposed in electrical communication with the light source. The heat spreader, heat sink and outer optic, in combination, have an overall height H and an overall outside dimension D such that the ratio of H/D is equal to or less than 0.25. The defined combination is so dimensioned as to: cover an opening defined by a nominally sized four-inch can light fixture; and, cover an opening defined by a nominally sized four-inch electrical junction box.

[0008] An embodiment of the invention includes a luminaire having a housing with a light unit and a trim unit. The light unit includes a light source, and the trim unit is mechanically separable from the light unit. A means for mechanically separating the trim unit from the light unit provides a thermal conduction path therebetween. The light unit has sufficient thermal mass to spread heat generated by the light source to the means for mechanically separating, and the trim unit has sufficient thermal mass to serve as a heat sink to dissipate heat generated by the light source.

[0009] An embodiment of the invention includes a luminaire for retrofit connection to an installed light fixture having a concealed in-use housing. The luminaire includes a housing having a light unit and a trim unit, the light unit having a light source, and the trim unit being mechanically separable from the light unit. The trim unit defines a heat sinking thermal management element, configured to dissipate heat generated by the light source, that is completely 100% external of the concealed in-use housing of the installed light fixture.

[0010] An embodiment of the invention includes a luminaire and accessory kit combination. The luminaire includes a heat spreader; a heat sink; an LED light source; a power supply; an electrical supply line having a first end connected to the power supply,

and a second end connected to a plug-in connector; and, an optic securely retained relative to the heat spreader or heat sink. The accessory kit includes a first pre-wired jumper including a pair of insulated electrical wires having a first plug-in connector electrically connected at one end and an Edison base electrically connected at the other end; and/or, a second pre-wired jumper including a pair of insulated electrical wires having a second plug-in connector electrically connected at one end and unconnected wire ends at the other end. The plug-in connector of the first pre-wired jumper and the second pre-wired jumper are each configured to electrically engage with the plug-in connector of the electrical supply line.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Referring to the exemplary drawings wherein like elements are numbered alike in the accompanying Figures, abbreviated in each illustration as “Fig.”:

[0012] Figure 1 depicts an isometric top view of a luminaire in accordance with an embodiment of the invention;

[0013] Figure 2 depicts a top view of the luminaire of Figure 1;

[0014] Figure 2 depicts a bottom view of the luminaire of Figure 1;

[0015] Figure 4 depicts a side view of the luminaire of Figure 1;

[0016] Figure 5 depicts a top view of a heat spreader assembly, a heat sink, and an outer optic in accordance with an embodiment of the invention;

[0017] Figure 6 depicts an isometric view of the heat spreader of Figure 5;

[0018] Figure 7 depicts a partial isometric view of the heat sink of Figure 5;

[0019] Figure 8 depicts a top view of an alternative heat spreader assembly in accordance with an embodiment of the invention;

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.