
Microelectronics Processing



Find authenticated court documents without watermarks at <u>docketalarm.com</u>.

ADVANCES IN CHEMISTRY SERIES 221

Microelectronics Processing

Chemical Engineering Aspects

Dennis W. Hess, EDITOR University of California–Berkeley

Klavs F. Jensen, EDITOR University of Minnesota



American Chemical Society, Washington, DC 1989

Find authenticated court documents without watermarks at docketalarm.com.



Library of Congress Cataloging-in-Publication Data

Microelectronics Processing: Chemical Engineering Aspects Dennis W. Hess, editor, Klavs F. Jensen, editor
p. cm.—(Advances in chemistry series, ISSN 0065-2393; 221)
Bibliography: p.
Includes index.
ISBN 0-8412-1475-1
1. Microelectronics-Materials. 2. Integrated
Circuits—Design and Construction. 3. Surface Chemistry.
I. Hess, Dennis W. II. Jensen, Klavs F., 1952III. Series
TK7874.M4835 1989
621.381-dc19
89-6862

Copyright © 1989

DOCKE

American Chemical Society

All Rights Reserved. The appearance of the code at the bottom of the first page of each chapter in this volume indicates the copyright owner's consent that reprographic copies of the chapter may be made for personal or internal use or for the personal or internal use of specific clients. This consent is given on the condition, however, that the copier pay the stated per-copy fee through the Copyright Clearance Center, Inc., 27 Congress Street, Salem, MA 01970, for copying beyond that permitted by Sections 107 or 108 of the U.S. Copyright Law. This consent does not extend to copying or transmission by any means—graphic or electronic—for any other purpose, such as for general distribution, for advertising or promotional purposes, for creating a new collective work, for resale, or for information storage and retrieval systems. The copying fee for each chapter is indicated in the code at the bottom of the first page of the chapter.

CIP

The citation of trade names and/or names of manufacturers in this publication is not to be construed as an endorsement or as approval by ACS of the commercial products or services referenced herein; nor should the mere reference herein to any drawing, specification, chemical process, or other data be regarded as a license or as a conveyance of any right or permission to the holder, reader, or any other person or corporation, to manufacture, reproduce, use, or sell any patented invention or copyrighted work that may in any way be related thereto. Registered names, trademarks, etc., used in this publication, even without specific indication thereof, are not to be considered unprotected by law.

PRINTED IN THE UNITED STATES OF AMERICA

CONTENTS

Pre	face
1.	Microelectronics Processing
2.	Theory of Transport Processes in Semiconductor Crystal Growth from the Melt
3.	Liquid-Phase Epitaxy and Phase Diagrams of Compound Semiconductors
4.	Physical Vapor Deposition Reactors
	Chemical Vapor Deposition 199 Klavs F. Jensen
6.	Diffusion and Oxidation of Silicon 265 Richard B. Fair
7.	Resists in Microlithography
8.	Plasma-Enhanced Etching and Deposition
9,	Interconnection and Packaging of High-Performance Integrated Circuits
10.	Semiconductor Processing Problems Solved by Wet (Solution) Chemistry
	INDEXES

Author Index	23
Affiliation Index	23
Subject Index	23

DOCKET A L A R M **Resist Stripping.** After the additive or subtractive processes of the substrate are complete, the resist mask must be completely removed by either wet or dry etching. The selection of resist stripper is determined by previous resist history (bakes, exposure to plasma, etc.) that results in chemical alteration and by the underlying substrate stability (176). Wet etches are either solvent-based or inorganic reagents such as H_2SO_4 , HNO_3 or H_2O_2 . Solvent-type strippers are typically acetone for positive resists, trichloroethylene for negative resists, or commercial products developed to remove both types of resists. Commercial organic strippers were initially phenol-based solvents but have been manufactured recently with little or no phenol as a result of health and safety issues associated with the use of this chemical. Plasma stripping or ashing of resist with either O_2 or O_2 -CF₄ gases is clearly the method of choice from the standpoint of convenience, cost, and safety. However, the method cannot be used with substrates that are etched by these plasmas.

Auxiliary Process Steps. In addition to the standard process steps, auxiliary processes are sometimes necessary. These steps are not used for all situations but as required and will be considered in this section separately. Certain semiconductor-manufacturing processes are particularly damaging to polymeric films and require an additional step to harden the resist. For example, Al etching with chlorine plasma produces AlCl₃, which degrades resists. Ion implantation, in which the chamber temperature and, hence, the wafer temperature increase with increasing implant dose, causes thermal deformation of the resist image. One commonly used method to stabilize novolac-based resists is deep-UV flood exposure after patterning (177). With deep-UV exposure, cross-linking of the polymer surface produces a film with increased thermal resistance. With this procedure, positive resists can with-stand a 180 °C bake for 30 min. Fluorocarbon plasma treatment also stabilizes resists (178), because fluorine insertion impedes subsequent oxidation of the polymers.

As discussed previously, an optional postexposure, predevelopment bake can reduce problems with the standing-wave effect in DNQ-novolac positive resists. However, such a postexposure bake step is indispensable in the image reversal of positive resists (37-41) and certain resists based on chemical amplification of a photogenerated catalyst (64-67, 77, 78). For both types of resists, the chemistry that differentiates between exposed and unexposed areas does not occur solely during irradiation. Instead, differentiation occurs predominantly during a subsequent bake. Therefore, to obtain acceptable CD control in these systems, the bake conditions must be carefully optimized and monitored.

Rework. Masking steps frequently have the advantage over other ICmanufacturing processes of being able to undergo wafer rework. Rework

DOCKET A L A R M



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.