


THIRD EDITION



EDITED BY
VALERIE ILLINGWORTH

IPR2017-01819
NVIDIA v. Polaris
Polaris Ex. 2004



PENGUIN BOOKS

IPR2017-01819
NVIDIA v. Polaris
Polaris Ex. 2004

PENGUIN BOOKS

Published by the Penguin Group

Penguin Books Ltd, 27 Wrights Lane, London W8 5TZ, England

Penguin Putnam Inc., 375 Hudson Street, New York, New York 10014, USA

Penguin Books Australia Ltd, Ringwood, Victoria, Australia

Penguin Books Canada Ltd, 10 Alcorn Avenue, Toronto, Ontario, Canada M4V 3B2

Penguin Books India (P) Ltd, 11, Community Centre, Panchsheel Park, New Delhi - 110 017, India

Penguin Books (NZ) Ltd, Private Bag 102902, NSMC, Auckland, New Zealand

Penguin Books (South Africa) (Pty) Ltd, 5 Watkins Street, Denver Ext 4, Johannesburg 2094, South Africa

Penguin Books Ltd, Registered Offices: Harmondsworth, Middlesex, England

First edition 1979

Second edition 1988

Third edition 1998

3


Copyright © Market House Books Ltd, 1979, 1988, 1998

All rights reserved

Typeset in 8.5/10.5 pt Times New Roman PS

Printed in England by Clays Ltd, St Ives plc

Except in the United States of America, this book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form of binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser



Adaptive control system

adaptive control system A control system in which the controller has adjustable parameters and a mechanism for adjusting the parameters. The controller becomes nonlinear because of the parameter adjustment mechanism. An adaptive control system can be modelled as a system having two loops (see diagram). One loop is a normal feedback with the process and the controller. The other loop is the parameter adjustment loop, which is often slower than the normal feedback loop.

adaptive equalizer equalization.

ADC *Abbrev. for analogue-to-digital converter.*

ADCCP *Abbrev. for advance data communication control procedure.* In communications, a type of protocol developed by the American National Standards Institute. It works at the bit level within a message: particular bits in the message are used to indicate which bits are the message, which bits are the sender and recipient identifiers, and which bits are concerned with error handling.

Adcock direction finder *Syn.* Adcock antenna. A radio direction finder consisting of a number of spaced vertical antennas. The errors due to the horizontally polarized components of the received waves are effectively eliminated as such components have only a minimal effect on the observed bearings.

adder A circuit in a computer that performs mathematical addition. A *full adder* contains several identical sections each of which add the corresponding bits of the two

IPR2017-01819
 NVIDIA v. Polaris
 Polaris Ex. 2004

address bus A special-purpose computer bus that carries only address information. The size of the address bus will specify the memory space that is addressable: n address lines will allow 2^n memory locations to be individually identified.

addressing mode The way in which the address of a particular memory location is produced in a computer system. These can include direct addressing, indirect addressing, relative addressing, and indexed addressing modes. Addressing modes are specified for individual processors; the specification is part of the computer architect's task.

admittance Symbol: Y ; unit: siemens. The reciprocal of impedance. It is a complex quantity given by

$$Y = G + jB$$

where G is the conductance, B the susceptance, and $j = \sqrt{-1}$. Since impedance, Z , is given by

$$Z = R + jX,$$

where R and X are the resistance and reactance, respectively, then

$$Y = 1/Z = 1/(R + jX)$$

$$= (R - jX)/(R^2 + X^2)$$

admittance gap A gap in the wall of a cavity resonator that allows it to be excited by a source of radiofrequency energy, such as a velocity-modulated electron beam, or that allows it to affect such a source.

ADSR *Abbrev. for* attack decay sustain release.

aerial antenna.

IPR2017-01819
NVIDIA v. Polaris
Polaris Ex. 2004

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.