SYSTEM, APPARATUS, AND METHOD FOR PROVIDING CONTROL OF A TOY VEHICLE

CROSS-REFERENCES TO RELATED APPLICATIONS

This Application for Patent claims the benefit of priority from, and hereby incorporates by reference for any and all purposes the entire disclosure of, co-pending U.S. Provisional Application for Patent having Serial No. 60/268,447, filed February 12, 2001.



Dynacraft BSC, Inc.

Exhibit 1016

Dynacraft v. Mattel IPR2018-00038

BACKGROUND OF THE INVENTION

Technical Field of the Invention

The principals of the present invention generally relate to toy vehicles that may be ridden by people, and more specifically, but not by way of limitation, to a system, apparatus, and method for softening the initiation of motion of the toy vehicle.

Description of Related Art

10 As shown in FIGURE 1, toy vehicles 100 for riding on or in have become popular for operators 110, such as children. toy vehicles 100 may generally include ride-on and ride-in vehicles, including, but not limited to, automobiles, trucks, boats, airplanes, scooters, etc. Conventional control systems for the toy vehicles 100 have typically been limited to applying 15 a direct current (DC) from a DC battery to a motor upon pressing otherwise operating a "gas" pedal or other throttle mechanism. This type of control, however, basically operates as an on/off switch. In other words, when the pedal is pressed, 20 the motor is applied a voltage for full power (i.e. maximum angular velocity). One reason for such a simplistic design is cost reasons.



5

FIGURE 2 is an exemplary block diagram of a conventional control system 200 for the toy vehicle 100. The conventional control system 200 includes a battery 205, foot pedal switch 210, forward/reverse switch 215 for direction control, hi/lo 5 switch 220 for fast and slow speeds, and motors 225a and 225b. The toy vehicles 100 are typically limited to a battery 205 for a power source rather than using other fuel sources, such as gasoline. The battery 205 is coupled to a foot pedal switch 210, which operates to provide power from the battery 205 to 10 other electrical components of the control system 200 via line 212. The battery 205 supplies battery voltage V_{BATT} . Additionally, the foot pedal switch 210 operates as a failsafe device that prevents power from incidentally or accidentally being applied to the motors 225 for safety purposes. To operate 15 as a failsafe device, the foot pedal switch 210 is a "make or break" switch with a spring return to OFF as understood in the art. The foot pedal switch 210 is further coupled to the forward/reverse switch 215 via line 217 and generates a throttle signal 218.

20 The forward/reverse switch 215 receives battery power via line 217, is operable to switch the direction of the motors 225 from forward to reverse so as to operate the toy vehicle 100 forward or reverse, respectively. The forward/reverse switch



produces two signals, FWD and REV, which are applied to the hi/lo switch 220 via lines 222a and 222b (collectively 222). The hi/low switch 220 is further coupled to the motors 225 and operable to drive the motors 225 in parallel or series to provide for high and low speed of the toy vehicle 100. Further, the hi/lo switch 220 is coupled to the negative terminal 227 of the battery 205, which is electrically coupled to the low side. As understood in the art, each of the components of the control system 200 receive power from the battery, but that power is relatively high for solid state electronics, thereby making alternative control systems difficult and too expensive for the toy industry to consider a viable option.

There exists several problems when utilizing the control 200, or any other basic direct drive system for These problems may include (i) controlling toy vehicles 100. excessive acceleration, (ii) jerk, (iii) safety (e.g., controlling and flipping the vehicle at startup), and (iv) wearing of the mechanical components of the drive train for the toy vehicle 100. While each of these problems have existed in the toy vehicles 100 for a long period of time, the toy industry and makers of toy vehicles 100 are very cost sensitive due to Solutions to consumer pricing demands and production costs. these problems have been unavailable due in large part to



10

15

20

pricing and technical concerns of toy manufacturers for the toy vehicles 100.

With regard to excessive acceleration (dV/dt) and jerk (dA/dt), the acceleration and jerk result in a whiplash effect 5 on the operator 110 and passenger(s). In terms of wearing of the mechanical components, when the toy vehicle 100 changes direction from forward to reverse and vice versa, a complete stop is not required. As all gear drives have a certain amount of backlash (i.e., small amounts of gap between gear teeth), the 10 gears allow the motor to turn in the opposite direction without applying force to the output (e.g., wheels) of the drive train until the entire backlash is reduced to zero, thereby subjecting the motors 225 and drive train to the full load at full speed at each change in direction. In other words, since the motor 225 15 significant initial resistance to movement no opposite direction due to backlash, the motor 225 accelerates rapidly until the backlash is eliminated. The motor 225 is therefore moving at near full speed in the reverse direction while the vehicle is still moving in a high speed in the 20 opposite direction. Once the backlash is eliminated, the input and output to the drive train are rotating in the opposite direction and the gears exert substantial forces on one another the drive train suddenly reverses direction. These as



DOCKET

Explore Litigation Insights



Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

