

IBM DICTIONARY OF COMPUTING

Compiled and edited by
GEORGE McDANIEL

McGRAW-HILL, INC.
New York San Francisco Washington, D.C. Auckland Bogotá
Caracas Lisbon London Madrid Mexico City Milan
Montreal New Delhi San Juan Singapore
Sydney Tokyo Toronto

Limitation of Liability

While the Editor and Publisher of this book have made reasonable efforts to ensure the accuracy and timeliness of the information contained herein, neither the Editor nor the Publisher shall have any liability with respect to loss or damage caused or alleged to be caused by reliance on any information contained herein.

Copyright © 1994 by International Business Machines Corporation. All rights reserved. Printed in the United States of America. Except as permitted under the United States Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a data base or retrieval system, without the prior written permission of the publisher.

6 7 8 9 0 DOC/DOC 9 9 8 7

ISBN 0-07-031488-8 (HC)
ISBN 0-07-031489-6 (PBK)

The sponsoring editor for this book was Daniel A. Gonneau and the production supervisor was Thomas G. Kowalczyk.

Printed and bound by R. R. Donnelley & Sons Company.

Tenth Edition (August 1993)

This is a major revision of the *IBM Dictionary of Computing*, SC20-1699-8, which is made obsolete by this edition. Changes are made periodically to the information provided herein.

It is possible that this material may contain reference to, or information about, IBM products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that IBM intends to announce such IBM products, programming, or services in your country. Comments may be addressed to IBM Corporation, Department E37/656, P. O. Box 12195, Research Triangle Park, NC 27709.

International Edition

Copyright © 1994 by International Business Machines Corporation. Exclusive rights by McGraw-Hill, Inc. for manufacture and export. This book cannot be re-exported from the country to which it is consigned by McGraw-Hill. The International Edition is not available in North America.

When ordering this title, use ISBN 0-07-113383-6.

ue color

ree com-
ance with

ster.

ents. (I)

of color
or three
n.

e system
ire only
c of one

igned to
achine,
iety of

m with
ion that
exploit
ccess to
mple, a
ve file.

hidden

minate
rdware.

lied to
pected

ates in
mping

Top-

ement

vs, a
fields
nding
ormap

true complement

[709]

TS

typically near-linearly-increasing ramps. (2) Pertaining to the use of 24-bits per pixel direct red, green, blue RGB, in which there are 8 bits (256 levels) of red, 8 bits (256 levels) of green, and 8 bits (256 levels) of blue, for a total of $256*256*256$ or 16 777 216 different combinations of red, green, and blue intensities. The number of different colored pixels that can then be simultaneously displayed is only limited by the number of pixels displayable from the frame buffer. (3) See also background color, direct color, pseudocolor.

true complement Deprecated term for radix complement.

true run list Synonym for dispatch list.

truncate (1) To terminate a computational process in accordance with some rule; for example, to end the evaluation of a power series at a specified term. (A)

(2) To remove the beginning or ending elements of a string. (3) To drop data that cannot be printed or displayed in the line width specified or available. Contrast with fold (3). (4) To shorten a field or statement to a specified length.

truncated binary exponential backoff In a local area network, the algorithm used to schedule retransmission after a collision such that the retransmission is delayed by an amount of time derived from the slot time and the number of attempts to retransmit. (T)

truncation (1) The deletion or omission of a leading or of a trailing portion of a string in accordance with specified criteria. (I) (A) (2) The termination of a computation process, before its final conclusion or natural termination, if any, in accordance with specified rules. (I) (A) (3) Contrast with round.

truncation error An error due to truncation. (I) (A)

trunk (1) In telephony, circuits that connect two switching systems, as opposed to connecting a customer line to a switching system. (2) A telephone channel between two central offices or switching devices that is used in providing a telephone connection between subscribers. (3) See tie trunk. (4) See also line, link, path, route.

trunk cable (1) A cable connecting trunk coupling units for the purpose of allowing communication among data stations. (T) (2) In an ESCON environment, a cable consisting of multiple fiber pairs that do not directly attach to an active device. This cable usually exists between distribution panels and can be located within, or external to, a building. Contrast with jumper cable.

cable. The trunk coupling unit contains the means for inserting the station into the network or having it bypassed. (T)

trunk exchange An exchange devoted primarily to interconnecting trunks.

trunk group Those trunks between two points, both of which are switching centers, individual message distribution points, or both, and that use the same multiplex terminal equipments.

trunk hunting A method of switching incoming calls to the next consecutive or next available number if the first called number is busy.

trunk line A telecommunication line that links a private telecommunication system to a public switched network.

trusted computer system In computer security, a system that employs sufficient hardware and software data integrity measures to allow simultaneous processing of a range of sensitive or classified information.

trusted computing base (TCB) In computer security, all of the protection mechanisms within a computer system, including hardware, software, and firmware, the combination of which enforces a security policy. It creates a basic protection environment and provides additional user services required for a trusted computer system.

Trusted Computing System Evaluation Criteria In computer security, a standard of the U.S. Government for the evaluation of trusted computer systems. Synonymous with Orange Book.

trusted path In computer security, a mechanism by which a person at a terminal can communicate directly with the trusted computing base. This mechanism can be activated only by the person or the trusted computing base and cannot be imitated by untrusted software.

trusted software In computer security, the software portion of a trusted computing base.

truth table (1) An operation table for a logic operation. (I) (A) (2) A table that describes a logic function by listing all possible combinations of input values and indicating for each combination the output value. (A)

truth value In COBOL, the representation of the result of the evaluation of a condition in terms of one of two values: true, false.