

**UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE PATENT TRIAL AND APPEAL BOARD**

Sony Corporation,
Petitioner,

v.

One-E-Way, Inc.
Patent Owner.

Patent No. 7,865,258

Issue Date: January 4, 2011

Title: Wireless Digital Audio System

EXHIBIT 1008

**COMPARISON OF 2001 APPLICATION SPECIFICATION
AND 2003 APPLICATION SPECIFICATION
AS ORIGINALLY FILED**

No. IPR2018-00216

On the following pages, the as-filed specification of U.S. App. No. 10/027,391, filed on Dec. 21, 2001 (“the 2001 specification”) is compared to the as-filed specification of U.S. App. No. 10/648,012, filed on Aug. 26, 2003 (“the 2003 specification”). Blue text in square brackets appears in the 2003 specification but not in the 2001 specification. Red text in strikeout appears in the 2001 specification but not in the 2003 specification.

FUZZY AUDIO WIRELESS ~~DIGITAL AUDIO~~ MUSIC SYSTEM

This is a continuation-in-part of application Serial No. 10/027,739 which patent application is pending

BACKGROUND OF THE INVENTION

[0001] This invention relates to audio player devices and more particularly to systems that include headphone listening devices. The new audio system uses existing audio player device headphone jacks to connect a [battery powered] transmitter for wireless transmission of a signal to a [battery powered] receiving headphone.

[0002] Use of audio headphones with audio player devices such as radio, tape players, CD players, computers, television audio and the like have been in use for many years. ~~Such use includes the portable player systems such as cassette tape players that may be used during exercising as for example running.~~ These systems usually incorporate an audio source having a headphone jack to which a headphone ~~is~~ [may be] connected by wire and connector.

[0003] There are also known wireless headphones that may receive [A.M. and F.M.] radio transmissions. ~~Also, audio player devices have been modified to allow wireless communication with a headphone receiver.~~ However, these systems do not allow use of a simple plug in [battery powered] transmitter for connection to ~~the~~ [any] audio player device jack [such as, laptop and desktop computers, portable compact disc players, portable MP3 players, portable cassette players and the like] for wireless transmission [and reception of audio music for private listening to multiple users occupying the same space. Existing audio systems make use of electrical wire connections between the audio source and the headphones to accomplish private listening to multiple users] ~~between space separated devices.~~

[0004] ~~As can be seen,~~ There is a need for a [battery powered] simple connection system for existing audio player devices, to allow wireless transmission to a headphone receiver [that accomplishes private listening to multiple users occupying the same space].

SUMMARY OF THE INVENTION

[0005] The present invention is directed to ~~wireless digital audio~~ [FAWM (Fuzzy Audio Wireless Music)] systems for [coded digital] transmission of a [an audio] signal from ~~any~~ audio player device [with a] headphone [jack] to a [receiver] headphone. ~~An audio~~ [using fuzzy logic technology.] ~~An audio~~ [A battery powered digital] transmitter may include a headphone plug in

~~communication with an analog low pass filter wherein the headphone plug may be connectable to a headphone jack of an audio source. The low pass filter output signal may be in communication with an A/D converter whose output may be in communication with a digital low pass filter that outputs a signal to an encoder. The encoder output may be in communication with a channel encoder the output of which may be in communication with a block interleaver. The block interleaver output may be in communication with a modulator the output of which may be summed with a transmitter code generator output in a summing element. The modulator may be a 64 Ary modulator. The summing element output may be in communication with a differential phase shift key transmitter the output of which may be in communication with a transmit antenna for wireless transmission of a signal. The transmitted signal may be transmitted to an audio receiver for processing to power a headphone speaker. [any of the previously mentioned audio sources, laptop and desktop computers, portable compact disc players, portable MP3 players, portable cassette players and the like. The FAWM system converts the audio music signal that may be supplied by the source, into a digital signal. This conversion takes place in the small battery powered transmitter that connects to the headphone jack of the source. The transmitter then adds a unique user code and transmits it to the battery powered receiver headphones where the fuzzy logic detector decodes only the unique user code to allow private listening without inference from other users.]~~

[0006] These and other features, aspects and advantages of the present invention will become better understood with reference to the following drawings, description and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Figure 1 illustrates a schematic diagram representation of the ~~wireless digital audio~~ [FAWM] system;

[0008] Figure 2 illustrates a ~~functional block diagram of the audio transmitter~~ [graph of the high and low bit fuzzy logic if-then part fuzzy set] according to an embodiment of the invention;

[0009] ~~Figure 3 illustrates a functional block diagram of the audio receiver according to an embodiment of the invention.~~

DETAILED DESCRIPTION

[0010] The following detailed description is the best currently contemplated modes for carrying out the invention. The description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the invention.

[0011] Referring to Figure 1, a ~~wireless digital audio~~ [FAWM] system 10 may include ~~an audio~~ [a battery powered] transmitter 20 connected to ~~an~~ [a portable] audio player or audio source 80. The ~~audio~~ [battery powered] transmitter 20 may be connected to the audio source 80 headphone jack 82 using a headphone plug 22. The ~~audio~~ [battery powered] transmitter 20 may have a transmitting antenna 24 that may be omni-directional for transmitting ~~an electromagnetic~~ [a coded digital modulated] signal to a receiving antenna 52 of ~~an audio~~ [a battery powered] receiver 50 that may be a headphone receiver. The ~~audio~~ [battery powered] receiver 50 may have headphone speakers 54 in headphones 55 for listening to the ~~audio~~ [demodulated and decoded digital] signal. The ~~audio system 10~~ [FAWM transmitter 20] may digitize the audio signal ~~and may transmit an electromagnetic signal at 2.4 GHz using approximately 100 milliwatts or less of power.~~ [This digital signal has a throughput of approximately 1.4 Mbps, which may be determined by the analog to digital A/D converter sampling rate of 44.1kHz multiplied by 16 bit quantization. To reduce the effects of channel noise, the battery powered transmitter 20 may use convolutional encoding and interleaving. For further noise immunity, spread spectrum modulation may be utilized. The battery powered transmitter 20 may contain a shift register generator (SRG) that may be used to create a unique user code. The unique user code generated is specifically associated with one FAWM user, and it is the only code recognized by the battery powered FAWM headphone receiver 50 of that particular user. The radio frequency (RF) spectrum utilized (as taken from the Industrial, Scientific and Medical (ISM) band), may be approximately 2.4 GHz. and the power radiated by the transmitter adheres to the ISM standard.]

[0012] ~~Referring to Figure 2, an audio transmitter 20 may receive an audio signal from an audio source 80. The audio transmitter 20 may be a compact device that may be connected to the audio source 80 to remain therewith for transmitting a signal to an audio receiver. An audio source 80 normally provides an analog output signal in the approximate range of 20 Hz to 20 kHz. This signal may then be processed through an analog low pass filter 30 to then be digitized by a 4 bit analog to digital (A/D) converter 32. After digital conversion of the analog audio signal, the digital signal may be processed by a digital low pass filter 34 to reduce unwanted out of band noise that may have been produced by the A/D converter 32.~~

[0013] ~~An encoder 36 may be used to reduce intersymbol interference (ISI) by using a transform code to encode the digital signal. The reduction of ISI may lower the probability of a signal detection error in the audio receiver. The digital signal may next be processed by a channel~~

~~encoder 38 and a block interleaver 40 to produce encoded redundancies in the transmitted signal to reduce errors that may occur during transmission.~~

[0014] ~~Modulation of the digital signal may be performed using direct sequence spread spectrum communication technology. A 64 Ary modulator 42 may be used for summation at summation element 46 with a transmitter code generator 44 signal to produce a high symbol rate, and a unique codeword that spreads the signal spectrum. The output of the summation element 46 may then be communicated to a differential phase shift key (DPSK) transmitter 48 that modulates the digital signal to be transmitted by an omni-directional transmitting antenna 24 at approximately 2.4 GHz. The transmit power may be limited to 100 milliwatts.~~

[0015] ~~The transmitted~~ [Referring to Figure 1, the digital modulated] signal from transmit antenna 24 may be received by receiving antenna 52 and [then demodulated, decoded and deinterleaved in the battery powered receiver 50 headphones. The battery powered receiver 50 may utilize fuzzy logic to optimize the detection of the received user code]. ~~communicated to a wideband band pass filter (BPF) 54. The received spread spectrum signal may then be communicated to a 2.4 GHz direct conversion receiver 56. The direct conversion receiver 56 may provide a method for down converting the received signal while utilizing timing and synchronization to capture the correct bit sequence embedded in the received spread spectrum signal. The audio receiver 50 may utilize fuzzy logic (or continuous logic) to optimize performance of the audio receiver 50.~~

[Each receiver 50 user may be able to listen (privately) to high fidelity audio music, using any of the audio devices listed previously, without the use of wires, and without interference from any other receiver 50 user. Because of the fuzzy logic detection technique used in the wireless digital audio system, user separation through code division may be achieved.]

[The battery powered transmitter 20 sends the audio information to the battery powered receiver 50 in digital packet format. Each packet may consist of, at minimum, a start bit to indicate the beginning of a packet, the unique user code, the digitized audio information and a stop bit to indicate the end of a packet. These packets may flow to create a digital bit stream rate less than or equal to 1 Mb/s.]

[The user code bits in each packet may be received and detected by a fuzzy logic detector in the headset receiver 50. For each consecutive packet received, the fuzzy logic detector may compute a conditional density with respect to the context and fuzziness of the user code vector,

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.