

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application No. : 12/775,310 Confirmation No. : 9888  
Applicant : Frederic S. Maxik  
Filing Date : 05/06/2010  
Group Art Unit : 2875  
Examiner : Ali Alavi  
Docket No. : LSG0347US2  
Customer No. : 23413  
Title: LOW PROFILE LIGHT

---

**REPLY TO NON-FINAL OFFICE ACTION  
UNDER 37 C.F.R. § 1.111, WITH AMENDMENT**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

**AMENDMENT**

Dear Sir:

In response to the Office Action of October 12, 2011, please amend the above-identified application as follows:

**Amendments to the Claims** are reflected in the listing of claims which begins on page 2 of this paper.

**Remarks/Arguments** begin on page 7 of this paper.

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A luminaire, comprising:  
a heat spreader and a heat sink thermally coupled to ~~and disposed diametrically outboard~~  
of the heat spreader, the heat sink being substantially ring-shaped and being disposed around and  
coupled to an outer periphery of the heat spreader;

an outer optic securely retained relative to at least one of the heat spreader and the heat  
sink; and

a light source disposed in thermal communication with the heat spreader, the light source  
comprising a plurality of light emitting diodes (LEDs) that are disposed on the heat spreader  
such that the heat spreader dissipates heat from the LEDs;

wherein the heat spreader, the heat sink and the outer optic, in combination, have an  
overall height H and an overall outside dimension D such that the ratio of H/D is equal to or less  
than 0.25;

wherein the combination defined by the heat spreader, the heat sink and the outer optic, is  
so dimensioned as to: cover an opening defined by a nominally sized four-inch can light fixture;  
and, cover an opening defined by a nominally sized four-inch electrical junction box.

2. (Original) The luminaire of Claim 1, wherein:

the heat spreader and the heat sink are integrally formed such that a heat flow path from  
the light source through the heat spreader to the heat sink is continuous and uninterrupted.

3. (Original) The luminaire of Claim 1, further comprising:

a power conditioner mechanically supported by the heat spreader, the power conditioner  
being configured and disposed to receive AC voltage from an electrical supply line and to deliver  
DC voltage to the plurality of LEDs.

4. (Original) The luminaire of Claim 3, further comprising:

a reflector disposed on the heat spreader, the reflector having an aperture in which the plurality of LEDs are disposed.

5. (Original) The luminaire of Claim 1, wherein:

the heat spreader comprises mounting holes suitably spaced apart to receive mounting fasteners to secure the heat spreader to an electrical junction box.

6. (Original) The luminaire of Claim 4, wherein:

the heat spreader comprises mounting holes and the reflector comprises mounting holes suitably spaced apart to receive mounting fasteners to secure the heat spreader to an electrical junction box.

7. (Original) The luminaire of Claim 1, further comprising:

a mounting bracket; and

a power conditioner, the power conditioner being configured and disposed to receive AC voltage from an electrical supply line and to deliver DC voltage to the plurality of LEDs;

wherein the power conditioner is supported by the mounting bracket on one side thereof, and the heat spreader and heat sink are supported by the mounting bracket on another opposing side thereof; and

wherein the mounting bracket comprises mounting holes disposed to secure the luminaire to an electrical junction box.

8. (Original) The luminaire of Claim 7, further comprising:

at least one torsion spring configured and disposed so as to secure the luminaire to a can light fixture.

9. (Original) The luminaire of Claim 3, wherein:

the power conditioner is disposed on a same side of the heat spreader as the plurality of LEDs.

10. (Original) The luminaire of Claim 3, wherein:

the power conditioner is disposed on an opposite side of the heat spreader as the plurality of LEDs, the power conditioner being so dimensioned as to fit within: a nominally sized four-inch can light fixture; and, a nominally sized four-inch electrical junction box.

11. (Original) The luminaire of Claim 1, further comprising:

an inner optic disposed over the plurality of LEDs.

12. (Original) The luminaire of Claim 11, wherein:

the inner optic is integrally formed with the reflector.

13. (Original) The luminaire of Claim 11, wherein:

the inner optic comprises a color mixing diffuser.

14. (Original) The luminaire of Claim 1, further comprising:

a phosphor disposed over the plurality of LEDs comprising material to produce a color temperature output of 2700 deg-Kelvin.

15. (Original) The luminaire of Claim 1, further comprising:

a trim ring;

wherein the outer optic is securely retained relative to at least one of the heat spreader and the heat sink via fasteners; and

wherein the trim ring snap-fits onto the outer optic in such a manner as to cover the fasteners securely retaining the outer optic.

16. (Original) The luminaire of Claim 2, wherein the heat spreader and the heat sink are integrally formed to define a base, wherein a back side of the base comprises a plurality of heat sink fins and air flow channels configured and disposed to transport heat generated by the light source away from the light source.

17. (Currently Amended) A luminaire, comprising:

a heat spreader and a ring-shaped heat sink thermally coupled to and disposed diametrically outboard of the heat spreader;

an outer optic securely retained relative to at least one of the heat spreader and the heat sink;

a light source disposed in thermal communication with the heat spreader, the light source comprising a plurality of light emitting diodes (LEDs) that are disposed on the heat spreader such that the heat spreader dissipates heat from the LEDs; and

the heat spreader, the heat sink and the outer optic define a combination having an overall height H and an overall outside dimension D such that the ratio of H/D is equal to or less than 0.25; and

a power conditioner disposed in electrical communication with the light source, the power conditioner being configured to receive AC voltage from an electrical supply line and to deliver DC voltage to the plurality of LEDs, the power conditioner being so dimensioned as to fit within at least one of: a nominally sized four-inch can light fixture; and, a nominally sized four-inch electrical junction box.

18. (Original) The luminaire of Claim 17, wherein:

the power conditioner is so dimensioned as to fit completely within at least one of: a nominally sized four-inch can light fixture; and, a nominally sized four-inch electrical junction box.

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.