


# **Snap Action Switches**

This page of product is RoHS compliant



#### ALPS SDDH SERIES: IP68 WATER RESISTANT SNAP ACTION SWITCH

- Compatible with broad rating range from weak
- to medium currents (10mA to 4.5A)

   Terminal tab (#187) pitch is 9.2mm, improving insulation

   Snap action contact mechanism provides clear-cut clicking feel

   Dimensions (WxDxH): 28.5 x 9.0 x 2.43mm

#### Applications:

- Motorbike stop lamp on/off switching
- Motorbike stop lamp on/off switching
   Power switching/detection applications in sports mobiles (e.g. buggies and personal watercraft), ship-related applications, or other applications requiring water resistance
- Power switching/detection applications in agricultural, industrial or other equipment requiring high water resistance

For quantities greater than instea, can for quote.															
MOUSER	Alps		Alps		Alps		Alps		Operating Rating		Circuit	Price Each			
STOCK NO.	Part No.	Fig.	Force	Min. Max.		Configuration	1	25	50	100					
688-SDDHA10100 SDDHA	A10100	Α	4.6N Max.	12VDC 10mA	12VDC 4.5A	SPST(Normally closed)	7.51	6.76	6.01	5.72					

#### **GRIV** HB SERIES: SINGLE POLE STANDARD PRECISION SNAP-ACTING SWITCH

Operating

13 oz./368 grams

#### Features/Benefits:

Low differential travel, high repeatability
 Long life—150,000 cycles typical
 Single and double pole circuitry
 Sealed actuator and case

MOUSER

В

- Typical Applications:
  Thermostats Industrial controls ThermostatsMotors

For quantities greater than listed, call for quote Electrical Price Each 25 Actuator Termination Rating 20A @ 125 & 250, 480VAC Stub plunger Flat base, solder 14.96 12.88

terminals & 4-40 screw

# HBS2KCB4SD011C **C**& MS SERIES: MICRO SNAP-ACTING SWITCHES

C&K

Specifications:
• Contact Form : SPDT

For quantities greater than listed, call for quote.

MOUSER	C&K	Fig.	Operating	Electrical	Actuator	Termination	Price Each			
STOCK NO.	Part No.		Force	Rating	Actuator	Termination	1	25	100	
611-MS-105A01H	MS-105A01H	С	230 gf	125 VAC	Plunger, Pin	Solder Lug	2.19	2.01	1.60	
611-MS-118305-G	MS-118305-G	D	25 gf	30VDC	Lever	PC/Wire Wrap	.83	.748	.686	
611-MS-118405-H	MS-118405-H	E	25 gf	30VDC	Lever	Solder Lug	1.11	1.01	.924	

0.25A @ 250VDC; 0.5 A @ 125VDC

#### **Call** TM SERIES: MINIATURE SNAP-ACTING SWITCHES

Features/Benefits:

Switches

Action

Snap

- Broad range of operating forces available Wide variety of actuator and terminal styles
- Cost-effective solution High electrical life up to 15A
- **Typical Applications:** 
  - Consumer appliance Pumps and motors White goods

Wide variety or actuator and term	inal styles • High electric	ai iire u	0 to 15A	Write goods		For	quantities grea	ter than listed,	call for quote.
MOUSER	MOUSER C&K STOCK NO. Part No.		Operating	Electrical	Actuator	Termination	Price Each		
STOCK NO.			Force	Rating			1	25	50
611-TMCGD6SA1040C	TMCGD6SA1040C F 2.65 oz./75 grams 1		2.65 oz./75 grams	10A @ 125 & 250VAC; 1/3HP @ 125 &	.81" lever, roller,	.187 Quick	5.75	4.43	4.26
		250		250V AC;1/2A @ 125VDC; 1/4A @ 250VDC	high force	Connect			

## **C**& ZMA SERIES: SUBMINIATURE SNAP-ACTING SWITCHES

- Features/Benefits:
- Reliable snap-acting mechanism
  Long electrical and mechanical life
  Compact size—Ideal when space is limited
- Various PCB terminals and actuators SPDT
- **Typical Applications:** 
  - Security/Alarm systems
- PCB detection switch
   Communication devices
   Testing equipment

For quantities greater than listed, call for quote

MOUSER	C&K		Operating	Electrical	A -44	Ti	<u> </u>	Price Each	
STOCK NO.	Part No.	Fig.	Force	Rating	Actuator	Termination	1	25	50
611-ZMA00A080L04RC	ZMA00A080L04RC	G	2.82 oz. / 80 grams	0.1A 30VDC	Lever 4.55mm	Right-footed, PC	1.10	1.02	.97
611-ZMA00A150P00LC	ZMA00A150P00LC	G	5.29 oz. / 150 grams	0.1A 30VDC	Pin plunger	Left-footed, PC	.99	.925	.875
611-ZMA00A150P00RC	ZMA00A150P00RC	G	5.29 oz. / 150 grams	0.1A 30VDC	Pin plunger	Right-footed, PC	.99	.925	.875
611-ZMA00A150S06LC	ZMA00A150S06LC	G	5.29 oz. / 150 grams	0.1A 30VDC	Simulated roller 2.03mm	Left-footed	1.36	1.27	1.21
611-ZMA00A150S06PC	ZMA00A150S06PC	G	5.29 oz. / 150 grams	0.1A 30VDC	Simulated roller 2.03mm	PC thru-hole	.98	.925	.881

## **C&** ZM SERIES: SUBMINIATURE SNAP-ACTING SWITCHES

#### Features/Benefits:

- Broad range of operating forces available
   Wide variety of actuator and terminal styles
- **Typical Applications:**

Pumps and motors
 White goods
 Consumer appliance

3.00

	r - F								quantities greater than listed, call for quote.				
MOUSER	MOUSER C&K STOCK NO. Part No.		Operating	Electrical	Actuator	Termination	Price Each						
STOCK NO.			Force Rating	Rating		remination	1	25	50				
611-ZMCHF7L3K	ZMCHF7L3K	Н	90 grams	3A, 125VAC	Leaf	PC thru-hole with retention feature	1.53	1.34	1.25				
611-ZMCHF7T23T	ZMCHF7T23T	H	90 grams	3A, 125VAC	Simulated roller	PC thru-hole	1.74	1.61	1.53				
611-ZMCHM9T23K	ZMCHM9T23K	H	90 grams	0.2A, 60VDC	Simulated roller	PC thru-hole with retention feature	2.14	2.00	1.95				
611-ZMCHM9T23T	ZMCHM9T23T	Н	90 grams	0.2A, 60VDC	Simulated roller	PC thru-hole	2.01	1.74	1.64				
611-ZMCJF7L0K	ZMCJF7L0K	н	150 grams	3A, 125VAC	Leaf	PC thru-hole with retention feature	1.67	1.43	1.34				
611-7MC IE7T13I	ZMC IEZT13I	ΙнΙ	150 grame	3A 125VAC	Simulated roller	Left-footed PC thru-hole	2 1 2	1.85	1 73				

### **C**<sub>&</sub>**K** ZMS SERIES: SUBMINIATURE SNAP-ACTING SWITCH (DUST PROOF)

### Features/Benefits:

MOUSER

- Reliable snap-acting mechanism
   Long electrical and mechanical life
   Compact size–Ideal when space is limited
- Various PCB terminals and actuators
   IP67 on some models

ZMSL00130T11LLC I 130 grams / 4.59

C&K

- Typical Applications:
   PCB detection switch
   Communication devices
   Testing equipment
  - Security/Alarm systems

10mA @ 12VDC

ntities greater than listed, call for quote Operating Electrical Price Each Actuator Termination Force Rating

.28 simulated roller Left form, PC thru-hole

