

USB 2.0 Specification Engineering Change Notice (ECN) #1: Mini-B connector

Date: 10/20/2000

Reason for ECN:

The USB 2.0 specified device-side connector – the B connector – is too large for use with a new generation of handheld and mobile devices, e.g., cell phones which would benefit from connectivity to the PC. This ECN incorporates a specification of a device-side mini connector (hereafter referred to as a mini-B connector). The new connector only applies to upstream facing ports, i.e., connectors on devices.

Summary of ECN:

The bulk of the ECN specifies the mechanical requirements for the mini-B plug, receptacle and cable assembly. It also identifies the usage scope of this connector. The last part of the ECN describes the minimum test criteria and performance requirements for the new connector.

Benefits of ECN:

The ECN enables standardization of miniature device-side USB connectors and consequent economies of scales and lower cost for a new and growing class of devices which will benefit from connectivity to the PC. The standardization also allows leveraging of the compliance test and certification model which is already in place for USB connectors.

Assessment of Impact on Current Specification and Current USB Products:

The connector specified in the ECN will not have any impact on hardware or software of existing USB products. The current USB spec already allows for vendor-specific device side connectors – such cable assemblies are called captive assemblies. All that the ECN does is to identify one such connector for use in devices which need the smaller size of connector. There is a potential for some end-user confusion because of two standard cable options; but this can be mitigated by appropriate end-user education.

Structure of ECN:

The ECN is in the form of a new Chapter 6 with the mini-B connector requirements inserted into the appropriate locations. This format enables specification of the new connector in context.

Chapter 6 Mechanical

This chapter provides the mechanical and electrical specifications for the cables, connectors, and cable assemblies used to interconnect USB devices. The specification includes the dimensions, materials, electrical, and reliability requirements. This chapter documents minimum requirements for the external USB interconnect. Substitute material may be used as long as it meets these minimums.

6.1 Architectural Overview

The USB physical topology consists of connecting the downstream hub port to the upstream port of another hub or to a device. The USB can operate at three speeds. High-speed (480 Mb/s) and full-speed (12 Mb/s) require the use of a shielded cable with two power conductors and twisted pair signal conductors. Low-speed (1.5 Mb/s) recommends, but does not require the use of a cable with twisted pair signal conductors.

The connectors are designed to be hot plugged. The USB Icon on the plugs provides tactile feedback making it easy to obtain proper orientation.

6.2 Keyed Connector Protocol

To minimize end user termination problems, USB uses a “keyed connector” protocol. The physical difference in the Series “A” and “B” (or “mini-B”) connectors insures proper end user connectivity. The “A” connector is the principle means of connecting USB devices directly to a host or to the downstream port of a hub. All USB devices must have the standard Series “A” connector specified in this chapter. The “B” (or “mini-B”) “B” connector allows device vendors to provide a standard detachable cable. This facilitates end user cable replacement. Figure 6-1~~Figure 6-1~~ illustrates the keyed connector protocol.







Series "A" Connectors	Series "B" Connectors
<p>◆ Series "A" plugs are always oriented upstream towards the <i>Host System</i></p>  <p>"A" Plugs (From the USB Device)</p> <p>"A" Receptacles (Downstream Output from the USB Host or Hub)</p> 	<p>◆ Series "B" plugs are always oriented downstream towards the <i>USB Device</i></p>  <p>"B" Plugs (From the Host System)</p> <p>"B" Receptacles (Upstream Input to the USB Device or Hub)</p> 
	<p>Series "mini-B" Connectors</p> <p>◆ Series "mini-B" plugs are always oriented downstream towards the <i>USB Device</i></p>  <p>"mini-B" Plugs (From the Host System)</p> <p>"mini-B" Receptacles (Upstream Input to the USB Device or Hub)</p> 

Figure 6-1. Keyed Connector Protocol

Universal Serial Bus Specification Revision 2.0

The following list explains how the plugs and receptacles can be mated:

- Series “A” receptacle mates with a Series “A” plug. Electrically, Series “A” receptacles function as outputs from host systems and/or hubs.
- Series “A” plug mates with a Series “A” receptacle. The Series “A” plug always is oriented towards the host system.
- Series “B” receptacle mates with a Series “B” plug (male). Electrically, Series “B” receptacles function as inputs to hubs or devices.
- Series “B” plug mates with a Series “B” receptacle. The Series “B” plug is always oriented towards the USB hub or device.
- Series “mini-B” receptacle mates with a Series “mini-B” plug (male). Electrically, Series “mini-B” receptacles function as inputs to hubs or devices.
- Series “mini-B” plug mates with a Series “mini-B” receptacle. The Series “mini-B” plug is always oriented towards the USB hub or device.

6.3 Cable

USB cable consists of four conductors, two power conductors, and two signal conductors.

High-/full-speed cable consists of a signaling twisted pair, VBUS, GND, and an overall shield. High-/full-speed cable must be marked to indicate suitability for USB usage (see Section 6.6.2). High-/full-speed cable may be used with either low-speed, full-speed, or high-speed devices. When high-/full-speed cable is used with low-speed devices, the cable must meet all low-speed requirements.

Low-speed recommends, but does not require the use of a cable with twisted signaling conductors.

6.4 Cable Assembly

This specification describes three USB cable assemblies: standard detachable cable, high-/full-speed captive cable, and low-speed captive cable.

A standard detachable cable is a high-/full-speed cable that is terminated on one end with a Series “A” plug and terminated on the opposite end with a series “B” (or “mini-B”) “B” plug. A high-/full-speed captive cable is terminated on one end with a Series “A” plug and has a vendor-specific connect means (hardwired or custom detachable) on the opposite end for the high-/full-speed peripheral. The low-speed captive cable is terminated on one end with a Series “A” plug and has a vendor-specific connect means (hardwired or custom detachable) on the opposite end for the low-speed peripheral. Any other cable assemblies are prohibited.

The color used for the cable assembly is vendor specific; recommended colors are white, grey, or black.

6.4.1 Standard Detachable Cable Assemblies

High-speed and full-speed devices can utilize the “B” (or “mini-B”) “B” connector. This allows the device to have a standard detachable USB cable. This eliminates the need to build the device with a hardwired cable and minimizes end user problems if cable replacement is necessary.

Devices utilizing the “B” (or “mini-B”) “B” connector must be designed to work with worst case maximum length detachable cable. Standard detachable cable assemblies may be used only on high-speed and full-speed devices. Using a high-/full-speed standard detachable cable on a low-speed device may exceed the maximum low-speed cable length.

Figure 6-2 ~~Figure 6-2~~ and Figure 6-3 illustrates a standard detachable cable assemblyiesy.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.