PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G05D 1/02	**A1**	(11) International Publication Number: **WO 00/04430** (43) International Publication Date: 27 January 2000 (27.01.00)

(21) International Application Number: PCT/US99/16078

(22) International Filing Date: 16 July 1999 (16.07.99)

(30) Priority Data:
98305761.3   20 July 1998 (20.07.98)   EP

(71) Applicant *(for all designated States except US)*: THE PROC-TER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: BOTTOMLEY, Ian [GB/GB]; 17 Howick Street, Alnwick, Northumberland NE66 1UZ (GB). COATES, David [GB/GB]; 14 Percy Road, Shilbottle, Northumberland NE66 2HF (GB). GRAY-DON, Andrew, Russell [GB/GB]; 42 The Wills Building, Wills Oval, Newcastle–upon–Tyne NE7 7RW (GB).

(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217–1087 (US).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.

---

(54) Title: ROBOTIC SYSTEM

(57) Abstract

A self–propelled robot is disclosed for movement over a surface to be treated. The robot has a power supply (11) and a pair of wheels (8,9) driven by motors (6, 7) for moving the robot over the ssurface. A mechanism (113, 115, 16) is provided for controllably depositing a fluent material onto the surface. Navigation sensors (4, 13, 18, 21) provide signals for enabling the robot to navigate over the surface and one or more detectors (14, 15, 17) detect the presence of the material on the surface and provide signals indicative of its presence. A control system (100) receives the signals from the sensors and detectors and controls the motors and the depositing mechanism in dependence upon the signals received from the sensors and detectors.

ROBOTIC SYSTEM

The present invention relates to robotic systems and, more particularly to a mobile robotic system capable of movement over a surface and capable of treating the surface.

Conventionally robotic systems, or robots, of this type may be described as semi-autonomous, i.e. self-propelling but relying for navigational guidance on transmitters, receivers and sensors to establish a coordinate system by which the robot navigates, in effect learning the location of obstacles within its field of movement. More recently it has been proposed to allow a robot to move without establishing a coordinate system, instead relying on the sensing of *ad hoc* stimuli to enable the robot to navigate around obstacles. For example, it has been proposed to provide a robotic vacuum cleaner operating along these lines. Self-navigational robotic systems of this type are referred to as autonomous robots.

However, robots of these types, often intended for operation in a domestic environment, need a control system which is capable of allowing the robot to move around its environment in safety and therefore additionally need some sort of collision detection system which is capable of providing information on collisions or impending collisions to a control system capable of acting very quickly to prevent the collision or else to minimise the impact, and to perform collision avoidance by re-orienting the robot before further movement. Unfortunately, on-board processing power is inevitably limited by cost constraints in particular and therefore present systems, to avoid be prohibitively expensive, have relatively limiting navigational abilities which result, in use, in the robot tracing a path which involves passing over the same areas of the surface on plural occasions. Whilst this may not be problematic in say a vacuum cleaner, if the robot has the

function of treating the surface in other ways, then such
redundant movement may result in over-treatment of the
surface which is not only wasteful of the product used for
the treatment (a serious problem where the payload is
restricted), but may also damage the surface or otherwise
actually be harmful.

The present invention is aimed at providing a self-
propelled robot which can overcome such problems.

According to the present invention, there is provided
a self-propelled robot for movement over a surface to be
treated, the robot comprising

a power supply;

a traction mechanism receiving power from the power
supply, for moving the robot over the surface;

a mechanism for controllably depositing a fluent
material on to the surface;

a plurality of navigation sensors providing signals
for enabling the robot to navigate over the surface;

one or more detectors adapted to detect the presence
of the material on the surface and provide signals
indicative thereof; and

a control system receiving the signals from the
sensors and detectors, for controlling the traction
mechanism and the depositing mechanism in dependence upon
the signals received from the sensors and detectors.

By detecting the application of the fluent material,
which may be a liquid or gaseous fluid or else a flowable
powder, the over-application of material can be avoided or
minimised by either navigating the robot around areas
already treated and/or by controlling the depositing
mechanism to stop the deposit of material over such
previously treated areas.

Material for treatment is preferably contained within
a reservoir on the robot and may comprise suitable
compositions for treatment of floors, carpets and other
floor coverings. The robot may, if desired, also include

means for cleaning the floor or floor covering prior to treatment, for example in the form of a vacuum cleaning device.

The invention also includes a method of treating a surface using a robot as defined above. The treatment method may be used for various applications on carpets, and other floor coverings, such as cleaning, protective treatment, for example for stain and soil protection, fire protection, UV protection, wear resistance, dust mite control, anti microbial treatment and the like, as well as treatment to provide an aesthetic benefit such as odorization/deodorization. The treatment method may also find application on other surfaces such as synthetic floor coverings, ceramics or wood. As well as polishing hard surfaces, the robot may also be used to apply coatings to either enhance aesthetics or to act as a protective layer.

Thus, according to a further aspect of the invention, there is provided a method for controllably depositing a fluent material on to floors, carpets and other floor coverings using an autonomous, self propelled, deposition-sensing robot. The material deposited may, for example, be a carpet cleaning composition, a hard surface cleaning composition, or one of a number of compositions applied simultaneously, or successively, and may include a marker, the presence of which can be detected to provide detection of the extent of treatment material deposition. Such a marker may have a limited detection life, for example, 12, 24 or 48 hours.

Non-visible treatment may also be provided by the robot of the invention, for example, for odour control, antibacterial action of dust mite control.

The robot preferably comprises a plurality of navigation sensors providing signals for enabling the robot to navigate over the surface, and one or more detectors adapted to detect the presence of the material on the surface and provide signals indicative thereof. The

DOCKET ALARM

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts

Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research

With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips

Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.