

What is ID3v2?


ID3v2 is a new tagging system that lets you put enriching and relevant information about your audio files within them. In more down to earth terms, ID3v2 is a chunk of data prepended to the binary audio data. Each ID3v2 tag holds one or more smaller chunks of information, called frames. These frames can contain any kind of information and data you could think of such as title, album, performer, website, lyrics, equalizer presets, pictures etc. The block scheme to the right is an example of how the layout of a typical ID3v2 tagged audio file may look like.

One of the design goals were that the ID3v2 should be very flexible and expandable. It is very easy to add new functions to the ID3v2 tag, because, just like in HTML, all parsers will ignore any information they don't recognize. Since each frame can be 16MB and the entire tag can be 256MB you'll probably never again be in the same situation as when you tried to write a useful comment in the old ID3 being limited to 30 characters.

Speaking of characters, the ID3v2 supports Unicode so even if you use the Bopomofo character set you'll be able to write in your native language. You can also include in which language you're writing so that one file might contain e.g. the same lyrics but in different languages.

Even though the tag supports a lot of byte consuming capabilities like inline pictures and even the possibility to include any other file, ID3v2 still tries to use the bytes as efficient as possibly. If you convert an ID3v1 tag to an ID3v2 tag it is even likely that the new tag will be smaller. If you convert an ID3v1 tag where all fields are full (that is, all 30 characters are used in every field) to an ID3v2 tag it will be 56 bytes bigger. This is the worst case scenario for ID3v1 to ID3v2 conversion.

Since it's so easy to implement new functionality into ID3v2, one can hope that we'll see a lot of creative uses for ID3v2 in the future.



Example of the internal layout of an ID3v2 tagged file.

http://www.id2.org/oper.html

5/12/2003

E.g. there is a built-in system for rating the music and counting how often you listen to a file, just to mention some brainstorm results that are included. This feature can be used to build playlists that play your favourite songs more often than others.

Some main features

- The ID3v2 tag is a container format, just like IFF or PNG files, allowing new frames (chunks) as evolution proceeds.
- Residing in the beginning of the audio file makes it suitable for streaming.
- Has an 'unsynchronization scheme' to prevent ID3v2-incompatible players to attempt to play the tag.
- Maximum tag size is 256 megabytes and maximum frame size is 16 megabytes.
- Byte conservative and with the capability to compress data it keeps the files small.
- The tag supports Unicode.
- Isn't entirely focused on musical audio, but also other types of audio.
- Has several new text fields such as composer, conductor, media type, BPM, copyright message, etc. and the possibility to design your own as you see fit.
- Can contain lyrics as well as music-synced lyrics (karaoke) in almost any language.
- Is able to contain volume, balance, equalizer and reverb settings.
- Could be linked to CD-databases such as CDDB.
- Is able to contain images and just about any file you want to include.
- Supports enciphered information, linked information and weblinks.
- and more... (a complete list of all frames and their functions can be found here)

سريرف تبلد فيزيشونها ه

This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problems Mailbox.

Informal standard Document: id3v2.3.0.html

M. Nilsson 3rd February 1999

ID3 tag version 2.3.0

Status of this document

This document is an informal standard and replaces the ID3v2.2.0 standard. The informal standard is released so that implementors could have a set standard before a formal standard is set. The formal standard will use another version or revision number if not identical to what is described in this document. The contents in this document may change for clarifications but never for added or altered functionallity.

Distribution of this document is unlimited.

Abstract

This document describes the ID3v2.3.0, which is a more developed version of the ID3v2 informal standard (version 2.2.0), evolved from the ID3 tagging system. The ID3v2 offers a flexible way of storing information about an audio file within itself to determine its origin and contents. The information may be technical information, such as equalisation curves, as well as related meta information, such as title, performer, copyright etc.

1. Table of contents

2. Conventions in this document

3. ID3v2 overview

- 3.1. ID3v2 header
- 3.2. ID3v2 extended header
- 3.3. ID3v2 frames overview
 - 3.3.1. Frame header flags
 - 3.3.2. Default flags

4. Declared ID3v2 frames

- 4.1. Unique file identifier
- 4.2. Text information frames
 - 4.2.1. Text information frames details
 - 4.2.2. User defined text information frame
- 4.3. URL link frames
 - 4.3.1. URL link frames details
 - 4.3.2. User defined URL link frame
- 4.4. Involved people list
- 4.5. Music CD Identifier
- 4.6. Event timing codes

http://www.id3.org/id3v2.3.0.html

5/12/2003

4.7. MPEG location lookup table

4.8. Synced tempo codes

4.9. Unsychronised lyrics/text transcription

4.10. Synchronised lyrics/text

4.11. Comments

4.12. Relative volume adjustment

4.13. Equalisation

4.14. Reverb

4.15. Attached picture

4.16. General encapsulated object

4.17. Play counter

4.18. Popularimeter

4.19. Recommended buffer size

4.20. Audio encryption

4.21. Linked information

4.22. Position synchronisation frame

4.23. Terms of use

4.24. Ownership frame

4.25. Commercial frame

4.26. Encryption method registration

4.27. Group identification registration

4.28. Private frame

5. The 'unsynchronisation scheme'

6. Copyright

7. References

8. Appendix

A. Appendix A - Genre List from ID3v1

9. Author's Address

2.Conventions in this document

In the examples, text within "" is a text string exactly as it appears in a file. Numbers preceded with \$ are hexadecimal and numbers preceded with % are binary. \$xx is used to indicate a byte with unknown content. %x is used to indicate a bit with unknown content. The most significant bit (MSB) of a byte is called 'bit 7' and the least significant bit (LSB) is called 'bit 0'.

A tag is the whole tag described in this document. A frame is a block of information in the tag. The tag consists of a header, frames and optional padding. A field is a piece of information; one value, a string etc. A numeric string is a string that consists of the characters 0-9 only.

3.ID3v2 overview

The two biggest design goals were to be able to implement ID3v2 without disturbing old software too much and that ID3v2 should be as flexible and expandable as possible.

The first criterion is met by the simple fact that the MPEG decoding software uses a syncsignal, embedded in the audiostream, to 'lock on to' the audio. Since the

++m.//----- : d? ---/: d?-.? ? A 1-+m.

5/10/0003

DOCKET A L A R M



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.