

(51) International Patent Classification ⁶ :

A61M 5/315, 5/24

A1

(11) International Publication Number:

WO 99/38554

(43) International Publication Date:

5 August 1999 (05.08.99)

(21) International Application Number: PCT/DK99/00042

(22) International Filing Date: 28 January 1999 (28.01.99)

(30) Priority Data:
PA 1998 00130 30 January 1998 (30.01.98) DK

(71) Applicant: NOVO NORDISK A/S [DK/DK]; Novo Allé, DK-2880 Bagsværd (DK).

(72) Inventors: STEENFELDT-JENSEN, Søren; Holmevænget 2B, DK-3100 Hornbæk (DK). HANSEN, Steffen; Gl. Frederiksborgvej 64A, DK-3400 Hillerød (DK).

(74) Agent: NOVO NORDISK A/S; Corporate Patents, Novo Allé, DK-2880 Bagsværd (DK).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: AN INJECTION SYRINGE

(57) Abstract

In an injection syringe comprising a housing (1), a piston rod (6) with a not circular cross section and an outer thread (7), a piston rod drive comprising a piston rod guide (85) mating the cross section of the piston rod (6) and a nut (4) which is not axially displaceable and mates the thread (7) of the piston rod (6) to form a self locking thread connection, and a dose setting mechanism comprising a not self locking thread connection along which an injection button by rotation of a dose setting element (81) is screwed out to project from the housing (1) and which thread connection by axial returning of the injection button (88) transforms this axial movement into a rotation of one of the piston drive elements (85) relative to the other one (4). A unidirectional coupling between the nut member (4) and the piston rod guide (85) allows rotation in one direction by which the piston rod (6) is transported in a distal direction. The coupling has an initial reluctance to be overcome before rotation takes place said reluctance being large enough to resist torques exerted during the dose setting.



Sanofi Exhibit 2153.001

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Sanofi Exhibit 2153.002

An injection syringe

5 The invention relates to injection syringes of the kind apportioning set doses of a medicine from a cartridge containing an amount of medicine sufficient for the preparation of a number of therapeutic doses.

10 Such syringes are mainly made for users who have to inject themselves frequently, e. g. diabetics. A number of demands are set to such syringes. The setting of a dose must be easy an unambiguous and it must be easy to read the set dose. It must be possible with a minimum of trouble to cancel or change a wrongly set dose and when the dose is injected the dose setting must return to zero. When a disposable syringe is in question, i.e. a syringe which is disposed of when the cartridge is empty, the syringe must further be cheap and made of materials suited for recycling or burning without producing noxious gases. For these purposes the number of parts from which the syringe is constructed and the number of different kinds of materials used in the syringe should be kept at a minimum.

20 Most dose setting devices work with a threaded piston rod co-operating with a nut where the nut and the piston rod may be rotated relative to each other. The dose setting may be obtained by screwing the nut away from a stop to which it is returned during the injection by pressing the piston rod until the nut member abuts the stop. By other dose setting devices one of the elements, the nut or the piston rod, is kept inrotatable and the other is allowed to rotate a set angle depending on the set dose, whereby the piston rod is screwed a distance through the nut.

25 In most syringes for apportioning set doses it is preferred that the piston rod is backing up the piston upon which it works during the injection. To obtain this precaution is taken to prevent the piston rod from moving in a proximal direction.

30 The syringe according to EP 327 910 is of the type wherein a nut is screwed away from a stop. During the setting of the dose the screwing may be performed in both direction so that a too large set dose may be lowered just by rotating the nut in an opposite direction. Means are provided preventing that negative doses are set. The mutual rotation of the piston rod and the nut is obtained by rotating a cap relative to the pen housing and a set dose may be

read on a scale and a pointer provided at adjacent edges of the housing and the cap, these edges being so shaped that the cap can only be mounted firmly on the housing when the pointer points zero on the scale. It may be seen as a weak point that doses larger than the one obtained by rotating the parts 360° must be calculated by adding the number pointed at
5 on the scale and a number printed on the side of a tubular extension of the nut which is moved out from the proximal end of the housing proportionally with the dose set and which tubular extension is closed at its proximal end to form an injection button.

10 In EP 450 905 the above drawback is overcome by writing the numbers along a helical line on a tubular extension of the nut so that these numbers may successively be seen in a window in a housing element enclosing said tubular extension. Hereby the size of the dose is indicated unambiguously but the user has to remember to set the dose setting device on zero before the next setting of a dose is performed. If this is forgotten a wrong dose may be set and the number may not be seen clearly in the window.

15

In EP 608 343 is described a pen having a dose setting mechanism wherein the dose is set by rotating a button relative to a housing to set a dose. By the rotation the button is screwed up from the end of the housing in a thread having a pitch so large that the thread connection is not self blocking, i. e. when the button is pressed back to the end of the housing it will rotate back in the thread. The button is through a ratchet coupled to a driver, the ratchet forming a unidirectional coupling which during the rotation of the button in one direction to set a dose rides or clicks over the teeth of the ratchet. The cylindrical side of the button carries
20 numbers which shows the size of the set dose in a window when the button is screwed outward. When the button is screwed back the unidirectional coupling will transmit the rotation to the driver which has a nut co-operating with a threaded piston rod which is made inrotatable in a housing. This thread connection has a pitch which makes the nut self locking on the piston rod. A set dose may be cancelled by drawing the engaging parts of the ratchet out of engagement against the force of a spring so that the rotation of the button is not transmitted to the driver and then press the button back to the housing. This pen fulfils all the
25 objects mentioned only the dose cancelling procedure is a little troublesome as the dose set button cannot as it will come most naturally just be screwed back if a too large dose is set. Concomitantly forcing the coupling parts apart against the force of the spring and pressing or screwing the button back may be a little difficult and the demand for a spring necessitates use of metal parts in the syringe.

It is an object of the invention to provide a syringe which has the mentioned advantageous features without having the drawbacks known from existing syringes.

5 This is obtained by an injection syringes for apportioning set doses of a medicine from a cartridge containing an amount of medicine sufficient for the preparation of a number of therapeutic doses, comprising

a housing

10

a piston rod having a not circular cross-section and an outer thread

a piston rod drive comprising two elements

15 a) a piston rod guide in relation to which the piston rod is axially displaceable but not rotatable, and

b) a nut member which is rotatable but not axially displaceable in the housing and which has an inner thread mating the thread of the piston rod to form a self locking thread connection,

20

a dose setting mechanism comprising a not self locking thread connection along which an injection button by rotation of a dose setting element relative to said housing is screwed out from the proximal end of the housing to project from this proximal end a distance determined by the angle of said rotation and which thread connection by axial returning of the injection button transforms this axial movement to a rotation of one of the piston drive elements relative to the other,

25

which syringe according to the invention is characterised in that

30

a unidirectional coupling is provided between the nut member and the piston rod guide allowing rotation of these parts relative to each other in one direction but not in the opposite direction, the allowed rotation being one by which the piston rod is transported in a distal di-

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.