

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application No. : 13/590,423 Confirmation No. 9482  
Applicant : Aleksandar Modrag Tasic  
Filed : August 21, 2012  
Art Unit : 2631  
Examiner : Khanh C. Tran  
Docket No. : 121973  
Customer No. : 23696

**RESPONSE**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

In response to an Office Action dated August 1, 2014, please amend the above-identified application as follows:

**Amendments to the Claims** are reflected in the listing of claims which begins on page 2 of this paper.

**Remarks/Arguments** begin on page 7 of this paper.

**Amendments to the Claims:**

Please note that all claims currently pending and under consideration in the referenced application are shown below. This listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims:**

1. (Previously presented) An apparatus comprising:
  - a first amplifier stage configured to receive and amplify an input radio frequency (RF) signal and provide a first output RF signal to a first load circuit when the first amplifier stage is enabled, the input RF signal employing carrier aggregation comprising transmissions sent on multiple carriers at different frequencies to a wireless device, the first output RF signal including at least a first carrier of the multiple carriers; and
  - a second amplifier stage configured to receive and amplify the input RF signal and provide a second output RF signal to a second load circuit when the second amplifier stage is enabled, the second output RF signal including at least a second carrier of the multiple carriers different than the first carrier.
2. (Original) The apparatus of claim 1, the first amplifier stage comprising a first gain transistor coupled to a first cascode transistor, the second amplifier stage comprising a second gain transistor coupled to a second cascode transistor, and the input RF signal being provided to both the first and second gain transistors.
3. (Original) The apparatus of claim 2, the first amplifier stage further comprising a first inductor coupled to the first gain transistor, and the second amplifier stage further comprising a second inductor coupled to the second gain transistor.

4. (Original) The apparatus of claim 2, the first and second gain transistors having sources coupled to circuit ground.
5. (Original) The apparatus of claim 2, the first and second amplifier stages providing the first and second output RF signals in a first mode and providing the first output RF signal but not the second output RF signal in a second mode, the first and second cascode transistors being enabled in the first mode, and only one of the first and second cascode transistors being enabled in the second mode.
6. (Original) The apparatus of claim 5, the first and second gain transistors being applied the input RF signal in both the first mode and the second mode, and one of the first and second gain transistors operating in a saturation region and the other one of the first and second gain transistors operating in a linear region in the second mode.
7. (Original) The apparatus of claim 1, further comprising:  
a feedback circuit coupled between an output and an input of at least one of the first and second amplifier stages.
8. (Original) The apparatus of claim 7, the feedback circuit comprising a resistor, or a capacitor, or both a resistor and a capacitor.
9. (Original) The apparatus of claim 1, further comprising:  
a first attenuation circuit coupled to the first amplifier stage and configured to receive the input RF signal; and  
a second attenuation circuit coupled to the second amplifier stage and configured to receive the input RF signal.
10. (Original) The apparatus of claim 1, further comprising:  
an attenuation circuit coupled to the first and second amplifier stages and configured to

receive the input RF signal.

11. (Original) The apparatus of claim 1, further comprising:
  - an input matching circuit coupled to the first and second amplifier stages and configured to receive a receiver input signal and provide the input RF signal.
12. (Original) The apparatus of claim 11, the input matching circuit being tunable and comprising at least one adjustable circuit component.
13. (Original) The apparatus of claim 1, further comprising:
  - a third amplifier stage configured to receive and amplify a second input RF signal and provide the first output RF signal to the first load circuit when the third amplifier stage is enabled; and
  - a fourth amplifier stage configured to receive and amplify the second input RF signal and provide the second output RF signal to the second load circuit when the fourth amplifier stage is enabled.
14. (Original) The apparatus of claim 1,
  - the first amplifier stage configured to receive and amplify the input RF signal or a second input RF signal and provide the first output RF signal to the first load circuit when the first amplifier stage is enabled, and
  - the second amplifier stage configured to receive and amplify the input RF signal or the second input RF signal and provide the second output RF signal to the second load circuit when the second amplifier stage is enabled.
15. (Original) The apparatus of claim 2, the first amplifier stage further comprising a third gain transistor coupled to a third cascode transistor, the second amplifier stage further comprising a fourth gain transistor coupled to a fourth cascode transistor, and a second input RF signal being provided to both the third and fourth gain transistors.

16. (Original) The apparatus of claim 14, further comprising:
- a third amplifier stage configured to receive and amplify a third input RF signal or a fourth input RF signal and provide the first output RF signal to the first load circuit when the third amplifier stage is enabled; and
  - a fourth amplifier stage configured to receive and amplify the third input RF signal or the fourth input RF signal and provide the second output RF signal to the second load circuit when the fourth amplifier stage is enabled.
17. (Previously presented) A method comprising:
- amplifying a first input radio frequency (RF) signal with a first amplifier stage to obtain a first output RF signal when the first amplifier stage is enabled, the first input RF signal employing carrier aggregation comprising transmissions sent on multiple carriers at different frequencies to a wireless device, the first output RF signal including at least a first carrier of the multiple carriers; and
  - amplifying the first input RF signal or a second input RF signal with a second amplifier stage to obtain a second output RF signal when the second amplifier stage is enabled, the second output RF signal including at least a second carrier of the multiple carriers different than the first carrier.
18. (Original) The method of claim 17, further comprising:
- enabling the first and second amplifier stages in a first mode to obtain the first and second output RF signals; and
  - enabling the first amplifier stage and disabling the second amplifier stage in a second mode to obtain the first output RF signal but not the second output RF signal.

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.