3GPP TS 36.101 V11.0.0 (2012-03)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception (Release 11)





The present document has been developed within the 3rd Generation Partnership Project (3GPP TM) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented



_____Keywords radio

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© 2012, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).


All rights reserved.

UMTSTM is a Trade Mark of ETSI registered for the benefit of its members 3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTETM is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association



Contents

Forew	ord	13
1	Scope	14
2	References	14
3	Definitions, symbols and abbreviations	14
3.1	Definitions	
3.2	Symbols	
3.3	Abbreviations	17
4	General	18
4.1	Relationship between minimum requirements and test requirements	18
4.2	Applicability of minimum requirements	18
4.3	Void	18
4.3A	Applicability of minimum requirements (CA, UL-MIMO, eDL-MIMO)	18
4.4	RF requirements in later releases	19
5	Operating bands and channel arrangement	19
5.1	General	
5.2	Void	19
5.3	Void	19
5.4	Void	
5.5	Operating bands	
5.5A	Operating bands for CA	
5.5B	Operating bands for UL-MIMO	
5.6	Channel bandwidth	
5.6.1	Channel bandwidths per operating band	
5.6A	Channel bandwidth for CA	
5.6A.1	1 1 6	
5.6B	Channel bandwidth for UL-MIMO	
5.6B.1 5.7	Channel bandwidths per operating band for UL-MIMO	
5.7.1	Channel arrangement	
5.7.1A	1 0	
5.7.1A 5.7.2	Channel raster	
5.7.2A		
5.7.2A 5.7.3	Carrier frequency and EARFCN	
5.7.4	TX–RX frequency separation	
5.7.4A		
•		
6 6.1	Transmitter characteristics	
6.2	Transmit power	
6.2.1	Void	
6.2.2	UE maximum output power	
6.2.2A	1 1	
6.2.2B		
6.2.3	UE maximum output power for modulation / channel bandwidth	
6.2.3A		
6.2.3B		
6.2.4	UE maximum output power with additional requirements	
6.2.4A		
6.2.4A	.1 A-MPR for CA_NS_01 for CA_1C	37
6.2.4A	.2 A-MPR for CA_NS_02 for CA_1C	38
6.2.4A		38
6.2.4A	.4 A-MPR for CA_NS_04	38
6.2.4B		
6.2.5	Configured transmitted power	39



6.2.5A	Configured transmitted power for CA	
6.2.5B	Configured transmitted power for UL-MIMO	4
6.3	Output power dynamics	4
6.3.1	(Void)	4
6.3.2	Minimum output power	4
6.3.2.1	Minimum requirement	
6.3.2A	UE Minimum output power for CA	
6.3.2A.1	Minimum requirement for CA	
6.3.2B	UE Minimum output power for UL-MIMO	
6.3.2B.1	Minimum requirement	
6.3.3	Transmit OFF power	
6.3.3.1.	Minimum requirement	
6.3.3A	UE Transmit OFF power for CA	
6.3.3A.1	Minimum requirement for CA	
6.3.3B	UE Transmit OFF power for UL-MIMO	
6.3.3B.1	Minimum requirement	
6.3.4	ON/OFF time mask	
6.3.4.1	General ON/OFF time mask	
6.3.4.2	PRACH and SRS time mask	
6.3.4.2.1	PRACH time mask	
6.3.4.2.2 6.3.4.3	SRS time mask	
	Slot / Sub frame boundary time mask	
6.3.4.4	PUCCH / PUSCH / SRS time mask	
6.3.4A	ON/OFF time mask for CA	
6.3.4B	ON/OFF time mask for UL-MIMO	
6.3.5	Power Control	
6.3.5.1	Absolute power tolerance	
6.3.5.1.1	Minimum requirements	
6.3.5.2	Relative Power tolerance	
6.3.5.2.1	Minimum requirements	
6.3.5.3	Aggregate power control tolerance	
6.3.5.3.1	Minimum requirement	
6.3.5A	Power control for CA	52
6.3.5A.1	Absolute power tolerance	52
6.3.5A.1.1	Minimum requirements	52
6.3.5A.2	Relative power tolerance	5.
6.3.5A.2.1	Minimum requirements	5
6.3.5A.3	Aggregate power control tolerance	
6.3.5A.3.1		
6.3.5B	Power control for UL-MIMO	
6.4	Void	
6.5	Transmit signal quality	5
6.5.1	Frequency error	5
6.5.1A	Frequency error for CA	
6.5.1B	Frequency error for UL-MIMO	
6.5.2	Transmit modulation quality	
6.5.2.1	Error Vector Magnitude	
6.5.2.1.1	Minimum requirement	
6.5.2.2	Carrier leakage	
6.5.2.2.1	Minimum requirements	
6.5.2.3	In-band emissions	
6.5.2.3.1	Minimum requirements	
6.5.2.4	EVM equalizer spectrum flatness	
6.5.2.4.1	1 1	
	Minimum requirements	
6.5.2A	Transmit modulation quality for CA	
6.5.2A.1	Error Vector Magnitude	
6.5.2A.2	Void	
6.5.2A.3	In-band emissions	
6.5.2A.3.1		
6.5.2B	Transmit modulation quality for UL-MIMO	
6.5.2B.1	Error Vector Magnitude	59



6.5.2B.2	Carrier leakage	
6.5.2B.3	In-band emissions	
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	59
6.6	Output RF spectrum emissions	59
6.6.1	Occupied bandwidth	
6.6.1A	Occupied bandwidth for CA	
6.6.1B	Occupied bandwidth for UL-MIMO	
6.6.2	Out of band emission	60
6.6.2.1	Spectrum emission mask	60
6.6.2.1.1	Minimum requirement	60
6.6.2.1A	Spectrum emission mask for CA	61
6.6.2.2	Additional spectrum emission mask	
6.6.2.2.1	Minimum requirement (network signalled value "NS_03" and "NS_11")	
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	62
6.6.2.2A	Additional Spectrum Emission Mask for CA	
6.6.2.2A.1		
6.6.2.3	Adjacent Channel Leakage Ratio	
6.6.2.3.1	Minimum requirement E-UTRA	
6.6.2.3.1A	Void	64
6.6.2.3.2	Minimum requirements UTRA	
6.6.2.3.2A	1	
6.6.2.3.3A	1	
6.6.2.4	Void	66
6.6.2.4.1	Void	66
6.6.2A	Void	
6.6.2B	Out of band emission for UL-MIMO	
6.6.3	Spurious emissions	
6.6.3.1	Minimum requirements	
6.6.3.1A	Minimum requirements for CA	
6.6.3.2	Spurious emission band UE co-existence	
6.6.3.2A	Spurious emission band UE co-existence for CA	
6.6.3.3	Additional spurious emissions	
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	74
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	
6.6.3.3A	Additional spurious emissions for CA	
6.6.3.3A.1		
6.6.3.3A.2		75
6.6.3.3A.3		
6.6.3A	Void	
6.6.3B	Spurious emission for UL-MIMO	
6.6A	Void	
6.6B	Void	
6.7	Transmit intermodulation	
6.7.1	Minimum requirement	
6.7.1A	Minimum requirement for CA	
6.7.1B	Minimum requirement for UL-MIMO	
6.8	Time alignment between transmitter branches for UL-MIMO	
6.8.1	Minimum Requirements	78
7 Re	ceiver characteristics	78
7.1	General	
7.2	Diversity characteristics	
	Reference sensitivity power level	
7.3.1	Minimum requirements (QPSK)	
7.3.1A	Minimum requirements (QPSK) for CA	



DOCKET

Explore Litigation Insights



Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

