

# Tungsten

Properties, Chemistry, Technology of the  
Element, Alloys, and Chemical Compounds

Erik Lassner and  
Wolf-Dieter Schubert

*Vienna University of Technology  
Vienna, Austria*

Kluwer Academic / Plenum Publishers

---

Library of Congress Cataloging-in-Publication Data

Lassner, Erik.

Tungsten : properties, chemistry, technology of the element, alloys, and chemical compounds / Erik Lassner and Wolf-Dieter Schubert.

p. cm.

Includes bibliographical references and index.

ISBN 0-306-45053-4

1. Tungsten. I. Schubert, Wolf-Dieter. II. Title.

QD181.W1L37 1998

620.1'8934--dc21

98-45787

CIP

---

ISBN 0-306-45053-4

© 1999 Kluwer Academic / Plenum Publishers, New York  
233 Spring Street, New York, N.Y. 10013

10 9 8 7 6 5 4 3 2 1

A C.I.P. record for this book is available from the Library of Congress.

All rights reserved

No part of this book may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, microfilming, recording, or otherwise, without written permission from the Publisher

affect the recrystallization grain morphology and the retained dislocation substructure. In particular, non-sag tungsten is significantly more creep-resistant than pure tungsten, mainly as a result of the interlocking grain structure, which forms on recrystallization and which prevents both grain boundary sliding and diffusional creep. In addition, the fine dispersion of potassium bubbles contributes to the outstanding creep resistance through pinning of dislocations [1.62, 1.66].

Non-sag tungsten wires are the most creep-resistant wires, with the exception of monocrystalline tungsten. They are therefore used for sag-free lamp filaments at service temperatures of up to 3000 °C ( $0.88 T_m$ ), and shear stresses in the range of 0.5 to 10 MPa [1.66].

#### 1.2.4. Thermal Properties

Melting point:  $3422 \pm 15$  °C (3695 K) [1.67],

$3390 \pm 40$  °C (3663 K) [1.68],

$3423 \pm 30$  °C (3696) [1.69].

The high melting point (highest of all metals) is the most prominent and important property in regard to all applications as refractory metal. It is a consequence of the electron density of states. Small amounts of impurities, such as carbon, lower the melting point.

The molar volume increases by 8% on melting. This is the largest expansion observed for bcc metals [1.70].

The melting curve of W has been determined to 5 GPa [1.71].

*Enthalpy of fusion:*  $46 \pm 4$  kJ · mol<sup>-1</sup> [1.68].

*Entropy of fusion:*  $14$  J · mol<sup>-1</sup> · K<sup>-1</sup> [1.70].

*Enthalpy of sublimation:*  $858.9 \pm 4.6$  kJ · mol<sup>-1</sup> [1.35].

*Vapor Pressure.* Tungsten has the lowest vapor pressure of all metals. Within the temperature range from 2600 to 3100 K, it obeys the following equation [1.76]:

$$\log p[\text{Pa}] = -45395T^{-1} + 12.8767$$

At 2000 °C, the vapor pressure is  $8.15 \times 10^{-8}$  Pa; at 3000 °C it is  $10^{-1}$  Pa. Experimental data for  $p$  over liquid W are not available.

The *rate of evaporation* in vacuum is about  $6.2 \times 10^{-11}$  g · cm<sup>-2</sup> · s<sup>-1</sup> at 2000 °C, about  $7 \times 10^{-8}$  g · cm<sup>-2</sup> · s<sup>-1</sup> at 2500 °C, and about  $2.5 \times 10^{-5}$  g · cm<sup>-2</sup> · s<sup>-1</sup> at 3000 °C [1.72]. It is markedly reduced by an inert gas atmosphere (Ar, Kr). Therefore, modern incandescent lamps contain inert gas fillings to avoid enhanced wall-blackening (the rate of evaporation in vacuum is about 500 times larger as compared to an Ar atmosphere of 1.2 bar) [1.73].

*Boiling Point:* calculated from rates of evaporation of solid tungsten,

$5663$  °C (5936 K) [1.74],

$5700 \pm 200$  °C [1.64].

*Critical temperature:*  $13400 \pm 1400$  K [1.75].

*Critical pressure:*  $(3.37 \pm 0.85) \times 10^8$  Pa [1.75].

*Critical density:*  $4.31 \text{ g} \cdot \text{cm}^{-3}$  [1.35].

*Thermal expansion.* At room temperature, values between 4.32 and  $4.68 \times 10^{-6} \text{ K}^{-1}$  were obtained for the linear coefficient of expansion  $\alpha$ , depending on the material (P/M sheet, arc-cast sheet, etc.) and the type of measurement. Values for low and high temperatures are listed in Table 1.12. The linear coefficient of expansion can also be calculated according to the following equations [1.76]:

temperature range: 293–1395 K

$$\alpha = 4.266 \times 10^{-6}(T - 293) + 8.479 \times 10^{-10}(T - 293)^2 - 1.974 \times 10^{-13}(T - 293)^3$$

temperature range 1395–2495 K

$$\alpha = 0.00548 + 5.416 \times 10^{-6}(T - 1395) + 1.952 \times 10^{-10}(T - 1395)^2 + 4.422 \times 10^{-13}(T - 1395)^3$$

temperature range 2495–3600 K

$$\alpha = 0.01226 + 7.451 \times 10^{-6}(T - 2495) + 1.654 \times 10^{-9}(T - 2495)^2 + 7.568 \times 10^{-14}(T - 2495)^3$$

The very low thermal expansion of tungsten makes it compatible with glass and ceramics in high temperature applications.

*Thermodynamic functions* [1.35]. Thermodynamic functions for solid tungsten are listed in Table 1.13. For more details and data for liquid tungsten, see elsewhere [1.10].

TABLE 1.12. Thermal Expansion Coefficient for Low and High Temperatures [1.35]

T (K)	$10^6 \cdot \alpha(\text{K}^{-1})$	T (K)	$10^6 \cdot \alpha(\text{K}^{-1})$
10	0.006	160	3.82
15	0.019	190	4.06
20	0.048	220	4.20
25	0.102	260	4.32
30	0.20	300	4.49
40	0.53	600	4.75
50	0.90	1000	5.02
60	1.43	1400	5.46
70	1.88	1800	6.11
80	2.30	2200	6.89
100	2.82	2600	7.76
130	3.42	3000	9.05
		3400	11.60

TABLE 1.13. Thermodynamic Functions [1.35]

$T$ (K)	$H_T - H_{298.5}$ (kJ · mol <sup>-1</sup> )	$H_T - H_0$ (kJ · mol <sup>-1</sup> )	$S$ (kJ · mol <sup>-1</sup> · K <sup>-1</sup> )	$S - S_0$ (kJ · mol <sup>-1</sup> · K <sup>-1</sup> )	$C_p$ (kJ · mol <sup>-1</sup> · K <sup>-1</sup> )	$C_v$ (kJ · mol <sup>-1</sup> · K <sup>-1</sup> )
298.15	0	4.970	32.640	32.618	24.10–24.42	23.96
500	5.022–5.024	10.007	45.516	45.457	24.33–25.44	25.16
1000	18.23–18.25	23.142	63.658	63.686	27.19–27.60	26.70
1500	32.33–32.62	37.249	75.068	75.099	29.23–29.86	28.12
2000	47.59–48.11	52.599	83.881	83.585	31.37–32.13	29.80
2500	64.52–64.78	69.476	91.399	91.397	34.67–36.00	—
3000	83.10–83.88	88.310	98.254	98.442	39.25–41.80	35.91
3500	105.19	109.845	104.880	—	46.49–50.85	—
3600	110.5–111.8	114.574	106.212	106.89	48.11–54.68	—

Analyses of thermodynamic properties of tungsten at high temperatures are available [1.77, 1.78].

The heat capacity at low temperatures is:

$T$ in K	25	30	35	40	50	60	70	80	100
$C_p$ (J · mol <sup>-1</sup> · K <sup>-1</sup> )	0.73	1.35	2.22	3.30	5.82	8.39	10.74	12.81	16.04
$T$ in K	120	140	160	180	200	220	260	300	
$C_p$ (J · mol <sup>-1</sup> · K <sup>-1</sup> )	18.28	19.87	21.01	21.86	22.54	23.04	23.81	24.35	

The heat capacity of liquid tungsten is 35.564 J mol<sup>-1</sup> · K<sup>-1</sup> [1.10]

*Self-diffusion* [1.35]. At a certain temperature, the diffusion process is characterized by the diffusion coefficient  $D$ . Its temperature dependency is given by the Arrhenius equation  $D = D_0 \exp(-Q/R \cdot T)$  with  $D_0$  a constant in cm<sup>2</sup> · g<sup>-1</sup>,  $T$  the absolute temperature,  $R$  the molar gas constant in J · K<sup>-1</sup> · mol<sup>-1</sup>, and  $Q$  the activation enthalpy in kJ · mol<sup>-1</sup>.

Activation enthalpies for the lattice (volume) diffusion were derived between 586 and 628 kJ · mol<sup>-1</sup> for single crystals and between 502 and 586 kJ · mol<sup>-1</sup> for polycrystalline tungsten. Accordingly, the following equations were set up [1.79]:

Self-diffusion in tungsten single crystals:  $D = 42.8 \exp(-640/RT)$ .

Self diffusion in polycrystalline tungsten:  $D = 54 \exp(-504/RT)$ .

Over the range of 1900 to 2800 °C, a linear relationship between log  $D$  and  $1/T$  was obtained for polycrystalline tungsten.

The self-diffusion parameters  $D_0$  and  $Q$  are influenced by the impurity content of the diffusion zone. Higher values for both were obtained for impure tungsten. This effect is more pronounced at low temperatures and vanishes above 2043 K. (It is assumed that impurities attract vacancies and the higher vacancy concentration disturbs the diffusion process).

The fact that lower  $Q$  values were obtained for polycrystalline tungsten than for single crystals, especially for  $T < 0.7T_m$ , is due to a more or less significant contribution of grain

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.