




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>7</sup> : <b>H03M 7/40, H04N 7/50</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 00/51243</b></p> <p>(43) International Publication Date: 31 August 2000 (31.08.00)</p>
<p>(21) International Application Number: PCT/KR99/00764</p> <p>(22) International Filing Date: 11 December 1999 (11.12.99)</p> <p>(30) Priority Data: 1999/6157 24 February 1999 (24.02.99) KR</p> <p>(71)(72) Applicant and Inventor: YOU, Soo, Geun [KR/KR]; Jamwon Hansin Apt. 1-1103, 56-3, Jamwon-dong, Seocho-gu, Seoul 137-030 (KR).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): PARK, Jung, Jae [KR/KR]; 6516, Taepyeong 1-dong, Sujeong-gu, Seongnam, Kyunggi-do 461-191 (KR).</p> <p>(74) Agent: PARK, Lae, Bong; 4F TLBS B/D, 464-1, Kunja-dong, Kwangjin-gu, Seoul 143-150 (KR).</p>		<p>(81) Designated States: AU, BR, CA, CN, DE, ES, GB, IN, JP, RU, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: A BACKWARD DECODING METHOD OF DIGITAL AUDIO DATA



## (57) Abstract

This invention provides a method of backward decoding compressed digital audio data into an analog audio data reversed in time. The method according to this invention comprises the steps of locating a header of a last frame of the compressed digital audio data; dequantizing a plurality of data blocks constructing the frame based on information contained in the located header; extracting time signals of each frequency subband from the dequantized data blocks, reducing discontinuities between the dequantized data blocks; and synthesizing the extracted time signals of all subbands backward into real audio signal reversed in time. Therefore, this invention enables to record the decoded analog signal on both tracks on a magnetic tape simultaneously while the magnetic tape travels in one direction with little increase of computation load and memory size, resulting in a high speed recording.

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

# DESCRIPTION

## A BACKWARD DECODING METHOD OF DIGITAL AUDIO DATA

### 1. Technical Field

The present invention relates to a method of decoding  
5 compressed digital audio data backward, more particularly,  
to a method of backward decoding an MPEG (Moving Picture  
Experts Group) encoded audio data into analog audio  
signal with little increase of computation load and  
memory size.

### 10 2. Background Art

Digital audio signal is in general more robust to noise  
than analog signal and thus the quality is not subject to  
degradation during copy or transmission over network. The  
digital audio signals are, moreover, transmitted more  
15 rapidly and stored in storage media of less capacity due  
to effective compression methods recently developed.

Many compression methods have been proposed to  
effectively encode audio signals into digital data. MPEG  
(Moving Picture Experts Group) audio coding schemes have  
20 been used for the standard in this area. The MPEG audio  
standards that are standardized as ISO (International  
Standardization Organization) - MPEG audio layer-1,

layer-2, and layer-3 were devised to encode high-quality stereo audio signals with little or no perceptible loss of quality. They have been widely adopted in digital music broadcasting area and in addition have been used  
5 with MPEG video standards to encode multimedia data. In addition to MPEG-1, standard specifications for digital environments have been proposed; MPEG-2 includes standards on compression of multimedia data. Standards for object oriented multimedia communication are included  
10 in MPEG-4, which is in progress.

MPEG-1 consists of five coding standards for compressing and storing moving picture and audio signals in digital storage media. MPEG audio standard includes three audio coding methods: layer-1, layer-2, and layer-3.  
15 MPEG audio layer-3 (hereinafter referred to as "MP3") algorithm includes a much more refined approach than in layer-1 and layer-2 to achieve higher compression ratio and sound quality, which will be described briefly below.

MPEG audio layer-1, 2, 3 compress audio data using  
20 perceptual coding techniques which address perception of sound waves of the human auditory system. To be specific, they take an advantage of the human auditory system's inability to hear quantization noise under conditions of auditory masking. The "masking" is a perceptual property

of the human ear which occurs whenever the presence of a strong audio signal makes a temporal or spectral neighborhood of weaker audio signals imperceptible. Let us suppose that a pianist plays the piano in front of  
5 audience. When the pianist does not touch keyboard, the audience can hear trailing sounds, but is no longer able to hear the trailing sounds at the instant of touching the keyboard. This is because, in presence of masking sounds, or the newly generated sounds, the trailing  
10 sounds which fall inside frequency bands centering the masking sound, so-called critical bands, and loudness of which is lower than a masking threshold are not audible. This phenomenon is called spectral masking effect. The masking ability of a given signal component depends on  
15 its frequency position and its loudness. The masking threshold is low in the sensitive frequency bands of the human ear, i.e., 2KHz to 5KHz, but high in other frequency bands.

There is the temporal masking phenomenon in the human  
20 auditory system. That is, after hearing a loud sound, it takes a period of time for us to be able to hear a new sound that is not louder than the sound. For instance, it requires 5 milliseconds for us to be able to hear a new sound of 40 dB after hearing a sound of 60 dB during 5

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.