

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

A/Prov

Docket Number 2001-0027

INVENTOR(S)

Name (line 1) Matthew J. Sherman
 Address (line 1) 4 Atlantis Drive
 Address (line 2) Succasunna
 Address (line 3) Morris County
 Address (line 4) NJ
 Address (line 5) USA
 Zip Code 07876

101/16/01
 60/261935
 101/16/01

 Additional Inventors are being named on the separately numbered sheets attached hereto**TITLE OF THE INVENTION (180 characters max)**

Interoperability Methods For IEEE 802.11a And HIPERLAN

CORRESPONDENCE ADDRESS Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or Correspondence address below

NAME Samuel H. Dworetsky

ADDRESS AT&T CORP. P.O. Box 4110

CITY Middletown

STATE

New Jersey

ZIP CODE

07748-4110

COUNTRY United States of America

FAX

732-368-6932

ENCLOSED APPLICATION PARTS (check all that apply) Specification Number of Pages 3 Small Entity Statement Other (specify) Drawing(s) Number of Sheets 12 Return Receipt Postcard (MPEP 503)**METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)**

The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 01-2745

Filing Fee Amount (\$): \$150.00

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

 No. Yes, the name of the U.S. Government agency and the Government contract number are :**SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**


NAME Alfred G. Steinmetz

Reg. #

22971

TELEPHONE 908-221-5425

SIGNATURE



DATE

01/15/2001

"Express Mail" Mailing Label Number EL354902032US

Date of Deposit 01/15/2001

I hereby certify that this provisional application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents, Washington D.C., 20231

Shawn McGee

(Printed Name of Person Mailing Paper)


(Signature of Person Mailing Paper)

SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, DC 20231.

01/16/01
Jc960 U.S. PTO

Interoperability Methods For IEEE 802.11a and HIPERLAN

Matthew Sherman
Jan. 14, 2001

Background of the Invention

Wireless data transmission is a rapidly growing field. One increasingly popular form of such transmission is wireless local areas networks (WLANs). A number of standards currently exist for WLANs. However they tend to be fragmented and largely incompatible. There is desire for a worldwide standard that would allow a single device to function virtually anywhere in the world providing high-speed connectivity.

Recently, bands have opened up that hold that promise between 5 and 6 GHz. Wireless standards are being developed to utilize those bands. One such standard is HIPERLAN/2 (High Performance Radio Local Area network Type 2), which is of European origin [1-3]. Another such standard is IEEE 802.11a, which originate primarily in the US [4-5]. Japan is developing standards similar to both those in the US and Europe. Both the US and European standards profess similar levels of performance, and use very similar waveforms to communicate. However, the two standards are currently incompatible – Particularly at the Media Access Control (MAC) layer. As such a large push has developed to create a single hybrid standard, or provide some means for the two standards to easily interoperate.

Methods for Interoperation of HIPERLAN and 802.11a systems are being contemplated in which systems conforming to both standards might share one common channel. A MAC frame structure has been proposed to support this application. The proposed structure contemplates a super frame with an 802.11 phase and a HIPERLAN/2 phase (see FIG. X). The super frame has a length of $2^k \times 2$ ms, where k is an integer. Duration of the 802.11 beacon plus the 802.11a phase is set at $n \times 2$ ms. The HIPERLAN/2 phase comprises $m \times 2$ ms. The sum of m and n would be 2^k .

While this is an interesting approach it does have some drawbacks. For one, the approach presumes the 802.11 terminals can be prevented from transmitting during the HIPERLAN phase. Currently, no mechanism exists within the 802.11 standard to allow this. It is possible that new mechanisms could be introduced into newer versions of the standard, and be supported by future generations of 802.11 stations. However, the problem would be best addressed if the solution were somehow compatible with current generations of terminals. It is the purpose of this disclosure to present such solutions.

Summary of the Invention

This application builds upon prior work for developing interoperability between the HIPERLAN and 802.11a standards. It builds upon mechanisms suggested in a prior application, to increase the interoperability possible between the two standards. Specifically, it introduces mechanisms to prevent 802.11 terminals from transmitting during time periods allocated to HIPERLAN, so that a single channel can be shared between the two standards. It also improves upon the protection available by suggesting a “super frame” format where HIPERLAN transmissions are offered the highest level of protection possible within 802.11, which is that within the 802.11 Contention Free Period (CFP).

Brief Description of Drawings

See slide set titled “Proposed HIPERLAN 802.11 Compatibility Frame”.

Detailed Description of Invention

It has been suggested that a Superframe structure can be developed that allows 802.11a stations (STA) to share a single channel with HIPERLAN/2 stations. One such proposal is shown in figure X. The problem is that there is nothing in the proposal that would force 802.11a STA to cease transmissions during the HIPERLAN phase of the Superframe. The 802.11a STA would view the HIPERLAN phase as a part of the 802.11 Contention Period (CP), and would normally be free to transmit during the CP. 802.11 STA have a mechanism call the Network Allocation Vector (NAV) that can be set to prevent the STA from transmitting. However, the NAV is set only under very specific conditions that do not exist at the time the HIPERLAN/2 frames need to seize the medium.

A prior application includes an 802.11 mechanism that can be used to cause the NAV to be set while the HIPERLAN/2 transmissions occur. The mechanism is called there an Enhanced CTS (ECTS). If the HIPERLAN/2 phase is preceded by an ECTS with the duration field properly set prevent transmissions during the desired frame, then a working Superframe structure can be developed consisting of

Beacon, 802.11 phase, ECTS, HIPERLAN/2 phase.

The Superframe would then repeat, with a Beacon following the HIPERLAN/2 phase. The Superframe structure would be constructed such that its total length would be 2^k times 2 milliseconds (msec), where k is an integer. The 802.11 Beacon period (time between Beacons) would be selected to be identical to the Superframe length. The HIPERLAN/2 phase would be n times 2 msec, and the 802.11 phase (which actually would include the Beacon and ECTS) would be m times 2 msec, where $m+n = 2^k$. For greater coverage, an Enhanced RTS (ERTS) followed by CTS could be used instead of the ECTS.

While this scheme could work, it does have one important drawback in that 802.11a STA that are hidden from the STA sending the ECTS would not set their NAV's, and might transmit during the HIPERLAN/2 phase of the superframe. This would interfere with the operation of the HIPERLAN/2 STA. To fix this, a different approach can be used where the HIPERLAN phase is buried in the Contention Free Period (CFP) of 802.11. The CFP occurs with a regular period, and all 802.11 terminals set their NAV's during the CFP. To realize such a super frame the following sequence:

CFP_Beacon, 802.11 Broadcast, 802.11 CFP, HIPERLAN/2 phase, CF_End, 802.11 CP

Here, CFP_Beacon is a Beacon starting a CFP. Not all Beacons need start a CFP. However, the CFP must recur every integral number of Beacons. The inference is that the Beacon period must be a sub multiple of the super frame size (which is still 2^k time 2 msec). Now however, 3 phases really exist. The first would consist of the CFP_Beacon, 802.11 Broadcast, and 802.11 CFP. This would need to be an integral number times 2 msec, and that number will be specified as l for this application. The HIPERLAN/2 phase would remain at n times 2 msec, and the CF_End, 802.11 CP would have to be m times 2 msec. The sum $l+m+n$ must be 2^k .

Note that Broadcast traffic must immediately follow a beacon which is why it is located as such. The HIPERLAN/2 phase will be viewed by 802.11 terminals as part of the CFP, and accorded protection accordingly. The CFP's maximum length is determined by a variable regularly broadcast in Beacon messages. It should be set very close to the full length of the superframe. To relinquish the time to the CP, when the CF_End is sent, all terminals will automatically reset their NAV's. Normal CP transmissions would then occur. Note that additional Beacons might occur during the CP that does not start a new CFP. The existence of these Beacons may make it easier to handle broadcast traffic, and 802.11 power saver terminals, but is not a requirement.

There may be some concern about Beacon jitter since this may result in jitter in the superframe. HIPERLAN/2 is not very tolerant of jitter. However, by utilizing the ECTS mechanism (or more likely an ERTS) jitter before the Beacon can be controlled. Alternatively, the Access Port (AP), which is a special STA, which provides access to a Distribution Service (DS) for the medium among other things, could just broadcast dummy traffic just prior to Beacon transmission if desired preventing other traffic from seizing

the medium. Also, while it is unlikely to be needed, an ECTS could still be transmitted prior to the HIPERLAN/2 phase if desired to further assure that no 802.11 STA are active during the HIPERLAN/2 phase.

References:

- [1] TS 101 761-1, Broadband Radio Access Networks (BRAN); High Performance Radio Local Area Network (HIPERLAN) Type 2; Data Link Control (DLC) Layer - Part 1 - Basic Data Transport Function, ETSI Project BRAN, 2000
- [2] TS 101 761-2, Broadband Radio Access Networks (BRAN); High Performance Radio Local Area Network (HIPERLAN) Type 2; Data Link Control (DLC) Layer - Part 2 - Radio Link Control (RLC), ETSI Project BRAN, 2000
- [3] TS 101 475, Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Physical (PHY) Layer, ETSI Project BRAN, 2000
- [4] IEEE, "Reference number ISO/IEC 8802-11:1999 (E) IEEE STD 802.11, 1999 edition. International Standard [for] Information Technology-Telecommunications and information exchange between systems-Local and metropolitan area networks-Specific Requirements- Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications", 1999.
- [5] IEEE, "Supplement to STANDARD [for] Information Technology-Telecommunications and information exchange between systems-Local and metropolitan area networks-Specific requirements-Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: High-speed Physical Layer in the 5 GHz Band," IEEE Std 802.11a-1999, September 1999.

IEEE Std 802.11a-2003

January 14, 2001

doc.: IEEE

Proposed HIPERLAN / 802.11a Compatibility Superframe Fo

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.